



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

M.535

**MAINTENANCE:
INTERNATIONAL TRANSMISSION SYSTEMS
(ANALOGUE)**

**SPECIAL MAINTENANCE PROCEDURES FOR
MULTIPLE DESTINATION UNIDIRECTIONAL
(MU) GROUP AND SUPERGROUP LINKS**

ITU-T Recommendation M.535

(Extract from the *Blue Book*)

NOTES

- 1 ITU-T Recommendation M.535 was published in Fascicle IV.1 of the *Blue Book*. This file is an extract from the *Blue Book*. While the presentation and layout of the text might be slightly different from the *Blue Book* version, the contents of the file are identical to the *Blue Book* version and copyright conditions remain unchanged (see below).
- 2 In this Recommendation, the expression “Administration” is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

© ITU 1988, 1993

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

Recommendation M.535

SPECIAL MAINTENANCE PROCEDURES FOR MULTIPLE DESTINATION, UNIDIRECTIONAL (MU) GROUP AND SUPERGROUP LINKS

The Recommendations covering the maintenance of groups and supergroups will apply as far as possible but there will be a number of new maintenance problems which are peculiar to multiple destination links. In particular, arrangements will be needed to check the performance of the MU main section of such links. In order to simplify the procedures and minimize interference to other users of the common path, it is recommended that the send reference station (see Figure 1/M.460) for the MU main section should act as a focal point for reports and inquiries concerning the MU main section. The group, supergroup, etc., control stations will still be responsible for localizing a fault to a particular section of a link in accordance with Recommendation M.130.

When a fault is found to be in the communication satellite link, the send reference station will report the fault to the satellite control responsible for this link from baseband-in to baseband-out. When the fault is cleared, the send reference station will advise the MU main section controls which will in turn advise the group, supergroup, etc., controls concerned.