



INTERNATIONAL TELECOMMUNICATION UNION

**ITU-T**

TELECOMMUNICATION  
STANDARDIZATION SECTOR  
OF ITU

**Q.326**

**SPECIFICATIONS OF SIGNALLING SYSTEM R1  
REGISTER SIGNALLING**

---

**SWITCHING TO THE SPEECH POSITION**

**ITU-T Recommendation Q.326**

(Extract from the *Blue Book*)

---

## NOTES

1 ITU-T Recommendation Q.326 was published in Fascicle VI.4 of the *Blue Book*. This file is an extract from the *Blue Book*. While the presentation and layout of the text might be slightly different from the *Blue Book* version, the contents of the file are identical to the *Blue Book* version and copyright conditions remain unchanged (see below).

2 In this Recommendation, the expression “Administration” is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

## **Recommendation Q.326**

### **3.7 SWITCHING TO THE SPEECH POSITION**

At all exchanges, the circuit shall be switched to the speech position when the registers<sup>1</sup> (incoming or outgoing) are released.

---

<sup>1</sup> As used in this Recommendation, the term register includes traditional registers in electromechanical exchanges and also the equivalent receiving device, memory and logic in stored program exchanges.