



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

Q.662

INTERWORKING OF SIGNALLING SYSTEMS

**LOGIC PROCEDURES FOR
INTERWORKING OF SIGNALLING
SYSTEM No. 7 (TUP) TO No. 5**

ITU-T Recommendation Q.662

(Extract from the *Blue Book*)


NOTES

1 ITU-T Recommendation Q.662 was published in Fascicle VI.6 of the *Blue Book*. This file is an extract from the *Blue Book*. While the presentation and layout of the text might be slightly different from the *Blue Book* version, the contents of the file are identical to the *Blue Book* version and copyright conditions remain unchanged (see below).

2 In this Recommendation, the expression “Administration” is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Recommendation Q.662

LOGIC PROCEDURES FOR INTERWORKING OF SIGNALLING SYSTEM No. 7 (TUP) TO No. 5



<i>State number</i>	<i>State description</i>	<i>Sheet reference</i>
00	Idle	1, 2
01	Wait for CPCI-FITE	1
02	Wait for COT	1
03	Wait for address-complete	2
04	Wait for register deactivation	2
05	Wait for answer	2
06	Answered	2
07	Clear-back	2

FIGURE 1/Q.662

State overview diagram for interworking of Signalling System No. 7 (TUP) to No. 5

FIGURE 2/Q.662

(Reserved for future notes)





FIGURE 3/Q.662 (Sheet 1 of 2)
 Interworking of Signalling System No. 7 (TUP) to No. 5

Connector reference



T1104862-87

FIGURE 3/Q.662 (Sheet 2 of 2)
 Interworking of Signalling System No. 7 (TUP) to No. 5