



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

V.14

Corrigendum 1
(09/98)

SERIES V: DATA COMMUNICATION OVER THE
TELEPHONE NETWORK

Interfaces and voiceband modems

Transmission of start-stop characters over
synchronous bearer channels

Corrigendum 1

ITU-T Recommendation V.14 – Corrigendum 1

(Previously CCITT Recommendation)

ITU-T V-SERIES RECOMMENDATIONS
DATA COMMUNICATION OVER THE TELEPHONE NETWORK

| | |
|---|------------------|
| General | V.1–V.9 |
| Interfaces and voiceband modems | V.10–V.34 |
| Wideband modems | V.35–V.39 |
| Error control | V.40–V.49 |
| Transmission quality and maintenance | V.50–V.59 |
| Simultaneous transmission of data and other signals | V.60–V.99 |
| Interworking with other networks | V.100–V.199 |
| Interface layer specifications for data communication | V.200–V.249 |
| Control procedures | V.250–V.299 |
| Modems on digital circuits | V.300–V.399 |

For further details, please refer to ITU-T List of Recommendations.

ITU-T RECOMMENDATION V.14

**TRANSMISSION OF START-STOP CHARACTERS
OVER SYNCHRONOUS BEARER CHANNELS**

CORRIGENDUM 1

Source

Corrigendum 1 to ITU-T Recommendation V.14 was prepared by ITU-T Study Group 16 (1997-2000) on the 25th of September 1998.

FOREWORD

ITU (International Telecommunication Union) is the United Nations Specialized Agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of the ITU. The ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Conference (WTSC), which meets every four years, establishes the topics for study by the ITU-T Study Groups which, in their turn, produce Recommendations on these topics.

The approval of Recommendations by the Members of the ITU-T is covered by the procedure laid down in WTSC Resolution No. 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation the term *recognized operating agency (ROA)* includes any individual, company, corporation or governmental organization that operates a public correspondence service. The terms *Administration*, *ROA* and *public correspondence* are defined in the *Constitution of the ITU (Geneva, 1992)*.

INTELLECTUAL PROPERTY RIGHTS

The ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. The ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, the ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 1999

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

Recommendation V.14

TRANSMISSION OF START-STOP CHARACTERS OVER SYNCHRONOUS BEARER CHANNELS

CORRIGENDUM 1

(Geneva, 1998)

1) Subclause 1.1

Replace subclause 1.1 as follows:

1.1 This Recommendation describes a method of conveying start-stop characters over synchronous bearer channels using an async-to-sync converter. Start-stop characters at signalling rates below or equal to 300 bit/s can be conveyed over synchronous bearer channels by oversampling at a signalling rate of at least 1200 bit/s.

2) Clause 2

Replace clause 2 as follows:

2 Data signalling rates

The nominal signalling rates for both the start-stop characters and the synchronous DCE shall be the same. The tolerance of the signalling rate of the synchronous transmission shall be $\pm 0.01\%$.

ITU-T RECOMMENDATIONS SERIES

- Series A Organization of the work of the ITU-T
- Series B Means of expression: definitions, symbols, classification
- Series C General telecommunication statistics
- Series D General tariff principles
- Series E Overall network operation, telephone service, service operation and human factors
- Series F Non-telephone telecommunication services
- Series G Transmission systems and media, digital systems and networks
- Series H Audiovisual and multimedia systems
- Series I Integrated services digital network
- Series J Transmission of television, sound programme and other multimedia signals
- Series K Protection against interference
- Series L Construction, installation and protection of cables and other elements of outside plant
- Series M TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits
- Series N Maintenance: international sound programme and television transmission circuits
- Series O Specifications of measuring equipment
- Series P Telephone transmission quality, telephone installations, local line networks
- Series Q Switching and signalling
- Series R Telegraph transmission
- Series S Telegraph services terminal equipment
- Series T Terminals for telematic services
- Series U Telegraph switching
- Series V Data communication over the telephone network**
- Series X Data networks and open system communications
- Series Y Global information infrastructure and Internet protocol aspects
- Series Z Languages and general software aspects for telecommunication systems