



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

X.217

Amendment 1
(10/96)

SERIES X: DATA NETWORKS AND OPEN SYSTEM
COMMUNICATION

Open System Interconnection – Service definitions

Information technology – Open Systems
Interconnection – Service definition for the
association control service element

**Amendment 1: Support of authentication
mechanisms for the connectionless mode**

ITU-T Recommendation X.217 – Amendment 1

(Previously CCITT Recommendation)

ITU-T X-SERIES RECOMMENDATIONS
DATA NETWORKS AND OPEN SYSTEM COMMUNICATION

PUBLIC DATA NETWORKS	X.1–X.199
Services and facilities	X.1–X.19
Interfaces	X.20–X.49
Transmission, signalling and switching	X.50–X.89
Network aspects	X.90–X.149
Maintenance	X.150–X.179
Administrative arrangements	X.180–X.199
OPEN SYSTEM INTERCONNECTION	X.200–X.299
Model and notation	X.200–X.209
Service definitions	X.210–X.219
Connection-mode protocol specifications	X.220–X.229
Connectionless-mode protocol specifications	X.230–X.239
PICS proformas	X.240–X.259
Protocol Identification	X.260–X.269
Security Protocols	X.270–X.279
Layer Managed Objects	X.280–X.289
Conformance testing	X.290–X.299
INTERWORKING BETWEEN NETWORKS	X.300–X.399
General	X.300–X.349
Satellite data transmission systems	X.350–X.399
MESSAGE HANDLING SYSTEMS	X.400–X.499
DIRECTORY	X.500–X.599
OSI NETWORKING AND SYSTEM ASPECTS	X.600–X.699
Networking	X.600–X.629
Efficiency	X.630–X.649
Naming, Addressing and Registration	X.650–X.679
Abstract Syntax Notation One (ASN.1)	X.680–X.699
OSI MANAGEMENT	X.700–X.799
Systems Management framework and architecture	X.700–X.709
Management Communication Service and Protocol	X.710–X.719
Structure of Management Information	X.720–X.729
Management functions	X.730–X.799
SECURITY	X.800–X.849
OSI APPLICATIONS	X.850–X.899
Commitment, Concurrency and Recovery	X.850–X.859
Transaction processing	X.860–X.879
Remote operations	X.880–X.899
OPEN DISTRIBUTED PROCESSING	X.900–X.999

For further details, please refer to ITU-T List of Recommendations.

FOREWORD

ITU (International Telecommunication Union) is the United Nations Specialized Agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of the ITU. Some 179 member countries, 84 telecom operating entities, 145 scientific and industrial organizations and 38 international organizations participate in ITU-T which is the body which sets world telecommunications standards (Recommendations).

The approval of Recommendations by the Members of ITU-T is covered by the procedure laid down in WTSC Resolution No. 1 (Helsinki, 1993). In addition, the World Telecommunication Standardization Conference (WTSC), which meets every four years, approves Recommendations submitted to it and establishes the study programme for the following period.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC. The text of ITU-T Recommendation X.217, Amendment 1, was approved on 5th of October 1996. The identical text is also published as ISO/IEC International Standard 8649.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

© ITU 1997

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

CONTENTS

		<i>Page</i>
1)	Subclause 7.2	1
2)	Subclause 9.5.1.14	2
3)	Subclause 9.5.1, Table 7	2

Summary

This amendment to the ACSE service definition defines the use of the authentication functional unit in the connectionless mode.

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

**INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION –
SERVICE DEFINITION FOR THE ASSOCIATION
CONTROL SERVICE ELEMENT**

AMENDMENT 1

Support of authentication mechanisms for the connectionless mode

1) Subclause 7.2

Delete the second paragraph and replace with the following subclause and table.

7.2.1 Functional units

Functional units are used by this Service Definition to identify ACSE user requirements. Two functional units are defined:

- a) Kernel functional unit; and
- b) Authentication functional unit.

The Kernel functional unit is always available.

The Authentication functional unit supports peer entity authentication. This functional unit does not include additional services. It adds parameters to the A-UNIT-DATA service.

Table 2 *bis* shows the services and parameters associated with the ACSE functional units for the connectionless mode of communication.

Table 2 *bis* – Functional unit services and their parameters (connectionless mode)

Functional Unit	Service	Parameter
Kernel	A-UNIT-DATA	Application Context Name Calling AP Title Calling AE Qualifier Calling AP Invocation-identifier Calling AE Invocation-identifier Called AP Title Called AE Qualifier Called AP Invocation-identifier Called AE Invocation-identifier User Information Calling Presentation Address Called Presentation Address Presentation Context Definition List Quality of Service
Authentication	A-UNIT-DATA	Authentication-mechanism Name Authentication-value ACSE Requirements

2) Subclause 9.5.1.14

Add the following new subclauses after subclause 9.5.1.14:

9.5.1.15 ACSE Requirements

This parameter is used by the requestor to indicate the functional units requested for the transfer of the data unit. If it is not present, only the Kernel functional unit is requested.

This parameter takes on the following symbolic value:

- authentication.

9.5.1.16 Authentication-mechanism Name

This parameter shall only be used if the ACSE Requirements parameter includes the Authentication functional unit. If present, the value of this parameter identifies the authentication-mechanism in use. If not present, the communicating AEIs must implicitly know the mechanism in use (e.g. by prior understanding).

9.5.1.17 Authentication value

This parameter shall only be used if the ACSE Requirements parameter includes the Authentication functional unit.

If present, this parameter contains an authentication-value generated by the authentication-function in the AEI that issued the service primitive. It is intended for the peer's authentication-function.

3) Subclause 9.5.1, Table 7

Add the following rows to the end of Table 7:

ACSE Requirements	U	C
Authentication-mechanism Name	U	C(=)
Authentication value	U	C(=)

ITU-T RECOMMENDATIONS SERIES

- Series A Organization of the work of the ITU-T
- Series B Means of expression: definitions, symbols, classification
- Series C General telecommunication statistics
- Series D General tariff principles
- Series E Overall network operation, telephone service, service operation and human factors
- Series F Non-telephone telecommunication services
- Series G Transmission systems and media, digital systems and networks
- Series H Audiovisual and multimedia systems
- Series I Integrated services digital network
- Series J Transmission of television, sound programme and other multimedia signals
- Series K Protection against interference
- Series L Construction, installation and protection of cables and other elements of outside plant
- Series M Maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits
- Series N Maintenance: international sound programme and television transmission circuits
- Series O Specifications of measuring equipment
- Series P Telephone transmission quality, telephone installations, local line networks
- Series Q Switching and signalling
- Series R Telegraph transmission
- Series S Telegraph services terminal equipment
- Series T Terminals for telematic services
- Series U Telegraph switching
- Series V Data communication over the telephone network
- Series X Data networks and open system communication**
- Series Z Programming languages