
SwitchPower:1 Service Template Version 1.01

For UPnP™ Version 1.0

Status: Standardized DCP

Date: November 23, 2003

This Standardized DCP has been adopted as a Standardized DCP by the Steering Committee of the UPnP™ Forum, pursuant to Section 2.1(c)(ii) of the UPnP™ Forum Membership Agreement. UPnP™ Forum Members have rights and licenses defined by Section 3 of the UPnP™ Forum Membership Agreement to use and reproduce the Standardized DCP in UPnP™ Compliant Devices. All such use is subject to all of the provisions of the UPnP™ Forum Membership Agreement.

THE UPNP™ FORUM TAKES NO POSITION AS TO WHETHER ANY INTELLECTUAL PROPERTY RIGHTS EXIST IN THE STANDARDIZED DCPS. THE STANDARDIZED DCPS ARE PROVIDED "AS IS" AND "WITH ALL FAULTS". THE UPNP™ FORUM MAKES NO WARRANTIES, EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE STANDARDIZED DCPS, INCLUDING BUT NOT LIMITED TO ALL IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT AND FITNESS FOR A PARTICULAR PURPOSE, OF REASONABLE CARE OR WORKMANLIKE EFFORT, OR RESULTS OR OF LACK OF NEGLIGENCE.

© 2000 - 2003 Contributing Members of the UPnP™ Forum. All Rights Reserved.

Authors	Company
Richard Hasha	Microsoft
Scott Manchester	Panja
Jeffrey Schlimmer	Microsoft
Hans J. Langels	Siemens

Contents

1. OVERVIEW AND SCOPE	3
2. SERVICE MODELING DEFINITIONS	4
2.1. SERVICETYPE	4
2.2. STATE VARIABLES	4
2.2.1. Target	4
2.2.2. Status	4
2.3. EVENTING AND MODERATION	5
2.4. ACTIONS	5
2.4.1. SetTarget	5
2.4.2. GetTarget	6
2.4.3. GetStatus	6
2.4.4. Non-Standard Actions Implemented by a UPnP Vendor	7
2.4.5. Common Error Codes	7
2.5. THEORY OF OPERATION	8
3. XML SERVICE DESCRIPTION	9
4. TEST	12

List of Tables

Table 2-1: State Variables	4
Table 2-2: Event Moderation	5
Table 2-3: Actions	5
Table 2-4: Arguments for SetTarget	5
Table 2-5: Error Codes for SetTarget	6
Table 2-6: Arguments for GetTarget	6
Table 2-7: Error Codes for GetTarget	6
Table 2-8: Arguments for GetStatus	6
Table 2-9: Error Codes for GetStatus	7
Table 2-10: Common Error Codes	7

1. Overview and Scope

This service definition is compliant with the UPnP Device Architecture version 1.0 and Version 1.01 of the UPnP Standard Service Template.

This service-type enables the following functions:

- basic power switching for embedding devices.

This service template does not address:

- It is assumed that implementations of this service will not disable themselves as a side effect of driving their output load to a disabled state.

2. Service Modeling Definitions

2.1. ServiceType

The following service type identifies a service that is compliant with this template:

`urn:schemas-upnp-org:service:SwitchPower:1`.

2.2. State Variables

Table 2-1: State Variables

Variable Name	Req. or Opt. ¹	Data Type	Allowed Value ²	Default Value ²	Eng. Units
Target	R	Boolean		0	
Status	R	Boolean		0	
<i>Non-standard state variables implemented by an UPnP vendor go here.</i>	X	TBD	TBD	TBD	TBD

¹ R = Required, O = Optional, X = Non-standard.

² Values listed in this column are required. To specify standard optional values or to delegate assignment of values to the vendor, you must reference a specific instance of an appropriate table below.

2.2.1. Target

Set to 0 to request a power-off state or to 1 to request a power-on state.

2.2.2. Status

This reflects the actual state of the power control output state.

This value will typically follow the requested state changes to Target but may be different because of delays within the actual implementation or because of a hard failure.

Simple implementations can implement the constant function: Status = Target.

2.3. Eventing and Moderation

Table 2-2: Event Moderation

Variable Name	Evented	Moderated Event	Max Event Rate ¹	Logical Combination	Min Delta per Event ²
Target	No	n/a		n/a	
Status	Yes	No		None	None
<i>Non-standard state variables implemented by an UPnP vendor go here.</i>	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>

¹ Determined by N, where Rate = (Event)/(N secs).

² (N) * (allowedValueRange Step).

2.4. Actions

Immediately following this table is detailed information about these actions, including short descriptions of the actions, the effects of the actions on state variables, and error codes defined by the actions.

Table 2-3: Actions

Name	Req. or Opt. ¹
SetTarget	R
GetTarget	R
GetStatus	R
<i>Non-standard actions implemented by an UPnP vendor go here.</i>	<i>X</i>

¹ R = Required, O = Optional, X = Non-standard.

2.4.1. SetTarget

2.4.1.1. Arguments

Table 2-4: Arguments for SetTarget

Argument	Direction	relatedStateVariable
NewTargetValue	IN	Target

2.4.1.2. Effect on State (if any)

Requests the Power Switch Service instance output to be driven to the state indicated by *newTargetValue*.

2.4.1.3. Errors

Table 2-5: Error Codes for SetTarget

ErrorCode	errorDescription	Description
401	Invalid Action	See UPnP Device Architecture Section on Control.
402	Invalid Args	See UPnP Device Architecture Section on Control.
403	Out of Synch	See UPnP Device Architecture Section on Control.
501	Action Failed	See UPnP Device Architecture Section on Control.
600-699	TBD	Common action errors. Defined by the UPnP Forum Technical Committee.

2.4.2. GetTarget

Provided for testing and debugging purposes.

2.4.2.1. Arguments

Table 2-6: Arguments for GetTarget

Argument	Direction	relatedStateVariable
RetTargetValue	OUT	Target

2.4.2.2. Effect on State (if any)

None.

Requests the Power Switch Service instance to return the value of Target.

2.4.2.3. Errors

Table 2-7: Error Codes for GetTarget

ErrorCode	errorDescription	Description
401	Invalid Action	See UPnP Device Architecture Section on Control.
402	Invalid Args	See UPnP Device Architecture Section on Control.
403	Out of Synch	See UPnP Device Architecture Section on Control.
501	Action Failed	See UPnP Device Architecture Section on Control.
600-699	TBD	Common action errors. Defined by the UPnP Forum Technical Committee.

2.4.3. GetStatus

2.4.3.1. Arguments

Table 2-8: Arguments for GetStatus

Argument	Direction	relatedStateVariable
ResultStatus	OUT	Status

2.4.3.2. Effect on State

None.

Requests the Power Switch Service instance to return the value of Status.

2.4.3.3. Errors

Table 2-9: Error Codes for GetStatus

ErrorCode	ErrorDescription	Description
401	Invalid Action	See UPnP Device Architecture Section on Control.
402	Invalid Args	See UPnP Device Architecture Section on Control.
403	Out of Synch	See UPnP Device Architecture Section on Control.
501	Action Failed	See UPnP Device Architecture Section on Control.
600-699	TBD	Common action errors. Defined by the UPnP Forum Technical Committee.

2.4.4. Non-Standard Actions Implemented by a UPnP Vendor

To facilitate certification, non-standard actions implemented by UPnP vendors should be included in this service template. The UPnP Device Architecture lists naming requirements for non-standard actions (see the section on Description).

2.4.5. Common Error Codes

The following table lists error codes common to actions for this service type. If an action results in multiple errors, the most specific error must be returned.

Table 2-10: Common Error Codes

errorCode	errorDescription	Description
401	Invalid Action	See UPnP Device Architecture section on Control.
402	Invalid Args	See UPnP Device Architecture section on Control.
404	Invalid Var	See UPnP Device Architecture section on Control.
501	Action Failed	See UPnP Device Architecture section on Control.
600-699	TBD	Common action errors. Defined by UPnP Forum Technical Committee.
701-799		Common action errors defined by the UPnP Forum working committees.

errorCode	errorDescription	Description
800-899	TBD	(Specified by UPnP vendor.)

2.5. Theory of Operation

Instances of Power Switch Services are embedded into devices to provide a standard means of programmatic control over these embedding devices' powered-on (enabled/disabled) state, this being either on (1) or off (0).

This service model provides for situations where requested state changes may not result in actual one-for-one output state changes, reflected via the *Status* variable, for any number of reasons. For example if there are time delays involved or maybe the requested state can't be achieved because of a hardware failure.

In the simplest of cases the output state (*Status*) will always follow the requested state changes submitted via *SetTarget*.

There is also the situation where the *Status* variable could change state without any programmatic action against this model at all. For example, this could happen if there was a front-panel power control that was changed by a user.

3. XML Service Description

```

<?xml version="1.0"?>
<scpd xmlns="urn:schemas-upnp-org:service-1-0">
  <specVersion>
    <majormajorminorminorspecVersion>
  <actionList>
    <action>
      <namename>
      <argumentList>
        <argument>
          <namename>
          <relatedStateVariablerelatedStateVariable>
          <directiondirection>
        </argument>
      </argumentList>
    </action>
    <action>
      <namename>
      <argumentList>
        <argument>
          <namename>
          <relatedStateVariablerelatedStateVariable>
          <directiondirection>
        </argument>
      </argumentList>
    </action>
    <action>
      <namename>
      <argumentList>
        <argument>
          <namename>
          <relatedStateVariablerelatedStateVariable>
          <directiondirection>
        </argument>
      </argumentList>
    </action>
  <Declarations for other actions added by UPnP vendor (if any) go here>
</actionList>
<serviceStateTable>
  <stateVariable sendEvents="no">
    <namename>
    <dataTypedataType>
    <defaultValuedefaultValue>
  </stateVariable>
  <stateVariable sendEvents="yes">
    <namename>
    <dataTypedataType>
    <defaultValuedefaultValue>
  </stateVariable>
  <Declarations for other state variables added by UPnP vendor (if any) go here>
</serviceStateTable>

```

</**scpd**>

4. Test

Syntactical testing is performed by the UPnP test tool based on the XML description as provided in Section 3.

The working committee and the implementers have come to the conclusion that further test descriptions e.g. for semantical testing do not provide a higher level of interoperability.

Thus the XML description is deemed to be sufficient for testing of devices that implement this template and further test descriptions are not provided by this template.