
DigitalSecurityCameraStillImage:1 Service Template Version 1.01

For UPnP™ Version 1.0
Status: Standardized DCP
Date: March 24, 2005

This Standardized DCP has been adopted as a Standardized DCP by the Steering Committee of the UPnP™ Forum, pursuant to Section 2.1(c)(ii) of the UPnP™ Forum Membership Agreement. UPnP™ Forum Members have rights and licenses defined by Section 3 of the UPnP™ Forum Membership Agreement to use and reproduce the Standardized DCP in UPnP™ Compliant Devices. All such use is subject to all of the provisions of the UPnP™ Forum Membership Agreement.

THE UPNP™ FORUM TAKES NO POSITION AS TO WHETHER ANY INTELLECTUAL PROPERTY RIGHTS EXIST IN THE STANDARDIZED DCPS. THE STANDARDIZED DCPS ARE PROVIDED "AS IS" AND "WITH ALL FAULTS". THE UPNP™ FORUM MAKES NO WARRANTIES, EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE STANDARDIZED DCPS, INCLUDING BUT NOT LIMITED TO ALL IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT AND FITNESS FOR A PARTICULAR PURPOSE, OF REASONABLE CARE OR WORKMANLIKE EFFORT, OR RESULTS OR OF LACK OF NEGLIGENCE.

© 2005 Contributing Members of the UPnP™ Forum. All Rights Reserved.

Authors	Company
Joacim Tullberg	Axis Communications AB
Ted Hartzell	Axis Communications AB
Göran Haraldsson	Axis Communications AB

Contents

1. OVERVIEW AND SCOPE	4
2. SERVICE MODELING DEFINITIONS	5
2.1. SERVICE TYPE	5
2.2. STATE VARIABLES	5
2.2.1. AvailableEncodings	5
2.2.2. DefaultEncoding	5
2.2.3. AvailableCompressionLevels	5
2.2.4. DefaultCompressionLevel	6
2.2.5. AvailableResolutions	6
2.2.6. DefaultResolutions	6
2.2.7. ImageURL	6
2.2.8. ImagePresentationURL	6
2.3. EVENTING AND MODERATION	7
2.4. ACTIONS	8
2.4.1. GetAvailableEncodings	8
2.4.2. SetDefaultEncoding	9
2.4.3. GetDefaultEncoding	9
2.4.4. GetAvailableCompressionLevels	9
2.4.5. SetDefaultCompressionLevel	10
2.4.6. GetDefaultCompressionLevel	10
2.4.7. GetAvailableResolutions	10
2.4.8. SetDefaultResolution	11
2.4.9. GetDefaultResolution	11
2.4.10. GetImageURL	12
2.4.11. GetDefaultImageURL	12
2.4.12. GetImagePresentationURL	13
2.4.13. GetDefaultImagePresentationURL	13
2.4.14. Non-Standard Actions Implemented by a UPnP Vendor	14
2.4.15. Common Error Codes	14
2.5. THEORY OF OPERATION	15
3. XML SERVICE DESCRIPTION	16
4. TEST	20

List of Tables

Table 1: State Variables	5
Table 2: Event Moderation	7
Table 3: Actions	8
Table 4: Arguments for GetAvailableEncodings	8
Table 5: Arguments for SetDefaultEncoding	9
Table 6: Arguments for GetDefaultEncoding	9
Table 7: Arguments for GetAvailableCompressionLevels	9

Table 8: Arguments for <u>SetDefaultCompressionLevel</u>	10
Table 9: Arguments for <u>GetDefaultCompressionLevel</u>	10
Table 10: Arguments for <u>GetAvailableResolutions</u>	10
Table 11: Arguments for <u>SetDefaultResolution</u>	11
Table 12: Arguments for <u>GetDefaultResolution</u>	11
Table 13: Arguments for <u>GetImageURL</u>	12
Table 13: Arguments for <u>GetDefaultImageURL</u>	12
Table 14: Arguments for <u>GetImagePresentationURL</u>	13
Table 15: Arguments for <u>GetDefaultImagePresentationURL</u>	13
Table 16: Common Error Codes.....	14

1. Overview and Scope

This service definition is compliant with the UPnP Device Architecture version *1.0*.

The service enables delivery and control of live snapshot images from a digital security camera.

2. Service Modeling Definitions

2.1. ServiceType

A service that is compliant with this template is identified with the following service type: **urn:schemas-upnp-org:service: [DigitalSecurityCameraStillImage:1](#)**.

2.2. State Variables

Table 1: State Variables

Variable Name	Req. or Opt. ¹	Data Type	Allowed Value	Default Value	Eng. Units
AvailableEncodings	<i>R</i>	<i>string</i>			
DefaultEncoding	<i>R</i>	<i>string</i>			
AvailableCompressionLevels	<i>R</i>	<i>string</i>			
DefaultCompressionLevel	<i>R</i>	<i>string</i>			
AvailableResolutions	<i>R</i>	<i>string</i>			
DefaultResolutions	<i>R</i>	<i>string</i>			
ImageURL	<i>R</i>	<i>string</i>			
ImagePresentationURL	<i>R</i>	<i>string</i>			
<i>Non-standard state variables implemented by an UPnP vendor go here.</i>	X	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>

¹ R = Required, O = Optional, X = Non-standard.

2.2.1. AvailableEncodings

The value of this string should be a list of all by the vendor specific service supported MIME-type still image types. The types in the list should be separated by a “,”.

Example: image/jpeg, image/gif, image/bmp

This is a read only property.

2.2.2. DefaultEncoding

The value of this string must be a MIME-type still image type. Any MIME still image type listed in AvailableEncodings may be used as an allowed value.

2.2.3. AvailableCompressionLevels

Compression level describes how much an image should be compressed. Since a wide variety of compression methods and algorithms are available compression levels become subjective values that are hard to quantify. The value of this string should be a list of all supported compression levels separated by a “,”. The list order should be the lowest compression level first.

Example1: 0, 1, 2, 3, 4, 5

Example2: Lowest, Highest

This is a read only property.

2.2.4. DefaultCompressionLevel

The value of this string must be one of the supported compression levels specified in AvailableCompressionLevels.

AvailableEncodings may be used as an allowed value.

2.2.5. AvailableResolutions

Resolution is the actual number of horizontal and vertical pixels an image contains. It does not tell anything of the image quality apart from the size in pixels. There must be at least one resolution available. Presented in ascending order based on first the value of X multiplied by Y and as second order the value of X. Always formatted as "XxY". Where X is the horizontal number of pixels and Y the vertical number of pixels.

Example: 320x240, 640x480

This is a read only property.

Resolution is always based on Rotation = 0.

(See: Security Camera Settings Service for more information)

2.2.6. DefaultResolutions

The value of this string must be one of the supported resolutions specified in AvailableResolutions.

2.2.7. ImageURL

The ImageURL is the URL for the image itself.

This is a read only property.

2.2.8. ImagePresentationURL

This is the URL for an html presentation page of the current image. The typical implementation would be an html page that includes the ImageURL. This field must exist but may contain the empty string.

2.3. Eventing and Moderation

Table 2: Event Moderation

Variable Name	Evented	Moderated Event	Max Event Rate ¹	Logical Combination	Min Delta per Event ²
<u>AvailableEncodings</u>	<u>No</u>	<u>No</u>	<u>N/A</u>		<u>N/A</u>
<u>DefaultEncoding</u>	<u>Yes</u>	<u>No</u>	<u>N/A</u>		<u>N/A</u>
<u>AvailableCompressionLevels</u>	<u>No</u>	<u>No</u>	<u>N/A</u>		<u>N/A</u>
<u>DefaultCompressionLevel</u>	<u>Yes</u>	<u>No</u>	<u>N/A</u>		<u>N/A</u>
<u>AvailableResolutions</u>	<u>No</u>	<u>No</u>	<u>N/A</u>		<u>N/A</u>
<u>DefaultResolution</u>	<u>Yes</u>	<u>No</u>	<u>N/A</u>		<u>N/A</u>
<u>ImageURL</u>	<u>No</u>	<u>No</u>	<u>N/A</u>		<u>N/A</u>
<u>ImagePresentationURL</u>	<u>No</u>	<u>No</u>	<u>N/A</u>		<u>N/A</u>
<i>Non-standard state variables implemented by an UPnP vendor go here.</i>	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>

¹ Determined by N, where Rate = (Event)/(N secs).

² (N) * (allowedValueRange Step).

2.4. Actions

Immediately following this table is detailed information about these actions, including short descriptions of the actions, the effects of the actions on state variables, and error codes defined by the actions.

Table 3: Actions

Name	Req. or Opt. ¹
<u>GetAvailableEncodings</u>	<u>R</u>
<u>SetDefaultEncoding</u>	<u>R</u>
<u>GetDefaultEncoding</u>	<u>R</u>
<u>GetAvailableCompressionLevels</u>	<u>R</u>
<u>SetDefaultCompressionLevel</u>	<u>R</u>
<u>GetDefaultCompressionLevel</u>	<u>R</u>
<u>GetAvailableResolutions</u>	<u>R</u>
<u>SetDefaultResolution</u>	<u>R</u>
<u>GetDefaultResolution</u>	<u>R</u>
<u>GetImageURL</u>	<u>R</u>
<u>GetDefaultImageURL</u>	<u>R</u>
<u>GetImagePresentationURL</u>	<u>R</u>
<u>GetDefaultImagePresentationURL</u>	<u>R</u>
<i>Non-standard actions implemented by an UPnP vendor go here.</i>	<u>X</u>

¹ R = Required, O = Optional, X = Non-standard.

2.4.1. GetAvailableEncodings

Get the list of supported MIME-type still image types.

2.4.1.1. Arguments

Table 4: Arguments for [GetAvailableEncodings](#)

Argument	Direction	relatedStateVariable
<u>RetAvailableEncodings</u>	<u>OUT</u>	<u>AvailableEncodings</u>

2.4.2. SetDefaultEncoding

Set the DefaultEncoding.

2.4.2.1. Arguments

Table 5: Arguments for [SetDefaultEncoding](#)

Argument	Direction	relatedStateVariable
<u>ReqEncoding</u>	<u>IN</u>	<u>DefaultEncoding</u>

2.4.2.2. Effect on State

Changes the value of DefaultEncoding to ReqEncoding.

2.4.2.3. Errors

errorCode	errorDescription	Description
<u>700</u>	<u>ReqEncoding not supported</u>	ReqEncoding is not one of the supported encodings specified in AvailableEncodings.

2.4.3. GetDefaultEncoding

Get the DefaultEncoding.

2.4.3.1. Arguments

Table 6: Arguments for [GetDefaultEncoding](#)

Argument	Direction	relatedStateVariable
<u>RetEncoding</u>	<u>OUT</u>	<u>DefaultEncoding</u>

2.4.4. GetAvailableCompressionLevels

Get the list of supported compression levels.

2.4.4.1. Arguments

Table 7: Arguments for [GetAvailableCompressionLevels](#)

Argument	Direction	relatedStateVariable
<u>RetAvailableCompressionLevels</u>	<u>OUT</u>	<u>AvailableCompressionLevels</u>

2.4.5. SetDefaultCompressionLevel

Set the DefaultCompressionLevel.

2.4.5.1. Arguments

Table 8: Arguments for [SetDefaultCompressionLevel](#)

Argument	Direction	relatedStateVariable
<u>ReqCompressionLevel</u>	<u>IN</u>	<u>DefaultCompressionLevel</u>

2.4.5.2. Effect on State

Changes the value of DefaultCompressionLevel to ReqCompressionLevel.

2.4.5.3. Errors

errorCode	errorDescription	Description
<u>701</u>	<u>ReqCompressionLevel not supported</u>	ReqCompressionLevel is not one of the supported compression levels specified in AvailableCompressionLevels.

2.4.6. GetDefaultCompressionLevel

Get the DefaultCompressionLevel.

2.4.6.1. Arguments

Table 9: Arguments for [GetDefaultCompressionLevel](#)

Argument	Direction	relatedStateVariable
<u>RetCompressionLevel</u>	<u>OUT</u>	<u>DefaultCompressionLevel</u>

2.4.7. GetAvailableResolutions

Get the list of supported resolutions.

2.4.7.1. Arguments

Table 10: Arguments for [GetAvailableResolutions](#)

Argument	Direction	relatedStateVariable
<u>RetAvailableResolutions</u>	<u>OUT</u>	<u>AvailableResolutions</u>

2.4.8. SetDefaultResolution

Set the DefaultResolution.

2.4.8.1. Arguments

Table 11: Arguments for SetDefaultResolution

Argument	Direction	relatedStateVariable
<u>ReqResolution</u>	<u>IN</u>	<u>DefaultResolution</u>

2.4.8.2. Effect on State

Changes the value of DefaultResolution to ReqResolution.

2.4.8.3. Errors

errorCode	errorDescription	Description
<u>702</u>	<u>ReqResolution not supported</u>	ReqResolution is not one of the supported resolutions specified in AvailableResolutions.

2.4.9. GetDefaultResolution

Get the DefaultResolution.

2.4.9.1. Arguments

Table 12: Arguments for GetDefaultResolution

Argument	Direction	relatedStateVariable
<u>RetResolution</u>	<u>OUT</u>	<u>DefaultResolution</u>

2.4.10. GetImageURL

Get a URL to the image itself. The RetImageURL is being built depending on how the different parameters has been set.

ReqEncoding should be one of the supported encodings.

ReqCompression should be one of the supported compressions.

ReqResolution should be one of the supported resolutions.

2.4.10.1. Arguments

Table 13: Arguments for [GetImageURL](#)

Argument	Direction	relatedStateVariable
ReqEncoding	IN	DefaultEncoding
ReqCompression	IN	DefaultCompression
ReqResolution	IN	DefaultResolution
RetImageURL	OUT	ImageURL

2.4.10.2. Errors

errorCode	errorDescription	Description
700	ReqEncoding not supported	ReqEncoding is not one of the supported encodings specified in AvailableEncodings.
701	ReqCompressionLevel not supported	ReqCompressionLevel is not one of the supported compression levels specified in AvailableCompressionLevels.
702	ReqResolution not supported	ReqResolution is not one of the supported resolutions specified in AvailableResolutions.

2.4.11. GetDefaultImageURL

Get a URL to the image itself. The RetImageURL is being built depending on how the different default parameters DefaultEncoding, DefaultCompressionLevel and DefaultResolution has been set.

2.4.11.1. Arguments

Table 13: Arguments for [GetDefaultImageURL](#)

Argument	Direction	relatedStateVariable
RetImageURL	OUT	ImageURL

2.4.12. GetImagePresentationURL

Get a URL to an html presentation page of the current image.

The ReqImagePresentationURL is being built depending on how the different parameters has been set.

ReqEncoding should be one of the supported encodings.

ReqCompression should be one of the supported compressions.

ReqResolution should be one of the supported resolutions.

2.4.12.1. Arguments

Table 14: Arguments for [GetImagePresentationURL](#)

Argument	Direction	relatedStateVariable
<u>ReqEncoding</u>	<u>IN</u>	<u>DefaultEncoding</u>
<u>ReqCompression</u>	<u>IN</u>	<u>DefaultCompression</u>
<u>ReqResolution</u>	<u>IN</u>	<u>DefaultResolution</u>
<u>RetImagePresentationURL</u>	<u>OUT</u>	<u>ImagePresentationURL</u>

2.4.12.2. Errors

errorCode	errorDescription	Description
<u>700</u>	<u>ReqEncoding not supported</u>	ReqEncoding is not one of the supported encodings specified in AvailableEncodings.
<u>701</u>	<u>ReqCompressionLevel not supported</u>	ReqCompressionLevel is not one of the supported compression levels specified in AvailableCompressionLevels.
<u>702</u>	<u>ReqResolution not supported</u>	ReqResolution is not one of the supported resolutions specified in AvailableResolutions.

2.4.13. GetDefaultImagePresentationURL

Get a URL to an html presentation page of the current image. The RetImagePresentationURL is being built depending on how the different default parameters DefaultEncoding, DefaultCompressionLevel and DefaultResolution has been set.

2.4.13.1. Arguments

Table 15: Arguments for [GetDefaultImagePresentationURL](#)

Argument	Direction	relatedStateVariable
<u>RetImagePresentationURL</u>	<u>OUT</u>	<u>ImagePresentationURL</u>

2.4.14. Non-Standard Actions Implemented by a UPnP Vendor

To facilitate certification, non-standard actions implemented by UPnP vendors should be included in this service template. The UPnP Device Architecture lists naming requirements for non-standard actions (see the section on Description).

2.4.15. Common Error Codes

The following table lists error codes common to actions for this service type. If an action results in multiple errors, the most specific error should be returned.

Table 16: Common Error Codes

errorCode	errorDescription	Description
401	Invalid Action	See UPnP Device Architecture section on Control.
402	Invalid Args	See UPnP Device Architecture section on Control.
404	Invalid Var	See UPnP Device Architecture section on Control.
501	Action Failed	See UPnP Device Architecture section on Control.
600-699	TBD	Common action errors. Defined by UPnP Forum Technical Committee.
<u>700</u>	<u>ReqEncoding not supported</u>	ReqEncoding is not one of the supported encodings specified in AvailableEncodings.
<u>701</u>	<u>ReqCompressionLevel not supported</u>	ReqCompressionLevel is not one of the supported compression levels specified in AvailableCompressionLevels.
<u>702</u>	<u>ReqResolution not supported</u>	ReqResolution is not one of the supported resolutions specified in AvailableResolutions.
800-899	TBD	<i>(Specified by UPnP vendor.)</i>

2.5. Theory of Operation

An instance of Digital Security Camera Still Image Service may be embedded into a Digital Security Camera Device or other devices requiring this service.

This service will enable access to live snapshot still images by providing the retrieval address of the desired image. The retrieval address will be in the form of a complete URL.

Method of image data transfer is in no way restricted by this specification, implementers are free to use any available transport protocols that can be described in the form of a URL.

The operation of this service is “stateless”. The action of fetching an ImageURL or ImagePresentationURL does not affect the properties of previous, simultaneous or later fetched Image and ImagePresentation URLs. This allows for multiple User Control Points to receive images with different properties without potential interference.

The properties AvailableResolutions, AvailableCompressionLevels and AvailableEncodings are vendor specific descriptions of the complete set of available options of the matching property.

The ImageURL property is the URL where the image (file) itself can be fetched.

The ImagePresentationURL is a container document needed for *display* of the image by a user control point. This does for instance allow for display of images that require special image viewers such as ActiveX components or Java applets.

3. XML Service Description

```

<?xml version="1.0"?>
<scpd xmlns="urn:schemas-upnp-org:service-1-0">
  <specVersion>
    <major>1</major>
    <minor>0</minor>
  </specVersion>
  <actionList>
    <action>
      <name>GetAvailableEncodings</name>
      <argumentList>
        <argument>
          <name>RetAvailableEncodings</name>
          <relatedStateVariable>AvailableEncodings
          </relatedStateVariable>
          <direction>out</direction>
        </argument>
      </argumentList>
    </action>
    <action>
      <name>GetDefaultEncoding</name>
      <argumentList>
        <argument>
          <name>RetEncoding</name>
          <relatedStateVariable>DefaultEncoding</relatedStateVariable>
          <direction>out</direction>
        </argument>
      </argumentList>
    </action>
    <action>
      <name>SetDefaultEncoding</name>
      <argumentList>
        <argument>
          <name>ReqEncoding</name>
          <relatedStateVariable>DefaultEncoding</relatedStateVariable>
          <direction>in</direction>
        </argument>
      </argumentList>
    </action>
    <action>
      <name>GetAvailableCompressionLevels</name>
      <argumentList>
        <argument>
          <name>RetAvailableCompressionLevels</name>
          <relatedStateVariable>AvailableCompressionLevels
          </relatedStateVariable>
          <direction>out</direction>
        </argument>
      </argumentList>
    </action>
    <action>
      <name>GetDefaultCompressionLevel</name>
      <argumentList>
        <argument>

```

```

    <name>RetCompressionLevel</name>
    <relatedStateVariable>DefaultCompressionLevel
  </relatedStateVariable>
  <direction>out</direction>
</argument>
</argumentList>
</action>
<action>
<name>SetDefaultCompressionLevel</name>
  <argumentList>
    <argument>
      <name>ReqCompressionLevel</name>
      <relatedStateVariable>DefaultCompressionLevel
    </relatedStateVariable>
      <direction>in</direction>
    </argument>
  </argumentList>
</action>
<action>
<name>GetAvailableResolutions</name>
  <argumentList>
    <argument>
      <name>RetAvailableResolutions</name>
      <relatedStateVariable>AvailableResolutions
    </relatedStateVariable>
      <direction>out</direction>
    </argument>
  </argumentList>
</action>
<action>
<name>GetDefaultResolution</name>
  <argumentList>
    <argument>
      <name>RetResolution</name>
      <relatedStateVariable>DefaultResolution
    </relatedStateVariable>
      <direction>out</direction>
    </argument>
  </argumentList>
</action>
<action>
<name>SetDefaultResolution</name>
  <argumentList>
    <argument>
      <name>ReqResolution</name>
      <relatedStateVariable>DefaultResolution
    </relatedStateVariable>
      <direction>in</direction>
    </argument>
  </argumentList>
</action>
<action>
<name>GetImageURL</name>
  <argumentList>
    <argument>
      <name>ReqEncoding</name>

```

```

    <relatedStateVariable>DefaultEncoding</relatedStateVariable>
    <direction>in</direction>
  </argument>
  <argument>
    <name>ReqCompression</name>
    <relatedStateVariable>DefaultCompressionLevel
  </relatedStateVariable>
    <direction>in</direction>
  </argument>
  <argument>
    <name>ReqResolution</name>
    <relatedStateVariable>DefaultResolution
  </relatedStateVariable>
    <direction>in</direction>
  </argument>
  <argument>
    <name>RetImageURL</name>
    <relatedStateVariable>ImageURL
  </relatedStateVariable>
    <direction>out</direction>
  </argument>
</argumentList>
</action>
<action>
  <name>GetDefaultImageURL</name>
  <argumentList>
    <argument>
      <name>RetImageURL</name>
      <relatedStateVariable>ImageURL
    </relatedStateVariable>
      <direction>out</direction>
    </argument>
  </argumentList>
</action>
<action>
  <name>GetImagePresentationURL</name>
  <argumentList>
    <argument>
      <name>ReqEncoding</name>
      <relatedStateVariable>DefaultEncoding</relatedStateVariable>
      <direction>in</direction>
    </argument>
    <argument>
      <name>ReqCompression</name>
      <relatedStateVariable>DefaultCompressionLevel
    </relatedStateVariable>
      <direction>in</direction>
    </argument>
    <argument>
      <name>ReqResolution</name>
      <relatedStateVariable>DefaultResolution
    </relatedStateVariable>
      <direction>in</direction>
    </argument>
    <argument>
      <name>RetImagePresentationURL</name>

```

```

    <relatedStateVariable>ImagePresentationURL
  </relatedStateVariable>
  <direction>out</direction>
</argument>
</argumentList>
</action>
<action>
<name>GetDefaultImagePresentationURL</name>
  <argumentList>
    <argument>
      <name>RetImagePresentationURL</name>
      <relatedStateVariable>ImagePresentationURL
    </relatedStateVariable>
      <direction>out</direction>
    </argument>
  </argumentList>
</action>
</actionList>
<serviceStateTable>
  <stateVariable sendEvents="no">
    <name>AvailableEncodings</name>
    <dataType>string</dataType>
  </stateVariable>
  <stateVariable sendEvents="yes">
    <name>DefaultEncoding</name>
    <dataType>string</dataType>
  </stateVariable>
  <stateVariable sendEvents="no">
    <name>AvailableCompressionLevels</name>
    <dataType>string</dataType>
  </stateVariable>
  <stateVariable sendEvents="yes">
    <name>DefaultCompressionLevel</name>
    <dataType>string</dataType>
  </stateVariable>
  <stateVariable sendEvents="no">
    <name>AvailableResolutions</name>
    <dataType>string</dataType>
  </stateVariable>
  <stateVariable sendEvents="yes">
    <name>DefaultResolution</name>
    <dataType>string</dataType>
  </stateVariable>
  <stateVariable sendEvents="no">
    <name>ImageURL</name>
    <dataType>string</dataType>
  </stateVariable>
  <stateVariable sendEvents="no">
    <name>ImagePresentationURL</name>
    <dataType>string</dataType>
  </stateVariable>
</serviceStateTable>
</scpd>

```

4. Test

Testing of the UPnP functions Addressing, Discovery, Description, Control (Syntax) and Eventing are performed by the UPnP Test Tool v1.1 based on the following documents:

- UPnP Device Architecture v1.0
- The Service Definitions in chapter 2 of this document
- The XML Service Description in chapter 3 of this document
- The UPnP Test Tool service template test file: *DigitalSecurityCameraStillImage1.xml*
- The UPnP Test Tool service template test file:
DigitalSecurityCameraStillImage1.SyntaxTests.xml

The test suite does not include tests for Control Semantics, since it is felt that such tests would not provide a higher level of interoperability.