

# [MS-ADA1]: Active Directory Schema Attributes A-L

---

This document contains a partial list of the objects that exist in the Microsoft Active Directory schema. Active Directory and all associated terms and concepts are described in the document titled "Active Directory Technical Specification", which has the following normative reference:

[MS-ADTS] Microsoft Corporation, "[Active Directory Technical Specification](#)", June 2007.

**Note** This document is not intended to stand on its own; it is intended to act as an appendix to the Active Directory Technical Specification, as specified in the normative reference shown above. For details about the Active Directory schema, see [\[MS-ADTS\]](#) section 3.1.1.2 (Active Directory Schema).

This document contains Active Directory schema objects of type "attribute" whose names start with the letters A through L.

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No

association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
02/22/2007	0.01		MCPP Milestone 3 Initial Availability
06/01/2007	1.0	Major	Updated and revised the technical content.
07/03/2007	1.0.1	Editorial	Revised and edited the technical content.
07/20/2007	1.0.2	Editorial	Revised and edited the technical content.
08/10/2007	1.0.3	Editorial	Revised and edited the technical content.
09/28/2007	1.0.4	Editorial	Revised and edited the technical content.
10/23/2007	1.0.5	Editorial	Revised and edited the technical content.
11/30/2007	2.0	Major	Updated and revised the technical content.
01/25/2008	3.0	Major	Updated and revised the technical content.
03/14/2008	3.1	Minor	Clarified status of several attributes.
05/16/2008	3.1.1	Editorial	Revised and edited the technical content.
06/20/2008	3.1.2	Editorial	Revised and edited the technical content.
07/25/2008	4.0	Major	Updated and revised the technical content.
08/29/2008	5.0	Major	Updated and revised the technical content.
10/24/2008	6.0	Major	Updated and revised the technical content.
12/05/2008	7.0	Major	Updated and revised the technical content.
01/16/2009	7.0.1	Editorial	Revised and edited the technical content.
02/27/2009	7.0.2	Editorial	Revised and edited the technical content.
04/10/2009	8.0	Major	Updated and revised the technical content.

<b>Date</b>	<b>Revision History</b>	<b>Revision Class</b>	<b>Comments</b>
05/22/2009	8.1	Minor	Updated the technical content.
07/02/2009	8.2	Minor	Updated the technical content.
08/14/2009	8.2.1	Editorial	Revised and edited the technical content.
09/25/2009	8.2.2	Editorial	Revised and edited the technical content.
11/06/2009	8.3	Minor	Updated the technical content.
12/18/2009	9.0	Major	Updated and revised the technical content.
01/29/2010	10.0	Major	Updated and revised the technical content.
03/12/2010	11.0	Major	Updated and revised the technical content.
04/23/2010	12.0	Major	Updated and revised the technical content.
06/04/2010	13.0	Major	Updated and revised the technical content.
07/16/2010	13.1	Minor	Clarified the meaning of the technical content.
08/27/2010	14.0	Major	Significantly changed the technical content.
10/08/2010	15.0	Major	Significantly changed the technical content.
11/19/2010	16.0	Major	Significantly changed the technical content.
01/07/2011	17.0	Major	Significantly changed the technical content.
02/11/2011	18.0	Major	Significantly changed the technical content.

## Contents

<b>1 References .....</b>	<b>12</b>
<b>2 Attributes .....</b>	<b>14</b>
2.1 Attribute accountExpires .....	14
2.2 Attribute accountNameHistory .....	14
2.3 Attribute aCSAggregateTokenRatePerUser .....	15
2.4 Attribute aCSAllocableRSVPBandwidth .....	15
2.5 Attribute aCSCacheTimeout .....	15
2.6 Attribute aCSDirection .....	16
2.7 Attribute aCSDSBMDeadTime .....	16
2.8 Attribute aCSDSBMPriority .....	16
2.9 Attribute aCSDSBMRefresh .....	17
2.10 Attribute acSEnableACSService .....	17
2.11 Attribute acSEnableRSVPAccounting .....	18
2.12 Attribute acSEnableRSVPMessageLogging .....	18
2.13 Attribute acSEventLogLevel .....	18
2.14 Attribute acSIdentityName .....	19
2.15 Attribute acSMaxAggregatePeakRatePerUser .....	19
2.16 Attribute acSMaxDurationPerFlow .....	19
2.17 Attribute acSMaximumSDUSize .....	20
2.18 Attribute acSMaxNoOfAccountFiles .....	20
2.19 Attribute acSMaxNoOfLogFile .....	21
2.20 Attribute acSMaxPeakBandwidth .....	21
2.21 Attribute acSMaxPeakBandwidthPerFlow .....	21
2.22 Attribute acSMaxSizeOfRSVPAccountFile .....	22
2.23 Attribute acSMaxSizeOfRSVPLogFile .....	22
2.24 Attribute acSMaxTokenBucketPerFlow .....	22
2.25 Attribute acSMaxTokenRatePerFlow .....	23
2.26 Attribute acSMinimumDelayVariation .....	23
2.27 Attribute acSMinimumLatency .....	24
2.28 Attribute acSMinimumPolicedSize .....	24
2.29 Attribute acSNonReservedMaxSDUSize .....	24
2.30 Attribute acSNonReservedMinPolicedSize .....	25
2.31 Attribute acSNonReservedPeakRate .....	25
2.32 Attribute acSNonReservedTokenSize .....	25
2.33 Attribute acSNonReservedTxLimit .....	26
2.34 Attribute acSNonReservedTxSize .....	26
2.35 Attribute acSPermissionBits .....	27
2.36 Attribute acSPolicyName .....	27
2.37 Attribute acSPriority .....	27
2.38 Attribute acSRSPVAccountFilesLocation .....	28
2.39 Attribute acSRSPVLogFileLocation .....	28
2.40 Attribute acSServerList .....	28
2.41 Attribute acSServiceType .....	29
2.42 Attribute acSTimeOfDay .....	29
2.43 Attribute acSTotalNoOfFlows .....	30
2.44 Attribute additionalTrustedServiceNames .....	30
2.45 Attribute addressBookRoots .....	30
2.46 Attribute addressBookRoots2 .....	31
2.47 Attribute addressEntryDisplayTable .....	31

2.48	Attribute addressEntryDisplayTableMSDOS.....	32
2.49	Attribute addressSyntax .....	32
2.50	Attribute addressType .....	33
2.51	Attribute adminContextMenu .....	33
2.52	Attribute adminCount .....	33
2.53	Attribute adminDescription.....	34
2.54	Attribute adminDisplayName .....	34
2.55	Attribute adminMultiSelectPropertyPages.....	35
2.56	Attribute adminPropertyPages .....	35
2.57	Attribute allowedAttributes.....	36
2.58	Attribute allowedAttributesEffective .....	36
2.59	Attribute allowedChildClasses .....	36
2.60	Attribute allowedChildClassesEffective .....	37
2.61	Attribute altSecurityIdentities .....	37
2.62	Attribute anR .....	38
2.63	Attribute applicationName .....	38
2.64	Attribute appliesTo .....	39
2.65	Attribute appSchemaVersion .....	39
2.66	Attribute assetNumber.....	39
2.67	Attribute assistant.....	40
2.68	Attribute associatedDomain.....	40
2.69	Attribute associatedName .....	41
2.70	Attribute assocNTAccount .....	41
2.71	Attribute attributeCertificateAttribute .....	41
2.72	Attribute attributeDisplayNames .....	42
2.73	Attribute attributeID.....	42
2.74	Attribute attributeSecurityGUID .....	42
2.75	Attribute attributeSyntax .....	43
2.76	Attribute attributeTypes.....	43
2.77	Attribute audio .....	44
2.78	Attribute auditingPolicy .....	44
2.79	Attribute authenticationOptions .....	44
2.80	Attribute authorityRevocationList .....	45
2.81	Attribute auxiliaryClass .....	45
2.82	Attribute badPasswordTime .....	46
2.83	Attribute badPwdCount .....	46
2.84	Attribute birthLocation .....	47
2.85	Attribute bootFile .....	47
2.86	Attribute bootParameter .....	47
2.87	Attribute bridgeheadServerListBL .....	48
2.88	Attribute bridgeheadTransportList .....	48
2.89	Attribute buildingName .....	48
2.90	Attribute builtinCreationTime .....	49
2.91	Attribute builtinModifiedCount.....	49
2.92	Attribute businessCategory .....	50
2.93	Attribute bytesPerMinute.....	50
2.94	Attribute c.....	50
2.95	Attribute cACertificate .....	51
2.96	Attribute cACertificateDN .....	51
2.97	Attribute cAConnect .....	52
2.98	Attribute canonicalName .....	52
2.99	Attribute canUpgradeScript .....	53
2.100	Attribute carLicense.....	53

2.101	Attribute catalogs.....	53
2.102	Attribute categories .....	54
2.103	Attribute categoryId .....	54
2.104	Attribute cAUUsages.....	54
2.105	Attribute cAWEBURL.....	55
2.106	Attribute certificateAuthorityObject.....	55
2.107	Attribute certificateRevocationList .....	56
2.108	Attribute certificateTemplates .....	56
2.109	Attribute classDisplayName .....	56
2.110	Attribute cn .....	57
2.111	Attribute co .....	57
2.112	Attribute codePage .....	58
2.113	Attribute cOMClassID.....	58
2.114	Attribute cOMCLSID.....	58
2.115	Attribute cOMInterfaceID .....	59
2.116	Attribute comment .....	59
2.117	Attribute cOMOtherProgId .....	60
2.118	Attribute company.....	60
2.119	Attribute cOMPProgID.....	60
2.120	Attribute cOMTreatAsClassId .....	61
2.121	Attribute cOMTypeLibId .....	61
2.122	Attribute cOMUniqueLIBID.....	62
2.123	Attribute contentIndexingAllowed .....	62
2.124	Attribute contextMenu .....	62
2.125	Attribute controlAccessRights.....	63
2.126	Attribute cost.....	63
2.127	Attribute countryCode.....	63
2.128	Attribute createDialog .....	64
2.129	Attribute createTimeStamp.....	64
2.130	Attribute createWizardExt .....	65
2.131	Attribute creationTime .....	65
2.132	Attribute creationWizard .....	65
2.133	Attribute creator .....	66
2.134	Attribute cRLObject .....	66
2.135	Attribute cRLPartitionedRevocationList .....	67
2.136	Attribute crossCertificatePair.....	67
2.137	Attribute currentLocation.....	67
2.138	Attribute currentParentCA .....	68
2.139	Attribute currentValue .....	68
2.140	Attribute currMachineId .....	69
2.141	Attribute dBCSPwd .....	69
2.142	Attribute dc .....	69
2.143	Attribute defaultClassStore .....	70
2.144	Attribute defaultGroup .....	70
2.145	Attribute defaultHidingValue .....	71
2.146	Attribute defaultLocalPolicyObject .....	71
2.147	Attribute defaultObjectCategory .....	71
2.148	Attribute defaultPriority.....	72
2.149	Attribute defaultSecurityDescriptor .....	72
2.150	Attribute deltaRevocationList .....	73
2.151	Attribute department .....	73
2.152	Attribute departmentNumber .....	73
2.153	Attribute description .....	74

2.154 Attribute desktopProfile.....	74
2.155 Attribute destinationIndicator .....	75
2.156 Attribute dhcpClasses .....	75
2.157 Attribute dhcpFlags .....	75
2.158 Attribute dhcpIdentification .....	76
2.159 Attribute dhcpMask.....	76
2.160 Attribute dhcpMaxKey.....	76
2.161 Attribute dhcpObjDescription .....	77
2.162 Attribute dhcpObjName.....	77
2.163 Attribute dhcpOptions .....	77
2.164 Attribute dhcpProperties.....	78
2.165 Attribute dhcpRanges .....	78
2.166 Attribute dhcpReservations.....	78
2.167 Attribute dhcpServers .....	79
2.168 Attribute dhcpSites.....	79
2.169 Attribute dhcpState .....	79
2.170 Attribute dhcpSubnets .....	80
2.171 Attribute dhcpType.....	80
2.172 Attribute dhcpUniqueKey.....	80
2.173 Attribute dhcpUpdateTime .....	81
2.174 Attribute directReports.....	81
2.175 Attribute displayName .....	81
2.176 Attribute displayNamePrintable .....	82
2.177 Attribute distinguishedName.....	82
2.178 Attribute dITContentRules .....	83
2.179 Attribute division.....	83
2.180 Attribute dMDLocation .....	84
2.181 Attribute dmdName .....	84
2.182 Attribute dNReferenceUpdate.....	85
2.183 Attribute dnsAllowDynamic.....	85
2.184 Attribute dnsAllowXFR .....	85
2.185 Attribute dNSHostName .....	86
2.186 Attribute dnsNotifySecondaries .....	86
2.187 Attribute dNSProperty .....	87
2.188 Attribute dnsRecord.....	87
2.189 Attribute dnsRoot .....	87
2.190 Attribute dnsSecureSecondaries .....	88
2.191 Attribute dNSTombstoned .....	88
2.192 Attribute documentAuthor .....	89
2.193 Attribute documentIdentifier.....	89
2.194 Attribute documentLocation .....	89
2.195 Attribute documentPublisher.....	90
2.196 Attribute documentTitle .....	90
2.197 Attribute documentVersion .....	90
2.198 Attribute domainCAs.....	91
2.199 Attribute domainCrossRef.....	91
2.200 Attribute domainID.....	91
2.201 Attribute domainIdentifier .....	92
2.202 Attribute domainPolicyObject .....	92
2.203 Attribute domainPolicyReference .....	92
2.204 Attribute domainReplica .....	93
2.205 Attribute domainWidePolicy .....	93
2.206 Attribute drink .....	94

2.207	Attribute driverName .....	94
2.208	Attribute driverVersion.....	94
2.209	Attribute dSASignature .....	95
2.210	Attribute dSCorePropagationData .....	95
2.211	Attribute dSHeuristics .....	96
2.212	Attribute dSUIAdminMaximum .....	96
2.213	Attribute dSUIAdminNotification.....	96
2.214	Attribute dSUIShellMaximum .....	97
2.215	Attribute dynamicLDAPServer .....	97
2.216	Attribute eFSPolicy .....	97
2.217	Attribute employeeID .....	98
2.218	Attribute employeeNumber.....	98
2.219	Attribute employeeType .....	99
2.220	Attribute Enabled .....	99
2.221	Attribute enabledConnection.....	100
2.222	Attribute enrollmentProviders .....	100
2.223	Attribute entryTTL .....	100
2.224	Attribute extendedAttributeInfo .....	101
2.225	Attribute extendedCharsAllowed.....	101
2.226	Attribute extendedClassInfo .....	102
2.227	Attribute extensionName.....	102
2.228	Attribute extraColumns .....	103
2.229	Attribute facsimileTelephoneNumber.....	103
2.230	Attribute fileExtPriority.....	104
2.231	Attribute flags.....	104
2.232	Attribute flatName.....	104
2.233	Attribute forceLogoff.....	105
2.234	Attribute foreignIdentifier.....	105
2.235	Attribute friendlyNames .....	106
2.236	Attribute fromEntry .....	106
2.237	Attribute fromServer .....	106
2.238	Attribute frsComputerReference .....	107
2.239	Attribute frsComputerReferenceBL.....	107
2.240	Attribute fRSControlDataCreation .....	108
2.241	Attribute fRSControlInboundBacklog .....	108
2.242	Attribute fRSControlOutboundBacklog.....	108
2.243	Attribute fRSDirectoryFilter.....	109
2.244	Attribute fRSDSPoll.....	109
2.245	Attribute fRSExtensions .....	110
2.246	Attribute fRSFaultCondition .....	110
2.247	Attribute fRSFileFilter.....	110
2.248	Attribute fRSFlags .....	111
2.249	Attribute fRSLevelLimit .....	111
2.250	Attribute fRSMemberReference .....	111
2.251	Attribute fRSMemberReferenceBL.....	112
2.252	Attribute fRSPartnerAuthLevel .....	112
2.253	Attribute fRSPrimaryMember .....	113
2.254	Attribute fRSReplicaSetGUID .....	113
2.255	Attribute fRSReplicaSetType .....	113
2.256	Attribute fRSRootPath .....	114
2.257	Attribute fRSRootSecurity.....	114
2.258	Attribute fRSServiceCommand .....	115
2.259	Attribute fRSServiceCommandStatus .....	115

2.260	Attribute fRSStagingPath.....	115
2.261	Attribute frSTimeLastCommand.....	116
2.262	Attribute frSTimeLastConfigChange.....	116
2.263	Attribute fRSUpdateTimeout .....	117
2.264	Attribute fRSVersion .....	117
2.265	Attribute fRSVersionGUID.....	117
2.266	Attribute fRSWorkingPath.....	118
2.267	Attribute fSMORoleOwner.....	118
2.268	Attribute garbageCollPeriod .....	119
2.269	Attribute gecos .....	119
2.270	Attribute generatedConnection.....	119
2.271	Attribute generationQualifier.....	120
2.272	Attribute gidNumber .....	120
2.273	Attribute givenName.....	120
2.274	Attribute globalAddressList .....	121
2.275	Attribute globalAddressList2 .....	121
2.276	Attribute governsID .....	122
2.277	Attribute gPCFileSysPath .....	122
2.278	Attribute gPCFunctionalityVersion .....	123
2.279	Attribute gPCMchineExtensionNames .....	123
2.280	Attribute gPCUserExtensionNames .....	123
2.281	Attribute gPCWQLFilter .....	124
2.282	Attribute gPLink .....	124
2.283	Attribute gPOptions .....	124
2.284	Attribute groupAttributes .....	125
2.285	Attribute groupMembershipSAM .....	125
2.286	Attribute groupPriority .....	125
2.287	Attribute groupsToIgnore .....	126
2.288	Attribute groupType .....	126
2.289	Attribute hasMasterNCs.....	127
2.290	Attribute hasPartialReplicaNCs .....	127
2.291	Attribute helpData16 .....	128
2.292	Attribute helpData32 .....	128
2.293	Attribute helpFileName .....	129
2.294	Attribute hideFromAB .....	129
2.295	Attribute homeDirectory.....	129
2.296	Attribute homeDrive .....	130
2.297	Attribute homePhone .....	130
2.298	Attribute homePostalAddress .....	131
2.299	Attribute host .....	131
2.300	Attribute houseIdentifier .....	132
2.301	Attribute iconPath .....	132
2.302	Attribute implementedCategories .....	132
2.303	Attribute indexedScopes .....	133
2.304	Attribute info .....	133
2.305	Attribute initialAuthIncoming .....	134
2.306	Attribute initialAuthOutgoing .....	134
2.307	Attribute initials .....	135
2.308	Attribute installUiLevel .....	135
2.309	Attribute instanceType .....	135
2.310	Attribute internationalISDNNumber .....	136
2.311	Attribute interSiteTopologyFailover.....	137
2.312	Attribute interSiteTopologyGenerator.....	137

2.313 Attribute interSiteTopologyRenew .....	138
2.314 Attribute invocationId .....	138
2.315 Attribute ipHostNumber .....	139
2.316 Attribute ipNetmaskNumber .....	139
2.317 Attribute ipNetworkNumber .....	139
2.318 Attribute ipPhone .....	140
2.319 Attribute ipProtocolNumber .....	140
2.320 Attribute ipsecData.....	140
2.321 Attribute ipsecDataType .....	141
2.322 Attribute ipsecFilterReference .....	141
2.323 Attribute ipsecID .....	141
2.324 Attribute ipsecISAKMPReference .....	142
2.325 Attribute ipsecName .....	142
2.326 Attribute iPSECNegotiationPolicyAction.....	143
2.327 Attribute ipsecNegotiationPolicyReference .....	143
2.328 Attribute iPSECNegotiationPolicyType.....	143
2.329 Attribute ipsecNFAReference.....	144
2.330 Attribute ipsecOwnersReference.....	144
2.331 Attribute ipsecPolicyReference .....	144
2.332 Attribute ipServicePort .....	145
2.333 Attribute ipServiceProtocol .....	145
2.334 Attribute isCriticalSystemObject.....	145
2.335 Attribute isDefunct .....	146
2.336 Attribute isDeleted .....	146
2.337 Attribute isEphemeral .....	147
2.338 Attribute isMemberOfPartialAttributeSet .....	147
2.339 Attribute isPrivilegeHolder .....	147
2.340 Attribute isRecycled .....	148
2.341 Attribute isSingleValued .....	148
2.342 Attribute jpegPhoto .....	149
2.343 Attribute keywords .....	149
2.344 Attribute knowledgeInformation .....	149
2.345 Attribute l.....	150
2.346 Attribute labeledURI .....	150
2.347 Attribute lastBackupRestorationTime .....	151
2.348 Attribute lastContentIndexed .....	151
2.349 Attribute lastKnownParent .....	151
2.350 Attribute lastLogoff.....	152
2.351 Attribute lastLogon .....	152
2.352 Attribute lastLogonTimestamp .....	153
2.353 Attribute lastSetTime .....	153
2.354 Attribute lastUpdateSequence .....	154
2.355 Attribute IDAPAdminLimits.....	154
2.356 Attribute IDAPDisplayName.....	155
2.357 Attribute IDAPIPDenyList .....	155
2.358 Attribute ISACreationTime .....	155
2.359 Attribute ISAModifiedCount .....	156
2.360 Attribute legacyExchangeDN.....	156
2.361 Attribute linkID .....	157
2.362 Attribute linkTrackSecret.....	157
2.363 Attribute lmPwdHistory .....	158
2.364 Attribute localeID .....	158
2.365 Attribute localizationDisplayId .....	158

2.366 Attribute localizedDescription.....	159
2.367 Attribute localPolicyFlags.....	159
2.368 Attribute localPolicyReference .....	160
2.369 Attribute location .....	160
2.370 Attribute lockoutDuration .....	160
2.371 Attribute lockOutObservationWindow .....	161
2.372 Attribute lockoutThreshold .....	161
2.373 Attribute lockoutTime .....	162
2.374 Attribute loginShell.....	162
2.375 Attribute logonCount .....	163
2.376 Attribute logonHours .....	163
2.377 Attribute logonWorkstation.....	163
<b>3 Change Tracking.....</b>	<b>165</b>
<b>4 Index .....</b>	<b>167</b>

## 1 References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[ISO-3166] International Organization for Standardization, "Codes for the Representation of Names of Countries and Their Subdivisions", ISO 3166,  
[http://www.iso.org/iso/iso\\_catalogue/catalogue\\_tc/catalogue\\_detail.htm?csnumber=24591](http://www.iso.org/iso/iso_catalogue/catalogue_tc/catalogue_detail.htm?csnumber=24591)

**Note** There is a charge to download the specification.

[JFIF] Hamilton, E., "JPEG File Interchange Format, Version 1.02", September 1992,  
<http://www.w3.org/Graphics/JPEG/jfif.txt>

[MS-ADA3] Microsoft Corporation, "[Active Directory Schema Attributes N-Z](#)", June 2007.

[MS-ADTS] Microsoft Corporation, "[Active Directory Technical Specification](#)", June 2007.

[MS-DTYP] Microsoft Corporation, "[Windows Data Types](#)", January 2007.

[MS-LSAD] Microsoft Corporation, "[Local Security Authority \(Domain Policy\) Remote Protocol Specification](#)", June 2007.

[MS-SAMR] Microsoft Corporation, "[Security Account Manager \(SAM\) Remote Protocol Specification \(Client-to-Server\)](#)", June 2007.

[MSDN-ACL] Microsoft Corporation, "ACL", <http://msdn.microsoft.com/en-us/library/aa374931.aspx>

If you have any trouble finding [MSDN-ACL], please check [here](#).

[MSDN-CP] Microsoft Corporation, "Code Page Identifiers", [http://msdn.microsoft.com/en-us/library/dd317756\(VS.85\).aspx](http://msdn.microsoft.com/en-us/library/dd317756(VS.85).aspx)

If you have any trouble finding [MSDN-CP], please check [here](#).

[MSDN-GroupType] Microsoft Corporation, "Group-Type", <http://msdn.microsoft.com/en-us/library/ms675935.aspx>

If you have any trouble finding [MSDN-GroupType], please check [here](#).

[MSDN-ExtUserIntDirObj] Microsoft Corporation, "Extending the User Interface for Directory Objects", <http://msdn.microsoft.com/en-us/library/ms676902.aspx>

[RFC2251] Wahl, M., Howes, T., and Kille, S., "Lightweight Directory Access Protocol (v3)", RFC 2251, December 1997, <http://www.ietf.org/rfc/rfc2251.txt>

[RFC2307] Howard, L., "An Approach for Using LDAP as a Network Information Service", RFC 2307, March 1998, <http://www.ietf.org/rfc/rfc2307.txt>

[RFC2849] Good, G., "The LDAP Data Interchange Format (LDIF) - Technical Specification", RFC 2849, June 2000, <http://www.ietf.org/rfc/rfc2849.txt>

[X500] ITU-T, "Information Technology - Open Systems Interconnection - The Directory: Overview of Concepts, Models and Services", Recommendation X.500, August 2005, <http://www.itu.int/rec/T-REC-X.500-200508-I/en>

**Note** There is a charge to download the specification.

[X509] ITU-T, "Information Technology - Open Systems Interconnection - The Directory: Public-Key and Attribute Certificate Frameworks", Recommendation X.509, August 2005,  
<http://www.itu.int/rec/T-REC-X.509/en>

**Note** There is a charge to download the specification.

## 2 Attributes

The following sections specify attributes in the Active Directory schema whose names start with the letters A through L.

These sections normatively specify the schema definition of each attribute and version-specific behavior of those schema definitions (such as when the attribute was added to the schema). Additionally, as an aid to the reader some of the sections include informative notes about how the attribute can be used.

**Note** Lines of text in the attribute definitions that are excessively long have been "folded" in accordance with [\[RFC2849\]](#) Note 2.

### 2.1 Attribute accountExpires

This attribute specifies the date the account expires. This value represents the number of 100-nanosecond intervals since January 1, 1601, Coordinated Universal Time (Greenwich Mean Time). A value of 0 or 0xFFFFFFFFFFFFFF (9223372036854775807) indicates that the account never expires.

```
cn: Account-Expires
ldapDisplayName: accountExpires
attributeId: 1.2.840.113556.1.4.159
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf967915-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
attributeSecurityGuid: 4c164200-20c0-11d0-a768-00aa006e0529
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

### 2.2 Attribute accountNameHistory

This attribute specifies the length of time the account has been active.

```
cn: Account-Name-History
ldapDisplayName: accountNameHistory
attributeId: 1.2.840.113556.1.4.1307
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 031952ec-3b72-11d2-90cc-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

### 2.3 Attribute aCSAggregateTokenRatePerUser

This attribute specifies the maximum quality of service token rate for any user for all flows.

```
cn: ACS-Aggregate-Token-Rate-Per-User
ldapDisplayName: aCSAggregateTokenRatePerUser
attributeId: 1.2.840.113556.1.4.760
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 7f56127d-5301-11d1-a9c5-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

### 2.4 Attribute aCSAllocableRSVPBandwidth

This attribute specifies the maximum bandwidth that can be reserved.

```
cn: ACS-Allocable-RSVP-Bandwidth
ldapDisplayName: aCSAllocableRSVPBandwidth
attributeId: 1.2.840.113556.1.4.766
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 7f561283-5301-11d1-a9c5-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

### 2.5 Attribute aCSCacheTimeout

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Cache-Timeout
ldapDisplayName: aCSCacheTimeout
attributeId: 1.2.840.113556.1.4.779
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 1cb355a1-56d0-11d1-a9c6-0000f80367c1
systemOnly: FALSE
```

```
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.6 Attribute aCSDirection

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Direction
ldapDisplayName: aCSDirection
attributeId: 1.2.840.113556.1.4.757
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 7f56127a-5301-11d1-a9c5-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.7 Attribute aCSDSBMDeadTime

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-DSBM-DeadTime
ldapDisplayName: aCSDSBMDeadTime
attributeId: 1.2.840.113556.1.4.778
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 1cb355a0-56d0-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.8 Attribute aCSDSBMPriority

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-DSBM-Priority
```

```
ldapDisplayName: aCSDSBMPriority
attributeId: 1.2.840.113556.1.4.776
attributesSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 1cb3559e-56d0-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.9 Attribute aCSDSBMRefresh

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-DSBM-Refresh
ldapDisplayName: aCSDSBMRefresh
attributeId: 1.2.840.113556.1.4.777
attributesSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 1cb3559f-56d0-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.10 Attribute aCSEnableACSService

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Enable-ACS-Service
ldapDisplayName: aCSEnableACSService
attributeId: 1.2.840.113556.1.4.770
attributesSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: 7f561287-5301-11d1-a9c5-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.11 Attribute aCSEnableRSVPAccounting**

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Enable-RSVP-Accounting
ldapDisplayName: aCSEnableRSVPAccounting
attributeId: 1.2.840.113556.1.4.899
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: f072230e-aef5-11d1-bDCF-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.12 Attribute aCSEnableRSVPMessageLogging**

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Enable-RSVP-Message-Logging
ldapDisplayName: aCSEnableRSVPMessageLogging
attributeId: 1.2.840.113556.1.4.768
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: 7f561285-5301-11d1-a9c5-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.13 Attribute aCSEventLogLevel**

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Event-Log-Level
ldapDisplayName: aCSEventLogLevel
attributeId: 1.2.840.113556.1.4.769
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 7f561286-5301-11d1-a9c5-0000f80367c1
systemOnly: FALSE
searchFlags: 0
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.14 Attribute aCSIIdentityName

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Identity-Name
ldapDisplayName: aCSIIdentityName
attributeId: 1.2.840.113556.1.4.784
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: dab029b6-ddf7-11d1-90a5-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.15 Attribute aCSMaxAggregatePeakRatePerUser

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Max-Aggregate-Peak-Rate-Per-User
ldapDisplayName: aCSMaxAggregatePeakRatePerUser
attributeId: 1.2.840.113556.1.4.897
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: f072230c-aef5-11d1-bdcf-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.16 Attribute aCSMaxDurationPerFlow

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Max-Duration-Per-Flow
ldapDisplayName: aCSMaxDurationPerFlow
```

```
attributeId: 1.2.840.113556.1.4.761
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 7f56127e-5301-11d1-a9c5-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.17 Attribute aCSMaximumSDUSize

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Maximum-SDU-Size
ldapDisplayName: aCSMaximumSDUSize
attributeId: 1.2.840.113556.1.4.1314
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 87a2d8f9-3b90-11d2-90cc-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.18 Attribute aCSMaxNoOfAccountFiles

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Max-No-Of-Account-Files
ldapDisplayName: aCSMaxNoOfAccountFiles
attributeId: 1.2.840.113556.1.4.901
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: f0722310-aef5-11d1-bdcf-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.19 Attribute aCSMaxNumberOfLogFiles**

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Max-No-Of-Log-Files
ldapDisplayName: aCSMaxNumberOfLogFiles
attributeId: 1.2.840.113556.1.4.774
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 1cb3559c-56d0-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.20 Attribute aCSMaxPeakBandwidth**

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Max-Peak-Bandwidth
ldapDisplayName: aCSMaxPeakBandwidth
attributeId: 1.2.840.113556.1.4.767
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 7f561284-5301-11d1-a9c5-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.21 Attribute aCSMaxPeakBandwidthPerFlow**

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Max-Peak-Bandwidth-Per-Flow
ldapDisplayName: aCSMaxPeakBandwidthPerFlow
attributeId: 1.2.840.113556.1.4.759
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 7f56127c-5301-11d1-a9c5-0000f80367c1
systemOnly: FALSE
searchFlags: 0
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.22 Attribute aCSMaxSizeOfRSVPAccountFile

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Max-Size-Of-RSVP-Account-File
ldapDisplayName: aCSMaxSizeOfRSVPAccountFile
attributeId: 1.2.840.113556.1.4.902
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: f0722311-aef5-11d1-bDCF-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.23 Attribute aCSMaxSizeOfRSVPLLogFile

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Max-Size-Of-RSVP-Log-File
ldapDisplayName: aCSMaxSizeOfRSVPLLogFile
attributeId: 1.2.840.113556.1.4.775
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 1cb3559d-56d0-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.24 Attribute aCSMaxTokenBucketPerFlow

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Max-Token-Bucket-Per-Flow
ldapDisplayName: aCSMaxTokenBucketPerFlow
```

```
attributeId: 1.2.840.113556.1.4.1313
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 81f6e0df-3b90-11d2-90cc-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.25 Attribute aCSMaxTokenRatePerFlow

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Max-Token-Rate-Per-Flow
ldapDisplayName: aCSMaxTokenRatePerFlow
attributeId: 1.2.840.113556.1.4.758
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 7f56127b-5301-11d1-a9c5-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.26 Attribute aCSMinimumDelayVariation

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Minimum-Delay-Variation
ldapDisplayName: aCSMinimumDelayVariation
attributeId: 1.2.840.113556.1.4.1317
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 9c65329b-3b90-11d2-90cc-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.27 Attribute aCSMinimumLatency**

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Minimum-Latency
ldapDisplayName: aCSMinimumLatency
attributeId: 1.2.840.113556.1.4.1316
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 9517fefb-3b90-11d2-90cc-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.28 Attribute aCSMinimumPolicedSize**

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Minimum-Policed-Size
ldapDisplayName: aCSMinimumPolicedSize
attributeId: 1.2.840.113556.1.4.1315
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 8d0e7195-3b90-11d2-90cc-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.29 Attribute aCSNonReservedMaxSDUSize**

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Non-Reserved-Max-SDU-Size
ldapDisplayName: aCSNonReservedMaxSDUSize
attributeId: 1.2.840.113556.1.4.1320
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: aec2cfe3-3b90-11d2-90cc-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.30 Attribute aCSNonReservedMinPolicedSize

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Non-Reserved-Min-Policed-Size
ldapDisplayName: aCSNonReservedMinPolicedSize
attributeId: 1.2.840.113556.1.4.1321
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: b6873917-3b90-11d2-90cc-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.31 Attribute aCSNonReservedPeakRate

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Non-Reserved-Peak-Rate
ldapDisplayName: aCSNonReservedPeakRate
attributeId: 1.2.840.113556.1.4.1318
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: a331a73f-3b90-11d2-90cc-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.32 Attribute aCSNonReservedTokenSize

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Non-Reserved-Token-Size
ldapDisplayName: aCSNonReservedTokenSize
```

```
attributeId: 1.2.840.113556.1.4.1319
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: a916d7c9-3b90-11d2-90cc-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

### 2.33 Attribute aCSNonReservedTxLimit

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Non-Reserved-Tx-Limit
ldapDisplayName: aCSNonReservedTxLimit
attributeId: 1.2.840.113556.1.4.780
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 1cb355a2-56d0-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

### 2.34 Attribute aCSNonReservedTxSize

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Non-Reserved-Tx-Size
ldapDisplayName: aCSNonReservedTxSize
attributeId: 1.2.840.113556.1.4.898
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: f072230d-aef5-11d1-bdcf-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.35 Attribute aCSPermissionBits**

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Permission-Bits
ldapDisplayName: aCSPermissionBits
attributeId: 1.2.840.113556.1.4.765
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 7f561282-5301-11d1-a9c5-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.36 Attribute aCSPolicyName**

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Policy-Name
ldapDisplayName: aCSPolicyName
attributeId: 1.2.840.113556.1.4.772
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 1cb3559a-56d0-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.37 Attribute aCSPriority**

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Priority
ldapDisplayName: aCSPriority
attributeId: 1.2.840.113556.1.4.764
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 7f561281-5301-11d1-a9c5-0000f80367c1
systemOnly: FALSE
searchFlags: 0
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.38 Attribute aCSRSVPAccountFilesLocation

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-RSVP-Account-Files-Location
ldapDisplayName: aCSRSVPAccountFilesLocation
attributeId: 1.2.840.113556.1.4.900
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f072230f-aef5-11d1-bDCF-0000F80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.39 Attribute aCSRSVPLogFileLocation

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-RSVP-Log-Files-Location
ldapDisplayName: aCSRSVPLogFileLocation
attributeId: 1.2.840.113556.1.4.773
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 1cb3559b-56d0-11d1-a9c6-0000F80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.40 Attribute aCSServerList

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Server-List
ldapDisplayName: aCSServerList
```

```
attributeId: 1.2.840.113556.1.4.1312
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 7cbd59a5-3b90-11d2-90cc-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.41 Attribute aCSServiceType

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Service-Type
ldapDisplayName: aCSServiceType
attributeId: 1.2.840.113556.1.4.762
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 7f56127f-5301-11d1-a9c5-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.42 Attribute acSTimeOfDay

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Time-Of-Day
ldapDisplayName: acSTimeOfDay
attributeId: 1.2.840.113556.1.4.756
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 7f561279-5301-11d1-a9c5-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.43 Attribute aCSTotalNoOfFlows**

This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: ACS-Total-No-Of-Flows
ldapDisplayName: aCSTotalNoOfFlows
attributeId: 1.2.840.113556.1.4.763
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 7f561280-5301-11d1-a9c5-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.44 Attribute additionalTrustedServiceNames**

This attribute specifies a list of services in the domain that can be trusted. This attribute is not necessary for Active Directory to function. The protocol does not define a format beyond that required by the schema.

```
cn: Additional-Trusted-Service-Names
ldapDisplayName: additionalTrustedServiceNames
attributeId: 1.2.840.113556.1.4.889
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 032160be-9824-11d1-aec0-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.45 Attribute addressBookRoots**

This attribute is used by Microsoft® Exchange Server and is not necessary for Active Directory functioning. It specifies the trees of address book containers to appear in the Messaging Application Programming Interface (MAPI) address book.

```
cn: Address-Book-Roots
ldapDisplayName: addressBookRoots
attributeId: 1.2.840.113556.1.4.1244
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: f70b6e48-06f4-11d2-aa53-00c04fd7d83a
```

```
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.46 Attribute addressBookRoots2

This attribute is used by Microsoft® Exchange Server and is not necessary for Active Directory functioning. It specifies the trees of address book containers to appear in the MAPI address book. Similar to [addressBookRoots](#), it differs by being a linked attribute.

```
cn: Address-Book-Roots2
ldapDisplayName: addressBookRoots2
attributeId: 1.2.840.113556.1.4.2046
attributeSyntax: 2.5.5.1
linkID: 2122
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 508ca374-a511-4e4e-9f4f-856f61a6b7e4
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Windows Server® 2008 operating system and Windows Server® 2008 R2 operating system.

## 2.47 Attribute addressEntryDisplayTable

This attribute is used by Microsoft® Exchange Server and is not necessary for Active Directory functioning. It specifies the display table for an address entry.

```
cn: Address-Entry-Display-Table
ldapDisplayName: addressEntryDisplayTable
attributeId: 1.2.840.113556.1.2.324
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 5fd42461-1262-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 32768
mapiID: 32791
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.48 Attribute addressEntryDisplayTableMSDOS

This attribute is used by Microsoft® Exchange Server and is not necessary for Active Directory functioning. It specifies the MAPI display table for an address entry for an MS-DOS client.

```
cn: Address-Entry-Display-Table-MSDOS
ldapDisplayName: addressEntryDisplayTableMSDOS
attributeId: 1.2.840.113556.1.2.400
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 5fd42462-1262-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 32768
mapiID: 32839
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.49 Attribute addressSyntax

This attribute is used by Microsoft® Exchange Server and is not necessary for Active Directory functioning. It specifies a grammar for encoding the display table properties as a string.

```
cn: Address-Syntax
ldapDisplayName: addressSyntax
attributeId: 1.2.840.113556.1.2.255
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 5fd42463-1262-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 4096
mapiID: 32792
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.50 Attribute addressType

This attribute is used by Microsoft® Exchange Server and is not necessary for Active Directory functioning. It specifies a character string describing the format of the user's address. Address types map to address formats. That is, by looking at a recipient's address type, client applications can determine how to format an address appropriate for the recipient.

```
cn: Address-Type
ldapDisplayName: addressType
attributeId: 1.2.840.113556.1.2.350
attributeSyntax: 2.5.5.4
omSyntax: 20
isSingleValued: TRUE
schemaIdGuid: 5fd42464-1262-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 32
mapiID: 32840
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.51 Attribute adminContextMenu

This attribute specifies the order number and GUID of the context menu to be used on administration screens. GUID is defined in [\[MS-DTYP\]](#) section 2.3.2.

```
cn: Admin-Context-Menu
ldapDisplayName: adminContextMenu
attributeId: 1.2.840.113556.1.4.614
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 553fd038-f32e-11d0-b0bc-00c04fd8dca6
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.52 Attribute adminCount

This attribute specifies that a given object has had its access control lists (ACLs) changed to a more secure value by the Active Directory system (see [\[MS-ADSO\]](#) section 2.1) because it is a member of

one of the administrative groups, either directly or transitively. For more information on the ACL structure, see [\[MSDN-ACL\]](#).

```
cn: Admin-Count
ldapDisplayName: adminCount
attributeId: 1.2.840.113556.1.4.150
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf967918-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.53 Attribute adminDescription

This attribute specifies the description displayed on administration screens.

```
cn: Admin-Description
ldapDisplayName: adminDescription
attributeId: 1.2.840.113556.1.2.226
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967919-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 1024
attributeSecurityGuid: 59ba2f42-79a2-11d0-9020-00c04fc2d3cf
mapiID: 32842
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.54 Attribute adminDisplayName

This attribute specifies the name to be displayed on administration screens.

```
cn: Admin-Display-Name
ldapDisplayName: adminDisplayName
attributeId: 1.2.840.113556.1.2.194
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf96791a-0de6-11d0-a285-00aa003049e2
```

```
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 256
mapiID: 32843
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.55 Attribute adminMultiselectPropertyPages

This attribute specifies the GUID of a Component Object Model (COM) object that implements multiselect property pages for the Active Directory Users and Computers snap-in.

```
cn: Admin-Multiselect-Property-Pages
ldapDisplayName: adminMultiselectPropertyPages
attributeId: 1.2.840.113556.1.4.1690
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 18f9b67d-5ac6-4b3b-97db-d0a406afb7ba
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.56 Attribute adminPropertyPages

This attribute specifies the GUID of the property pages for an object to be displayed on Active Directory administration screens. For more information, see the document, "Extending the User Interface for Directory Objects" [\[MSDN-ExtUserIntDirObj\]](#).

```
cn: Admin-Property-Pages
ldapDisplayName: adminPropertyPages
attributeId: 1.2.840.113556.1.4.562
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 52458038-ca6a-11d0-afff-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.57 Attribute allowedAttributes

This attribute specifies attributes that will be permitted to be assigned to a class.

```
cn: Allowed-Attributes
ldapDisplayName: allowedAttributes
attributeId: 1.2.840.113556.1.4.913
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: 9a7ad940-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.58 Attribute allowedAttributesEffective

This attribute specifies a list of attributes that can be modified on the object.

```
cn: Allowed-Attributes-Effective
ldapDisplayName: allowedAttributesEffective
attributeId: 1.2.840.113556.1.4.914
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: 9a7ad941-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.59 Attribute allowedChildClasses

This attribute specifies classes that may be contained by a class.

```
cn: Allowed-Child-Classes
ldapDisplayName: allowedChildClasses
attributeId: 1.2.840.113556.1.4.911
```

```

attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: 9a7ad942-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL

```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.60 Attribute allowedChildClassesEffective

This attribute specifies a list of classes that can be modified.

```

cn: Allowed-Child-Classes-Effective
ldapDisplayName: allowedChildClassesEffective
attributeId: 1.2.840.113556.1.4.912
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: 9a7ad943-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL

```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.61 Attribute altSecurityIdentities

This attribute specifies a given user mapping for [\[X509\]](#) certificates or external Kerberos user accounts for the purpose of authentication.

```

cn: Alt-Security-Identities
ldapDisplayName: altSecurityIdentities
attributeId: 1.2.840.113556.1.4.867
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 00fbff30c-91fe-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: fATTINDEX

```

```
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
  FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.62 Attribute aNR

This attribute specifies whether ambiguous name resolution is to be used when choosing between objects.

```
cn: ANR
ldapDisplayName: aNR
attributeId: 1.2.840.113556.1.4.1208
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 45b01500-c419-11d1-bbc9-0080c76670c0
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
  FLAG_DOMAIN_DISALLOW_RENAME
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.63 Attribute applicationName

This attribute is used to store the name of the application.

```
cn: Application-Name
ldapDisplayName: applicationName
attributeId: 1.2.840.113556.1.4.218
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: dd712226-10e4-11d0-a05f-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.64 Attribute appliesTo

This attribute specifies the list of object classes that an extended right applies to. For more information on Active Directory object classes, see [\[MS-ADTS\]](#).

```
cn: Applies-To
ldapDisplayName: appliesTo
attributeId: 1.2.840.113556.1.4.341
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 8297931d-86d3-11d0-afda-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
rangeLower: 36
rangeUpper: 36
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.65 Attribute appSchemaVersion

This attribute specifies the schema version of the directory. It is used to provide correct behavior across schema changes. For more information on the schema, see [\[MS-ADTS\]](#) section 3.1.1.2.

```
cn: App-Schema-Version
ldapDisplayName: appSchemaVersion
attributeId: 1.2.840.113556.1.4.848
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 96a7dd65-9118-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.66 Attribute assetNumber

This attribute is used to store the tracking number of the object.

```
cn: Asset-Number
ldapDisplayName: assetNumber
attributeId: 1.2.840.113556.1.4.283
attributeSyntax: 2.5.5.12
```

```
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: ba305f75-47e3-11d0-ala6-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.67 Attribute assistant

This attribute can be used to store the distinguished name of an administrative assistant for a user.

```
cn: Assistant
ldapDisplayName: assistant
attributeId: 1.2.840.113556.1.4.652
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 0296c11c-40da-11d1-a9c0-0000f80367c1
systemOnly: FALSE
searchFlags: fCOPY
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.68 Attribute associatedDomain

The associatedDomain attribute type specifies a fully qualified domain name (FQDN) (2) ([\[MS-ADTS\]](#) section 1.1) associated with an object.

```
cn: associatedDomain
ldapDisplayName: associatedDomain
attributeId: 0.9.2342.19200300.100.1.37
attributeSyntax: 2.5.5.5
omSyntax: 22
isSingleValued: FALSE
schemaIdGuid: 3320fc38-c379-4c17-a510-1bdf6133c5da
systemOnly: FALSE
searchFlags: 0
rangeUpper: 256
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.69 Attribute associatedName**

The associatedName attribute type specifies an entry in the directory associated with a DNS domain.

```
cn: associatedName
ldapDisplayName: associatedName
attributeId: 0.9.2342.19200300.100.1.38
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: f7fbfc45-85ab-42a4-a435-780e62f7858b
systemOnly: FALSE
searchFlags: 0
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.70 Attribute assocNTAccount**

The Microsoft Windows NT® operating system account that applies to this object.

```
cn: Assoc-NT-Account
ldapDisplayName: assocNTAccount
attributeId: 1.2.840.113556.1.4.1213
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 398f63c0-ca60-11d1-bbd1-0000f81f10c0
systemOnly: FALSE
searchFlags: 0
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.71 Attribute attributeCertificateAttribute**

A digitally signed or certified identity and set of attributes. Used to bind authorization information to an identity.

```
cn: attributeCertificateAttribute
ldapDisplayName: attributeCertificateAttribute
attributeId: 2.5.4.58
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: fa4693bb-7bc2-4cb9-81a8-c99c43b7905e
systemOnly: FALSE
searchFlags: 0
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.72 Attribute attributeDisplayNames

The name to be displayed for this object.

```
cn: Attribute-Display-Names
ldapDisplayName: attributeDisplayNames
attributeId: 1.2.840.113556.1.4.748
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: cb843f80-48d9-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.73 Attribute attributeID

This attribute specifies the unique X.500 object identifier (OID) for identifying an attribute. For more information, see [\[X500\]](#).

```
cn: Attribute-ID
ldapDisplayName: attributeID
attributeId: 1.2.840.113556.1.2.30
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: TRUE
schemaIdGuid: bf967922-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags:fPRESERVEONDELETE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.74 Attribute attributeSecurityGUID

This attribute specifies the GUID used to apply security credentials to a set of objects.

```
cn: Attribute-Security-GUID
ldapDisplayName: attributeSecurityGUID
attributeId: 1.2.840.113556.1.4.149
attributeSyntax: 2.5.5.10
omSyntax: 4
```

```
isSingleValued: TRUE
schemaIdGuid: bf967924-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 16
rangeUpper: 16
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.75 Attribute attributeSyntax

This attribute specifies the OID for the syntax for this attribute.

```
cn: Attribute-Syntax
ldapDisplayName: attributeSyntax
attributeId: 1.2.840.113556.1.2.32
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: TRUE
schemaIdGuid: bf967925-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags:fPRESERVEONDELETE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.76 Attribute attributeTypes

A multivalued property containing strings that represent each attribute in the schema.

```
cn: Attribute-Types
ldapDisplayName: attributeTypes
attributeId: 2.5.21.5
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 9a7ad944-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.77 Attribute audio

This attribute can be used to store audio.

```
cn: audio
ldapDisplayName: audio
attributeId: 0.9.2342.19200300.100.1.55
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: d0e1d224-e1a0-42ce-a2da-793ba5244f35
systemOnly: FALSE
searchFlags: 0
rangeUpper: 250000
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.78 Attribute auditingPolicy

This attribute specifies the auditing policy for the local policy.

```
cn: Auditing-Policy
ldapDisplayName: auditingPolicy
attributeId: 1.2.840.113556.1.4.202
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 6da8a4fe-0e52-11d0-a286-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.79 Attribute authenticationOptions

This attribute specifies the authentication options used in the Active Directory Service Interface (ADSI) to bind to directory services objects.

```
cn: Authentication-Options
ldapDisplayName: authenticationOptions
```

```
attributeId: 1.2.840.113556.1.4.11
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf967928-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.80 Attribute authorityRevocationList

Cross-certificate, certificate revocation list.

```
cn: Authority-Revocation-List
ldapDisplayName: authorityRevocationList
attributeId: 2.5.4.38
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: 1677578d-47f3-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeUpper: 10485760
mapiID: 32806
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, rangeUpper is not defined.

## 2.81 Attribute auxiliaryClass

This attribute specifies the list of auxiliary classes to be associated with this class.

```
cn: Auxiliary-Class
ldapDisplayName: auxiliaryClass
attributeId: 1.2.840.113556.1.2.351
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: FALSE
schemaIdGuid: bf96792c-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.82 Attribute badPasswordTime

This attribute specifies the last time and date that an attempt to log on to this account was made with an invalid password. This value is stored as a large integer that represents the number of 100 nanosecond intervals since January 1, 1601 (UTC). A value of zero means that the last invalid password time is unknown.

```
cn: Bad-Password-Time
ldapDisplayName: badPasswordTime
attributeId: 1.2.840.113556.1.4.49
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf96792d-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.83 Attribute badPwdCount

This attribute specifies the number of times the user tried to log on to the account by using an incorrect password. A value of 0 indicates that the value is unknown.

```
cn: Bad-Pwd-Count
ldapDisplayName: badPwdCount
attributeId: 1.2.840.113556.1.4.12
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf96792e-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: 5f202010-79a5-11d0-9020-00c04fc2d4cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.84 Attribute birthLocation

This attribute specifies the location where an individual associated with a user account was born.

```
cn: Birth-Location
ldapDisplayName: birthLocation
attributeId: 1.2.840.113556.1.4.332
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 1f0075f9-7e40-11d0-af6-00c04fd930c9
systemOnly: FALSE
searchFlags: fATTINDEX
rangeLower: 32
rangeUpper: 32
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.85 Attribute bootFile

This attribute specifies the boot image name.

```
cn: BootFile
ldapDisplayName: bootFile
attributeId: 1.3.6.1.1.1.24
attributeSyntax: 2.5.5.5
omSyntax: 22
isSingleValued: FALSE
schemaIdGuid: e3f3cb4e-0f20-42eb-9703-d2ff26e52667
systemOnly: FALSE
searchFlags: 0
rangeUpper: 10240
```

Version-Specific Behavior: Implemented on Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.86 Attribute bootParameter

This attribute specifies the rpc.bootparameter.

```
cn: BootParameter
ldapDisplayName: bootParameter
attributeId: 1.3.6.1.1.1.23
attributeSyntax: 2.5.5.5
omSyntax: 22
isSingleValued: FALSE
schemaIdGuid: d72a0750-8c7c-416e-8714-e65f11e908be
systemOnly: FALSE
searchFlags: 0
rangeUpper: 10240
```

Version-Specific Behavior: Implemented on Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.87 Attribute bridgeheadServerListBL

This attribute is the back link attribute of bridgeheadServerList and contains the list of servers that are bridgeheads for Active Directory replication.

```
cn: Bridgehead-Server-List-BL
ldapDisplayName: bridgeheadServerListBL
attributeId: 1.2.840.113556.1.4.820
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: d50c2cdb-8951-11d1-aebc-0000f80367c1
systemOnly: TRUE
searchFlags: 0
linkID: 99
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.88 Attribute bridgeheadTransportList

This attribute specifies the replication transports for which this server is an Active Directory bridgehead DC.

```
cn: Bridgehead-Transport-List
ldapDisplayName: bridgeheadTransportList
attributeId: 1.2.840.113556.1.4.819
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: d50c2cda-8951-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
linkID: 98
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.89 Attribute buildingName

This attribute specifies the name of the building where an organization or organizational unit is based.

```
cn: buildingName
ldapDisplayName: buildingName
attributeId: 0.9.2342.19200300.100.1.48
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: f87fa54b-b2c5-4fd7-88c0-daccb21d93c5
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 256
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.90 Attribute builtinCreationTime

This attribute is used to support replication to Microsoft Windows NT® 4.0 operating system domains.

```
cn: Builtin-Creation-Time
ldapDisplayName: builtinCreationTime
attributeId: 1.2.840.113556.1.4.13
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf96792f-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.91 Attribute builtinModifiedCount

This attribute is used to support replication to Microsoft Windows NT® 4.0 operating system domains.

```
cn: Builtin-Modified-Count
ldapDisplayName: builtinModifiedCount
attributeId: 1.2.840.113556.1.4.14
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf967930-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.92 Attribute businessCategory

This attribute specifies descriptive text on an organizational unit.

```
cn: Business-Category
ldapDisplayName: businessCategory
attributeId: 2.5.4.15
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: bf967931-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 128
mapiID: 32855
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.93 Attribute bytesPerMinute

This attribute specifies the printer data transfer rate.

```
cn: Bytes-Per-Minute
ldapDisplayName: bytesPerMinute
attributeId: 1.2.840.113556.1.4.284
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: ba305f76-47e3-11d0-a1a6-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.94 Attribute c

This attribute specifies the country/region in the address of the user. The country/region is represented as the two-character country code based on [\[ISO-3166\]](#).

```
cn: Country-Name
ldapDisplayName: c
attributeId: 2.5.4.6
attributeSyntax: 2.5.5.12
omSyntax: 64
```

```
isSingleValued: TRUE
schemaIdGuid: bf967945-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 1
rangeUpper: 3
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
mapiID: 32873
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.95 Attribute cACertificate

This attribute specifies certificates of trusted certificate authorities (CAs).

```
cn: CA-Certificate
ldapDisplayName: cACertificate
attributeId: 2.5.4.37
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: bf967932-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 32768
mapiID: 32771
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.96 Attribute cACertificateDN

This attribute specifies the full distinguished name from the certificate authority (CA) certificate.

```
cn: CA-Certificate-DN
ldapDisplayName: cACertificateDN
attributeId: 1.2.840.113556.1.4.697
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 963d2740-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
```

```
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.97 Attribute cAConnect

This attribute specifies the connection string for binding to a CA.

```
cn: CA-Connect
ldapDisplayName: cAConnect
attributeId: 1.2.840.113556.1.4.687
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 963d2735-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.98 Attribute canonicalName

This attribute specifies the name of the object in canonical format; myserver2.fabrikam.com/users/jeffsmith is an example of a distinguished name in canonical format.

This is a constructed attribute. The results returned are identical to those returned by the following Active Directory function: DsCrackNames(NULL, DS\_NAME\_FLAG\_SYNTACTICAL\_ONLY, DS\_FQDN\_1779\_NAME, DS\_CANONICAL\_NAME, ...).

```
cn: Canonical-Name
ldapDisplayName: canonicalName
attributeId: 1.2.840.113556.1.4.916
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 9a7ad945-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## **2.99 Attribute canUpgradeScript**

This attribute specifies the list of application packages that can be upgraded by this application package or that can upgrade this application package.

```
cn: Can-Upgrade-Script
ldapDisplayName: canUpgradeScript
attributeId: 1.2.840.113556.1.4.815
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: d9e18314-8939-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.100 Attribute carLicense**

This attribute can be used to store a vehicle license or registration plate.

```
cn: carLicense
ldapDisplayName: carLicense
attributeId: 2.16.840.1.113730.3.1.1
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: d4159c92-957d-4a87-8a67-8d2934e01649
systemOnly: FALSE
searchFlags: 0
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.101 Attribute catalogs**

This attribute specifies the list of catalogs indexing storage on a given computer.

```
cn: Catalogs
ldapDisplayName: catalogs
attributeId: 1.2.840.113556.1.4.675
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 7bfdcb81-4807-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.102 Attribute categories

This attribute specifies a list of category IDs (GUIDs) for categories that apply to this application.

```
cn: Categories
ldapDisplayName: categories
attributeId: 1.2.840.113556.1.4.672
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 7bfdcb7e-4807-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 36
rangeUpper: 36
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.103 Attribute categoryId

This attribute specifies the ID for a component category.

```
cn: Category-Id
ldapDisplayName: categoryId
attributeId: 1.2.840.113556.1.4.322
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 7d6c0e94-7e20-11d0-afed-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
rangeLower: 16
rangeUpper: 16
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.104 Attribute cAUUsages

This attribute specifies the list of OID/cryptographic service provider (CSP) name concatenations.

```
cn: CA-Usages
ldapDisplayName: cAUUsages
attributeId: 1.2.840.113556.1.4.690
attributeSyntax: 2.5.5.12
omSyntax: 64
```

```
isSingleValued: FALSE
schemaIdGuid: 963d2738-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.105 Attribute cAWEBURL

This attribute specifies the URL for an HTTP connection to a CA.

```
cn: CA-WEB-URL
ldapDisplayName: cAWEBURL
attributeId: 1.2.840.113556.1.4.688
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 963d2736-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.106 Attribute certificateAuthorityObject

This attribute specifies a reference to the CA associated with a certificate revocation list (CRL) distribution point.

```
cn: Certificate-Authority-Object
ldapDisplayName: certificateAuthorityObject
attributeId: 1.2.840.113556.1.4.684
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 963d2732-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

On Windows 2000 Server, rangeUpper is not defined.

## **2.107 Attribute certificateRevocationList**

This attribute represents a list of certificates that have been revoked.

```
cn: Certificate-Revocation-List
ldapDisplayName: certificateRevocationList
attributeId: 2.5.4.39
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 1677579f-47f3-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeUpper: 10485760
mapiID: 32790
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, rangeUpper is not defined.

## **2.108 Attribute certificateTemplates**

This attribute contains information for a certificate issued by a certificate server.

```
cn: Certificate-Templates
ldapDisplayName: certificateTemplates
attributeId: 1.2.840.113556.1.4.823
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 2a39c5b1-8960-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.109 Attribute classDisplayName**

This attribute specifies the object name to be displayed on dialogs.

```
cn: Class-Display-Name
ldapDisplayName: classDisplayName
attributeId: 1.2.840.113556.1.4.610
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 548e1c22-dea6-11d0-b010-0000f80367c1
systemOnly: FALSE
```

```
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.110 Attribute cn

This attribute specifies the name that represents an object. It is used to perform searches.

```
cn: Common-Name
ldapDisplayName: cn
attributeId: 2.5.4.3
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf96793f-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fATTINDEX
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
mapiID: 14863
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
  FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.111 Attribute co

This attribute specifies the country/region in which the user is located.

```
cn: Text-Country
ldapDisplayName: co
attributeId: 1.2.840.113556.1.2.131
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f0f8ffa7-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 1
rangeUpper: 128
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
mapiID: 14886
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.112 Attribute codePage

This attribute specifies the code page for the user's language of choice. The space of values is the Microsoft code page designation. For more information, see [\[MSDN-CP\]](#).

```
cn: Code-Page
ldapDisplayName: codePage
attributeId: 1.2.840.113556.1.4.16
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf967938-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 0
rangeUpper: 65535
attributeSecurityGuid: 59ba2f42-79a2-11d0-9020-00c04fc2d3cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, rangeLower and rangeUpper are not defined.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.113 Attribute cOMClassID

This attribute specifies the list of ClassIDs implemented in this application package.

```
cn: COM-ClassID
ldapDisplayName: cOMClassID
attributeId: 1.2.840.113556.1.4.19
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: bf96793b-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fATTINDEX
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.114 Attribute cOMCLSID

This attribute specifies the GUID associated with this object class.

```
cn: COM-CLSID
ldapDisplayName: cOMCLSID
attributeId: 1.2.840.113556.1.4.249
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 281416d9-1968-11d0-a28f-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 36
rangeUpper: 36
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.115 Attribute cOMInterfaceID

This attribute specifies the list of interfaces implemented in this application package.

```
cn: COM-InterfaceID
ldapDisplayName: cOMInterfaceID
attributeId: 1.2.840.113556.1.4.20
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: bf96793c-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 36
rangeUpper: 36
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.116 Attribute comment

This attribute can be used to store a comment for a user.

```
cn: User-Comment
ldapDisplayName: comment
attributeId: 1.2.840.113556.1.4.156
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967a6a-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: 59ba2f42-79a2-11d0-9020-00c04fc2d3cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.117 Attribute cOMOtherProgId

This attribute specifies the list of other program ID strings for the host class.

```
cn: COM-Other-Prog-Id
ldapDisplayName: cOMOtherProgId
attributeId: 1.2.840.113556.1.4.253
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 281416dd-1968-11d0-a28f-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.118 Attribute company

This attribute can be used to store a company name for a user.

```
cn: Company
ldapDisplayName: company
attributeId: 1.2.840.113556.1.2.146
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f0f8ff88-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
mapiID: 14870
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.119 Attribute cOMProgID

This attribute specifies the list of COM object program IDs implemented in this application package.

```
cn: COM-ProgID
ldapDisplayName: cOMProgID
attributeId: 1.2.840.113556.1.4.21
```

```
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: bf96793d-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.120 Attribute cOMTreatAsClassId

This attribute specifies the Treat-As string GUID class identifier (CLSID) for the host class.

```
cn: COM-Treat-As-Class-Id
ldapDisplayName: cOMTreatAsClassId
attributeId: 1.2.840.113556.1.4.251
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 281416db-1968-11d0-a28f-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 36
rangeUpper: 36
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.121 Attribute cOMTypelibId

This attribute specifies the list of type library IDs contained in this application package.

```
cn: COM-Typelib-Id
ldapDisplayName: cOMTypelibId
attributeId: 1.2.840.113556.1.4.254
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 281416de-1968-11d0-a28f-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 36
rangeUpper: 36
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.122 Attribute cOMUniqueLIBID**

This attribute specifies a single-valued string GUID LIBID for a type library.

```
cn: COM-Unique-LIBID
ldapDisplayName: cOMUniqueLIBID
attributeId: 1.2.840.113556.1.4.250
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 281416da-1968-11d0-a28f-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 36
rangeUpper: 36
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.123 Attribute contentIndexingAllowed**

Indicates whether the [volume](#) object can be content indexed.

```
cn: Content-Indexing-Allowed
ldapDisplayName: contentIndexingAllowed
attributeId: 1.2.840.113556.1.4.24
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: bf967943-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.124 Attribute contextMenu**

This attribute specifies the order number and GUID of the context menu to be used for an object.

```
cn: Context-Menu
ldapDisplayName: contextMenu
attributeId: 1.2.840.113556.1.4.499
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 4d8601ee-ac85-11d0-afe3-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.125 Attribute controlAccessRights

This attribute is used by DS Security to determine which users can perform specific operations on the host object.

```
cn: Control-Access-Rights
ldapDisplayName: controlAccessRights
attributeId: 1.2.840.113556.1.4.200
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: 6da8a4fc-0e52-11d0-a286-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 16
rangeUpper: 16
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.126 Attribute cost

This attribute contains the relative cost for routing messages through a particular site connector.

```
cn: Cost
ldapDisplayName: cost
attributeId: 1.2.840.113556.1.2.135
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf967944-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
mapiID: 32872
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.127 Attribute countryCode

This attribute specifies the country code for the user's language of choice.

```
cn: Country-Code
ldapDisplayName: countryCode
attributeId: 1.2.840.113556.1.4.25
```

```
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 5fd42471-1262-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 0
rangeUpper: 65535
attributeSecurityGuid: 59ba2f42-79a2-11d0-9020-00c04fc2d3cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, rangeLower and rangeUpper are not defined.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.128 Attribute `createDialog`

This attribute specifies the GUID of the dialog for creating an associated object.

```
cn: Create-Dialog
ldapDisplayName: createDialog
attributeId: 1.2.840.113556.1.4.810
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 2b09958a-8931-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.129 Attribute `createTimeStamp`

This attribute specifies the date this object was created. This value is replicated.

```
cn: Create-Time-Stamp
ldapDisplayName: createTimeStamp
attributeId: 2.5.18.1
attributeSyntax: 2.5.5.11
omSyntax: 24
isSingleValued: TRUE
schemaIdGuid: 2df90d73-009f-11d2-aa4c-00c04fd7d83a
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
```

```
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.130 Attribute `createWizardExt`

The GUID of wizard extensions for creating an associated object.

```
cn: Create-Wizard-Ext
ldapDisplayName: createWizardExt
attributeId: 1.2.840.113556.1.4.812
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 2b09958b-8931-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.131 Attribute `creationTime`

This attribute specifies the date and time that the object was created.

```
cn: Creation-Time
ldapDisplayName: creationTime
attributeId: 1.2.840.113556.1.4.26
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf967946-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.132 Attribute `creationWizard`

This attribute specifies the wizard to activate when creating objects of this class.

```
cn: Creation-Wizard
ldapDisplayName: creationWizard
attributeId: 1.2.840.113556.1.4.498
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 4d8601ed-ac85-11d0-afe3-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.133 Attribute creator

This attribute specifies the person who created the object.

```
cn: Creator
ldapDisplayName: creator
attributeId: 1.2.840.113556.1.4.679
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 7bfdcb85-4807-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.134 Attribute cRLObject

This attribute specifies the reference to the CRL object associated with a CA.

```
cn: CRL-Object
ldapDisplayName: cRLObject
attributeId: 1.2.840.113556.1.4.689
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 963d2737-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.135 Attribute cRLPartitionedRevocationList**

This attribute specifies the public key infrastructure–revocation lists.

```
cn: CRL-Partitioned-Revocation-List
ldapDisplayName: cRLPartitionedRevocationList
attributeId: 1.2.840.113556.1.4.683
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 963d2731-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeUpper: 10485760
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, rangeUpper is not defined.

## **2.136 Attribute crossCertificatePair**

This attribute specifies the version 3 (v3) cross-certificate.

```
cn: Cross-Certificate-Pair
ldapDisplayName: crossCertificatePair
attributeId: 2.5.4.40
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: 167757b2-47f3-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeUpper: 32768
mapiID: 32805
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, rangeUpper is not defined.

## **2.137 Attribute currentLocation**

This attribute specifies the computer location for an object that has moved.

```
cn: Current-Location
ldapDisplayName: currentLocation
attributeId: 1.2.840.113556.1.4.335
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
```

```
schemaIdGuid: 1f0075fc-7e40-11d0-af6-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
rangeLower: 32
rangeUpper: 32
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.138 Attribute currentParentCA

This attribute specifies a reference to the CAs that issued the current certificates for a CA.

```
cn: Current-Parent-CA
ldapDisplayName: currentParentCA
attributeId: 1.2.840.113556.1.4.696
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 963d273f-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.139 Attribute currentValue

This attribute is used to store the new value of a secret object. Secret objects are specified in [\[MS-LSAD\]](#) section 3.1.1.4. The format of the value of this attribute is outside the scope of the state model, and values stored in this attribute cannot be retrieved via the Lightweight Directory Access Protocol (LDAP). Instead, secret objects are retrieved and written as specified in [\[MS-LSAD\]](#) section 3.1.1.4.

```
cn: Current-Value
ldapDisplayName: currentValue
attributeId: 1.2.840.113556.1.4.27
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: bf967947-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.140 Attribute currMachineId

This attribute specifies the ID of the machine where a Link-Track-Vol-Entry object is located.

```
cn: Curr-Machine-Id
ldapDisplayName: currMachineId
attributeId: 1.2.840.113556.1.4.337
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 1f0075fe-7e40-11d0-af6-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
rangeLower: 16
rangeUpper: 16
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.141 Attribute dBCSPwd

This attribute specifies the account's LAN Manager password.

For more information, see [\[MS-SAMR\]](#) section 3.1.1.8.6.

```
cn: DBCS-Pwd
ldapDisplayName: dBCSPwd
attributeId: 1.2.840.113556.1.4.55
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: bf96799c-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.142 Attribute dc

This attribute specifies the naming attribute for domain and DNS objects. Usually displayed as dc=DomainName.

```
cn: Domain-Component
ldapDisplayName: dc
attributeId: 0.9.2342.19200300.100.1.25
```

```

attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 19195a55-6da0-11d0-af3-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 255
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL

```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.143 Attribute defaultClassStore

This attribute specifies the default Class Store for a given user.

```

cn: Default-Class-Store
ldapDisplayName: defaultClassStore
attributeId: 1.2.840.113556.1.4.213
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: bf967948-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.144 Attribute defaultGroup

This attribute specifies the group to which this object is assigned when it is created.

```

cn: Default-Group
ldapDisplayName: defaultGroup
attributeId: 1.2.840.113556.1.4.480
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 720bc4e2-a54a-11d0-afdf-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.145 Attribute defaultHidingValue

This attribute specifies a Boolean value that specifies the default setting of the showInAdvancedViewOnly property of new instances of this class.

```
cn: Default-Hiding-Value
ldapDisplayName: defaultHidingValue
attributeId: 1.2.840.113556.1.4.518
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: b7b13116-b82e-11d0-afee-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.146 Attribute defaultLocalPolicyObject

This attribute specifies a reference to a policy object that defines the local policy for the host object.

```
cn: Default-Local-Policy-Object
ldapDisplayName: defaultLocalPolicyObject
attributeId: 1.2.840.113556.1.4.57
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: bf96799f-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.147 Attribute defaultObjectCategory

This attribute specifies the value to use for the objectCategory attribute (see [\[MS-ADA3\]](#) section 2.38) if one is not specified on object instantiation. For more information on the defaultObjectCategory attribute, see [\[MS-ADTS\]](#) section 3.1.1.2.4.8.

```
cn: Default-Object-Category
```

```
ldapDisplayName: defaultObjectCategory
attributeId: 1.2.840.113556.1.4.783
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 26d97367-6070-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.148 Attribute defaultPriority

The default priority (for example, of a process or a print job).

```
cn: Default-Priority
ldapDisplayName: defaultPriority
attributeId: 1.2.840.113556.1.4.232
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 281416c8-1968-11d0-a28f-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.149 Attribute defaultSecurityDescriptor

This attribute specifies the security descriptor to be assigned to the object when it is created.

```
cn: Default-Security-Descriptor
ldapDisplayName: defaultSecurityDescriptor
attributeId: 1.2.840.113556.1.4.224
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 807a6d30-1669-11d0-a064-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 32767
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.150 Attribute deltaRevocationList

This list contains certificates revoked since the last delta update.

```
cn: Delta-Revocation-List
ldapDisplayName: deltaRevocationList
attributeId: 2.5.4.53
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: 167757b5-47f3-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeUpper: 10485760
mapiID: 35910
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, rangeUpper is not defined.

## 2.151 Attribute department

This attribute contains the name of the user's department.

```
cn: Department
ldapDisplayName: department
attributeId: 1.2.840.113556.1.2.141
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf96794f-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
mapiID: 14872
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.152 Attribute departmentNumber

This attribute can be used to store a department number within an organization.

```
cn: departmentNumber
ldapDisplayName: departmentNumber
attributeId: 2.16.840.1.113730.3.1.2
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: be9ef6ee-cbc7-4f22-b27b-96967e7ee585
systemOnly: FALSE
searchFlags: 0
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.153 Attribute description

This attribute specifies the description to display for an object.

```
cn: Description
ldapDisplayName: description
attributeId: 2.5.4.13
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: bf967950-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 1024
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
mapiID: 32879
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.154 Attribute desktopProfile

This attribute specifies the location of the desktop profile for a user or group of users.

```
cn: Desktop-Profile
ldapDisplayName: desktopProfile
attributeId: 1.2.840.113556.1.4.346
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: eea65906-8ac6-11d0-afda-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.155 Attribute destinationIndicator

This is part of the [\[X500\]](#) specification.

```
cn: Destination-Indicator
ldapDisplayName: destinationIndicator
attributeId: 2.5.4.27
attributeSyntax: 2.5.5.5
omSyntax: 19
isSingleValued: FALSE
schemaIdGuid: bf967951-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 128
mapiID: 32880
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.156 Attribute dhcpClasses

```
cn: dhcp-Classes
ldapDisplayName: dhcpClasses
attributeId: 1.2.840.113556.1.4.715
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: 963d2750-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.157 Attribute dhcpFlags

```
cn: dhcp-Flags
ldapDisplayName: dhcpFlags
attributeId: 1.2.840.113556.1.4.700
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 963d2741-48be-11d1-a9c3-0000f80367c1
```

```
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.158 Attribute dhcpIdentification

```
cn: dhcp-Identification
ldapDisplayName: dhcpIdentification
attributeId: 1.2.840.113556.1.4.701
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 963d2742-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.159 Attribute dhcpMask

```
cn: dhcp-Mask
ldapDisplayName: dhcpMask
attributeId: 1.2.840.113556.1.4.706
attributeSyntax: 2.5.5.5
omSyntax: 19
isSingleValued: FALSE
schemaIdGuid: 963d2747-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.160 Attribute dhcpMaxKey

```
cn: dhcp-MaxKey
ldapDisplayName: dhcpMaxKey
attributeId: 1.2.840.113556.1.4.719
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 963d2754-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.161 Attribute dhcpObjDescription

```
cn: dhcp-Obj-Description
ldapDisplayName: dhcpObjDescription
attributeId: 1.2.840.113556.1.4.703
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 963d2744-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.162 Attribute dhcpObjName

```
cn: dhcp-Obj-Name
ldapDisplayName: dhcpObjName
attributeId: 1.2.840.113556.1.4.702
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 963d2743-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.163 Attribute dhcpOptions

```
cn: dhcp-Options
ldapDisplayName: dhcpOptions
attributeId: 1.2.840.113556.1.4.714
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: 963d274f-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.164 Attribute dhcpProperties

```
cn: dhcp-Properties
ldapDisplayName: dhcpProperties
attributeId: 1.2.840.113556.1.4.718
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: 963d2753-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.165 Attribute dhcpRanges

```
cn: dhcp-Ranges
ldapDisplayName: dhcpRanges
attributeId: 1.2.840.113556.1.4.707
attributeSyntax: 2.5.5.5
omSyntax: 19
isSingleValued: FALSE
schemaIdGuid: 963d2748-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.166 Attribute dhcpReservations

```
cn: dhcp-Reservations
ldapDisplayName: dhcpReservations
attributeId: 1.2.840.113556.1.4.709
attributeSyntax: 2.5.5.5
omSyntax: 19
isSingleValued: FALSE
schemaIdGuid: 963d274a-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.167 Attribute dhcpServers**

This attribute contains a list of servers authorized in the enterprise. This attribute is sent by the Dynamic Host Configuration Protocol (DHCP) server and may contain either the name of the server or its IP address.

```
cn: dhcp-Servers
ldapDisplayName: dhcpServers
attributeId: 1.2.840.113556.1.4.704
attributeSyntax: 2.5.5.5
omSyntax: 19
isSingleValued: FALSE
schemaIdGuid: 963d2745-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
extendedCharsAllowed: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, extendedCharsAllowed is not defined.

## **2.168 Attribute dhcpSites**

```
cn: dhcp-Sites
ldapDisplayName: dhcpSites
attributeId: 1.2.840.113556.1.4.708
attributeSyntax: 2.5.5.5
omSyntax: 19
isSingleValued: FALSE
schemaIdGuid: 963d2749-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.169 Attribute dhcpState**

```
cn: dhcp-State
ldapDisplayName: dhcpState
attributeId: 1.2.840.113556.1.4.717
attributeSyntax: 2.5.5.5
omSyntax: 19
isSingleValued: FALSE
schemaIdGuid: 963d2752-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.170 Attribute dhcpSubnets

```
cn: dhcp-Subnets
ldapDisplayName: dhcpSubnets
attributeId: 1.2.840.113556.1.4.705
attributeSyntax: 2.5.5.5
omSyntax: 19
isSingleValued: FALSE
schemaIdGuid: 963d2746-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.171 Attribute dhcpType

The type of DHCP server. This attribute is sent by the DHCP server during authorization and is currently being set to 0.

```
cn: dhcp-Type
ldapDisplayName: dhcpType
attributeId: 1.2.840.113556.1.4.699
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 963d273b-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: fATTINDEX
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.172 Attribute dhcpUniqueKey

```
cn: dhcp-Unique-Key
ldapDisplayName: dhcpUniqueKey
attributeId: 1.2.840.113556.1.4.698
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 963d273a-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.173 Attribute dhcpUpdateTime

```
cn: dhcp-Update-Time
ldapDisplayName: dhcpUpdateTime
attributeId: 1.2.840.113556.1.4.720
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 963d2755-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.174 Attribute directReports

This attribute contains the list of users who directly report to a user. The users listed as reports are those who have their property-manager property set to this user. Each item in the list is a linked reference to the object that represents the corresponding user.

```
cn: Reports
ldapDisplayName: directReports
attributeId: 1.2.840.113556.1.2.436
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: bf967a1c-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
linkID: 43
mapiID: 32782
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.175 Attribute displayName

This attribute specifies the display name for an object, usually the combination of the user's first name, middle initial, and last name.

```
cn: Display-Name
ldapDisplayName: displayName
attributeId: 1.2.840.113556.1.2.13
attributeSyntax: 2.5.5.12
```

```

omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967953-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fANR | fATTINDEX
rangeLower: 0
rangeUpper: 256
attributeSecurityGuid: 59ba2f42-79a2-11d0-9020-00c04fc2d3cf
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL

```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.176 Attribute displayNamePrintable

This attribute specifies the printable display name for an object, usually the combination of the user's first name, middle initial, and last name.

```

cn: Display-Name-Printable
ldapDisplayName: displayNamePrintable
attributeId: 1.2.840.113556.1.2.353
attributeSyntax: 2.5.5.5
omSyntax: 19
isSingleValued: TRUE
schemaIdGuid: bf967954-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 256
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
mapiID: 14847
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL

```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.177 Attribute distinguishedName

This attribute is the same as the distinguished name for an object and is included on all objects in Active Directory. It is also used by Microsoft® Exchange Server. See [\[MS-ADTS\]](#) section 3.1.1.1.4 for more information.

```

cn: Obj-Dist-Name
ldapDisplayName: distinguishedName
attributeId: 2.5.4.49
attributeSyntax: 2.5.5.1

```

```

omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: bf9679e4-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags:fPRESERVEONDELETE
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
mapiID: 32828
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER | FLAG_ATTR_NOT_REPLICATED
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL

```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.178 Attribute dITContentRules

This attribute specifies the permissible content of entries of a particular structural object class via the identification of an optional set of auxiliary object classes, as well as mandatory, optional, and precluded attributes. Collective attributes shall be included in DIT-Content-Rules, as specified in [\[RFC2251\]](#) section 3.2.1.

```

cn: DIT-Content-Rules
ldapDisplayName: dITContentRules
attributeId: 2.5.21.2
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 9a7ad946-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL

```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.179 Attribute division

This attribute can be used to store the name of a division for a user.

```

cn: Division
ldapDisplayName: division
attributeId: 1.2.840.113556.1.4.261
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE

```

```
schemaIdGuid: fe6136a0-2073-11d0-a9c2-00aa006c33ed
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 0
rangeUpper: 256
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.180 Attribute dMDLocation

This attribute specifies the distinguished name to the schema partition.

```
cn: DMD-Location
ldapDisplayName: dMDLocation
attributeId: 1.2.840.113556.1.2.36
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: f0f8ff8b-1191-11d0-a060-00aa006c33ed
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.181 Attribute dmdName

This attribute specifies a name used to identify the schema partition.

```
cn: DMD-Name
ldapDisplayName: dmdName
attributeId: 1.2.840.113556.1.2.598
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 167757b9-47f3-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 1024
mapiID: 35926
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.182 Attribute dNReferenceUpdate

If an object is renamed, this attribute is used to track all the previous and current names assigned to the object so that linked objects can still find it.

```
cn: DN-Reference-Update
ldapDisplayName: dNReferenceUpdate
attributeId: 1.2.840.113556.1.4.1242
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 2df90d86-009f-11d2-aa4c-00c04fd7d83a
systemOnly: TRUE
searchFlags:fPRESERVEONDELETE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.183 Attribute dnsAllowDynamic

```
cn: Dns-Allow-Dynamic
ldapDisplayName: dnsAllowDynamic
attributeId: 1.2.840.113556.1.4.378
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: e0fa1e65-9b45-11d0-afdd-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.184 Attribute dnsAllowXFR

```
cn: Dns-Allow-XFR
ldapDisplayName: dnsAllowXFR
attributeId: 1.2.840.113556.1.4.379
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: e0fa1e66-9b45-11d0-afdd-00c04fd930c9
systemOnly: FALSE
```

```
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.185 Attribute dNSHostName

This attribute specifies the name of a computer as registered in DNS.

```
cn: DNS-Host-Name
ldapDisplayName: dNSHostName
attributeId: 1.2.840.113556.1.4.619
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 72e39547-7b18-11d1-adef-00c04fd8d5cd
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 2048
attributeSecurityGuid: 72e39547-7b18-11d1-adef-00c04fd8d5cd
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, attributeSecurityGuid is not defined.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.186 Attribute dnsNotifySecondaries

```
cn: Dns-Notify-Secondaries
ldapDisplayName: dnsNotifySecondaries
attributeId: 1.2.840.113556.1.4.381
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: FALSE
schemaIdGuid: e0fa1e68-9b45-11d0-afdd-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.187 Attribute dNSProperty

Written onto dnsZone objects. This attribute is used to store zone properties in BLOB format.

```
cn: DNS-Property
ldapDisplayName: dNSProperty
attributeId: 1.2.840.113556.1.4.1306
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: 675a15fe-3b70-11d2-90cc-00c04fd91ab1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.188 Attribute dnsRecord

This attribute is written onto dnsNode objects. Used to store DNS resource record definitions in BLOB format.

```
cn: Dns-Record
ldapDisplayName: dnsRecord
attributeId: 1.2.840.113556.1.4.382
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: e0fa1e69-9b45-11d0-afdd-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.189 Attribute dnsRoot

The uppermost fully qualified domain name (FQDN) (1) ([\[MS-ADTS\]](#) section 1.1) assigned to a domain naming context. This is set on a crossRef object and is used, among other things, for referral generation. A search through an entire domain tree must be initiated at the Dns-Root object. This attribute can be multivalued, in which case multiple referrals are generated.

```
cn: Dns-Root
ldapDisplayName: dnsRoot
attributeId: 1.2.840.113556.1.4.28
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: bf967959-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fATTINDEX
```

```
rangeLower: 1
rangeUpper: 255
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.190 Attribute dnsSecureSecondaries

```
cn: Dns-Secure-Secondaries
ldapDisplayName: dnsSecureSecondaries
attributeId: 1.2.840.113556.1.4.380
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: FALSE
schemaIdGuid: e0fa1e67-9b45-11d0-afdd-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.191 Attribute dNSTombstoned

Set to TRUE if this object has been tombstoned. This attribute exists to make searching for tombstoned records easier and faster.

Tombstoned objects are objects that have been deleted but not yet removed from the directory. When the value is missing or FALSE, the DNS node is active. When the value is TRUE, the DNS node has been logically deleted, but the dnsNode object is kept alive to avoid excess replication traffic and to replicate node deletions between DNS servers.

```
cn: DNS-Tombstoned
ldapDisplayName: dNSTombstoned
attributeId: 1.2.840.113556.1.4.1414
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: d5eb2eb7-be4e-463b-a214-634a44d7392e
systemOnly: FALSE
searchFlags: fATTINDEX
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.192 Attribute documentAuthor**

```
cn: documentAuthor
ldapDisplayName: documentAuthor
attributeId: 0.9.2342.19200300.100.1.14
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: f18a8e19-af5f-4478-b096-6f35c27eb83f
systemOnly: FALSE
searchFlags: 0
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.193 Attribute documentIdentifier**

```
cn: documentIdentifier
ldapDisplayName: documentIdentifier
attributeId: 0.9.2342.19200300.100.1.11
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 0b21ce82-ff63-46d9-90fb-c8b9f24e97b9
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 256
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.194 Attribute documentLocation**

```
cn: documentLocation
ldapDisplayName: documentLocation
attributeId: 0.9.2342.19200300.100.1.15
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: b958b14e-ac6d-4ec4-8892-be70b69f7281
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 256
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.195 Attribute documentPublisher**

This attribute specifies the person and/or organization that published a document.

```
cn: documentPublisher
ldapDisplayName: documentPublisher
attributeId: 0.9.2342.19200300.100.1.56
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 170f09d7-eb69-448a-9a30-f1afecfd32d7
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 256
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.196 Attribute documentTitle**

```
cn: documentTitle
ldapDisplayName: documentTitle
attributeId: 0.9.2342.19200300.100.1.12
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: de265a9c-ff2c-47b9-91dc-6e6fe2c43062
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 256
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.197 Attribute documentVersion**

```
cn: documentVersion
ldapDisplayName: documentVersion
attributeId: 0.9.2342.19200300.100.1.13
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 94b3a8a9-d613-4cec-9aad-5fbcc1046b43
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 256
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.198 Attribute domainCAs

The Domain-Certificate-Authorities attribute contains a list of certificate authorities for a given domain.

```
cn: Domain-Certificate-Authorities
ldapDisplayName: domainCAs
attributeId: 1.2.840.113556.1.4.668
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 7bfdcb7a-4807-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.199 Attribute domainCrossRef

This is a reference from a trusted domain object to the cross-reference object of the trusted domain.

```
cn: Domain-Cross-Ref
ldapDisplayName: domainCrossRef
attributeId: 1.2.840.113556.1.4.472
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: b000ea7b-a086-11d0-afdd-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The schemaFlagsEx attribute was added to this attribute definition in Windows Server 2008.

## 2.200 Attribute domainID

Reference to a domain associated with a CA.

```
cn: Domain-ID
ldapDisplayName: domainID
attributeId: 1.2.840.113556.1.4.686
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
```

```
schemaIdGuid: 963d2734-48be-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.201 Attribute domainIdentifier

The domain security identifier (SID), as defined in [\[MS-DTYP\]](#) section 2.4.2, identifying the domain. The SID can be represented in any of the three formats described in that section, depending on the type of protocol being used to carry the information.

```
cn: Domain-Identifier
ldapDisplayName: domainIdentifier
attributeId: 1.2.840.113556.1.4.755
attributeSyntax: 2.5.5.17
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 7f561278-5301-11d1-a9c5-0000f80367c1
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.202 Attribute domainPolicyObject

Reference to the policy object defining the Local Security Authority (LSA) policy for the host domain.

```
cn: Domain-Policy-Object
ldapDisplayName: domainPolicyObject
attributeId: 1.2.840.113556.1.4.32
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: bf96795d-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.203 Attribute domainPolicyReference

The distinguished name of a domain policy object that a policy object copies from.

```
cn: Domain-Policy-Reference
ldapDisplayName: domainPolicyReference
attributeId: 1.2.840.113556.1.4.422
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 80a67e2a-9f22-11d0-afdd-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: a29b89fe-c7e8-11d0-9bae-00c04fd92ef5
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.204 Attribute domainReplica

A Unicode string attribute that gives the NetBIOS name of the PDC at the time of upgrade from Microsoft Windows NT® 4.0 operating system, otherwise the default value is NULL.

```
cn: Domain-Replica
ldapDisplayName: domainReplica
attributeId: 1.2.840.113556.1.4.158
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf96795e-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 32767
attributeSecurityGuid: b8119fd0-04f6-4762-ab7a-4986c76b3f9a
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, attributeSecurityGuid is not defined.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.205 Attribute domainWidePolicy

This attribute is for user-extensible policy to be replicated to the clients.

```
cn: Domain-Wide-Policy
ldapDisplayName: domainWidePolicy
attributeId: 1.2.840.113556.1.4.421
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
```

```
schemaIdGuid: 80a67e29-9f22-11d0-afdd-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: a29b89fd-c7e8-11d0-9bae-00c04fd92ef5
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.206 Attribute drink

```
cn: drink
ldapDisplayName: drink
attributeId: 0.9.2342.19200300.100.1.5
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 1a1aa5b5-262e-4df6-af04-2cf6b0d80048
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 256
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.207 Attribute driverName

```
cn: Driver-Name
ldapDisplayName: driverName
attributeId: 1.2.840.113556.1.4.229
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 281416c5-1968-11d0-a28f-00aa003049e2
systemOnly: FALSE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.208 Attribute driverVersion

```
cn: Driver-Version
ldapDisplayName: driverVersion
attributeId: 1.2.840.113556.1.4.276
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
```

```
schemaIdGuid: ba305f6e-47e3-11d0-ala6-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.209 Attribute dSASignature

The [DSA-Signature](#) of an object is the [Invocation-ID](#) of the last directory to modify the object.

```
cn: DSA-Signature
ldapDisplayName: dSASignature
attributeId: 1.2.840.113556.1.2.74
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 167757bc-47f3-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
mapiID: 32887
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.210 Attribute dSCorePropagationData

This attribute is for internal use only.

```
cn: DS-Core-Propagation-Data
ldapDisplayName: dSCorePropagationData
attributeId: 1.2.840.113556.1.4.1357
attributeSyntax: 2.5.5.11
omSyntax: 24
isSingleValued: FALSE
schemaIdGuid: d167aa4b-8b08-11d2-9939-0000f87a57d4
systemOnly: TRUE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER | FLAG_ATTR_NOT_REPLICATED
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.211 Attribute dSHeuristics

This attribute contains global settings for the entire forest. For more information on global settings, see [\[MS-ADTS\]](#).

```
cn: DS-Heuristics
ldapDisplayName: dSHeuristics
attributeId: 1.2.840.113556.1.2.212
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f0f8ff86-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.212 Attribute dSUIAdminMaximum

This is the default maximum number of objects that will be shown in a container by the administration user interface (UI).

```
cn: DS-UI-Admin-Maximum
ldapDisplayName: dSUIAdminMaximum
attributeId: 1.2.840.113556.1.4.1344
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: ee8d0ae0-6f91-11d2-9905-0000f87a57d4
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.213 Attribute dSUIAdminNotification

This attribute specifies a list of the GUIDs of COM objects that support a callback interface that DSAdmin calls when an action has occurred on an object through the UI.

```
cn: DS-UI-Admin-Notification
ldapDisplayName: dSUIAdminNotification
attributeId: 1.2.840.113556.1.4.1343
attributeSyntax: 2.5.5.12
omSyntax: 64
```

```
isSingleValued: FALSE
schemaIdGuid: f6ea0a94-6f91-11d2-9905-0000f87a57d4
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.214 Attribute dSUIShellMaximum

This attribute specifies the default maximum number of objects that will be shown in a container by the shell UI.

```
cn: DS-UI-Shell-Maximum
ldapDisplayName: dSUIShellMaximum
attributeId: 1.2.840.113556.1.4.1345
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: fcaca766a-6f91-11d2-9905-0000f87a57d4
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.215 Attribute dynamicLDAPServer

This attribute specifies the fully qualified domain name (FQDN) (1) ([\[MS-ADTS\]](#) section 1.1) of the server-handling dynamic properties for this account.

```
cn: Dynamic-LDAP-Server
ldapDisplayName: dynamicLDAPServer
attributeId: 1.2.840.113556.1.4.537
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 52458021-ca6a-11d0-afff-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.216 Attribute eFSPolicy

The Encrypting File System (EFS) Policy.

```
cn: EFS Policy
ldapDisplayName: eFSPolicy
attributeId: 1.2.840.113556.1.4.268
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: 8e4eb2ec-4712-11d0-a1a0-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: a29b89fd-c7e8-11d0-9bae-00c04fd92ef5
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.217 Attribute employeeID

This attribute specifies the ID of an employee.

```
cn: Employee-ID
ldapDisplayName: employeeID
attributeId: 1.2.840.113556.1.4.35
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967962-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 16
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.218 Attribute employeeNumber

This attribute specifies the number assigned to an employee other than the ID.

```
cn: Employee-Number
ldapDisplayName: employeeNumber
attributeId: 1.2.840.113556.1.2.610
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: a8df73ef-c5ea-11d1-bbcb-0080c76670c0
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 512
```

```
mapiID: 35943
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, the following attributes are defined differently.

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

## 2.219 Attribute employeeType

This attribute specifies the job category for an employee.

```
cn: Employee-Type
ldapDisplayName: employeeType
attributeId: 1.2.840.113556.1.2.613
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: a8df73f0-c5ea-11d1-bbcb-0080c76670c0
systemOnly: FALSE
searchFlags: fCOPY
rangeLower: 1
rangeUpper: 256
mapiID: 35945
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, the following attributes are defined differently.

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

## 2.220 Attribute Enabled

This attribute is used to signify whether a given crossRef is enabled.

```
cn: Enabled
ldapDisplayName: Enabled
attributeId: 1.2.840.113556.1.2.557
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: a8df73f2-c5ea-11d1-bbcb-0080c76670c0
systemOnly: FALSE
searchFlags: 0
mapiID: 35873
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.221 Attribute `enabledConnection`

This attribute specifies whether a connection is available for use.

```
cn: Enabled-Connection
ldapDisplayName: enabledConnection
attributeId: 1.2.840.113556.1.4.36
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: bf967963-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.222 Attribute `enrollmentProviders`

Public key infrastructure (PKI) certificate templates.

```
cn: Enrollment-Providers
ldapDisplayName: enrollmentProviders
attributeId: 1.2.840.113556.1.4.825
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 2a39c5b3-8960-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.223 Attribute `entryTTL`

This operational attribute is maintained by the server and appears to be present in every dynamic entry. The attribute is not present when the entry does not contain the dynamicObject object class. The value of this attribute is the time in seconds that the entry will continue to exist before disappearing from the directory.

In the absence of intervening "refresh" operations, the values returned by reading the attribute in two successive searches are guaranteed to be nonincreasing. The smallest permissible value is 0, indicating that the entry may disappear without warning. The attribute is marked NO-USER-MODIFICATION because it may only be changed by using the refresh operation.

```
cn: Entry-TTL
ldapDisplayName: entryTTL
attributeId: 1.3.6.1.4.1.1466.101.119.3
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: d213decc-d81a-4384-aac2-dcfefcfd631cf8
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 31557600
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.224 Attribute extendedAttributeInfo

This attribute specifies a multivalued property containing strings that represent additional information for each attribute.

```
cn: Extended-Attribute-Info
ldapDisplayName: extendedAttributeInfo
attributeId: 1.2.840.113556.1.4.909
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 9a7ad947-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.225 Attribute extendedCharsAllowed

This attribute specifies whether extended characters are allowed in the value of this attribute. Applies only to IA5, numeric, printable, and teletex string attributes.

```
cn: Extended-Chars-Allowed
ldapDisplayName: extendedCharsAllowed
attributeId: 1.2.840.113556.1.2.380
attributeSyntax: 2.5.5.8
```

```
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: bf967966-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
mapiID: 32935
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, the following attributes are defined differently.

```
systemOnly: TRUE
```

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.226 Attribute extendedClassInfo

This attribute specifies a multivalued property containing strings that represent additional information for each class. Each value contains the governsID, IDAPDisplayName, and schemaIDGUID of the class.

```
cn: Extended-Class-Info
ldapDisplayName: extendedClassInfo
attributeId: 1.2.840.113556.1.4.908
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 9a7ad948-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.227 Attribute extensionName

This attribute specifies the name of a property page used to extend the UI of a directory object.

```
cn: Extension-Name
ldapDisplayName: extensionName
attributeId: 1.2.840.113556.1.2.227
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
```

```
schemaIdGuid: bf967972-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 255
mapiID: 32937
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.228 Attribute extraColumns

This is a multivalued attribute whose value(s) consist of a 5 tuple: (attribute name), (column title), (default visibility (0,1)), (column width (-1 for auto width)), and 0 (reserved for future use must be zero). This value is used by the Active Directory Users and Computers console.

```
cn: Extra-Columns
ldapDisplayName: extraColumns
attributeId: 1.2.840.113556.1.4.1687
attributesSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: d24e2846-1dd9-4bcf-99d7-a6227cc86da7
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.229 Attribute facsimileTelephoneNumber

Contains the telephone number of the user's business fax machine.

```
cn: Facsimile-Telephone-Number
ldapDisplayName: facsimileTelephoneNumber
attributeId: 2.5.4.23
attributesSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967974-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
mapiID: 14883
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.230 Attribute fileExtPriority

This attribute specifies a list of file extensions in an application package and their associated priorities.

```
cn: File-Ext-Priority
ldapDisplayName: fileExtPriority
attributeId: 1.2.840.113556.1.4.816
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: d9e18315-8939-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: fATTINDEX
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.231 Attribute flags

To be used by the object to store bit information.

```
cn: Flags
ldapDisplayName: flags
attributeId: 1.2.840.113556.1.4.38
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf967976-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.232 Attribute flatName

For Microsoft Windows NT® operating system domains, the flat name is the NetBIOS name. For links with non-Windows NT domains, the flat name is the identifying name of that domain or it is NULL.

```
cn: Flat-Name
ldapDisplayName: flatName
attributeId: 1.2.840.113556.1.4.511
attributeSyntax: 2.5.5.12
```

```
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: b7b13117-b82e-11d0-afee-0000f80367c1
systemOnly: FALSE
searchFlags: fATTINDEX
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.233 Attribute forceLogoff

This attribute is used in computing the kickoff time. Logoff time minus Force Log Off equals kickoff time.

```
cn: Force-Logoff
ldapDisplayName: forceLogoff
attributeId: 1.2.840.113556.1.4.39
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf967977-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: b8119fd0-04f6-4762-ab7a-4986c76b3f9a
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, attributeSecurityGuid is not defined.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.234 Attribute foreignIdentifier

This attribute specifies the security properties used by a foreign system.

```
cn: Foreign-Identifier
ldapDisplayName: foreignIdentifier
attributeId: 1.2.840.113556.1.4.356
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 3e97891e-8c01-11d0-afda-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.235 Attribute friendlyNames

This attribute specifies a list of default friendly name definitions supported by a catalog.

```
cn: Friendly-Names
ldapDisplayName: friendlyNames
attributeId: 1.2.840.113556.1.4.682
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 7bfdcb88-4807-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.236 Attribute fromEntry

This is a constructed attribute that is TRUE if the object is writable, and FALSE if it is read-only (for example, a global catalog replica instance).

```
cn: From-Entry
ldapDisplayName: fromEntry
attributeId: 1.2.840.113556.1.4.910
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: FALSE
schemaIdGuid: 9a7ad949-ca53-11d1-bbd0-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_IS_CONSTRUCTED |
FLAG_DOMAIN_DISALLOW_RENAME
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.237 Attribute fromServer

This attribute specifies the distinguished name of the replication source server.

```
cn: From-Server
ldapDisplayName: fromServer
attributeId: 1.2.840.113556.1.4.40
attributeSyntax: 2.5.5.1
```

```
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: bf967979-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fATTINDEX
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.238 Attribute frsComputerReference

This File Replication service (FRS) attribute contains a reference to a replica set member's computer object.

```
cn: Frs-Computer-Reference
ldapDisplayName: frsComputerReference
attributeId: 1.2.840.113556.1.4.869
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 2a132578-9373-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
linkID: 102
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.239 Attribute frsComputerReferenceBL

This FRS attribute is a back link attribute of [Attribute frsComputerReference](#) and contains a reference to replica sets to which this computer belongs.

```
cn: Frs-Computer-Reference-BL
ldapDisplayName: frsComputerReferenceBL
attributeId: 1.2.840.113556.1.4.870
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 2a132579-9373-11d1-aebc-0000f80367c1
systemOnly: TRUE
searchFlags: 0
linkID: 103
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.240 Attribute fRSControlDataCreation

This FRS attribute contains a Warning/Error level pair for file data creation (megabyte (MB) per second).

```
cn: FRS-Control-Data-Creation
ldapDisplayName: fRSControlDataCreation
attributeId: 1.2.840.113556.1.4.871
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 2a13257a-9373-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 32
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.241 Attribute fRSControlInboundBacklog

This FRS attribute contains a Warning/Error level pair for inbound backlog (number of files).

```
cn: FRS-Control-Inbound-Backlog
ldapDisplayName: fRSControlInboundBacklog
attributeId: 1.2.840.113556.1.4.872
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 2a13257b-9373-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 32
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.242 Attribute fRSControlOutboundBacklog

This FRS attribute contains a Warning/Error level pair for outbound backlog (number of files).

```
cn: FRS-Control-Outbound-Backlog
ldapDisplayName: fRSControlOutboundBacklog
attributeId: 1.2.840.113556.1.4.873
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 2a13257c-9373-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 32
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.243 Attribute fRSDirectoryFilter**

This FRS attribute contains a list of directories excluded from file replication (for example, the "temp" directory or the "obj" directory).

```
cn: FRS-Directory-Filter
ldapDisplayName: fRSDirectoryFilter
attributeId: 1.2.840.113556.1.4.484
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 1be8f171-a9ff-11d0-afe2-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 2048
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.244 Attribute fRSDSPoll**

This FRS attribute contains the DS polling interval for the file replication engine.

```
cn: FRS-DS-Poll
ldapDisplayName: fRSDSPoll
attributeId: 1.2.840.113556.1.4.490
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 1be8f177-a9ff-11d0-afe2-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.245 Attribute fRSExtensions

This FRS attribute contains binary data used by file replication.

```
cn: FRS-Extensions
ldapDisplayName: fRSExtensions
attributeId: 1.2.840.113556.1.4.536
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 52458020-ca6a-11d0-afff-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 65536
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.246 Attribute fRSFaultCondition

This FRS attribute contains the fault condition for a member.

```
cn: FRS-Fault-Condition
ldapDisplayName: fRSFaultCondition
attributeId: 1.2.840.113556.1.4.491
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 1be8f178-a9ff-11d0-afe2-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 16
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.247 Attribute fRSFileFilter

This FRS attribute contains the list of file extensions excluded from file replication.

```
cn: FRS-File-Filter
ldapDisplayName: fRSFileFilter
attributeId: 1.2.840.113556.1.4.483
attributeSyntax: 2.5.5.12
omSyntax: 64
```

```
isSingleValued: TRUE
schemaIdGuid: 1be8f170-a9ff-11d0-afe2-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 2048
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.248 Attribute fRSFlags

This FRS attribute contains the FRS option flags.

```
cn: FRS-Flags
ldapDisplayName: fRSFlags
attributeId: 1.2.840.113556.1.4.874
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 2a13257d-9373-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.249 Attribute fRSLevelLimit

This FRS attribute contains the limit depth of the directory tree to replicate for file replication.

```
cn: FRS-Level-Limit
ldapDisplayName: fRSLevelLimit
attributeId: 1.2.840.113556.1.4.534
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 5245801e-ca6a-11d0-afff-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.250 Attribute fRSMemberReference

This FRS attribute contains a reference to the member object for this subscriber.

```

cn: FRS-Member-Reference
ldapDisplayName: fRSMemberReference
attributeId: 1.2.840.113556.1.4.875
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 2a13257e-9373-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
linkID: 104
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER

```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.251 Attribute fRSMemberReferenceBL

This FRS attribute is the back link attribute of [Attribute fRSMemberReference](#) and contains a reference to subscriber objects for this member.

```

cn: FRS-Member-Reference-BL
ldapDisplayName: fRSMemberReferenceBL
attributeId: 1.2.840.113556.1.4.876
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 2a13257f-9373-11d1-aebc-0000f80367c1
systemOnly: TRUE
searchFlags: 0
linkID: 105
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED

```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.252 Attribute fRSPartnerAuthLevel

This FRS attribute contains the remote procedure call (RPC) security level.

```

cn: FRS-Partner-Auth-Level
ldapDisplayName: fRSPartnerAuthLevel
attributeId: 1.2.840.113556.1.4.877
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 2a132580-9373-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0

```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.253 Attribute fRSPrimaryMember

This FRS attribute contains a reference to the primary member of a replica set.

```
cn: FRS-Primary-Member
ldapDisplayName: fRSPrimaryMember
attributeId: 1.2.840.113556.1.4.878
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 2a132581-9373-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
linkID: 106
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.254 Attribute fRSReplicaSetGUID

This FRS attribute contains a GUID that identifies an FRS replica set.

```
cn: FRS-Replica-Set-GUID
ldapDisplayName: fRSReplicaSetGUID
attributeId: 1.2.840.113556.1.4.533
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 5245801a-ca6a-11d0-afff-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 16
rangeUpper: 16
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.255 Attribute fRSReplicaSetType

This FRS attribute contains a code that indicates whether this is a system volume (SYSVOL) replica set, a distributed file system (DFS) replica set, or other replica set.

```
cn: FRS-Replica-Set-Type
ldapDisplayName: fRSReplicaSetType
attributeId: 1.2.840.113556.1.4.31
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 26d9736b-6070-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.256 Attribute fRSRootPath

This FRS attribute contains a path to the root of the replicated file system tree.

```
cn: FRS-Root-Path
ldapDisplayName: fRSRootPath
attributeId: 1.2.840.113556.1.4.487
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 1be8f174-a9ff-11d0-afe2-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 2048
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.257 Attribute fRSRootSecurity

This FRS attribute contains a security descriptor of the replica set root for file replication.

```
cn: FRS-Root-Security
ldapDisplayName: fRSRootSecurity
attributeId: 1.2.840.113556.1.4.535
attributeSyntax: 2.5.5.15
omSyntax: 66
isSingleValued: TRUE
schemaIdGuid: 5245801f-ca6a-11d0-afff-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 65535
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.258 Attribute fRSServiceCommand

This FRS attribute contains a Unicode string that an administrator can set to pass a command to every replica set member.

```
cn: FRS-Service-Command
ldapDisplayName: fRSServiceCommand
attributeId: 1.2.840.113556.1.4.500
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: ddac0cee-af8f-11d0-afeb-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 512
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.259 Attribute fRSServiceCommandStatus

This FRS attribute contains the response from the last command issued to a member.

```
cn: FRS-Service-Command-Status
ldapDisplayName: fRSServiceCommandStatus
attributeId: 1.2.840.113556.1.4.879
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 2a132582-9373-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 512
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.260 Attribute fRSStagingPath

This FRS attribute contains a path to the file replication staging area.

```
cn: FRS-Staging-Path
ldapDisplayName: fRSStagingPath
attributeId: 1.2.840.113556.1.4.488
attributeSyntax: 2.5.5.12
```

```
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 1be8f175-a9ff-11d0-afe2-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 2048
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.261 Attribute fRSTimeLastCommand

This FRS attribute contains the time in which the last command was executed.

```
cn: FRS-Time-Last-Command
ldapDisplayName: fRSTimeLastCommand
attributeId: 1.2.840.113556.1.4.880
attributeSyntax: 2.5.5.11
omSyntax: 23
isSingleValued: TRUE
schemaIdGuid: 2a132583-9373-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.262 Attribute fRSTimeLastConfigChange

This FRS attribute contains the time in which the last configuration change was accepted.

```
cn: FRS-Time-Last-Config-Change
ldapDisplayName: fRSTimeLastConfigChange
attributeId: 1.2.840.113556.1.4.881
attributeSyntax: 2.5.5.11
omSyntax: 23
isSingleValued: TRUE
schemaIdGuid: 2a132584-9373-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.263 Attribute fRSUpdateTimeout**

This FRS attribute contains the maximum time, in minutes, to wait to complete an update before giving up.

```
cn: FRS-Update-Timeout
ldapDisplayName: fRSUpdateTimeout
attributeId: 1.2.840.113556.1.4.485
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 1be8f172-a9ff-11d0-afe2-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.264 Attribute fRSVersion**

This FRS attribute contains the version number and build date.

```
cn: FRS-Version
ldapDisplayName: fRSVersion
attributeId: 1.2.840.113556.1.4.882
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 2a132585-9373-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 32
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.265 Attribute fRSVersionGUID**

If this FRS attribute is present, changing its value indicates that a configuration change has been made on this replica set.

```
cn: FRS-Version-GUID
ldapDisplayName: fRSVersionGUID
attributeId: 1.2.840.113556.1.4.43
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 26d9736c-6070-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
```

```
rangeLower: 16
rangeUpper: 16
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.266 Attribute fRSWorkingPath

This FRS attribute contains the path to the file replication database.

```
cn: FRS-Working-Path
ldapDisplayName: fRSWorkingPath
attributeId: 1.2.840.113556.1.4.486
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 1be8f173-a9ff-11d0-afe2-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 2048
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.267 Attribute fSMORoleOwner

The fSMORoleOwner attribute stores the distinguished name of a DSA object as described in [\[MS-ADTS\]](#) section 3.1.1.11 (FSMO Roles).

```
cn: FSMO-Role-Owner
ldapDisplayName: fSMORoleOwner
attributeId: 1.2.840.113556.1.4.369
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 66171887-8f3c-11d0-afda-00c04fd930c9
systemOnly: FALSE
searchFlags: fATTINDEX
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.268 Attribute garbageCollPeriod

This attribute is located on the CN=Directory Service,CN=Windows NT,CN=Services,CN=Configuration,... object. It represents the period, in hours, between DS garbage collection runs.

```
cn: Garbage-Coll-Period
ldapDisplayName: garbageCollPeriod
attributeId: 1.2.840.113556.1.2.301
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 5fd424a1-1262-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
mapiID: 32943
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.269 Attribute gecos

The **GECOS** field (the common name, as specified in [\[RFC2307\]](#) section 3).

```
cn: Gecos
ldapDisplayName: gecos
attributeId: 1.3.6.1.1.1.2
attributeSyntax: 2.5.5.5
omSyntax: 22
isSingleValued: TRUE
schemaIdGuid: a3e03f1f-1d55-4253-a0af-30c2a784e46e
systemOnly: FALSE
searchFlags: 0
rangeUpper: 10240
```

Version-Specific Behavior: Implemented on Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.270 Attribute generatedConnection

Set to TRUE if this connection was created by autotopology generation.

```
cn: Generated-Connection
ldapDisplayName: generatedConnection
attributeId: 1.2.840.113556.1.4.41
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: bf96797a-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
```

```
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.271 Attribute generationQualifier

Indicates a person's generation; for example, junior (Jr.) or II.

```
cn: Generation-Qualifier
ldapDisplayName: generationQualifier
attributeId: 2.5.4.44
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 16775804-47f3-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
mapiID: 35923
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.272 Attribute gidNumber

An integer uniquely identifying a group in an administrative domain, as specified in [\[RFC2307\]](#).

```
cn: GidNumber
ldapDisplayName: gidNumber
attributeId: 1.3.6.1.1.1.1
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: c5b95f0c-ec9e-41c4-849c-b46597ed6696
systemOnly: FALSE
searchFlags: fATTINDEX
```

Version-Specific Behavior: Implemented on Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.273 Attribute givenName

Contains the given name (first name) of the user.

```
cn: Given-Name
ldapDisplayName: givenName
attributeId: 2.5.4.42
```

```
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f0f8ff8e-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: fANR | fATTINDEX
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
mapiID: 14854
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.274 Attribute **globalAddressList**

This attribute is used on an Microsoft® Exchange Server container to store the distinguished name of a newly created global address list (GAL). This attribute must have an entry before the implementer can enable MAPI clients to use a GAL.

```
cn: Global-Address-List
ldapDisplayName: globalAddressList
attributeId: 1.2.840.113556.1.4.1245
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: f754c748-06f4-11d2-aa53-00c04fd7d83a
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.275 Attribute **globalAddressList2**

This attribute is used on an Microsoft® Exchange Server container to store the distinguished name of a newly created GAL. This attribute must have an entry before the implementer can enable MAPI clients to use a GAL. Similar to [globalAddressList](#), it differs by being a linked attribute.

```
cn: Global-Address-List2
ldapDisplayName: globalAddressList2
attributeId: 1.2.840.113556.1.4.2047
attributeSyntax: 2.5.5.1
```

```
linkID: 2124
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 4898f63d-4112-477c-8826-3ca00bd8277d
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Windows Server® 2008 operating system and Windows Server® 2008 R2 operating system.

## 2.276 Attribute **governsID**

This attribute specifies the unique object ID of the class defined by this class-schema object.

```
cn: Governs-ID
ldapDisplayName: governsID
attributeId: 1.2.840.113556.1.2.22
attributeSyntax: 2.5.5.2
omSyntax: 6
isSingleValued: TRUE
schemaIdGuid: bf96797d-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags:fPRESERVEONDELETE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.277 Attribute **gPCFileSysPath**

This attribute specifies the Universal Naming Convention (UNC) path to the Group Policy object template located in the system volume (SYSVOL).

```
cn: GPC-File-Sys-Path
ldapDisplayName: gPCFileSysPath
attributeId: 1.2.840.113556.1.4.894
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f30e3bc1-9ff0-11d1-b603-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.278 Attribute gPCFunctionalityVersion**

This attribute specifies the version of the Group Policy Object Editor that created this object.

```
cn: GPC-Functionality-Version
ldapDisplayName: gPCFunctionalityVersion
attributeId: 1.2.840.113556.1.4.893
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: f30e3bc0-9ff0-11d1-b603-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.279 Attribute gPCMachineExtensionNames**

This attribute is used by the Group Policy object (GPO) for machine policies.

```
cn: GPC-Machine-Extension-Names
ldapDisplayName: gPCMachineExtensionNames
attributeId: 1.2.840.113556.1.4.1348
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 32ff8ecc-783f-11d2-9916-0000f87a57d4
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.280 Attribute gPCUserExtensionNames**

This attribute is used by the GPO for user policies.

```
cn: GPC-User-Extension-Names
ldapDisplayName: gPCUserExtensionNames
attributeId: 1.2.840.113556.1.4.1349
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 42a75fc6-783f-11d2-9916-0000f87a57d4
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.281 Attribute gPCWQLFilter

This attribute is used to store a string that contains a GUID for the filter and a Windows Management Instrumentation (WMI) namespace path.

```
cn: GPC-WQL-Filter
ldapDisplayName: gPCWQLFilter
attributeId: 1.2.840.113556.1.4.1694
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 7bd4c7a6-1add-4436-8c04-3999a880154c
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.282 Attribute gPLink

This attribute specifies a value used by the Group Policy Core Protocol. See [\[MS-GPOL\]](#) section 2.2.2.

```
cn: GP-Link
ldapDisplayName: gPLink
attributeId: 1.2.840.113556.1.4.891
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f30e3bbe-9ff0-11d1-b603-0000f80367c1
systemOnly: FALSE
searchFlags: 0
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.283 Attribute gPOptions

Options that affect all Group Policy associated with the object hosting this property.

```
cn: GP-Options
ldapDisplayName: gPOptions
attributeId: 1.2.840.113556.1.4.892
attributeSyntax: 2.5.5.9
omSyntax: 2
```

```
isSingleValued: TRUE
schemaIdGuid: f30e3bbf-9ff0-11d1-b603-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.284 Attribute groupAttributes

```
cn: Group-Attributes
ldapDisplayName: groupAttributes
attributeId: 1.2.840.113556.1.4.152
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf96797e-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fATTINDEX
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.285 Attribute groupMembershipSAM

Microsoft Windows NT® operating system security. Down-level Windows NT support.

```
cn: Group-Membership-SAM
ldapDisplayName: groupMembershipSAM
attributeId: 1.2.840.113556.1.4.166
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: bf967980-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.286 Attribute groupPriority

```
cn: Group-Priority
ldapDisplayName: groupPriority
attributeId: 1.2.840.113556.1.4.345
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
```

```
schemaIdGuid: eea65905-8ac6-11d0-afda-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.287 Attribute groupsToIgnore

```
cn: Groups-to-Ignore
ldapDisplayName: groupsToIgnore
attributeId: 1.2.840.113556.1.4.344
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: eea65904-8ac6-11d0-afda-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.288 Attribute groupType

This attribute contains a set of flags that define the type and scope of a group object. For more information about the possible values for this attribute, see the Remarks section of [\[MSDN-GroupType\]](#).

```
cn: Group-Type
ldapDisplayName: groupType
attributeId: 1.2.840.113556.1.4.750
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 9a9a021e-4a5b-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags:fPRESERVEONDELETE | fATTINDEX
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.289 Attribute hasMasterNCs

This attribute contains the distinguished names of naming contexts. Forward link for the [Mastered-By](#) attribute.

```
cn: Has-Master-NCs
ldapDisplayName: hasMasterNCs
attributeId: 1.2.840.113556.1.2.14
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: bf967982-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
linkID: 76
mapiID: 32950
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.290 Attribute hasPartialReplicaNCs

Sibling to [Has-Master-NCs](#). The [Has-Partial-Replica-NCs](#) attribute reflects the distinguished name for all other-domain NCs that have been replicated into a global catalog (GC).

```
cn: Has-Partial-Replica-NCs
ldapDisplayName: hasPartialReplicaNCs
attributeId: 1.2.840.113556.1.2.15
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: bf967981-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
linkID: 74
mapiID: 32949
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.291 Attribute helpData16

This attribute was used for the Win16 Help file format for Microsoft® Exchange Server 4.0. It is not used for any other versions of Exchange Server.

```
cn: Help-Data16
ldapDisplayName: helpData16
attributeId: 1.2.840.113556.1.2.402
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 5fd424a7-1262-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 32768
mapiID: 32826
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.292 Attribute helpData32

This attribute was used for the Win32 Help file format for Microsoft® Exchange Server 4.0. It is not used for any other versions of Exchange Server.

```
cn: Help-Data32
ldapDisplayName: helpData32
attributeId: 1.2.840.113556.1.2.9
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 5fd424a8-1262-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 32768
mapiID: 32784
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.293 Attribute helpFileName

This attribute was used for Microsoft® Exchange Server 4.0. It contained the name that should be used for the file when the provider downloaded Help data to a client computer. It is not used for any other versions of Exchange Server.

```
cn: Help-File-Name
ldapDisplayName: helpFileName
attributeId: 1.2.840.113556.1.2.327
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 5fd424a9-1262-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 13
mapiID: 32827
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.294 Attribute hideFromAB

This is a defunct attribute and it should not be used.

```
cn: Hide-From-AB
ldapDisplayName: hideFromAB
attributeId: 1.2.840.113556.1.4.1780
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: ec05b750-a977-4efe-8e8d-ba6c1a6e33a8
systemOnly: FALSE
searchFlags: 0
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.295 Attribute homeDirectory

This attribute specifies the home directory for the account. This value can be a null string.

```
cn: Home-Directory
ldapDisplayName: homeDirectory
attributeId: 1.2.840.113556.1.4.44
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
```

```
schemaIdGuid: bf967985-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
attributeSecurityGuid: 5f202010-79a5-11d0-9020-00c04fc2d4cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.296 Attribute homeDrive

This attribute specifies the drive letter to which to map the UNC path specified by [homeDirectory](#). The drive letter must be specified in the form "<DriveLetter>:" where <DriveLetter> is the letter of the drive to map. The <DriveLetter> must be a single, uppercase letter and the colon (:) is required.

```
cn: Home-Drive
ldapDisplayName: homeDrive
attributeId: 1.2.840.113556.1.4.45
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf967986-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
attributeSecurityGuid: 5f202010-79a5-11d0-9020-00c04fc2d4cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.297 Attribute homePhone

The user's main home telephone number.

```
cn: Phone-Home-Primary
ldapDisplayName: homePhone
attributeId: 0.9.2342.19200300.100.1.20
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f0f8fffa1-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
```

```
mapiID: 14857
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

On Windows 2000 Server, the following attributes are defined differently.

```
systemFlags: 0
```

## 2.298 Attribute **homePostalAddress**

This attribute specifies a user's home address.

```
cn: Address-Home
ldapDisplayName: homePostalAddress
attributeId: 1.2.840.113556.1.2.617
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 16775781-47f3-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 4096
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
mapiID: 14941
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

On Windows 2000 Server, the following attribute is defined differently.

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

## 2.299 Attribute **host**

This attribute type specifies a host computer.

```
cn: host
ldapDisplayName: host
attributeId: 0.9.2342.19200300.100.1.9
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 6043df71-fa48-46cf-ab7c-cbd54644b22d
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
```

```
rangeUpper: 256
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.300 Attribute houseIdentifier

The houseIdentifier attribute specifies a linguistic construct used to identify a particular building; for example, a house number or house name relative to a street, avenue, town, or city.

```
cn: houseIdentifier
ldapDisplayName: houseIdentifier
attributeId: 2.5.4.51
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: a45398b7-c44a-4eb6-82d3-13c10946dbfe
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 32768
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.301 Attribute iconPath

This attribute specifies the source for loading an icon.

```
cn: Icon-Path
ldapDisplayName: iconPath
attributeId: 1.2.840.113556.1.4.219
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: f0f8ff83-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 2048
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.302 Attribute implementedCategories

This attribute specifies a list of component category IDs that this object implements.

```
cn: Implemented-Categories
```

```
ldapDisplayName: implementedCategories
attributeId: 1.2.840.113556.1.4.320
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: 7d6c0e92-7e20-11d0-af6-00c04fd930c9
systemOnly: FALSE
searchFlags: fATTINDEX
rangeLower: 16
rangeUpper: 16
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.303 Attribute indexedScopes

This attribute specifies the list of indexed directory scopes (for example, C:\ or D:\).

```
cn: IndexedScopes
ldapDisplayName: indexedScopes
attributeId: 1.2.840.113556.1.4.681
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 7bfdcb87-4807-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.304 Attribute info

This attribute specifies the user's comments. This string can be a null string.

```
cn: Comment
ldapDisplayName: info
attributeId: 1.2.840.113556.1.2.81
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf96793e-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 1024
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
mapiID: 12292
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.305 Attribute initialAuthIncoming

This attribute is not necessary for Active Directory functioning, and this protocol does not define a format beyond that required by the schema.

```
cn: Initial-Auth-Incoming
ldapDisplayName: initialAuthIncoming
attributeId: 1.2.840.113556.1.4.539
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 52458023-ca6a-11d0-afff-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.306 Attribute initialAuthOutgoing

This attribute is used to contain information about an initial outgoing authentication sent by the authentication server for this domain to the client that requested authentication. The server that uses this attribute receives the authorization from the authentication server and sends it to the client.

```
cn: Initial-Auth-Outgoing
ldapDisplayName: initialAuthOutgoing
attributeId: 1.2.840.113556.1.4.540
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 52458024-ca6a-11d0-afff-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.307 Attribute initials

This attribute contains the initials for parts of the user's full name. This may be used as the middle initial in the Windows address book.

```
cn: Initials
ldapDisplayName: initials
attributeId: 2.5.4.43
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: f0f8ff90-1191-11d0-a060-00aa006c33ed
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 6
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
mapiID: 14858
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.308 Attribute installUiLevel

This attribute specifies information for the type (level) of installation that is used for the user interface. Possible installation levels are as follows: 2 INSTALLUILEVEL\_NONE (silent installation), 3 INSTALLUILEVEL\_BASIC (simple installation with error handling), 4 INSTALLUILEVEL\_REDUCED (authored UI, wizard dialogs suppressed), and 5 INSTALLUILEVEL\_FULL (authored UI with wizards, progress, and errors).

```
cn: Install-Ui-Level
ldapDisplayName: installUiLevel
attributeId: 1.2.840.113556.1.4.847
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: 96a7dd64-9118-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.309 Attribute instanceType

A bit field that dictates how the object is instantiated on a particular server. The value of this attribute can differ on different replicas even if the replicas are in sync. This attribute can be zero or a combination of one or more of the following bit flags.

Bit flag	Meaning
0x00000001	The head of naming context.
0x00000002	This replica is not instantiated.
0x00000004	The object is writable on this directory.
0x00000008	The naming context above this one on this directory is held.
0x00000010	The naming context is being constructed for the first time via replication.
0x00000020	The naming context is being removed from the local directory system agent (DSA).

```

cn: Instance-Type
ldapDisplayName: instanceType
attributeId: 1.2.840.113556.1.2.1
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf96798c-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags:fPRESERVEONDELETE
mapiID: 32957
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL

```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.310 Attribute **internationalISDNNumber**

This attribute specifies an international ISDN number associated with an object.

```

cn: International-ISDN-Number
ldapDisplayName: internationalISDNNumber
attributeId: 2.5.4.25
attributeSyntax: 2.5.5.6
omSyntax: 18
isSingleValued: FALSE
schemaIdGuid: bf96798d-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
rangeLower: 1
rangeUpper: 16
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
mapiID: 32958
systemFlags: FLAG_SCHEMA_BASE_OBJECT

```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.311 Attribute interSiteTopologyFailover

This attribute indicates how much time must transpire since the last keep-alive message for the intersite topology generator to be considered dead.

```
cn: Inter-Site-Topology-Failover
ldapDisplayName: interSiteTopologyFailover
attributeId: 1.2.840.113556.1.4.1248
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: b7c69e60-2cc7-11d2-854e-00a0c983f608
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

**Note** This attribute is used for the server-to-server replication implementation only; the meaning is not significant to Microsoft Windows® clients.

## 2.312 Attribute interSiteTopologyGenerator

This attribute specifies support failover for the machine designated as the one that runs Knowledge Consistency Checker (KCC) intersite topology generation in a given site.

```
cn: Inter-Site-Topology-Generator
ldapDisplayName: interSiteTopologyGenerator
attributeId: 1.2.840.113556.1.4.1246
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: b7c69e5e-2cc7-11d2-854e-00a0c983f608
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

**Note** This attribute is used for the server-to-server replication implementation only; the meaning is not significant to Microsoft Windows® clients.

### 2.313 Attribute `interSiteTopologyRenew`

This attribute indicates how often the intersite topology generator updates the keep-alive message that is sent to domain controllers that are contained in the same site.

```
cn: Inter-Site-Topology-Renew
ldapDisplayName: interSiteTopologyRenew
attributeId: 1.2.840.113556.1.4.1247
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: b7c69e5f-2cc7-11d2-854e-00a0c983f608
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

**Note** This attribute is used for the server-to-server replication implementation only; the meaning is not significant to Microsoft Windows® clients.

### 2.314 Attribute `invocationId`

This attribute is used to uniquely identify the specific version of the directory database associated with a domain controller.

```
cn: Invocation-Id
ldapDisplayName: invocationId
attributeId: 1.2.840.113556.1.2.115
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: bf96798e-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: fATTINDEX
mapiID: 32959
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, the following attributes are defined differently.

```
searchFlags: 0
```

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.315 Attribute ipHostNumber

This attribute specifies the IP address as a dotted decimal, omitting leading zeros.

```
cn: IpHostNumber
ldapDisplayName: ipHostNumber
attributeId: 1.3.6.1.1.1.19
attributeSyntax: 2.5.5.5
omSyntax: 22
isSingleValued: FALSE
schemaIdGuid: de8bb721-85dc-4fde-b687-9657688e667e
systemOnly: FALSE
searchFlags: 0
rangeUpper: 128
```

Version-Specific Behavior: Implemented on Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.316 Attribute ipNetmaskNumber

This attribute specifies the IP netmask as a dotted decimal, omitting leading zeros.

```
cn: IpNetmaskNumber
ldapDisplayName: ipNetmaskNumber
attributeId: 1.3.6.1.1.1.21
attributeSyntax: 2.5.5.5
omSyntax: 22
isSingleValued: TRUE
schemaIdGuid: 6ff64fc4-462e-4f62-b44a-9a5347659eb9
systemOnly: FALSE
searchFlags: 0
rangeUpper: 128
```

Version-Specific Behavior: Implemented on Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.317 Attribute ipNetworkNumber

This attribute specifies the IP network as a dotted decimal, omitting leading zeros.

```
cn: IpNetworkNumber
ldapDisplayName: ipNetworkNumber
attributeId: 1.3.6.1.1.1.20
attributeSyntax: 2.5.5.5
omSyntax: 22
isSingleValued: TRUE
schemaIdGuid: 4e3854f4-3087-42a4-a813-bb0c528958d3
systemOnly: FALSE
searchFlags: 0
rangeUpper: 128
```

Version-Specific Behavior: Implemented on Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.318 Attribute ipPhone

This attribute specifies the TCP/IP address for the telephone. It is used by telephony.

```
cn: Phone-Ip-Primary
ldapDisplayName: ipPhone
attributeId: 1.2.840.113556.1.4.721
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 4d146e4a-48d4-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
rangeUpper: 64
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, rangeUpper is not defined.

## 2.319 Attribute ipProtocolNumber

This attribute is part of the protocols map and stores the unique number that identifies the protocol.

```
cn: IpProtocolNumber
ldapDisplayName: ipProtocolNumber
attributeId: 1.3.6.1.1.1.1.17
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: ebf5c6eb-0e2d-4415-9670-1081993b4211
systemOnly: FALSE
searchFlags: 0
```

Version-Specific Behavior: Implemented on Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.320 Attribute ipsecData

The Ipsec-Data attribute is for internal use only.

```
cn: Ipsec-Data
ldapDisplayName: ipsecData
attributeId: 1.2.840.113556.1.4.623
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: b40ff81f-427a-11d1-a9c2-0000f80367c1
```

```
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.321 Attribute ipsecDataType

The Ipsec-Data-Type attribute is for internal use only.

```
cn: Ipsec-Data-Type
ldapDisplayName: ipsecDataType
attributeId: 1.2.840.113556.1.4.622
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: b40ff81e-427a-11d1-a9c2-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.322 Attribute ipsecFilterReference

The Ipsec-Filter-Reference attribute.

```
cn: Ipsec-Filter-Reference
ldapDisplayName: ipsecFilterReference
attributeId: 1.2.840.113556.1.4.629
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: b40ff823-427a-11d1-a9c2-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.323 Attribute ipsecID

The Ipsec-ID attribute.

```
cn: Ipsec-ID
ldapDisplayName: ipsecID
```

```
attributeId: 1.2.840.113556.1.4.621
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: b40ff81d-427a-11d1-a9c2-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.324 Attribute ipsecISAKMPReference

The Ipsec-ISAKMP-Reference attribute (see [\[MS-GPIPSEC\]](#) section 2.2.1.1.1).

```
cn: Ipsec-ISAKMP-Reference
ldapDisplayName: ipsecISAKMPReference
attributeId: 1.2.840.113556.1.4.626
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: b40ff820-427a-11d1-a9c2-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.325 Attribute ipsecName

The Ipsec-Name attribute.

```
cn: Ipsec-Name
ldapDisplayName: ipsecName
attributeId: 1.2.840.113556.1.4.620
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: b40ff81c-427a-11d1-a9c2-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.326 Attribute iPSECNegotiationPolicyAction**

The IPSEC-Negotiation-Policy-Action attribute.

```
cn: IPSEC-Negotiation-Policy-Action
ldapDisplayName: iPSECNegotiationPolicyAction
attributeId: 1.2.840.113556.1.4.888
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 07383075-91df-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.327 Attribute ipsecNegotiationPolicyReference**

The Ipsec-Negotiation-Policy-Reference attribute.

```
cn: Ipsec-Negotiation-Policy-Reference
ldapDisplayName: ipsecNegotiationPolicyReference
attributeId: 1.2.840.113556.1.4.628
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: b40ff822-427a-11d1-a9c2-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## **2.328 Attribute iPSECNegotiationPolicyType**

The IPSEC-Negotiation-Policy-Type attribute.

```
cn: IPSEC-Negotiation-Policy-Type
ldapDisplayName: iPSECNegotiationPolicyType
attributeId: 1.2.840.113556.1.4.887
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 07383074-91df-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.329 Attribute ipsecNFAReference

The [Ipsec-NFA-Reference](#) attribute (see [\[MS-GPIPSEC\]](#) section 2.2.1.1.1).

```
cn: Ipsec-NFA-Reference
ldapDisplayName: ipsecNFAReference
attributeId: 1.2.840.113556.1.4.627
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: b40ff821-427a-11d1-a9c2-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.330 Attribute ipsecOwnersReference

The [Ipsec-Owners-Reference](#) attribute.

```
cn: Ipsec-Owners-Reference
ldapDisplayName: ipsecOwnersReference
attributeId: 1.2.840.113556.1.4.624
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: b40ff824-427a-11d1-a9c2-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.331 Attribute ipsecPolicyReference

The [Ipsec-Policy-Reference](#) attribute.

```
cn: Ipsec-Policy-Reference
ldapDisplayName: ipsecPolicyReference
attributeId: 1.2.840.113556.1.4.517
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
```

```
schemaIdGuid: b7b13118-b82e-11d0-afee-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.332 Attribute ipServicePort

This is a part of the services map and contains the port at which the UNIX service is available.

```
cn: IpServicePort
ldapDisplayName: ipServicePort
attributeId: 1.3.6.1.1.1.15
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: ff2daebf-f463-495a-8405-3e483641eaa2
systemOnly: FALSE
searchFlags: 0
```

**Version-Specific Behavior:** Implemented on Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.333 Attribute ipServiceProtocol

This is a part of the services map and stores the protocol number for a UNIX service.

```
cn: IpServiceProtocol
ldapDisplayName: ipServiceProtocol
attributeId: 1.3.6.1.1.1.16
attributeSyntax: 2.5.5.5
omSyntax: 22
isSingleValued: FALSE
schemaIdGuid: cd96ec0b-1ed6-43b4-b26b-f170b645883f
systemOnly: FALSE
searchFlags: 0
rangeUpper: 1024
```

**Version-Specific Behavior:** Implemented on Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.334 Attribute isCriticalSystemObject

If TRUE, the object hosting this attribute must be replicated during installation of a new replica.

```
cn: Is-Critical-System-Object
ldapDisplayName: isCriticalSystemObject
attributeId: 1.2.840.113556.1.4.868
attributeSyntax: 2.5.5.8
omSyntax: 1
```

```
isSingleValued: TRUE
schemaIdGuid: 00fbf30d-91fe-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.335 Attribute **isDefunct**

If TRUE, the class or attribute is no longer usable. Old versions of this object may exist, but new ones cannot be created.

```
cn: Is-Defunct
ldapDisplayName: isDefunct
attributeId: 1.2.840.113556.1.4.661
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: 28630ebe-41d5-11d1-a9c1-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.336 Attribute **isDeleted**

If TRUE, this object has been marked for deletion and will be removed from the Active Directory system (see [\[MS-ADSO1\]](#) section 2.1).

```
cn: Is-Deleted
ldapDisplayName: isDeleted
attributeId: 1.2.840.113556.1.2.48
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: bf96798f-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
mapiID: 32960
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
```

```
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.337 Attribute **isEphemeral**

```
cn: Is-Ephemeral
ldapDisplayName: isEphemeral
attributeId: 1.2.840.113556.1.4.1212
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: f4c453f0-c5f1-11d1-bbcb-0080c76670c0
systemOnly: TRUE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.338 Attribute **isMemberOfPartialAttributeSet**

If TRUE, this attribute is replicated to the global catalog.

```
cn: Is-Member-Of-Partial-Attribute-Set
ldapDisplayName: isMemberOfPartialAttributeSet
attributeId: 1.2.840.113556.1.4.639
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: 19405b9d-3cfa-11d1-a9c0-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.339 Attribute **isPrivilegeHolder**

This attribute specifies a back link to privileges held by a given principal.

```
cn: Is-Privilege-Holder
ldapDisplayName: isPrivilegeHolder
attributeId: 1.2.840.113556.1.4.638
```

```
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: FALSE
schemaIdGuid: 19405b9c-3cfa-11d1-a9c0-0000f80367c1
systemOnly: TRUE
searchFlags: 0
linkID: 71
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.340 Attribute **isRecycled**

If TRUE, this object has been marked for permanent deletion. Additionally, if the Recycle Bin optional feature is enabled, the value TRUE marks an object that cannot be undeleted. It will be removed from the Active Directory system (see [\[MS-ADSO\]](#) section 2.1).

```
cn: Is-Recycled
ldapDisplayName: isRecycled
attributeId: 1.2.840.113556.1.4.2058
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: 8fb59256-55f1-444b-aacb-f5b482fe3459
systemOnly: TRUE
searchFlags: fPRESERVEONDELETE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Windows Server® 2008 R2 operating system.

## 2.341 Attribute **isSingleValued**

If TRUE, this attribute can only store one value.

```
cn: Is-Single-Valued
ldapDisplayName: isSingleValued
attributeId: 1.2.840.113556.1.2.33
attributeSyntax: 2.5.5.8
omSyntax: 1
isSingleValued: TRUE
schemaIdGuid: bf967992-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
mapiID: 32961
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.342 Attribute jpegPhoto

Used to store one or more images of a person by using the JPEG File Interchange Format, as specified in [\[JFIF\]](#).

```
cn: jpegPhoto
ldapDisplayName: jpegPhoto
attributeId: 0.9.2342.19200300.100.1.60
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: bac80572-09c4-4fa9-9ae6-7628d7adbe0e
systemOnly: FALSE
searchFlags: 0
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.343 Attribute keywords

This attribute specifies a list of keywords that can be used to locate a given connection point.

```
cn: Keywords
ldapDisplayName: keywords
attributeId: 1.2.840.113556.1.4.48
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: bf967993-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fATTINDEX
rangeLower: 1
rangeUpper: 256
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.344 Attribute knowledgeInformation

This attribute specifies a human-readable accumulated description of knowledge that is mastered by a specific DSA.

```

cn: Knowledge-Information
ldapDisplayName: knowledgeInformation
attributeId: 2.5.4.2
attributeSyntax: 2.5.5.4
omSyntax: 20
isSingleValued: FALSE
schemaIdGuid: 1677581f-47f3-11d1-a9c3-0000f80367c1
systemOnly: FALSE
searchFlags: 0
mapiID: 32963

```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.345 Attribute l

This attribute represents the name of a locality, such as a town or city.

```

cn: Locality-Name
ldapDisplayName: l
attributeId: 2.5.4.7
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf9679a2-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY | fATTINDEX
rangeLower: 1
rangeUpper: 128
attributeSecurityGuid: 77b5b886-944a-11d1-aebd-0000f80367c1
mapiID: 14887
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT |
FLAG_ATTR_REQ_PARTIAL_SET_MEMBER
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL

```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.346 Attribute labeledURI

This attribute specifies a Uniform Resource Identifier (URI) followed by a label. The label is used to describe the resource to which the URI points, and it is intended as a friendly name.

```

cn: labeledURI
ldapDisplayName: labeledURI
attributeId: 1.3.6.1.4.1.250.1.57
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: c569bb46-c680-44bc-a273-e6c227d71b45

```

```
systemOnly: FALSE
searchFlags: 0
showInAdvancedViewOnly: FALSE
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.347 Attribute **lastBackupRestorationTime**

This attribute specifies when the last system restore occurred.

```
cn: Last-Backup-Restoration-Time
ldapDisplayName: lastBackupRestorationTime
attributeId: 1.2.840.113556.1.4.519
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 1fbb0be8-ba63-11d0-afef-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.348 Attribute **lastContentIndexed**

This attribute specifies the time this volume was last content-indexed.

```
cn: Last-Content-Indexed
ldapDisplayName: lastContentIndexed
attributeId: 1.2.840.113556.1.4.50
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf967995-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.349 Attribute **lastKnownParent**

This attribute specifies the distinguished name of the last known parent of an orphaned or deleted object.

```
cn: Last-Known-Parent
ldapDisplayName: lastKnownParent
```

```
attributeId: 1.2.840.113556.1.4.781
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 52ab8670-5709-11d1-a9c6-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.350 Attribute lastLogoff

This attribute specifies the last time the user logged off. This value is stored as a large integer that represents the number of 100 nanosecond intervals since January 1, 1601 (UTC). A value of zero means that the last logoff time is unknown.

```
cn: Last-Logoff
ldapDisplayName: lastLogoff
attributeId: 1.2.840.113556.1.4.51
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf967996-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: 5f202010-79a5-11d0-9020-00c04fc2d4cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.351 Attribute lastLogon

This attribute specifies the last time the user logged on. This value is stored as a large integer that represents the number of 100 nanosecond intervals since January 1, 1601 (UTC). A value of zero means that the last logon time is unknown.

```
cn: Last-Logon
ldapDisplayName: lastLogon
attributeId: 1.2.840.113556.1.4.52
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf967997-0de6-11d0-a285-00aa003049e2
```

```
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: 5f202010-79a5-11d0-9020-00c04fc2d4cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.352 Attribute lastLogonTimestamp

This is the time that the user last logged on to the domain. Whenever a user logs on, the value of this attribute is read from the DC. If [msDS-LogonTimeSyncInterval](#) is nonzero, and the value is older than (current\_time - [msDS-LogonTimeSyncInterval](#)), the value is updated with the current time. The initial update, after the domain functional level is raised to DS\_BEHAVIOR\_WIN2003 or higher, is calculated as 14 days minus a random percentage of 5 days.

**Note** This attribute is present on objects only when the domain functional level is DS\_BEHAVIOR\_WIN2003 or higher.

```
cn: Last-Logon-Timestamp
ldapDisplayName: lastLogonTimestamp
attributeId: 1.2.840.113556.1.4.1696
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: c0e20a04-0e5a-4ff3-9482-5efeaecd7060
systemOnly: FALSE
searchFlags: fATTINDEX
attributeSecurityGuid: 5f202010-79a5-11d0-9020-00c04fc2d4cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.353 Attribute lastSetTime

This attribute specifies the last time the secret was changed.

```
cn: Last-Set-Time
ldapDisplayName: lastSetTime
attributeId: 1.2.840.113556.1.4.53
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf967998-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
```

```
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.354 Attribute lastUpdateSequence

This attribute specifies the update sequence number for the last item in the class store that was changed.

```
cn: Last-Update-Sequence
ldapDisplayName: lastUpdateSequence
attributeId: 1.2.840.113556.1.4.330
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 7d6c0e9c-7e20-11d0-af6-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.355 Attribute IDAPAdminLimits

This attribute contains a set of attribute-value pairs defining LDAP server administrative limits.

```
cn: LDAP-Admin-Limits
ldapDisplayName: lDAPAdminLimits
attributeId: 1.2.840.113556.1.4.843
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: 7359a352-90f7-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.356 Attribute **IDAPDisplayName**

This attribute specifies the name used by LDAP clients, such as the ADSI LDAP provider, to read and write the attribute by using the LDAP protocol.

```
cn: LDAP-Display-Name
ldapDisplayName: lDAPDisplayName
attributeId: 1.2.840.113556.1.2.460
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: bf96799a-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags:fPRESERVEONDELETE | fATTINDEX
rangeLower: 1
rangeUpper: 256
mapiID: 33137
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.357 Attribute **IDAPIPDenyList**

This attribute holds a list of binary IP addresses that are denied access to an LDAP server.

```
cn: LDAP-IPDeny-List
ldapDisplayName: lDAPIPDenyList
attributeId: 1.2.840.113556.1.4.844
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: 7359a353-90f7-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.358 Attribute **ISACreationTime**

This attribute is used to support replication to Microsoft Windows NT® 4.0 operating system domains.

```
cn: LSA-Creation-Time
```

```
ldapDisplayName: lSACreationTime
attributeId: 1.2.840.113556.1.4.66
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf9679ad-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.359 Attribute ISAModifiedCount

This attribute is used to support replication to Microsoft Windows NT® 4.0 operating system domains.

```
cn: LSA-Modified-Count
ldapDisplayName: lSAModifiedCount
attributeId: 1.2.840.113556.1.4.67
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf9679ae-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.360 Attribute legacyExchangeDN

This attribute specifies the distinguished name previously used by Microsoft® Exchange Server.

```
cn: Legacy-Exchange-DN
ldapDisplayName: legacyExchangeDN
attributeId: 1.2.840.113556.1.4.655
attributeSyntax: 2.5.5.4
omSyntax: 20
isSingleValued: TRUE
schemaIdGuid: 28630ebc-41d5-11d1-a9c1-0000f80367c1
systemOnly: FALSE
searchFlags:fPRESERVEONDELETE| fANR | fATTINDEX
attributeSecurityGuid: e48d0154-bcf8-11d1-8702-00c04fb96050
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.361 Attribute linkID

This attribute specifies an integer that indicates that the attribute is a linked attribute. An even integer is a forward link and an odd integer is a back link.

```
cn: Link-ID
ldapDisplayName: linkID
attributeId: 1.2.840.113556.1.2.50
attributesyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf96799b-0de6-11d0-a285-00aa003049e2
systemOnly: TRUE
searchFlags: 0
mapiID: 32965
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.362 Attribute linkTrackSecret

This attribute specifies a link to a secret key that allows an encrypted file to be translated into plain text.

```
cn: Link-Track-Secret
ldapDisplayName: linkTrackSecret
attributeId: 1.2.840.113556.1.4.269
attributesyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: 2ae80fe2-47b4-11d0-a1a4-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
rangeLower: 0
rangeUpper: 16
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.363 Attribute lmPwdHistory

The password history of the user in LAN Manager (LM) one-way format (OWF). The LM OWF is used for compatibility with LAN Manager 2.x clients, Microsoft Windows® 95 operating system, and Microsoft Windows® 98 operating system.

For more information about usage, refer to [\[MS-SAMR\]](#) sections [3.1.1.6](#) and [3.1.1.9.1](#).

```
cn: Lm-Pwd-History
ldapDisplayName: lmPwdHistory
attributeId: 1.2.840.113556.1.4.160
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: FALSE
schemaIdGuid: bf96799d-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.364 Attribute localeID

This attribute specifies a list of locale IDs supported by this application. A locale ID represents a geographic location; for example, a country/region, a city, or a county.

```
cn: Locale-ID
ldapDisplayName: localeID
attributeId: 1.2.840.113556.1.4.58
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: FALSE
schemaIdGuid: bf9679a1-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.365 Attribute localizationDisplayId

This attribute is used to index the Extrts.mc file to get the localized [displayName](#) for the objects, for UI purposes.

```
cn: Localization-Display-Id
ldapDisplayName: localizationDisplayId
attributeId: 1.2.840.113556.1.4.1353
attributeSyntax: 2.5.5.9
```

```
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: a746f0d1-78d0-11d2-9916-0000f87a57d4
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.366 Attribute **localizedDescription**

This attribute specifies the localization ID and display name for an object.

```
cn: Localized-Description
ldapDisplayName: localizedDescription
attributeId: 1.2.840.113556.1.4.817
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: FALSE
schemaIdGuid: d9e18316-8939-11d1-aebc-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.367 Attribute **localPolicyFlags**

This attribute specifies flags that determine where a machine gets its policy ([Local-Policy-Reference](#)).

```
cn: Local-Policy-Flags
ldapDisplayName: localPolicyFlags
attributeId: 1.2.840.113556.1.4.56
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf96799e-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.368 Attribute localPolicyReference

This attribute specifies the distinguished name of a local policy object that a policy object copies from.

```
cn: Local-Policy-Reference
ldapDisplayName: localPolicyReference
attributeId: 1.2.840.113556.1.4.457
attributeSyntax: 2.5.5.1
omSyntax: 127
omObjectClass: 1.3.12.2.1011.28.0.714
isSingleValued: TRUE
schemaIdGuid: 80a67e4d-9f22-11d0-afdd-00c04fd930c9
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: a29b8a01-c7e8-11d0-9bae-00c04fd92ef5
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.369 Attribute location

This attribute specifies the user's location, such as an office number.

```
cn: Location
ldapDisplayName: location
attributeId: 1.2.840.113556.1.4.222
attributeSyntax: 2.5.5.12
omSyntax: 64
isSingleValued: TRUE
schemaIdGuid: 09dcbb9f-165f-11d0-a064-00aa006c33ed
systemOnly: FALSE
searchFlags: fATTINDEX
rangeLower: 0
rangeUpper: 1024
isMemberOfPartialAttributeSet: TRUE
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.370 Attribute lockoutDuration

This attribute specifies the amount of time an account is locked due to the [Lockout-Threshold](#) being exceeded. This value is stored as a large integer. It represents the negative of the number of 100 nanosecond intervals that must elapse, from the time the [Lockout-Threshold](#) is exceeded, before the account is unlocked.

```
cn: Lockout-Duration
ldapDisplayName: lockoutDuration
attributeId: 1.2.840.113556.1.4.60
attributeSyntax: 2.5.5.16
```

```
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf9679a5-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: c7407360-20bf-11d0-a768-00aa006e0529
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

In Windows 2000 Server, rangeUpper is not defined.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.371 Attribute lockOutObservationWindow

This attribute specifies the waiting period after which the [Lockout Threshold \(section 2.372\)](#) is reset. The valid values are <None> and 00:00:00:01 through the [Lockout Duration \(section 2.370\)](#) value.

```
cn: Lock-Out-Observation-Window
ldapDisplayName: lockOutObservationWindow
attributeId: 1.2.840.113556.1.4.61
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: bf9679a4-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: c7407360-20bf-11d0-a768-00aa006e0529
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.372 Attribute lockoutThreshold

This attribute specifies the number of invalid logon attempts that are permitted before the account is locked out.

```
cn: Lockout-Threshold
ldapDisplayName: lockoutThreshold
attributeId: 1.2.840.113556.1.4.73
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf9679a6-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
```

```
rangeUpper: 65535
attributeSecurityGuid: c7407360-20bf-11d0-a768-00aa006e0529
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.373 Attribute lockoutTime

This attribute specifies the date and time (UTC) that this account was locked out. This value is stored as a large integer that represents the number of 100 nanosecond intervals since January 1, 1601 (UTC). A value of zero means that the account is not currently locked out.

```
cn: Lockout-Time
ldapDisplayName: lockoutTime
attributeId: 1.2.840.113556.1.4.662
attributeSyntax: 2.5.5.16
omSyntax: 65
isSingleValued: TRUE
schemaIdGuid: 28630ebf-41d5-11d1-a9c1-0000f80367c1
systemOnly: FALSE
searchFlags: 0
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.374 Attribute loginShell

This attribute specifies the path to the logon shell. For more information, see [\[RFC2307\]](#) section 2.2.

```
cn: LoginShell
ldapDisplayName: loginShell
attributeId: 1.3.6.1.1.1.4
attributeSyntax: 2.5.5.5
omSyntax: 22
isSingleValued: TRUE
schemaIdGuid: a553d12c-3231-4c5e-8adf-8d189697721e
systemOnly: FALSE
searchFlags: 0
rangeUpper: 1024
```

**Version-Specific Behavior:** Implemented on Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

## 2.375 Attribute logonCount

This attribute specifies the number of times that the account has successfully logged on. A value of 0 indicates that the value is unknown.

```
cn: Logon-Count
ldapDisplayName: logonCount
attributeId: 1.2.840.113556.1.4.169
attributeSyntax: 2.5.5.9
omSyntax: 2
isSingleValued: TRUE
schemaIdGuid: bf9679aa-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: 0
attributeSecurityGuid: 5f202010-79a5-11d0-9020-00c04fc2d4cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT | FLAG_ATTR_NOT_REPLICATED
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.376 Attribute logonHours

This attribute specifies the hours that the user is allowed to log on to the domain.

```
cn: Logon-Hours
ldapDisplayName: logonHours
attributeId: 1.2.840.113556.1.4.64
attributeSyntax: 2.5.5.10
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: bf9679ab-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
attributeSecurityGuid: 5f202010-79a5-11d0-9020-00c04fc2d4cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT
schemaFlagsEx: FLAG_ATTR_IS_CRITICAL
```

Version-Specific Behavior: Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

The [schemaFlagsEx](#) attribute was added to this attribute definition in Windows Server 2008.

## 2.377 Attribute logonWorkstation

For more information, see the [userWorkstations](#) attribute in [\[MS-ADA3\]](#).

```
cn: Logon-Workstation
ldapDisplayName: logonWorkstation
attributeId: 1.2.840.113556.1.4.65
attributeSyntax: 2.5.5.10
```

```
omSyntax: 4
isSingleValued: TRUE
schemaIdGuid: bf9679ac-0de6-11d0-a285-00aa003049e2
systemOnly: FALSE
searchFlags: fCOPY
attributeSecurityGuid: 5f202010-79a5-11d0-9020-00c04fc2d4cf
systemFlags: FLAG_SCHEMA_BASE_OBJECT
```

**Version-Specific Behavior:** Implemented on Microsoft Windows® 2000 Server operating system, Windows Server® 2003 operating system, Windows Server® 2003 R2 operating system, Windows Server® 2008 operating system, and Windows Server® 2008 R2 operating system.

### 3 Change Tracking

This section identifies changes that were made to the [MS-ADA1] protocol document between the January 2011 and February 2011 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- The removal of a document from the documentation set.
- Changes made for template compliance.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact [protocol@microsoft.com](mailto:protocol@microsoft.com).

<b>Section</b>	<b>Tracking number (if applicable) and description</b>	<b>Major change (Y or N)</b>	<b>Change type</b>
<a href="#">2.277 Attribute gPCFileSysPath</a>	61051 Replaced Boolean setting with UNC path description.	Y	Content updated.

## 4 Index

### A

[Active Directory attributes beginning with A - L](#) 14  
[Active Directory references](#) 12  
[Attributes beginning with A - L](#) 14

### C

[Change tracking](#) 165

### R

[References - Active Directory](#) 12

### S

[Schema attributes - Active Directory](#) 14

### T

[Tracking changes](#) 165