

# [MS-BDCDP]: Business Data Catalog Data Web Service Protocol Specification

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
04/04/2008	0.1		Initial Availability
06/27/2008	1.0	Major	Revised and edited the technical content
12/12/2008	1.01	Editorial	Revised and edited the technical content
07/13/2009	1.02	Major	Changes made for template compliance
08/28/2009	1.03	Editorial	Revised and edited the technical content
11/06/2009	1.04	Editorial	Revised and edited the technical content
02/19/2010	2.0	Minor	Updated the technical content
03/31/2010	2.01	Editorial	Revised and edited the technical content
04/30/2010	2.02	Minor	Updated the technical content
06/07/2010	2.03	Editorial	Revised and edited the technical content
06/29/2010	2.04	Editorial	Changed language and formatting in the technical content.
07/23/2010	2.04	No change	No changes to the meaning, language, or formatting of the technical content.
09/27/2010	2.04	No change	No changes to the meaning, language, or formatting of the technical content.
11/15/2010	2.04	No change	No changes to the meaning, language, or formatting of the technical content.
12/17/2010	2.04	No change	No changes to the meaning, language, or formatting of the technical content.

# Table of Contents

<b>1 Introduction</b>	<b>5</b>
1.1 Glossary	5
1.2 References	5
1.2.1 Normative References	5
1.2.2 Informative References	6
1.3 Protocol Overview (Synopsis)	6
1.4 Relationship to Other Protocols	7
1.5 Prerequisites/Preconditions	7
1.6 Applicability Statement	7
1.7 Versioning and Capability Negotiation	7
1.8 Vendor-Extensible Fields	7
1.9 Standards Assignments	7
<b>2 Messages</b>	<b>8</b>
2.1 Transport	8
2.2 Common Message Syntax	8
2.2.1 Namespaces	8
2.2.2 Messages	8
2.2.3 Elements	8
2.2.4 Complex Types	9
2.2.5 Simple Types	9
2.2.6 Attributes	9
2.2.7 Groups	9
2.2.8 Attribute Groups	9
<b>3 Protocol Details</b>	<b>10</b>
3.1 Protocol Server Details	10
3.1.1 Abstract Data Model	10
3.1.2 Timers	10
3.1.3 Initialization	10
3.1.4 Message Processing Events and Sequencing Rules	11
3.1.4.1 Resolve	11
3.1.4.1.1 Messages	11
3.1.4.1.1.1 ResolveSoapIn	11
3.1.4.1.1.2 ResolveSoapOut	11
3.1.4.1.1.2 Elements	12
3.1.4.1.2.1 Resolve	12
3.1.4.1.2.2 ResolveResponse	12
3.1.4.1.3 Complex Types	13
3.1.4.1.3.1 ResolveResult	13
3.1.4.1.3.2 IdentifierField	13
3.1.4.1.3.3 ArrayOfFieldRecord	13
3.1.4.1.3.4 FieldRecord	14
3.1.4.1.4 Simple Types	14
3.1.4.1.4.1 ResolveStatus	14
3.1.4.1.5 Attributes	14
3.1.4.1.6 Groups	15
3.1.4.1.7 Attribute Groups	15
3.1.5 Timer Events	15
3.1.6 Other Local Events	15

<b>4 Protocol Examples</b> .....	<b>16</b>
4.1 Retrieving Field Values for LobSystem Entities.....	16
<b>5 Security</b> .....	<b>17</b>
5.1 Security Considerations for Implementers.....	17
5.2 Index of Security Parameters .....	17
<b>6 Appendix A: Full WSDL</b> .....	<b>18</b>
<b>7 Appendix B: Product Behavior</b> .....	<b>20</b>
<b>8 Change Tracking</b> .....	<b>21</b>
<b>9 Index</b> .....	<b>22</b>

# 1 Introduction

This document specifies the Business Data Catalog Data Web Service Protocol, which is an interface that protocol clients can use to search software systems that store business data and process rules for an instance of a particular entity.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

**serialize**

The following terms are defined in [\[MS-OFCGLOS\]](#):

**Entity**  
**EntityInstance**  
**EntityInstanceId**  
**field**  
**Identifier**  
**line-of-business (LOB) system**  
**LobSystem**  
**LobSystemInstance**  
**metadata store**  
**MetadataObject**  
**Model**  
**site**  
**SOAP action**  
**SOAP body**  
**SOAP fault**  
**URL (Uniform Resource Locator)**  
**XML namespace**

The following terms are specific to this document:

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>

[RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.ietf.org/rfc/rfc2616.txt>

[RFC3986] Berners-Lee, T., Fielding, R., and Masinter, L., "Uniform Resource Identifier (URI): Generic Syntax", STD 66, RFC 3986, January 2005, <http://www.ietf.org/rfc/rfc3986.txt>

[SOAP1.1] Box, D., Ehnebuske, D., Kakivaya, G., et al., "Simple Object Access Protocol (SOAP) 1.1", May 2000, <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

[SOAP1.2/1] Gudgin, M., Hadley, M., Mendelsohn, N., Moreau, J., and Nielsen, H.F., "SOAP Version 1.2 Part 1: Messaging Framework", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part1-20030624>

[SOAP1.2/2] Gudgin, M., Hadley, M., Mendelsohn, N., Moreau, J., and Nielsen, H.F., "SOAP Version 1.2 Part 2: Adjuncts", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part2-20030624>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XML10] World Wide Web Consortium, "Extensible Markup Language (XML) 1.0 (Third Edition)", February 2004, <http://www.w3.org/TR/REC-xml>

[XMLINFOSET] World Wide Web Consortium, "XML Information Set (Second Edition)", February 2004, <http://www.w3.org/TR/2004/REC-xml-infoset-20040204>

[XMLNS] World Wide Web Consortium, "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation 8 December 2009, <http://www.w3.org/TR/REC-xml-names/>

[XMLSCHEMA1] Thompson, H.S., Ed., Beech, D., Ed., Maloney, M., Ed., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., Ed. and Malhotra, A., Ed., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

### 1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)", March 2007.

[MS-OFCGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)", June 2008.

[RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000, <http://www.ietf.org/rfc/rfc2818.txt>

### 1.3 Protocol Overview (Synopsis)

This document specifies a consistent selection process for information stored in any line-of-business (LOB) system for protocol client retrieval.


Enterprises store a variety of information in various **line-of-business (LOB) systems**. This protocol specifies unified information selection for all types of **LobSystems**. The protocol enables consistent processing for the user experience because it describes LobSystems in terms of **Models**, **LobSystemInstances**, and the business data types they store as **Entities**. It also describes how the protocol client selects information from the protocol server.

This protocol enables a protocol client to retrieve an **EntityInstanceId** and the values for a list of **field (4)** names for an Entity associated with a LobSystemInstance. The protocol allows the protocol client to send the LobSystemInstance name, the Entity name, a value to resolve, and a list of Entity fields (4) to the protocol server, and to receive the **serialized EntityInstanceId** and the list of Entity field (4) name-value pairs.

## 1.4 Relationship to Other Protocols

This protocol uses the SOAP messaging protocol for formatting requests and responses as described either in [\[SOAP1.1\]](#) or in [\[SOAP1.2/1\]](#) and [\[SOAP1.2/2\]](#). It transmits these messages using the HTTP protocol as described in [\[RFC2616\]](#) or the HTTPS protocol as described in [\[RFC2818\]](#).

The following diagram shows the underlying messaging and transport stack that the protocol uses:



**Figure 1: This protocol in relation to other protocols**

## 1.5 Prerequisites/Preconditions

This protocol operates against a **site (2)** that is known to protocol clients by its **URL**. The protocol client forms an endpoint by appending `"/_vti_bin/bdcfieldsresolver.asmx"` to the URL of the site, for example `"http://www.contoso.com/Repository/_vti_bin/bdcfieldsresolver.asmx"`. This protocol assumes that the underlying protocols perform authentication.

## 1.6 Applicability Statement

None.

## 1.7 Versioning and Capability Negotiation

This document describes versioning issues in the following areas:

- **Supported Transports:** This protocol uses multiple transports with SOAP as specified in section [2.1](#).

## 1.8 Vendor-Extensible Fields

None.

## 1.9 Standards Assignments

None.

## 2 Messages

### 2.1 Transport

Protocol servers MUST support SOAP over HTTP. Protocol servers additionally support SOAP over HTTPS to secure communication with protocol clients.

Protocol messages MUST be formatted as specified either in [\[SOAP1.1\]](#), section 4 or in [\[SOAP1.2/1\]](#), section 5. Protocol server faults MUST be returned using HTTP Status Codes as specified in [\[RFC2616\]](#), section 10, or using **SOAP faults** as specified in [\[SOAP1.1\]](#), section 4.4 or in [\[SOAP1.2/1\]](#), section 5.4.

### 2.2 Common Message Syntax

This section contains common structures used by this protocol. The syntax of the structures uses XML schema, as specified in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and Web Services Description Language, as specified in [\[WSDL\]](#).

#### 2.2.1 Namespaces

This protocol specifies and references **XML namespaces** using the mechanisms specified in [\[XMLNS\]](#). Although this document associates an XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
soap	<a href="http://schemas.xmlsoap.org/wsdl/soap/">http://schemas.xmlsoap.org/wsdl/soap/</a>	<a href="#">[SOAP1.1]</a>
tns	<a href="http://microsoft.com/webservices/SharePointPortalServer/BDCClientWS/">http://microsoft.com/webservices/SharePointPortalServer/BDCClientWS/</a>	
s	<a href="http://www.w3.org/2001/XMLSchema">http://www.w3.org/2001/XMLSchema</a>	<a href="#">[XMLSCHEMA1]</a> <a href="#">[XMLSCHEMA2]</a>
soap12	<a href="http://schemas.xmlsoap.org/wsdl/soap12/">http://schemas.xmlsoap.org/wsdl/soap12/</a>	<a href="#">[SOAP1.2/1]</a> <a href="#">[SOAP1.2/2]</a>
(none)	<a href="http://microsoft.com/webservices/SharePointPortalServer/BDCClientWS/">http://microsoft.com/webservices/SharePointPortalServer/BDCClientWS/</a>	
wsdl	<a href="http://schemas.xmlsoap.org/wsdl/">http://schemas.xmlsoap.org/wsdl/</a>	<a href="#">[WSDL]</a>
mime	<a href="http://schemas.xmlsoap.org/wsdl/mime/">http://schemas.xmlsoap.org/wsdl/mime/</a>	<a href="#">[WSDL]</a>
http	<a href="http://schemas.xmlsoap.org/wsdl/http/">http://schemas.xmlsoap.org/wsdl/http/</a>	<a href="#">[WSDL]</a>
tm	<a href="http://microsoft.com/wsdl/mime/textMatching/">http://microsoft.com/wsdl/mime/textMatching/</a>	<a href="#">[WSDL]</a>
soapenc	<a href="http://schemas.xmlsoap.org/soap/encoding/">http://schemas.xmlsoap.org/soap/encoding/</a>	

#### 2.2.2 Messages

None.

#### 2.2.3 Elements

This specification does not define any common XML Schema element definitions.



#### **2.2.4 Complex Types**

This specification does not define any common XML Schema complex type definitions.

#### **2.2.5 Simple Types**

This specification does not define any common XML Schema simple type definitions.

#### **2.2.6 Attributes**

This specification does not define any common XML Schema attribute definitions.

#### **2.2.7 Groups**

This specification does not define any common XML Schema group definitions.

#### **2.2.8 Attribute Groups**

This specification does not define any common XML Schema attribute group definitions.

## 3 Protocol Details

This protocol operates between the protocol client and a protocol server. The protocol client initiates the communication, and the protocol server responds. The protocol server does not retain any states.

The client side of this protocol is simply a pass-through. That is, no additional timers or other state is required on the client side of this protocol. Calls made by the higher-layer protocol or application are passed directly to the transport, and the results returned by the transport are passed directly back to the higher-layer protocol or application.

Except where specified, protocol clients interpret HTTP Status Codes returned by the protocol server as specified in [\[RFC2616\]](#), section 10.

Protocol servers perform implementation-specific authorization checks and notify protocol clients of authorization faults using either HTTP status codes or SOAP faults.

### 3.1 Protocol Server Details

#### 3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

The protocol server MUST maintain lists of the following **MetadataObject** types: **LobSystem**, **LobSystemInstance** and **Entity**. The protocol server maintains the following relationships between these **MetadataObject** types:

- **LobSystems** contain all **Entities**.
- **LobSystems** contain all **LobSystemInstances**.

The protocol server MUST assign unique names to the following **MetadataObjects**.

- All **Entities** contained by a particular **LobSystem**.
- All **LobSystemInstances** contained by a **metadata store**.
- All **LobSystems** contained by a **metadata store**.

#### 3.1.2 Timers

None.

#### 3.1.3 Initialization

None.

### 3.1.4 Message Processing Events and Sequencing Rules

Operation	Description
<b>Resolve</b>	This operation retrieves the values of a list of <b>Entity fields (4)</b> associated with the <b>EntityInstance</b> that was specified in the input criteria.

#### 3.1.4.1 Resolve

This operation searches for an **EntityInstance** that matches the specified input criteria. The input criteria are the LobSystemInstance name, the Entity name and value to resolve. The mechanism used by the protocol server to match the EntityInstances is implementation-specific.

```
<wsdl:operation name="Resolve">
  <wsdl:input message="ResolveSoapIn" />
  <wsdl:output message="ResolveSoapOut" />
</wsdl:operation>
```

The protocol client sends a **ResolveSoapIn** request message and the protocol server responds with a **ResolveSoapOut** response message. The protocol client MUST specify:

- The name of the **LobSystemInstance** to search.
- The name of the **Entity** to search.
- The search string that represents the value to resolve.
- The field (4) names of the **Entity** for which to retrieve the values of the specified **EntityInstance**.

If exactly one **EntityInstance** is found, the protocol server sends the **serialized EntityInstanceId** of the specified **EntityInstance**, along with the list of name-value pairs for the fields (4) of the specified **Entity** and the status of the operation.

This operation MUST return a **ResolveResult** message with the **ResolveStatus** element set, as specified in sections [3.1.4.1.3.1](#).

#### 3.1.4.1.1 Messages

##### 3.1.4.1.1.1 ResolveSoapIn

The **ResolveSoapIn** message is the request message for the **Resolve** operation.

The **SOAP action** value of the message is:

```
http://microsoft.com/webservices/SharePointPortalServer/BDCClientWS/Resolve
```

The **SOAP body** contains a **Resolve** element.

##### 3.1.4.1.1.2 ResolveSoapOut

The **ResolveSoapOut** message is the response message for the **Resolve** operation.

The SOAP action value of the message is:

The SOAP body contains a **ResolveResponse** element that MUST specify the status of the operation.

### 3.1.4.1.2 Elements

#### 3.1.4.1.2.1 Resolve

The **Resolve** message contains the input data for the **Resolve** operation.

```
<s:element name="Resolve">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="1" maxOccurs="1" name="systemInstance" type="s:string" />
      <s:element minOccurs="1" maxOccurs="1" name="entity" type="s:string" />
      <s:element minOccurs="1" maxOccurs="1" name="valueToResolve" type="s:string" />
      <s:element minOccurs="1" maxOccurs="1" name="fieldNames" type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>
```

**systemInstance:** This element contains the name of the LobSystemInstance. The value is encoded as specified in [\[XML10\]](#). The protocol server MUST only match EntityInstances obtained from the specified LobSystemInstance.

**entity:** This element contains the name of the Entity. The value is encoded as specified in [\[XML10\]](#). The protocol server MUST only match EntityInstances of the specified Entity.

**valueToResolve:** This element contains the value to resolve to an EntityInstance. The value is encoded as specified in [\[XML10\]](#). The value is resolved to EntityInstances using an implementation-specific algorithm. For example, a specific implementation of a protocol server could resolve a given value of "ab" and Entity "Customer", by returning customers that have names starting with "ab". Another implementation of the protocol server could return customer whose names, last names, or addresses contain "ab".

**fieldNames:** This element contains the field (4) names associated with the Entity. Each field name is encoded as specified in [\[RFC3986\]](#). The field names are concatenated into a single string with a colon character, ":", between field names.

#### 3.1.4.1.2.2 ResolveResponse

The **ResolveResponse** message contains the output data of a **Resolve** operation.

```
<s:element name="ResolveResponse">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="1" maxOccurs="1" name="ResolveResult" type="tns:ResolveResult" />
    </s:sequence>
  </s:complexType>
</s:element>
```

**ResolveResult:** This element contains the serialized **EntityInstanceId** element that is associated with the specified **EntityInstance** element, along with the list of name-value pairs for the fields (4) of the specified **Entity** and the status of the operation.

### 3.1.4.1.3 Complex Types

#### 3.1.4.1.3.1 ResolveResult

The **ResolveResult** message contains the output data of a **Resolve** operation.

```
<s:complexType name="ResolveResult">
  <s:sequence>
    <s:element minOccurs="0" maxOccurs="1" name="Identifier" type="tns:IdentifierField" />
    <s:element minOccurs="0" maxOccurs="1" name="Results" type="tns:ArrayOfFieldRecord" />
    <s:element minOccurs="1" maxOccurs="1" name="Status" type="tns:ResolveStatus" />
  </s:sequence>
</s:complexType>
```

**Identifier:** This element contains the **Identifier** of the **EntityInstance** found. If exactly one **EntityInstance** is not found, the value **MUST** be absent.

**Results:** This element contains the list of name-value pairs of the fields (4) of the specified **Entity** if the **fieldNames** element is not absent. If exactly one **EntityInstance** element is not found, the value **MUST** be absent.

**Status:** This element contains the status of the operation. This **ResolveStatus** element **MUST** be present. The protocol server **MUST** set this value as specified in section [3.1.4.1.4.1](#).

#### 3.1.4.1.3.2 IdentifierField

The **IdentifierField** element contains the **Identifier** of the **EntityInstance**. If exactly one **EntityInstance** is not found, the value **MUST** be **absent**.

```
<s:complexType name="IdentifierField">
  <s:simpleContent>
    <s:extension base="s:string"/>
  </s:simpleContent>
</s:complexType>
```

#### 3.1.4.1.3.3 ArrayOfFieldRecord

This **ArrayOfFieldRecord** element contains an array of elements of type **FieldRecord**, as specified in section [3.1.4.1.3.4](#).

```
<s:complexType name="ArrayOfFieldRecord">
  <s:sequence>
    <s:element name="FieldRecord" type="tns:FieldRecord" nillable="true" minOccurs="0"
      maxOccurs="unbounded"/>
  </s:sequence>
</s:complexType>
```

**FieldRecord:** This element contains the **Entity** field (4) name-value pair.

### 3.1.4.1.3.4 FieldRecord

The **FieldRecord** element contains the **Entity** field (4) name-value pair. The name of the field is contained in the **FieldName** attribute of the element and the value of the field is the value of the element.

```
<s:complexType name="FieldRecord">
  <s:simpleContent>
    <s:extension base="s:string">
      <s:attribute name="FieldName" type="s:string"/>
    </s:extension>
  </s:simpleContent>
</s:complexType>
```

**FieldName:** This attribute contains the name of the field (4). Each field (4) name is encoded as specified in [\[RFC3986\]](#).

### 3.1.4.1.4 Simple Types

#### 3.1.4.1.4.1 ResolveStatus

The **ResolveStatus** simple type specifies the enumeration of status of the **Resolve** operation, as specified in section [3.1.4.1](#).

```
<s:simpleType name="ResolveStatus">
  <s:restriction base="s:string">
    <s:enumeration value="NoMatch"/>
    <s:enumeration value="MultipleMatch"/>
    <s:enumeration value="UniqueMatch"/>
    <s:enumeration value="InvalidData"/>
  </s:restriction>
</s:simpleType>
```

The values for this enumeration are specified in the following table.

Value	Description
<b>NoMatch</b>	The protocol server MUST return this value when there are no EntityInstances were found.
<b>MultipleMatch</b>	The protocol server MUST return this value when more than one EntityInstances were found.
<b>UniqueMatch</b>	The protocol server MUST return this value when exactly one EntityInstance was found.
<b>InvalidData</b>	The protocol server MUST return this value when the operation has failed because input data is not valid or an implementation-specific error has occurred.

#### 3.1.4.1.5 Attributes

None.

#### **3.1.4.1.6 Groups**

None.

#### **3.1.4.1.7 Attribute Groups**

None.

#### **3.1.5 Timer Events**

None.

#### **3.1.6 Other Local Events**

None.

## 4 Protocol Examples

### 4.1 Retrieving Field Values for LobSystem Entities

This scenario resolves the specified value to an **EntityInstance**. For this example, the protocol client is aware of the **LobSystemInstance** name, the Entity name, the value to resolve and the **Entity** field (4) names. The steps are as follows.

- The protocol client encodes and concatenates the **Entity field (4)** names using the colon character, ":", as a separator.

If the values of the fields ProductKey, ProductName, Price and Color are to be obtained, the client prepares a string of the form "ProductKey:ProductName:Price:Color"

1. The protocol client issues a Resolve request to the protocol server with the **LobSystemInstance** name, the **Entity** name, the value to resolve and the concatenated **Entity field (4)** names.

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"><soap:Body><Resolve
xmlns="http://microsoft.com/webservices/SharePointPortalServer/BDCClientWS/"><systemIn
stance>bdcdpExampleInstance</systemInstance><entity>Product</entity><valueToResolve>1<
/valueToResolve><fieldNames>ProductKey:ProductName:Price:Color</fieldNames></Resolve><
/soap:Body></soap:Envelope>
```

2. The protocol server responds with the status of the operation. If the **EntityInstance** is found, the protocol server also returns the specified **EntityInstance** and the name-value pairs for the **fields (4)**.

```
"<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"><soap:Body><ResolveResponse
xmlns="http://microsoft.com/webservices/SharePointPortalServer/BDCClientWS/"><ResolveR
esult><Identifier>__bg40001300</Identifier><Results><FieldRecord
FieldName="ProductKey">1</FieldRecord><FieldRecord
FieldName="ProductName">Bag</FieldRecord><FieldRecord
FieldName="Price">3.0000</FieldRecord><FieldRecord
FieldName="Color">Yellow</FieldRecord></Results><Status>UniqueMatch</Status></ResolveR
esult></ResolveResponse></soap:Body></soap:Envelope>
```



## **5 Security**

### **5.1 Security Considerations for Implementers**

None.

### **5.2 Index of Security Parameters**

None.

## 6 Appendix A: Full WSDL

For ease of implementation the following full **WSDL** is provided:

```
<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:tm="http://microsoft.com/wsdl/mime/textMatching/"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:mime="http://schemas.xmlsoap.org/wsdl/mime/"
xmlns:tns="http://microsoft.com/webservices/SharePointPortalServer/BDCClientWS/"
xmlns:s="http://www.w3.org/2001/XMLSchema"
xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/"
xmlns:http="http://schemas.xmlsoap.org/wsdl/http/"
targetNamespace="http://microsoft.com/webservices/SharePointPortalServer/BDCClientWS/"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
<wsdl:documentation xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">BDC Field Resolver Web
Service for Clients</wsdl:documentation>
<wsdl:types>
<s:schema elementFormDefault="qualified"
targetNamespace="http://microsoft.com/webservices/SharePointPortalServer/BDCClientWS/">
<s:element name="Resolve">
<s:complexType>
<s:sequence>
<s:element minOccurs="1" maxOccurs="1" name="systemInstance" type="s:string" />
<s:element minOccurs="1" maxOccurs="1" name="entity" type="s:string" />
<s:element minOccurs="1" maxOccurs="1" name="valueToResolve" type="s:string" />
<s:element minOccurs="1" maxOccurs="1" name="fieldNames" type="s:string" />
</s:sequence>
</s:complexType>
</s:element>
<s:element name="ResolveResponse">
<s:complexType>
<s:sequence>
<s:element minOccurs="1" maxOccurs="1" name="ResolveResult" type="tns:ResolveResult" />
</s:sequence>
</s:complexType>
</s:element>
<s:complexType name="ResolveResult">
<s:sequence>
<s:element minOccurs="0" maxOccurs="1" name="Identifier" type="tns:IdentifierField" />
<s:element minOccurs="0" maxOccurs="1" name="Results" type="tns:ArrayOfFieldRecord" />
<s:element minOccurs="1" maxOccurs="1" name="Status" type="tns:ResolveStatus" />
</s:sequence>
</s:complexType>
<s:complexType name="IdentifierField">
<s:simpleContent>
<s:extension base="s:string" />
</s:simpleContent>
</s:complexType>
<s:complexType name="ArrayOfFieldRecord">
<s:sequence>
<s:element minOccurs="0" maxOccurs="unbounded" name="FieldRecord" nillable="true"
type="tns:FieldRecord" />
</s:sequence>
</s:complexType>
<s:complexType name="FieldRecord">
<s:simpleContent>
<s:extension base="s:string">
<s:attribute name="FieldName" type="s:string" />

```

```

</s:extension>
</s:simpleContent>
</s:complexType>
<s:simpleType name="ResolveStatus">
<s:restriction base="s:string">
<s:enumeration value="NoMatch" />
<s:enumeration value="MultipleMatch" />
<s:enumeration value="UniqueMatch" />
<s:enumeration value="InvalidData" />
</s:restriction>
</s:simpleType>
</s:schema>
</wsdl:types>
<wsdl:message name="ResolveSoapIn">
<wsdl:part name="parameters" element="tns:Resolve" />
</wsdl:message>
<wsdl:message name="ResolveSoapOut">
<wsdl:part name="parameters" element="tns:ResolveResponse" />
</wsdl:message>
<wsdl:portType name="BDCFieldsResolverSoap">
<wsdl:operation name="Resolve">
<wsdl:input message="tns:ResolveSoapIn" />
<wsdl:output message="tns:ResolveSoapOut" />
</wsdl:operation>
</wsdl:portType>
<wsdl:binding name="BDCFieldsResolverSoap" type="tns:BDCFieldsResolverSoap">
<soap:binding transport="http://schemas.xmlsoap.org/soap/http" />
<wsdl:operation name="Resolve">
<soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/BDCClientWS/Resolve"
style="document" />
<wsdl:input>
<soap:body use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
</wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:binding name="BDCFieldsResolverSoap12" type="tns:BDCFieldsResolverSoap">
<soap12:binding transport="http://schemas.xmlsoap.org/soap/http" />
<wsdl:operation name="Resolve">
<soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/BDCClientWS/Resolve"
style="document" />
<wsdl:input>
<soap12:body use="literal" />
</wsdl:input>
<wsdl:output>
<soap12:body use="literal" />
</wsdl:output>
</wsdl:operation>
</wsdl:binding>
</wsdl:definitions>

```

## 7 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Office SharePoint® Server 2007
- Microsoft® SharePoint® Server 2010

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

## 8 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

## 9 Index

### A

Abstract data model  
[server](#) 10  
[Applicability](#) 7  
[Attribute groups](#) 9  
[Attributes](#) 9

### C

[Capability negotiation](#) 7  
[Change tracking](#) 21  
Client  
[overview](#) 10  
[Complex types](#) 9

### D

Data model - abstract  
[server](#) 10

### E

Events  
[local - server](#) 15  
[timer - server](#) 15  
Examples  
[retrieving field values for LobSystem Entities](#) 16

### F

[Fields - vendor-extensible](#) 7  
[Full WSDL](#) 18

### G

[Glossary](#) 5  
[Groups](#) 9

### I

[Implementer - security considerations](#) 17  
[Index of security parameters](#) 17  
[Informative references](#) 6  
Initialization  
[server](#) 10  
[Introduction](#) 5

### L

Local events  
[server](#) 15

### M

Message processing  
[server](#) 11  
Messages  
[attribute groups](#) 9

[attributes](#) 9  
[complex types](#) 9  
[elements](#) 8  
[enumerated](#) 8  
[groups](#) 9  
[namespaces](#) 8  
[simple types](#) 9  
[syntax](#) 8  
[transport](#) 8

### N

[Namespaces](#) 8  
[Normative references](#) 5

### O

Operations  
[Resolve](#) 11  
[Overview \(synopsis\)](#) 6

### P

[Parameters - security index](#) 17  
[Preconditions](#) 7  
[Prerequisites](#) 7  
[Product behavior](#) 20

### R

References  
[informative](#) 6  
[normative](#) 5  
[Relationship to other protocols](#) 7  
[Retrieving field values for LobSystem Entities  
example](#) 16

### S

Security  
[implementer considerations](#) 17  
[parameter index](#) 17  
Sequencing rules  
[server](#) 11  
Server  
[abstract data model](#) 10  
[initialization](#) 10  
[local events](#) 15  
[message processing](#) 11  
[overview](#) 10  
[Resolve operation](#) 11  
[sequencing rules](#) 11  
[timer events](#) 15  
[timers](#) 10  
[Simple types](#) 9  
[Standards assignments](#) 7  
Syntax  
[messages - overview](#) 8

## T

Timer events

[server](#) 15

Timers

[server](#) 10

[Tracking changes](#) 21

[Transport](#) 8

Types

[complex](#) 9

[simple](#) 9

## V

[Vendor-extensible fields](#) 7

[Versioning](#) 7

## W

[WSDL](#) 18