

[MS-OSCO]: Office Server ClickOnce Manifest Structure Specification

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
07/13/2009	0.1	Major	Initial Availability
08/28/2009	0.2	Major	Updated and revised the technical content
11/06/2009	0.3	Editorial	Revised and edited the technical content
02/19/2010	1.0	Editorial	Revised and edited the technical content
03/31/2010	1.01	Editorial	Revised and edited the technical content
04/30/2010	1.02	Editorial	Revised and edited the technical content
06/07/2010	1.03	Editorial	Revised and edited the technical content
06/29/2010	1.04	Editorial	Changed language and formatting in the technical content.
07/23/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
09/27/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
11/15/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
12/17/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.

Table of Contents

1 Introduction	9
1.1 Glossary	9
1.2 References	10
1.2.1 Normative References	10
1.2.2 Informative References	11
1.3 Structure Overview (Synopsis)	11
1.4 Relationship to Protocols and Other Structures	11
1.5 Applicability Statement	11
1.6 Versioning and Localization	12
1.7 Vendor-Extensible Fields	12
2 Structures	13
2.1 Deployment Manifest	13
2.1.1 Target namespace: urn:schemas-microsoft-com:asm.v1	13
2.1.1.1 Global Elements	13
2.1.1.1.1 assembly	13
2.1.1.2 Global Attributes	13
2.1.1.3 Complex Types	13
2.1.1.3.1 assemblyIdentityType	13
2.1.1.3.2 descriptionType	14
2.1.1.3.3 assemblyType	14
2.1.1.4 Simple Types	15
2.1.1.4.1 twoPartVersionType	15
2.1.1.4.2 publicKeyTokenType	16
2.1.1.4.3 fourPartVersionType	16
2.1.1.4.4 fileNameStringType	16
2.1.2 Target Namespace urn:schemas-microsoft-com:asm.v2	17
2.1.2.1 Global Elements	17
2.1.2.1.1 deployment	17
2.1.2.1.2 dependency	17
2.1.2.1.3 publisherIdentity	17
2.1.2.2 Global Attributes	17
2.1.2.2.1 publisher	17
2.1.2.2.2 product	18
2.1.2.3 Complex Types	18
2.1.2.3.1 deploymentType	18
2.1.2.3.2 dependencyType	18
2.1.2.3.3 dependentAssemblyType	19
2.1.2.3.4 hashType	19
2.1.2.3.5 assemblyIdentityType	20
2.1.2.3.6 publisherIdentityType	21
2.1.2.4 Simple Types	21
2.1.2.4.1 fourPartVersionType	21
2.1.2.4.2 fileNameStringType	22
2.1.2.4.3 publicKeyTokenType	22
2.2 Application Manifest	22
2.2.1 Target namespace: urn:schemas-microsoft-com:asm.v1	22
2.2.1.1 Global Elements	22
2.2.1.1.1 assembly	22
2.2.1.2 Global Attributes	23

2.2.1.3	Complex Types.....	23
2.2.1.3.1	assemblyIdentityType.....	23
2.2.1.3.2	assemblyType.....	23
2.2.1.4	Simple Types	24
2.2.1.4.1	twoPartVersionType.....	24
2.2.1.4.2	publicKeyTokenType	25
2.2.1.4.3	fourPartVersionType	25
2.2.1.4.4	fileNameStringType	25
2.2.2	Target namespace: urn:schemas-microsoft-com:asm.v2.....	26
2.2.2.1	Global Elements	26
2.2.2.1.1	application	26
2.2.2.1.2	entryPoint	26
2.2.2.1.3	trustInfo	26
2.2.2.1.4	dependency.....	27
2.2.2.1.5	file	27
2.2.2.1.6	assemblyIdentity.....	27
2.2.2.1.7	publisherIdentity	27
2.2.2.2	Global Attributes	27
2.2.2.3	Complex Types.....	28
2.2.2.3.1	applicationType.....	28
2.2.2.3.2	dependencyType	28
2.2.2.3.3	dependentAssemblyType.....	28
2.2.2.3.4	hashType	29
2.2.2.3.5	dependentOSType	30
2.2.2.3.6	osVersionInfoType.....	30
2.2.2.3.7	osType.....	31
2.2.2.3.8	assemblyIdentityType	31
2.2.2.3.9	publisherIdentityType	32
2.2.2.3.10	entryPointType.....	32
2.2.2.3.11	trustInfoType	33
2.2.2.3.12	securityType	33
2.2.2.3.13	applicationRequestMinimumType	34
2.2.2.3.14	PermissionSetType	34
2.2.2.3.15	defaultAssemblyRequestType.....	35
2.2.2.3.16	fileType	35
2.2.2.4	Simple Types	36
2.2.2.4.1	TwoByteVersion	36
2.2.2.4.2	OneByteVersion	36
2.2.2.4.3	dependencyTypeType	36
2.2.2.4.4	fileNameStringType	37
2.2.2.4.5	fourPartVersionType	37
2.2.2.4.6	publicKeyTokenType	37
2.2.3	Target namespace: urn:schemas-microsoft-com:asm.v3.....	38
2.2.3.1	Global Elements	38
2.2.3.1.1	asmv3	38
2.2.3.2	Global Attributes	38
2.2.3.3	Complex Types.....	38
2.2.3.3.1	requestedPrivilegesType.....	38
2.2.3.3.2	requestedExecutionLevelType	39
2.2.3.3.3	asmv3Type.....	39
2.2.3.4	Simple Types	39
2.2.4	Target namespace: urn:schemas-microsoft-com:clickonce.v1	39
2.2.4.1	Global Elements	39

2.2.4.1.1	customHostSpecified	39
2.2.4.2	Global Attributes	40
2.2.4.3	Complex Types.....	40
2.2.4.3.1	customHostSpecifiedType.....	40
2.2.4.4	Simple Types	40
2.2.5	Target namespace: urn:schemas-microsoft-com:vsta.v3.....	40
2.2.5.1	Global Elements	40
2.2.5.1.1	addin	40
2.2.5.2	Global Attributes	40
2.2.5.3	Complex Types.....	40
2.2.5.3.1	addinType.....	40
2.2.5.3.2	entryPointsCollectionType	41
2.2.5.3.3	entryPointsType	42
2.2.5.3.4	entryPointType	42
2.2.5.3.5	postActionEntryPointType.....	43
2.2.5.3.6	updateType	43
2.2.5.3.7	postActionsType.....	44
2.2.5.3.8	postActionType	44
2.2.5.3.9	postActionDataType.....	45
2.2.5.3.10	applicationType	45
2.2.5.4	Simple Types	45
2.2.6	Target namespace: urn:schemas-microsoft-com:vsto.v4.....	45
2.2.6.1	Global Elements	45
2.2.6.1.1	customizations.....	45
2.2.6.2	Global Attributes	46
2.2.6.3	Complex Types.....	46
2.2.6.3.1	customizationsType	46
2.2.6.3.2	customizationType	46
2.2.6.3.3	appAddInType	47
2.2.6.4	Simple Types	48
2.2.6.4.1	loadBehaviorType.....	48
2.2.6.4.2	keyStringType	48
2.3	Strong Name Signature	48
2.3.1	Target namespace: http://www.w3.org/2000/09/xmldsig#	49
2.3.1.1	Global Elements	49
2.3.1.1.1	Signature	49
2.3.1.1.2	SignatureValue	49
2.3.1.1.3	SignedInfo	49
2.3.1.1.4	CanonicalizationMethod.....	49
2.3.1.1.5	SignatureMethod.....	50
2.3.1.1.6	Reference.....	50
2.3.1.1.7	Transforms.....	50
2.3.1.1.8	Transform	51
2.3.1.1.9	DigestMethod	51
2.3.1.1.10	DigestValue	51
2.3.1.1.11	KeyInfo	51
2.3.1.1.12	KeyValue.....	52
2.3.1.1.13	RSAKeyValue	52
2.3.1.2	Global Attributes	52
2.3.1.3	Complex Types.....	52
2.3.1.3.1	SignatureType	52
2.3.1.3.2	SignatureValueType	53
2.3.1.3.3	SignedInfoType.....	53

2.3.1.3.4	CanonicalizationMethodType	54
2.3.1.3.5	SignatureMethodType	54
2.3.1.3.6	ReferenceType	55
2.3.1.3.7	TransformsType	55
2.3.1.3.8	TransformType	56
2.3.1.3.9	DigestMethodType	56
2.3.1.3.10	KeyInfoType	57
2.3.1.3.11	KeyValue-Type	57
2.3.1.3.12	RSAKeyValue-Type	58
2.3.1.4	Simple Types	58
2.3.1.4.1	CryptoBinary	58
2.3.1.4.2	DigestValue-Type	59
2.3.2	Target namespace: http://schemas.microsoft.com/windows/rel/2005/reldata	59
2.3.2.1	Global Elements	59
2.3.2.1.1	RelData	59
2.3.2.2	Global Attributes	59
2.3.2.3	Complex Types	59
2.3.2.3.1	RelDataType	59
2.3.2.4	Simple Types	60
2.4	Software Publisher Signature	60
2.4.1	Target namespace: urn:mpeg:mpeg21:2003:01-REL-R-NS	60
2.4.1.1	Global Elements	60
2.4.1.1.1	license	60
2.4.1.2	Global Attributes	60
2.4.1.3	Complex Types	60
2.4.1.3.1	License	60
2.4.1.3.2	Grant	61
2.4.1.3.3	Issuer	61
2.4.1.3.4	Right	62
2.4.1.4	Simple Types	62
2.4.2	Target namespace: http://schemas.microsoft.com/windows/pki/2005/Authenticode	62
2.4.2.1	Global Elements	62
2.4.2.1.1	ManifestInformation	62
2.4.2.1.2	SignedBy	62
2.4.2.1.3	AuthenticodePublisher	63
2.4.2.1.4	Timestamp	63
2.4.2.2	Global Attributes	63
2.4.2.3	Complex Types	63
2.4.2.3.1	ManifestInformationType	63
2.4.2.3.2	SignedByType	64
2.4.2.3.3	AuthenticodePublisherType	64
2.4.2.4	Simple Types	65
2.4.3	Target namespace: http://www.w3.org/2000/09/xmldsig#	65
2.4.3.1	Global Elements	65
2.4.3.1.1	Signature	65
2.4.3.1.2	SignatureValue	65
2.4.3.1.3	SignedInfo	65
2.4.3.1.4	CanonicalizationMethod	66
2.4.3.1.5	SignatureMethod	66
2.4.3.1.6	Reference	66
2.4.3.1.7	Transforms	66
2.4.3.1.8	Transform	67

2.4.3.1.9	DigestMethod	67
2.4.3.1.10	DigestValue	67
2.4.3.1.11	Object.....	68
2.4.3.1.12	KeyInfo	68
2.4.3.1.13	KeyValue.....	68
2.4.3.1.14	X509Data	68
2.4.3.1.15	RSAKeyValue	69
2.4.3.2	Global Attributes	69
2.4.3.3	Complex Types.....	69
2.4.3.3.1	SignatureType	69
2.4.3.3.2	SignatureValueType	70
2.4.3.3.3	SignedInfoType.....	70
2.4.3.3.4	CanonicalizationMethodType	71
2.4.3.3.5	SignatureMethodType	71
2.4.3.3.6	ReferenceType	71
2.4.3.3.7	TransformsType	72
2.4.3.3.8	TransformType	73
2.4.3.3.9	DigestMethodType	73
2.4.3.3.10	ObjectType	73
2.4.3.3.11	KeyInfoType	74
2.4.3.3.12	KeyValue.....	75
2.4.3.3.13	X509DataType	75
2.4.3.3.14	RSAKeyValue.....	76
2.4.3.4	Simple Types	76
2.4.3.4.1	CryptoBinary	76
2.4.3.4.2	DigestValueType	77
2.5	Algorithms	77
2.5.1	HashTransforms.Identity	77
2.5.2	Verification of Strong Name Signature	77
2.5.2.1	Conversion from RSA Public Key to publicKeyToken	78
2.5.2.2	CryptoAPI PUBLICKEYBLOB Format.....	78
2.5.2.3	PublicKeyBlob Format.....	79
2.5.3	Software Publisher Identity Verification	79
2.5.3.1	REL License Verification	80
2.5.3.2	Software Publisher Certificate Processing	80
2.5.3.3	Timestamp Processing	81
2.5.3.4	Converting an X.500 Distinguish Name to a String	81
3	Structure Examples	83
3.1	Deployment Manifest.....	83
3.2	Application Manifest	85
4	Security Considerations.....	89
4.1	Digital Signatures	89
5	Appendix A: XML Schema Files	90
5.1	Deployment Manifest XML Schemas	90
5.2	Application Manifest XML Schemas	92
5.3	http://schemas.microsoft.com/windows/pki/2005/Authenticode	100
6	Appendix B: Product Behavior	102
7	Change Tracking.....	103

1 Introduction

This document specifies the Office Server ClickOnce Manifest Structure Specification. This structure is used to package one or more customizations and their dependent components.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

certificate authority (CA) or certification authority
public key
XML

The following terms are defined in [\[MS-OFCGLOS\]](#):

add-in
deployment package
digest
digital signature
fully qualified class name
hash
locale
root element
strong name
time stamp authority
timestamp
XSD

The following terms are specific to this document:

application manifest: An XML file that describes the contents and requirements for a deployment package.

code access security permission set: A set of rules that are applied to an executable component to grant or restrict access to functionality and resources that are associated with that component.

deployment manifest: An XML file that describes the identity and version of a deployment package.

entry point: A starting address for an assembly that is written in the form NamespaceName.ClassName.

package file: A file that is in a deployment package and is not a manifest file.

post-deployment action: A method that can run before or after deployment events.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[Excl-C14N] Boyer, J., Eastlake 3rd, D. E., and Reagle, J., "Exclusive XML Canonicalization Version 1.0", July 2002, <http://www.w3.org/TR/xml-exc-c14n/>

[FIPS180-2] Federal Information Processing Standards Publication, "Secure Hash Standard", FIPS PUB 180-2, August 2002, <http://csrc.nist.gov/publications/fips/fips180-2/fips180-2.pdf>

[ISO/IEC-21000-5] International Organization for Standardization, "Information technology -- Multimedia framework (MPEG-21) -- Part 5: Rights Expression Language", 2004, http://www.iso.org/iso/catalogue_detail.htm?csnumber=36095

[ITU-X680] ITU-T, "Abstract Syntax Notation One (ASN.1): Specification of Basic Notation", Recommendation X.680, July 2002, <http://www.itu.int/ITU-T/studygroups/com17/languages/X.680-0207.pdf>

[PKCS9] RSA Laboratories, "PKCS #9: Selected Attribute Types", PKCS #9, version 1.1, November 1993, <http://www.rsa.com/rsalabs/node.asp?id=2131>

[RFC1321] Rivest, R., "The MD5 Message-Digest Algorithm", RFC 1321, April 1992, <http://www.ietf.org/rfc/rfc1321.txt>

[RFC1779] Kille, S., "A String Representation of Distinguished Names", March 1995, <http://www.ietf.org/rfc/rfc1779.txt>

[RFC2045] Freed, N., and Borenstein, N., "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies", RFC 2045, November 1996, <http://ietf.org/rfc/rfc2045.txt>

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>

[RFC2315] Kaliski, B., "PKCS #7: Cryptographic Message Syntax Version 1.5", RFC 2315, March 1998, <http://www.ietf.org/rfc/rfc2315.txt>

[RFC3279] Polk, W., Housley, R., and Bassham, L., "Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", RFC 3279, April 2002, <http://www.ietf.org/rfc/rfc3279.txt>

[RFC3280] Housley, R., Polk, W., Ford, W., and Solo, D., "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", RFC 3280, April 2002, <http://www.ietf.org/rfc/rfc3280.txt>

[RFC3447] Jonsson, J., and Kaliski, B., "Public-Key Cryptography Standards (PKCS) #1: RSA Cryptography Specifications Version 2.1", RFC 3447, February 2003, <http://www.ietf.org/rfc/rfc3447.txt>

[W3C-XSD] World Wide Web Consortium, "XML Schema Part 2: Datatypes Second Edition", October 2004, <http://www.w3.org/TR/2004/REC-xmlschema-2-20041028/>

[XMLDSig] Bartel, M., Boyer, J., Fox, B., LaMacchia, B., and Simon, E., "XML-Signature Syntax and Processing", February 2002, <http://www.w3.org/TR/xmlsig-core/>

[XMLSCHEMA1] Thompson, H.S., Ed., Beech, D., Ed., Maloney, M., Ed., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

1.2.2 Informative References

[MS-BCSDPFFS] Microsoft Corporation, "[Business Connectivity Services Deployment Package File Format Specification](#)", July 2009.

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)", March 2007.

[MS-OFCGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)", June 2008.

[XML] World Wide Web Consortium, "Extensible Markup Language (XML) 1.0 (Fourth Edition)", W3C Recommendation, August 2006, <http://www.w3.org/TR/2006/REC-xml-20060816/>

1.3 Structure Overview (Synopsis)

The Office Server ClickOnce manifest structure is used to create a **deployment package** for deploying one or more customizations and their related components to a computer.

A deployment package consists of a **deployment manifest** file (section 2.1) and an **application manifest** file (section 2.2). In addition to the manifest files, the deployment package also contains additional files as specified by the application manifest.

The deployment manifest file lists the identity and version of the deployment package. Contents of the deployment manifest also identify the publisher of the deployment package. The deployment manifest links to the application manifest for the deployment package.

The application manifest file lists the files associated with the deployment package and their relationship to the deployment package. The application manifest specifies run-time behavior about one or many customizations included in the deployment package. The application manifest describes the location of **package files** but does not describe the location to deploy the package files. An implementation of this structure can deploy package files to a temporary cache or provide the user with a choice of the final location.

1.4 Relationship to Protocols and Other Structures

The XML based structures in this document are defined according to the XML standard specified in [\[XML\]](#).

The manifest files in this structure are signed using XML signature syntax and processing rules as specified by [\[XMLDSig\]](#).

[\[MS-BCSDPFFS\]](#) section 1.3 is an example of an implementation that uses this structure.

1.5 Applicability Statement

This structure can be used to package and deploy one or more customizations. An implementation of this structure can package customizations dynamically and deploy them to a computer to customize applications running on the computer. This structure provides information necessary to successfully deploy a package and does not assure the functionality of the customizations present in the package.

1.6 Versioning and Localization

None

1.7 Vendor-Extensible Fields

None

2 Structures

XSD

A deployment package specifies the location of package files for deployment. A deployment package MUST contain the following files:

- A deployment manifest file as specified in section [2.1](#) of this document.
- An application manifest file as specified in section [2.2](#) of this document.
- At least one package file.

2.1 Deployment Manifest

The deployment manifest is a **XML** file that specifies the identity and version information of the deployment package. The file name of the deployment manifest MUST end with ".vsto". The file size of the deployment manifest MUST be less than 16 megabytes. The **root element** of the deployment manifest MUST be assembly (section [2.1.1.1.1](#)).

2.1.1 Target namespace: urn:schemas-microsoft-com:asm.v1

2.1.1.1 Global Elements

2.1.1.1.1 assembly

Target namespace: urn:schemas-microsoft-com:asm.v1

An [assemblyType](#) element that specifies a deployment manifest.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this element.

```
<xss:element name="assembly" type="assemblyType"/>
```

2.1.1.2 Global Attributes

None.

2.1.1.3 Complex Types

2.1.1.3.1 assemblyIdentityType

Target namespace: urn:schemas-microsoft-com:asm.v1

Referenced by: [assemblyType](#)

The **assemblyIdentityType** complex type specifies an identifier for a deployment package.

Attributes:

name : A [fileNameString](#) attribute that specifies the name. The length of the string value MUST be less than 252 characters.

version : A [fourPartVersionType](#) attribute that specifies the version.

processorArchitecture : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies the processor architecture.

publicKeyToken : A [publicKeyTokenType](#) attribute that specifies the last 8 bytes of the SHA-1 **hash** ([\[FIPS180-2\]](#) section 6.1) of the **public key** used to generate the strong name signature (section [2.3](#)) for the deployment manifest in accordance with section [2.5.2.1](#).

language : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies the **locale**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="assemblyIdentityType">
  <xs:attribute name="name" type="asm.v1:fileNameStringType" use="required"/>
  <xs:attribute name="version" type="asm.v1:fourPartVersionType" use="required"/>
  <xs:attribute name="processorArchitecture" type="xs:string" use="required" fixed="msil"/>
  <xs:attribute name="publicKeyToken" type="asm.v1:publicKeyTokenType" use="required"/>
  <xs:attribute name="language" type="xs:string" use="required" fixed="neutral"/>
</xs:complexType>
```

2.1.1.3.2 descriptionType

Target namespace: urn:schemas-microsoft-com:asm.v1

Referenced by: [assemblyType](#)

The **descriptionType** complext type specifies the description of a deployment package. The combined length of Publisher and Product attribute values MUST be less than 261 characters.

Attributes:

publisher : A [publisher](#) attribute that specifies the publisher name.

product : A [product](#) attribute that specifies the product name.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="descriptionType" mixed="true">
  <xs:attribute ref="asm.v2:publisher" use="required"/>
  <xs:attribute ref="asm.v2:product" use="required"/>
</xs:complexType>
```

2.1.1.3.3 assemblyType

Target namespace: urn:schemas-microsoft-com:asm.v1

Referenced by: [assembly](#)

The **assemblyType** complex typespecifies a deployment manifest.

Child Elements:

assemblyIdentity : An [assemblyIdentityType](#) element that specifies an identifier for the deployment package.

description : A [descriptionType](#) element that specifies the description.

deployment : A [deployment](#) element that specifies how files in the deployment package are stored.

dependency : A [dependency](#) element that specifies a dependency on an application manifest (section [2.2](#)).

publisherIdentity : A [publisherIdentity](#) element that specifies the publisher of a deployment package.

Signature : A [SignatureType](#) element that specifies the necessary information to validate a signed deployment manifest.

Attributes:

manifestVersion : A [twoPartVersionType](#) attribute that specifies the manifest version.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="assemblyType">
  <xs:sequence>
    <xs:element name="assemblyIdentity" type="asm.v1:assemblyIdentityType"/>
    <xs:element name="description" type="descriptionType"/>
    <xs:element ref="asm.v2:deployment"/>
    <xs:element ref="asm.v2:dependency"/>
    <xs:element ref="asm.v2:publisherIdentity"/>
    <xs:element ref="ds:Signature"/>
  </xs:sequence>
  <xs:attribute name="manifestVersion" type="asm.v1:twoPartVersionType" use="required"
fixed="1.0"/>
</xs:complexType>
```

2.1.1.4 Simple Types

2.1.1.4.1 twoPartVersionType

Target namespace: urn:schemas-microsoft-com:asm.v1

Referenced by: [assemblyType](#)

The **twoPartVersionType** simple type specifies a version.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this simple type.

```
<xs:simpleType name="twoPartVersionType">
  <xs:restriction base="xs:string">
    <xs:pattern value="(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-
9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-
4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])"/>
  </xs:restriction>
</xs:simpleType>
```

2.1.1.4.2 publicKeyTokenType

Target namespace: urn:schemas-microsoft-com:asm.v1

Referenced by: [assemblyIdentityType](#)

The **publicKeyTokenType** simple type specifies the last 8 bytes of the SHA-1 hash as specified by [\[FIPS180-2\]](#) section 6.1 of a public key in accordance with section [2.5.2.1](#).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this simple type.

```
<xs:simpleType name="publicKeyTokenType">
  <xs:restriction base="xs:string">
    <xs:pattern value="([0-9]|[a-f]|[A-F])\{16}" />
  </xs:restriction>
</xs:simpleType>
```

2.1.1.4.3 fourPartVersionType

Target namespace: urn:schemas-microsoft-com:asm.v1

Referenced by: [assemblyIdentityType](#)

The **fourPartVersionType** simple type specifies a version.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this simple type.

```
<xs:simpleType name="fourPartVersionType">
  <xs:restriction base="xs:string">
    <xs:pattern value="(0*[0-9]\{1,4\})|0*[1-5]\{0-9\}\{4\}|0*6\{0-4\}\{0-9\}\{3\}|0*65\{0-4\}\{0-9\}\{2\}|0*655\{0-2\}\{0-9\}|0*6553\{0-5\})\.(0*[0-9]\{1,4\})|0*[1-5]\{0-9\}\{4\}|0*6\{0-4\}\{0-9\}\{3\}|0*65\{0-4\}\{0-9\}\{2\}|0*655\{0-2\}\{0-9\}|0*6553\{0-5\})\.(0*[0-9]\{1,4\})|0*[1-5]\{0-9\}\{4\}|0*6\{0-4\}\{0-9\}\{3\}|0*65\{0-4\}\{0-9\}\{2\}|0*655\{0-2\}\{0-9\}|0*6553\{0-5\})\.(0*[0-9]\{1,4\})|0*[1-5]\{0-9\}\{4\}|0*6\{0-4\}\{0-9\}\{3\}|0*65\{0-4\}\{0-9\}\{2\}|0*655\{0-2\}\{0-9\}|0*6553\{0-5\})"/>
  </xs:restriction>
</xs:simpleType>
```

2.1.1.4.4 fileNameStringType

Target namespace: urn:schemas-microsoft-com:asm.v1

Referenced by: [assemblyIdentityType](#)

The **fileNameStringType** simple type specifies a string for a file name.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this simple type.

```
<xs:simpleType name="fileNameStringType">
  <xs:restriction base="xs:string">
    <xs:pattern value="([\u0020]|[\u0021]|[\u0024]|[\u0025]|[\u0027-\u0029]|[\u002B-\u002E]|[\u0030-\u0039]|[\u003B]|[\u003D]|[\u0040-\u005B]|[\u005D-\u007B]|[\u007D-\uFFFD]|[\u10000-\u10FFFF])*"/>
  </xs:restriction>
```

```
</xs:simpleType>
```

2.1.2 Target Namespace urn:schemas-microsoft-com:asm.v2

2.1.2.1 Global Elements

2.1.2.1.1 deployment

Target namespace: urn:schemas-microsoft-com:asm.v2

A [deploymentType](#) element that specifies a global element that is referenced by [assemblyType](#).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this element.

```
<xs:element name="deployment" type="asm.v2:deploymentType"/>
```

2.1.2.1.2 dependency

Target namespace: urn:schemas-microsoft-com:asm.v2

A [dependencyType](#) element that specifies a global element that is referenced by [assemblyType](#).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this element.

```
<xs:element name="dependency" type="asm.v2:dependencyType"/>
```

2.1.2.1.3 publisherIdentity

Target namespace: urn:schemas-microsoft-com:asm.v2

A [publisherIdentityType](#) element that specifies a global element that is referenced by [assemblyType](#).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this element.

```
<xs:element name="publisherIdentity" type="asm.v2:publisherIdentityType"/>
```

2.1.2.2 Global Attributes

2.1.2.2.1 publisher

Target namespace: urn:schemas-microsoft-com:asm.v2

A [fileNameStringType](#) attribute that specifies the publisher name.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this attribute.

```
<xs:attribute name="publisher" type="asm.v2:fileNameStringType" fixed="DefaultPublisher"/>
```

2.1.2.2.2 product

Target namespace: urn:schemas-microsoft-com:asm.v2

A [fileNameStringType](#) attribute that specifies the product name.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this attribute.

```
<xs:attribute name="product" type="asm.v2:fileNameStringType"/>
```

2.1.2.3 Complex Types

2.1.2.3.1 deploymentType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [deployment](#)

The **deploymentType** complex type specifies how files in the deployment package are stored.

Attributes:

install : A boolean ([W3C-XSD](#) section 3.2.2) attribute that specifies a reserved value.

mapFileExtensions : A boolean ([W3C-XSD](#) section 3.2.2) attribute that specifies whether package files have the string ".deploy" appended to the end of the file name. For example: the package file "file.dll" would be stored as "file.dll.deploy" if the value is "true".

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="deploymentType">
  <xs:attribute name="install" type="xs:boolean" use="required" fixed="false"/>
  <xs:attribute name="mapFileExtensions" type="xs:boolean" use="optional" default="false"/>
</xs:complexType>
```

2.1.2.3.2 dependencyType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [dependency](#)

The **dependencyType** complex type specifies a container for a [dependentAssemblyType](#) element.

Child Elements:

dependentAssembly : A dependentAssemblyType element that specifies the application manifest (section [2.2](#)).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```

<xs:complexType name="dependencyType">
  <xs:sequence>
    <xs:choice>
      <xs:element name="dependentAssembly" type="asm.v2:dependentAssemblyType"/>
    </xs:choice>
  </xs:sequence>
</xs:complexType>

```

2.1.2.3.3 dependentAssemblyType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [dependencyType](#)

The **dependentAssemblyType** complex type specifies an application manifest (section [2.2](#)).

Child Elements:

assemblyIdentity : An [assemblyIdentityType](#) element that specifies an identifier for the application manifest (section [2.2](#)).

hash : A [hashType](#) element that specifies the hash of the application manifest (section [2.2](#))

Attributes:

dependencyType : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies a dependency on a application manifest (section [2.2](#)).

codebase : An anyURI ([\[W3C-XSD\]](#) section 3.2.17) attribute that specifies a path to an application manifest (section [2.2](#)).

size : An integer ([\[W3C-XSD\]](#) section 3.3.13) attribute that specifies the size of an application manifest (section [2.2](#)) in bytes.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```

<xs:complexType name="dependentAssemblyType">
  <xs:sequence>
    <xs:element name="assemblyIdentity" type="asm.v2:assemblyIdentityType"/>
    <xs:element name="hash" type="asm.v2:hashType" minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
  <xs:attribute name="dependencyType" type="xs:string" use="required" fixed="install"/>
  <xs:attribute name="codebase" type="xs:anyURI"/>
  <xs:attribute name="size" type="xs:integer" use="optional"/>
</xs:complexType>

```

2.1.2.3.4 hashType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [dependentAssemblyType](#)

The **hashType** complex type specifies a hash of a file as specified by [\[XMLDSig\]](#) section 4.3.3.

The **Transforms** container element ([\[XMLDSig\]](#) section 4.3.3.4) MUST contain one **Transform** element. The value of the **Algorithm** attribute of the **Transform** element ([\[XMLDSig\]](#) section 4.3.3.4) MUST be "urn:schemas-microsoft-com:HashTransforms.Identity" (section [2.5.1](#)).

The value of the **Algorithm** attribute of the **DigestMethod** ([\[XMLDSig\]](#) section 4.3.3.5) MUST be "http://www.w3.org/2000/09/xmldsig#sha1".

All other attributes are ignored.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="hashType">
  <xs:complexContent>
    <xs:extension base="ds:ReferenceType">
      <xs:sequence>
        <xs:any namespace="##other" processContents="lax" minOccurs="0"
maxOccurs="unbounded"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

2.1.2.3.5 assemblyIdentityType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [dependentAssemblyType](#)

The **assemblyIdentityType** complex type specifies an identifier of an application manifest.

Attributes:

name : A [fileNameString](#) attribute that specifies the name. The length of the string value MUST be less than 252 characters.

version : A [fourPartVersion](#) attribute that specifies the version.

type : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies the reserved value.

processorArchitecture : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies the processor architecture.

publicKeyToken : A [publicKeyToken](#) attribute that specifies the last 8 bytes of the SHA-1 hash ([\[FIPS180-2\]](#) section 6.1) of the public key used to generate the strong name signature (section [2.3](#)) for the application manifest in accordance with section [2.5.2.1](#).

language : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies the locale.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="assemblyIdentityType">
  <xs:attribute name="name" type="asm.v2:fileNameStringType" use="required"/>
  <xs:attribute name="version" type="asm.v2:fourPartVersionType" use="required"/>
  <xs:attribute name="type" type="xs:string" use="optional" fixed="win32"/>
  <xs:attribute name="processorArchitecture" type="xs:string" use="required" fixed="msil"/>
```

```
<xs:attribute name="publicKeyToken" type="asm.v2:publicKeyTokenType" use="required"/>
<xs:attribute name="language" type="xs:string" use="required" fixed="neutral"/>
</xs:complexType>
```

2.1.2.3.6 publisherIdentityType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [publisherIdentity](#)

The **publisherIdentityType** complex type specifies a publisher of a deployment package.

Attributes:

name : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies the distinguished name of the publisher as specified in ([\[RFC1779\]](#) section 2.3.

issuerKeyHash : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies the SHA-1 hash ([\[FIPS180-2\]](#) section 6.1) of the public key in the certificate of the **certification authority** that issued the publisher's certificate ([\[RFC3280\]](#)). The SHA-1 public key hash is computed over the value of the subjectPublicKey field in the subjectPublicKeyInfo field ([\[RFC3280\]](#) section 4.1). The tag and length MUST be excluded from the value before calculation.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="publisherIdentityType">
  <xs:attribute name="name" type="xs:string"/>
  <xs:attribute name="issuerKeyHash" type="xs:string"/>
</xs:complexType>
```

2.1.2.4 Simple Types

2.1.2.4.1 fourPartVersionType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [assemblyIdentityType](#)

The **fourPartVersionType** specifies a version number.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this simple type.

```
<xs:simpleType name="fourPartVersionType">
  <xs:restriction base="xs:string">
    <xs:pattern value="(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])"/>
  </xs:restriction>
</xs:simpleType>
```

2.1.2.4.2 fileNameStringType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [publisher](#), [product](#), [assemblyIdentityType](#)

The **fileNameStringType** simple type specifies a string for a file name.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this simple type.

```
<xs:simpleType name="fileNameStringType">
  <xs:restriction base="xs:string">
    <xs:pattern value="([\u0020] | [\u0021] | [\u0024] | [\u0025] | [\u0027-\u0029] | [\u002B-
\u002E] | [\u0030-\u0039] | [\u003B] | [\u003D] | [\u0040-\u005B] | [\u005D-\u007B] | [\u007D-
\uFFFD] | [\u10000-\u10FFFF]) *"/>
  </xs:restriction>
</xs:simpleType>
```

2.1.2.4.3 publicKeyTokenType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [assemblyIdentityType](#)

The **publicKeyTokenType** simple type specifies the last 8 bytes of the SHA-1 hash as specified by [\[FIPS180-2\]](#) section 6.1 of a public key in accordance with section [2.5.2.1](#).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this simple type.

```
<xs:simpleType name="publicKeyTokenType">
  <xs:restriction base="xs:string">
    <xs:pattern value="([0-9] | [a-f] | [A-F]) {16}" />
  </xs:restriction>
</xs:simpleType>
```

2.2 Application Manifest

The application manifest is a XML file that specifies the dependencies and **entry points** for customizations included in the deployment package. The file name MUST end with ".manifest". The file size of the application manifest MUST be less than 16 megabytes. The root element of the application manifest must be assembly (section [2.2.1.1.1](#)).

2.2.1 Target namespace: urn:schemas-microsoft-com:asm.v1

2.2.1.1 Global Elements

2.2.1.1.1 assembly

Target namespace: urn:schemas-microsoft-com:asm.v1

An [assemblyType](#) element that specifies an application manifest.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this element.

```
<xs:element name="assembly" type="assemblyType"/>
```

2.2.1.2 Global Attributes

None.

2.2.1.3 Complex Types

2.2.1.3.1 assemblyIdentityType

Target namespace: urn:schemas-microsoft-com:asm.v1

Referenced by: [assemblyType](#)

The **assemblyIdentityType** complex type specifies an identifier for an application manifest.

Attributes:

name : A [fileNameStringType](#) attribute that specifies the name. The length of the string value MUST be less than 252 characters.

version : A [fourPartVersionType](#) attribute that specifies the version.

type : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies a reserved value.

processorArchitecture : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies the processor architecture.

publicKeyToken : A [publicKeyTokenType](#) attribute that specifies the last 8 bytes of the SHA-1 hash ([\[FIPS180-2\]](#) section 6.1) of the public key used to generate the strong name signature (section 2.3) for the application manifest in accordance with section [2.5.2.1](#).

language : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies the locale.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="assemblyIdentityType">
  <xs:attribute name="name" type="asm.v1:fileNameStringType" use="required"/>
  <xs:attribute name="version" type="asm.v1:fourPartVersionType" use="required"/>
  <xs:attribute name="type" type="xs:string" use="optional" fixed="win32"/>
  <xs:attribute name="processorArchitecture" type="xs:string" use="required" fixed="msil"/>
  <xs:attribute name="publicKeyToken" type="asm.v1:publicKeyTokenType" use="required"/>
  <xs:attribute name="language" type="xs:string" use="required" fixed="neutral"/>
</xs:complexType>
```

2.2.1.3.2 assemblyType

Target namespace: urn:schemas-microsoft-com:asm.v1

Referenced by: [assembly](#)

The **assemblyType** complex type specifies an application manifest.

Child Elements:

assemblyIdentity : An [assemblyIdentityType](#) element that specifies an identifier for the application manifest.

application : An [application](#) element that specifies ignored data.

entryPoint : An [entryPoint](#) element that specifies an entry point.

trustInfo : A [trustInfo](#) element that specifies a container for a [securityType](#) element.

dependency : A [dependency](#) element that specifies a dependency required for the deployment package.

file : A [file](#) element that specifies a file that is a part of the deployment package.

addIn : An [addIn](#) element that specifies run-time behavior of the deployment package.

publisherIdentity : A [publisherIdentity](#) element that specifies the publisher of the deployment package.

Signature : A [SignatureType](#) element that specifies the necessary information to validate a signed application manifest.

Attributes:

manifestVersion : A [twoPartVersionType](#) attribute that specifies the version of the application manifest.

The following W3C XML Schema ([\[XMLSHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="assemblyType">
  <xs:sequence>
    <xs:element name="assemblyIdentity" type="asm.v1:assemblyIdentityType"/>
    <xs:element ref="asm.v2:application"/>
    <xs:element ref="asm.v2:entryPoint"/>
    <xs:element ref="asm.v2:trustInfo"/>
    <xs:element ref="asm.v2:dependency" minOccurs="0" maxOccurs="24575"/>
    <xs:element ref="asm.v2:file" minOccurs="0" maxOccurs="24575"/>
    <xs:element ref="vsta.v3:addIn"/>
    <xs:element ref="asm.v2:publisherIdentity"/>
    <xs:element ref="ds:Signature"/>
  </xs:sequence>
  <xs:attribute name="manifestVersion" type="asm.v1:twoPartVersionType" use="required"
fixed="1.0"/>
</xs:complexType>
```

2.2.1.4 Simple Types

2.2.1.4.1 twoPartVersionType

Target namespace: urn:schemas-microsoft-com:asm.v1

Referenced by: [assemblyType](#)

The **twoPartVersionType** simple type specifies a version.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this simple type.

```
<xs:simpleType name="twoPartVersionType">
  <xs:restriction base="xs:string">
    <xs:pattern value="(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-
9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-
4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])"/>
  </xs:restriction>
</xs:simpleType>
```

2.2.1.4.2 publicKeyTokenType

Target namespace: urn:schemas-microsoft-com:asm.v1

Referenced by: [assemblyIdentityType](#)

The **publicKeyTokenType** simple type specifies the last 8 bytes of the SHA-1 hash as specified by [\[FIPS180-2\]](#) section 6.1 of a public key in accordance with section [2.5.2.1](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this simple type.

```
<xs:simpleType name="publicKeyTokenType">
  <xs:restriction base="xs:string">
    <xs:pattern value="([0-9]|[a-f]|[A-F]){16}"/>
  </xs:restriction>
</xs:simpleType>
```

2.2.1.4.3 fourPartVersionType

Target namespace: urn:schemas-microsoft-com:asm.v1

Referenced by: [assemblyIdentityType](#)

The **fourPartVersionType** type specifies a version.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this simple type.

```
<xs:simpleType name="fourPartVersionType">
  <xs:restriction base="xs:string">
    <xs:pattern value="(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-
9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-
4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-
9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-
9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])"/>
  </xs:restriction>
</xs:simpleType>
```

2.2.1.4.4 fileNameStringType

Target namespace: urn:schemas-microsoft-com:asm.v1

Referenced by: [assemblyIdentityType](#)

The **fileNameStringType** simple type specifies a string for a file name.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this simple type.

```
<xs:simpleType name="fileNameStringType">
  <xs:restriction base="xs:string">
    <xs:pattern value="([\u0020]|[\u0021]|[\u0024]|[\u0025]|[\u0027-\u0029]|[\u002B-
\u002E]|[\u0030-\u0039]|[\u003B]|[\u003D]|[\u0040-\u005B]|[\u005D-\u007B]|[\u007D-
\uFFFD]|[\u10000-\u10FFFF])*"/>
  </xs:restriction>
</xs:simpleType>
```

2.2.2 Target namespace: urn:schemas-microsoft-com:asm.v2

2.2.2.1 Global Elements

2.2.2.1.1 application

Target namespace: urn:schemas-microsoft-com:asm.v2

An [applicationType](#) element that specifies a global element that is referenced by [assemblyType](#).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this element.

```
<xs:element name="application" type="asm.v2:applicationType"/>
```

2.2.2.1.2 entryPoint

Target namespace: urn:schemas-microsoft-com:asm.v2

An [entryPointType](#) element that specifies a global element that is referenced by [assemblyType](#).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this element.

```
<xs:element name="entryPoint" type="asm.v2:entryPointType"/>
```

2.2.2.1.3 trustInfo

Target namespace: urn:schemas-microsoft-com:asm.v2

An [trustInfoType](#) element that specifies a global element that is referenced by [assemblyType](#).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this element.

```
<xs:element name="trustInfo" type="asm.v2:trustInfoType"/>
```

2.2.2.1.4 dependency

Target namespace: urn:schemas-microsoft-com:asm.v2

A [dependencyType](#) element that specifies a global element that is referenced by [assemblyType](#).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this element.

```
<xs:element name="dependency" type="asm.v2:dependencyType"/>
```

2.2.2.1.5 file

Target namespace: urn:schemas-microsoft-com:asm.v2

A [fileType](#) element that specifies a global element that is referenced by [assemblyType](#).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this element.

```
<xs:element name="file" type="asm.v2:fileType"/>
```

2.2.2.1.6 assemblyIdentity

Target namespace: urn:schemas-microsoft-com:asm.v2

An [assemblyIdentityType](#) element that specifies a global element that is referenced by [entryPointType](#), [postActionEntryPointType](#).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this element.

```
<xs:element name="assemblyIdentity" type="asm.v2:assemblyIdentityType"/>
```

2.2.2.1.7 publisherIdentity

Target namespace: urn:schemas-microsoft-com:asm.v2

A [publisherIdentityType](#) element that specifies a global element that is referenced by [assemblyType](#).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this element.

```
<xs:element name="publisherIdentity" type="asm.v2:publisherIdentityType"/>
```

2.2.2.2 Global Attributes

None.

2.2.2.3 Complex Types

2.2.2.3.1 applicationType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [application](#)

The **applicationType** complex type specifies ignored data.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="applicationType"/>
```

2.2.2.3.2 dependencyType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [dependency](#)

The **dependencyType** complex type specifies a dependency required by the deployment package.

Child Elements:

dependentAssembly : A [dependentAssemblyType](#) element that specifies the assembly is required by the deployment package.

dependentOS : A [dependentOSType](#) element that specifies a minimum operating system requirement of a deployment package.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="dependencyType">
  <xs:sequence>
    <xs:choice>
      <xs:element name="dependentAssembly" type="asm.v2:dependentAssemblyType"/>
      <xs:element name="dependentOS" type="asm.v2:dependentOSType"/>
    </xs:choice>
  </xs:sequence>
</xs:complexType>
```

2.2.2.3.3 dependentAssemblyType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [dependencyType](#)

The **dependentAssemblyType** complex type specifies an assembly that is required by the deployment package.

Child Elements:

assemblyIdentity : An [assemblyIdentityType](#) element that specifies the unique identifier of the assembly.

hash : A [hashType](#) element that specifies a hash of the assembly.

Attributes:

dependencyType : A [dependencyTypeType](#) attribute that specifies the type of the dependency of the deployment package on the assembly.

codebase : An anyURI ([\[W3C-XSD\]](#) section 3.2.17) attribute that specifies a path to the dependent assembly.

size : An integer ([\[W3C-XSD\]](#) section 3.3.13) attribute that specifies the file size in bytes of the dependent assembly.

allowDelayedBinding : A boolean ([\[W3C-XSD\]](#) section 3.2.2) attribute that specifies a reserved value.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="dependentAssemblyType">
  <xs:sequence>
    <xs:element name="assemblyIdentity" type="asm.v2:assemblyIdentityType"/>
    <xs:element name="hash" type="asm.v2:hashType" minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
  <xs:attribute name="dependencyType" type="asm.v2:dependencyTypeType" use="optional"
    default="preRequisite"/>
  <xs:attribute name="codebase" type="xs:anyURI"/>
  <xs:attribute name="size" type="xs:integer" use="optional"/>
  <xs:attribute name="allowDelayedBinding" type="xs:boolean" use="required" fixed="true"/>
</xs:complexType>
```

2.2.2.3.4 hashType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [dependentAssemblyType](#), [fileType](#)

The **hashType** complex type specifies a hash of a file as specified by [\[XMLDSig\]](#) section 4.3.3.

The Transforms container element ([\[XMLDSig\]](#) section 4.3.3.4) MUST contain one Transform element. The value of the Algorithm attribute of the Transform element ([\[XMLDSig\]](#) section 4.3.3.4) MUST be "urn:schemas-microsoft-com:HashTransforms.Identity" (section [2.5.1](#)).

The value of the Algorithm attribute of the DigestMethod ([\[XMLDSig\]](#) section 4.3.3.5) MUST be "http://www.w3.org/2000/09/xmldsig#sha1".

All other attributes are ignored.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="hashType">
  <xs:complexContent>
    <xs:extension base="ds:ReferenceType">
```

```

<xs:sequence>
  <xs:any namespace="##other" processContents="lax" minOccurs="0"
maxOccurs="unbounded"/>
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

2.2.2.3.5 dependentOSType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [dependencyType](#)

A dependentOSType element that specifies a minimum operating system requirement of a deployment package.

Child Elements:

osVersionInfo : An [osVersionInfoType](#) element that specifies the minimum operating system version.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```

<xs:complexType name="dependentOSType">
  <xs:sequence>
    <xs:element name="osVersionInfo" type="asm.v2:osVersionInfoType"/>
  </xs:sequence>
</xs:complexType>

```

2.2.2.3.6 osVersionInfoType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [dependentOSType](#)

The **osVersionInfoType** complex type specifies an operating system version.

Child Elements:

os : An [osType](#) element that specifies the operation system version.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```

<xs:complexType name="osVersionInfoType">
  <xs:sequence>
    <xs:element name="os" type="asm.v2:osType"/>
  </xs:sequence>
</xs:complexType>

```

2.2.2.3.7 osType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [osVersionInfoType](#)

The **osType** complex type specifies an operation system version.

Attributes:

majorVersion : A [TwoByteVersion](#) attribute that specifies the major version.

minorVersion : A TwoByteVersion attribute that specifies the minor version.

buildNumber : A TwoByteVersion attribute that specifies the build number.

servicePackMajor : A [OneByteVersion](#) attribute that specifies the service pack major version.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="osType">
  <xs:attribute name="majorVersion" type="asm.v2:TwoByteVersion" use="required" fixed="4"/>
  <xs:attribute name="minorVersion" type="asm.v2:TwoByteVersion" use="required" fixed="10"/>
  <xs:attribute name="buildNumber" type="asm.v2:TwoByteVersion" use="required" fixed="0"/>
  <xs:attribute name="servicePackMajor" type="asm.v2:OneByteVersion" use="required"
fixed="0"/>
</xs:complexType>
```

2.2.2.3.8 assemblyIdentityType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [dependentAssemblyType](#), [assemblyIdentity](#)

The **assemblyIdentityType** complex type specifies an identifier of an assembly.

Attributes:

name : A [fileNameString](#) attribute that specifies the name. The length of the string value MUST be less than 252 characters.

version : A [fourPartVersion](#) attribute that specifies the version.

type : A string ([W3C-XSD](#) section 3.2.1) attribute that specifies a reserved value.

processorArchitecture : A string ([W3C-XSD](#) section 3.2.1) attribute that specifies the processor architecture.

publicKeyToken : A [publicKeyToken](#) attribute that specifies the last 8 bytes of the SHA-1 hash ([FIPS180-2](#) section 6.1) of the public key used to verify the assembly in accordance with section [2.5.2.1](#).

language : A string ([W3C-XSD](#) section 3.2.1) attribute that specifies the locale.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```

<xs:complexType name="assemblyIdentityType">
  <xs:attribute name="name" type="asm.v2:fileNameStringType" use="required"/>
  <xs:attribute name="version" type="asm.v2:fourPartVersionType" use="required"/>
  <xs:attribute name="type" type="xs:string" use="optional" fixed="win32"/>
  <xs:attribute name="processorArchitecture" type="xs:string" use="optional" fixed="msil"/>
  <xs:attribute name="publicKeyToken" type="asm.v2:publicKeyTokenType" use="optional"/>
  <xs:attribute name="language" type="xs:string" use="optional" fixed="neutral"/>
</xs:complexType>

```

2.2.2.3.9 publisherIdentityType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [publisherIdentity](#)

The **publisherIdentityType** complex type specifies a publisher of a deployment package.

Attributes:

name : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies the distinguished name of the publisher as specified in [\[RFC1779\]](#) section 2.3.

issuerKeyHash : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies the SHA-1 hash ([\[FIPS180-2\]](#) section 6.1) of the public key in the certificate of the certification authority that issued the publisher's certificate ([\[RFC3280\]](#)). The SHA-1 public key hash is computed over the value of the subjectPublicKey field in the subjectPublicKeyInfo field ([\[RFC3280\]](#) section 4.1). The tag and length MUST be excluded from the value before calculation.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```

<xs:complexType name="publisherIdentityType">
  <xs:attribute name="name" type="xs:string"/>
  <xs:attribute name="issuerKeyHash" type="xs:string"/>
</xs:complexType>

```

2.2.2.3.10 entryPointType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [entryPoint](#)

The **entryPointType** complex type specifies an entry point.

Child Elements:

customHostSpecified : A [customHostSpecified](#) element specifies whether the entry points are defined in the [addin](#) element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```

<xs:complexType name="entryPointType">
  <xs:sequence>
    <xs:element ref="co.v1:customHostSpecified"/>

```

```
</xs:sequence>
</xs:complexType>
```

2.2.2.3.11 trustInfoType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [trustInfo](#)

The **trustInfoType** complex type specifies a container for a [securityType](#) element.

Child Elements:

security : A securityType element that specifies the permissions requested by the deployment package.

asmv3 : An [asmv3](#) element that specifies ignored data.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="trustInfoType">
  <xs:sequence>
    <xs:element name="security" type="asm.v2:securityType"/>
    <xs:element ref="asm.v3:asmv3" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
```

2.2.2.3.12 securityType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [trustInfoType](#)

The **securityType** complex type elements specifies the permissions requested by a deployment package.

Child Elements:

applicationRequestMinimum : An [applicationRequestMinimumType](#) element that specifies permissions requested by the deployment package.

requestedPrivileges : A [requestedPrivilegesType](#) element that specifies a reserved value.

asmv3 : An [asmv3](#) element that specifies ignored data.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="securityType">
  <xs:sequence>
    <xs:element name="applicationRequestMinimum"
      type="asm.v2:applicationRequestMinimumType"/>
    <xs:element name="requestedPrivileges" type="asm.v3:requestedPrivilegesType"/>
    <xs:element ref="asm.v3:asmv3" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
```

```
</xs:sequence>
</xs:complexType>
```

2.2.2.3.13 applicationRequestMinimumType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [securityType](#)

The **applicationRequestMinimumType** complex type specifies permissions requested by a deployment package.

Child Elements:

PermissionSet : A [PermissionSetType](#) element that specifies a **code access security permission set**.

defaultAssemblyRequest : A [defaultAssemblyRequestType](#) element that specifies the default code access security permission set requested by the deployment package.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="applicationRequestMinimumType">
  <xs:sequence>
    <xs:element name="PermissionSet" type="asm.v2:PermissionSetType"/>
    <xs:element name="defaultAssemblyRequest" type="asm.v2:defaultAssemblyRequestType"/>
  </xs:sequence>
</xs:complexType>
```

2.2.2.3.14 PermissionSetType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [applicationRequestMinimumType](#)

The **PermissionSetType** complex type specifies a code access security permission set.

Attributes:

ID : An ID ([W3C-XSD](#) section 3.3.8) attribute that specifies the identifier. MUST be "Custom".

Unrestricted : A boolean ([W3C-XSD](#) section 3.2.2) attribute that specifies the code access security permission set has no restrictions.

SameSite : A string ([W3C-XSD](#) section 3.2.1) attribute that specifies ignored data.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="PermissionSetType">
  <xs:attribute name="ID" type="xs:ID" use="required"/>
  <xs:attribute name="Unrestricted" type="xs:boolean" use="required" fixed="true"/>
  <xs:attribute name="SameSite" type="xs:string" use="required" fixed="site"/>
```

```
</xs:complexType>
```

2.2.2.3.15 defaultAssemblyRequestType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [applicationRequestMinimumType](#)

The **defaultAssemblyRequestType** complex type specifies a default code access security permission set requested by a deployment package.

Attributes:

permissionSetReference : An IDREF ([\[W3C-XSD\]](#) section 3.3.10) attribute that specifies a default set of permissions. MUST be "Custom".

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="defaultAssemblyRequestType">
  <xs:attribute name="permissionSetReference" type="xs:IDREF"/>
</xs:complexType>
```

2.2.2.3.16 fileType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [file](#)

The **fileType** complex type specifies a package file.

Child Elements:

hash : A [hashType](#) element that specifies the hash of the file.

Attributes:

name : A (string [\[W3C-XSD\]](#) section 3.2.1) attribute that specifies the name.

size : An (unsignedLong [\[W3C-XSD\]](#) section 3.3.21) attribute that specifies the file size in bytes.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="fileType">
  <xs:choice minOccurs="0" maxOccurs="unbounded">
    <xs:element name="hash" type="asm.v2:hashType"/>
  </xs:choice>
  <xs:attribute name="name" type="xs:string" use="required"/>
  <xs:attribute name="size" type="xs:unsignedLong" use="required"/>
</xs:complexType>
```

2.2.2.4 Simple Types

2.2.2.4.1 TwoByteVersion

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [osType](#)

The **TwoByteVersion** simple type specifies a version.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this simple type.

```
<xs:simpleType name="TwoByteVersion">
  <xs:restriction base="xs:integer">
    <xs:minInclusive value="0"/>
    <xs:maxInclusive value="65535"/>
  </xs:restriction>
</xs:simpleType>
```

2.2.2.4.2 OneByteVersion

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [osType](#)

The **OneByteVersion** simple type specifies a version.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this simple type.

```
<xs:simpleType name="OneByteVersion">
  <xs:restriction base="xs:integer">
    <xs:minInclusive value="0"/>
    <xs:maxInclusive value="255"/>
  </xs:restriction>
</xs:simpleType>
```

2.2.2.4.3 dependencyTypeType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [dependentAssemblyType](#)

The **dependencyTypeType** simple type specifies the type of a dependency.

Value	Meaning
preRequisite	Specifies the assembly is not a part of the deployment package.
install	Specifies the assembly is a part of the deployment package.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this simple type.

```

<xs:simpleType name="dependencyTypeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="preRequisite"/>
    <xs:enumeration value="install"/>
  </xs:restriction>
</xs:simpleType>

```

2.2.2.4.4 fileNameStringType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [assemblyIdentityType](#)

The **fileNameStringType** simple type specifies a string for a file name.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this simple type.

```

<xs:simpleType name="fileNameStringType">
  <xs:restriction base="xs:string">
    <xs:pattern value="([\u0020] | [\u0021] | [\u0024] | [\u0025] | [\u0027-\u0029] | [\u002B-
\u002E] | [\u0030-\u0039] | [\u003B] | [\u003D] | [\u0040-\u005B] | [\u005D-\u007B] | [\u007D-
\uFFFD] | [\u10000-\u10FFFF]) *"/>
  </xs:restriction>
</xs:simpleType>

```

2.2.2.4.5 fourPartVersionType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [assemblyIdentityType](#)

The **fourPartVersionType** simple type specifies a version.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this simple type.

```

<xs:simpleType name="fourPartVersionType">
  <xs:restriction base="xs:string">
    <xs:pattern value="(0*[0-9]{1,4})|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-
9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4})|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-
4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4})|0*[1-5][0-9]{4}|0*6[0-4][0-
9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4})|0*[1-5][0-9]{4}|0*6[0-
4][0-9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])"/>
  </xs:restriction>
</xs:simpleType>

```

2.2.2.4.6 publicKeyTokenType

Target namespace: urn:schemas-microsoft-com:asm.v2

Referenced by: [assemblyIdentityType](#)

The **publicKeyTokenType** simple type specifies the last 8 bytes of the SHA-1 hash as specified by [\[FIPS180-2\]](#) section 6.1 of a public key in accordance with section [2.5.2.1](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this simple type.

```
<xs:simpleType name="publicKeyTokenType">
  <xs:restriction base="xs:string">
    <xs:pattern value="([0-9]|[a-f]|[A-F])\{16\}" />
  </xs:restriction>
</xs:simpleType>
```

2.2.3 Target namespace: urn:schemas-microsoft-com:asm.v3

2.2.3.1 Global Elements

2.2.3.1.1 asmv3

Target namespace: urn:schemas-microsoft-com:asm.v3

An [asmv3Type](#) element that specifies a global element that is referenced by [trustInfoType](#), [securityType](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this element.

```
<xs:element name="asmv3" type="asm.v3:asmv3Type"/>
```

2.2.3.2 Global Attributes

None.

2.2.3.3 Complex Types

2.2.3.3.1 requestedPrivilegesType

Target namespace: urn:schemas-microsoft-com:asm.v3

The **RequestedPrivilegesType** complex type specifies a reserved value.

Child Elements:

requestedExecutionLevel : A [requestedExecutionLevelType](#) element that specifies a reserved value.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="requestedPrivilegesType">
  <xs:sequence>
    <xs:element name="requestedExecutionLevel" type="asm.v3:requestedExecutionLevelType" />
  </xs:sequence>
</xs:complexType>
```

2.2.3.3.2 requestedExecutionLevelType

Target namespace: urn:schemas-microsoft-com:asm.v3

Referenced by: [requestedPrivilegesType](#)

The **requestedExecutionLevelType** complex type specifies a reserved value.

Attributes:

level : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies a reserved value.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="requestedExecutionLevelType">
  <xs:attribute name="level" type="xs:string" use="required" fixed="asInvoker"/>
</xs:complexType>
```

2.2.3.3 asmv3Type

Target namespace: urn:schemas-microsoft-com:asm.v3

Referenced by: [asmv3](#)

The **asmv3Type** complex type specifies ignored data.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="asmv3Type">
  <xs:sequence>
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any" processContents="skip"/>
  </xs:sequence>
</xs:complexType>
```

2.2.3.4 Simple Types

None.

2.2.4 Target namespace: urn:schemas-microsoft-com:clickonce.v1

2.2.4.1 Global Elements

2.2.4.1.1 customHostSpecified

Target namespace: urn:schemas-microsoft-com:clickonce.v1

A [customHostSpecifiedType](#) element that specifies a global element that is referenced by [entryPointType](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this element.

```
<xs:element name="customHostSpecified" type="co.v1:customHostSpecifiedType"/>
```

2.2.4.2 Global Attributes

None.

2.2.4.3 Complex Types

2.2.4.3.1 customHostSpecifiedType

Target namespace: urn:schemas-microsoft-com:clickonce.v1

Referenced by: [customHostSpecified](#)

The **customHostSpecifiedType** element specifies that entry points are defined in an [addInType](#) element.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="customHostSpecifiedType"/>
```

2.2.4.4 Simple Types

None.

2.2.5 Target namespace: urn:schemas-microsoft-com:vsta.v3

2.2.5.1 Global Elements

2.2.5.1.1 addIn

Target namespace: urn:schemas-microsoft-com:vsta.v3

An [addInType](#) element that specifies a global element that is referenced by [assemblyType](#).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this element.

```
<xs:element name="addIn" type="vsta.v3:addInType"/>
```

2.2.5.2 Global Attributes

None.

2.2.5.3 Complex Types

2.2.5.3.1 addInType

Target namespace: urn:schemas-microsoft-com:vsta.v3

Referenced by: [addIn](#)

The **addInType** complex type specifies run-time behavior of the deployment package.

Child Elements:

entryPointsCollection : An [entryPointsCollectionType](#) element that specifies the container for [entryPointsType](#) elements.

update : An [updateType](#) element that specifies the update behavior for the deployment package.

postActions : A [postActionsType](#) element that contains the list of [postActionType](#) elements.

application : An [applicationType](#) element that contains a [customizationsType](#) element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="addInType">
  <xs:sequence>
    <xs:element name="entryPointsCollection" type="vsta.v3:entryPointsCollectionType"
      minOccurs="1" maxOccurs="1"/>
    <xs:element name="update" type="vsta.v3:updateType" maxOccurs="1" minOccurs="1"/>
    <xs:element name="postActions" type="vsta.v3:postActionsType" maxOccurs="1"
      minOccurs="0"/>
    <xs:element name="application" type="vsta.v3:applicationType" maxOccurs="1"
      minOccurs="0"/>
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other" processContents="skip"/>
  </xs:sequence>
  <xs:anyAttribute namespace="##other" processContents="skip"/>
</xs:complexType>
```

2.2.5.3.2 entryPointsCollectionType

Target namespace: urn:schemas-microsoft-com:vsta.v3

Referenced by: [addInType](#)

The **entryPointsCollectionType** complex type specifies a container for [entryPointsType](#) elements.

Child Elements:

entryPoints : An entryPointsType element that specifies a list of [entryPointType](#) elements.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="entryPointsCollectionType">
  <xs:sequence>
    <xs:element name="entryPoints" type="vsta.v3:entryPointsType" minOccurs="1"
      maxOccurs="unbounded"/>
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other" processContents="skip"/>
  </xs:sequence>
  <xs:anyAttribute namespace="##other" processContents="skip"/>
</xs:complexType>
```

2.2.5.3.3 entryPointsType

Target namespace: urn:schemas-microsoft-com:vsta.v3

Referenced by: [entryPointsCollectionType](#)

An entryPointsType specifies a list of entry points for a customization.

Child Elements:

entryPoint : An [entryPointType](#) element that specifies an entry point for the customization.

Attributes:

id : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies the identifier of the customization. MUST be present when the structure contains more than one [customizationType](#) element. MUST match the id attribute value of a customizationType element that implements the entry points.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="entryPointsType">
  <xs:sequence>
    <xs:element name="entryPoint" type="vsta.v3:entryPointType" maxOccurs="unbounded"/>
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="#other" processContents="skip"/>
  </xs:sequence>
  <xs:attribute name="id" type="xs:string" use="optional"/>
  <xs:anyAttribute namespace="#other" processContents="skip"/>
</xs:complexType>
```

2.2.5.3.4 entryPointType

Target namespace: urn:schemas-microsoft-com:vsta.v3

Referenced by: [entryPointsType](#)

The **entryPointType** complex type specifies an entry point for a customization.

Child Elements:

assemblyIdentity : An [assemblyIdentity](#) element that specifies the identity of the assembly that implements the entry point for the customization.

Attributes:

class : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies the entry point. MUST be a **fully qualified class name**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="entryPointType" mixed="true">
  <xs:sequence minOccurs="1" maxOccurs="1">
    <xs:element ref="asm.v2:assemblyIdentity"/>
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="#other" processContents="skip"/>
  </xs:sequence>
  <xs:attribute name="class" type="xs:string" use="required"/>
```

```
<xs:anyAttribute namespace="##other" processContents="skip"/>
</xs:complexType>
```

2.2.5.3.5 postActionEntryPointType

Target namespace: urn:schemas-microsoft-com:vsta.v3

Referenced by: [postActionType](#)

The **postActionEntryPointType** complex type specifies an entry point for a deployment package **post-deployment action**.

Child Elements:

assemblyIdentity : A [assemblyIdentity](#) element that specifies the identity of the assembly that implements the post-deployment action entry point for the deployment package.

Attributes:

class : A string [\[W3C-XSD\]](#) section 3.2.1 attribute that specifies an entry point class. MUST be a fully qualified class name.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="postActionEntryPointType" mixed="true">
  <xs:sequence minOccurs="1" maxOccurs="1">
    <xs:element ref="asm.v2:assemblyIdentity"/>
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other" processContents="skip"/>
  </xs:sequence>
  <xs:attribute name="class" type="xs:string" use="required"/>
  <xs:anyAttribute namespace="##other" processContents="skip"/>
</xs:complexType>
```

2.2.5.3.6 updateType

Target namespace: urn:schemas-microsoft-com:vsta.v3

Referenced by: [addInType](#)

The **updateType** complex type specifies an update behavior for a deployment package.

Attributes:

enabled : A boolean ([\[W3C-XSD\]](#) section 3.2.2) attribute that specifies automatic checks for updates.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="updateType">
  <xs:sequence>
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other" processContents="skip"/>
  </xs:sequence>
  <xs:attribute name="enabled" type="xs:boolean" use="required" fixed="false"/>
```

```
<xs:anyAttribute namespace="##other" processContents="skip"/>
</xs:complexType>
```

2.2.5.3.7 postActionsType

Target namespace: urn:schemas-microsoft-com:vsta.v3

Referenced by: [addInType](#)

The **postActionsType** type specifies a list of post-deployment actions for the deployment package.

Child Elements:

postAction : A [postActionType](#) element that specifies a post-deployment action.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="postActionsType">
  <xs:sequence>
    <xs:element name="postAction" type="vsta.v3:postActionType" maxOccurs="unbounded"
      minOccurs="0"/>
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other" processContents="skip"/>
  </xs:sequence>
  <xs:anyAttribute namespace="##other" processContents="skip"/>
</xs:complexType>
```

2.2.5.3.8 postActionType

Target namespace: urn:schemas-microsoft-com:vsta.v3

Referenced by: [postActionsType](#)

The **postActionType** complex type specifies a post-deployment action.

Child Elements:

entryPoint : An [entryPointType](#) element that specifies the entry point for the post-deployment action.

postActionData : A [postActionDataType](#) element that specifies the input data for the post-deployment action.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="postActionType">
  <xs:sequence>
    <xs:element name="entryPoint" type="vsta.v3:postActionEntryPointType" maxOccurs="1"
      minOccurs="1"/>
    <xs:element name="postActionData" type="vsta.v3:postActionDataType" maxOccurs="1"
      minOccurs="0"/>
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other" processContents="skip"/>
  </xs:sequence>
  <xs:anyAttribute namespace="##other" processContents="skip"/>
</xs:complexType>
```

```
</xs:complexType>
```

2.2.5.3.9 postActionDataType

Target namespace: urn:schemas-microsoft-com:vsta.v3

Referenced by: [post ActionType](#)

The **postActionDataType** complex type specifies input data for the post-deployment action.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="postActionDataType">
  <xs:sequence>
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="#other" processContents="skip"/>
  </xs:sequence>
  <xs:anyAttribute namespace="#other" processContents="skip"/>
</xs:complexType>
```

2.2.5.3.10 applicationType

Target namespace: urn:schemas-microsoft-com:vsta.v3

Referenced by: [addInType](#)

The **applicationType** complex type specifies a container for a [customizationsType](#) element.

Child Elements:

customizations : A [customizations](#) element that specifies a list of customizations in the deployment package.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="applicationType">
  <xs:sequence>
    <xs:element ref="vsto.v4:customizations"/>
  </xs:sequence>
</xs:complexType>
```

2.2.5.4 Simple Types

None.

2.2.6 Target namespace: urn:schemas-microsoft-com:vsto.v4

2.2.6.1 Global Elements

2.2.6.1.1 customizations

Target namespace: urn:schemas-microsoft-com:vsto.v4

45 / 109

[MS-OSCO] — v20101219
Office Server ClickOnce Manifest Structure Specification

Copyright © 2010 Microsoft Corporation.

Release: Sunday, December 19, 2010

A [customizationsType](#) element that specifies a global element that is referenced by [applicationType](#).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this element.

```
<xs:element name="customizations" type="vsto.v4:customizationsType"/>
```

2.2.6.2 Global Attributes

None.

2.2.6.3 Complex Types

2.2.6.3.1 customizationsType

Target namespace: urn:schemas-microsoft-com:vsto.v4

Referenced by: [customizations](#)

Contains a list of [customizationType](#) elements.

Child Elements:

customization : A customizationType element that specifies the customization.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="customizationsType">
  <xs:sequence>
    <xs:element name="customization" type="vsto.v4:customizationType" minOccurs="1"
maxOccurs="unbounded"/>
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other" processContents="skip"/>
  </xs:sequence>
  <xs:anyAttribute namespace="##other" processContents="skip"/>
</xs:complexType>
```

2.2.6.3.2 customizationType

Target namespace: urn:schemas-microsoft-com:vsto.v4

Referenced by: [customizationsType](#)

Specifies a customization.

Child Elements:

appAddIn : An [appAddInType](#) element that specifies the customization is an **add-in**.

Attributes:

id : A string ([W3C-XSD](#) section 3.2.1) attribute that specifies the identifier of the customization. MUST be unique within the scope of the parent customizationsType element. MUST be present when the structure contains more than one customizationType element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="customizationType">
  <xs:sequence>
    <xs:choice minOccurs="1" maxOccurs="1">
      <xs:element name="appAddIn" type="vsto.v4:appAddInType"/>
    </xs:choice>
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other" processContents="skip"/>
  </xs:sequence>
  <xs:attribute name="id" type="xs:string" use="optional"/>
  <xs:anyAttribute namespace="##other" processContents="skip"/>
</xs:complexType>
```

2.2.6.3.3 appAddInType

Target namespace: urn:schemas-microsoft-com:vsto.v4

Referenced by: [customizationType](#)

Specifies the installation values of an add-in.

Child Elements:

friendlyName : A string ([\[W3C-XSD\]](#) section 3.2.1) element that specifies the user-displayable name. The length of the string value MUST be less than 261 characters.

description : A string ([\[W3C-XSD\]](#) section 3.2.1) element that specifies the user-displayable description. The length of the string value MUST be less than 32,768 characters.

Attributes:

application : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies the customized application.

loadBehavior : A [loadBehaviorType](#) attribute that specifies the initial startup setting of the add-in.

keyName : A [keyStringType](#) attribute that specifies the name for storing and retrieving the installation values post installation. The length of the string value MUST be less than 215 characters. The length of the string value MUST be greater than zero characters.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment defines the contents of this complex type.

```
<xs:complexType name="appAddInType">
  <xs:sequence>
    <xs:element name="friendlyName" type="xs:string" maxOccurs="1" minOccurs="1"/>
    <xs:element name="description" type="xs:string" maxOccurs="1" minOccurs="0"/>
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other" processContents="skip"/>
  </xs:sequence>
  <xs:attribute name="application" type="xs:string" use="required" fixed="Outlook"/>
  <xs:attribute name="loadBehavior" type="vsto.v4:loadBehaviorType" use="optional"/>
  <xs:attribute name="keyName" type="vsto.v4:keyStringType" use="required"/>
  <xs:anyAttribute namespace="##other" processContents="skip"/>
</xs:complexType>
```

2.2.6.4 Simple Types

2.2.6.4.1 loadBehaviorType

Target namespace: urn:schemas-microsoft-com:vsto.v4

Referenced by: [appAddInType](#)

Specifies the initial start up setting of an add-in.

Value	Meaning
2	Specifies that the add-in is disabled.
3	Specifies that the add-in is configured to run on startup of the customized application.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this simple type.

```
<xs:simpleType name="loadBehaviorType">
  <xs:restriction base="xs:int">
    <xs:enumeration value="2"/>
    <xs:enumeration value="3"/>
  </xs:restriction>
</xs:simpleType>
```

2.2.6.4.2 keyStringType

Target namespace: urn:schemas-microsoft-com:vsto.v4

Referenced by: [appAddInType](#)

The **keyStringType** simple type specifies a string for a key name.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment defines the contents of this simple type.

```
<xs:simpleType name="keyStringType">
  <xs:restriction base="xs:string">
    <xs:pattern value="(\u0020|\u0021|[\u0023-\u0029]|\u002B-\u0039|\u003B|\u003D|\u0040-
\u005B|\u005D-\u007B]|\u007D-\uD7FF|[\uE000-\uFFFD]|\u10000-\u10FFFF)*"/>
  </xs:restriction>
</xs:simpleType>
```

2.3 Strong Name Signature

A strong name signature is a method to uniquely identify a manifest by using public key cryptography. The manifest MUST have the following criteria:

- The manifest file MUST be signed as specified in this section.
- The public key used to verify the strong name signature MUST be the same as the key used to generate the publicKeyToken attribute on the assemblyIdentity element (section [2.1.1.3.1](#) and section [2.2.1.3.1](#)) in accordance with section [2.5.2.1](#).

This section describes the profile of the XML Digital Signatures standard [\[XMLDSig\]](#) used by manifest signatures (section [2.1.1.3.3](#) and section [2.2.1.3.2](#)).

2.3.1 Target namespace: <http://www.w3.org/2000/09/xmldsig#>

2.3.1.1 Global Elements

2.3.1.1.1 Signature

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

A [SignatureType](#) element that is specified as a global element in [\[XMLDSig\]](#). This Signature element is referenced by assemblyType (section [2.1.1.3.3](#) and section [2.2.1.3.2](#)).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="Signature" type="ds:SignatureType" xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.3.1.1.2 SignatureValue

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignatureType](#)

A [SignatureValueType](#) element that is specified as a global element in [\[XMLDSig\]](#). This SignatureValue element is referenced by SignatureType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="SignatureValue" type="ds:SignatureValueType"
  xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.3.1.1.3 SignedInfo

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignatureType](#)

A [SignedInfoType](#) element that is specified as a global element in [\[XMLDSig\]](#). This SignedInfoType element is referenced by SignatureType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="SignedInfo" type="ds:SignedInfoType"
  xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.3.1.1.4 CanonicalizationMethod

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignedInfoType](#)

A [CanonicalizationMethodType](#) element that is specified as a global element in [\[XMLDSig\]](#). This CanonicalizationMethod element is referenced by SignedInfoType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="CanonicalizationMethod" type="ds:CanonicalizationMethodType"
  xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.3.1.1.5 SignatureMethod

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignedInfoType](#)

A [SignatureMethodType](#) element that is specified as a global element in [\[XMLDSig\]](#). This SignatureMethod element is referenced by SignedInfoType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="SignatureMethod" type="ds:SignatureMethodType"
  xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.3.1.1.6 Reference

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignedInfoType](#)

A [ReferenceType](#) element that is specified as a global element in [\[XMLDSig\]](#). This Reference element is referenced by SignedInfoType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="Reference" type="ds:ReferenceType" xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.3.1.1.7 Transforms

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [ReferenceType](#)

A [TransformsType](#) element that is specified as a global element in [\[XMLDSig\]](#). This Transforms element is referenced by ReferenceType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="Transforms" type="ds:TransformsType"
xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.3.1.8 Transform

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [TransformsType](#)

A [TransformType](#) element that is specified as a global element in [\[XMLDSig\]](#). This Transform element is referenced by [TransformsType](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="Transform" type="ds:TransformType" xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.3.1.9 DigestMethod

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [ReferenceType](#)

A [DigestMethodType](#) element that is specified as a global element in [\[XMLDSig\]](#). This DigestMethod element is referenced by [ReferenceType](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="DigestMethod" type="ds:DigestMethodType"
xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.3.1.10 DigestValue

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [ReferenceType](#)

A [DigestValueType](#) element that is specified as a global element in [\[XMLDSig\]](#). This DigestValue element is referenced by [ReferenceType](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="DigestValue" type="ds:DigestValueType"
xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.3.1.11 KeyInfo

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignatureType](#)

A [KeyInfoType](#) element that is specified as a global element in [\[XMLDSig\]](#). This KeyInfo element is referenced by SignatureType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="KeyInfo" type="ds:KeyInfoType" xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.3.1.1.12 KeyValue

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [KeyInfoType](#)

A [KeyValue](#) element that is specified as a global element in [\[XMLDSig\]](#). This KeyValue element is referenced by KeyInfoType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="KeyValue" type="ds:KeyValue" xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.3.1.1.13 RSAKeyValue

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [KeyValue](#)

A [RSAKeyValue](#) element that is specified as a global element in [\[XMLDSig\]](#). This RSAKeyValue element is referenced by KeyValue.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="RSAKeyValue" type="ds:RSAKeyValue" xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.3.1.2 Global Attributes

None.

2.3.1.3 Complex Types

2.3.1.3.1 SignatureType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [Signature](#)

SignatureType specifies the information that is necessary to verify the integrity of a **digital signature**.

Child Elements:

ds:SignedInfo : A [SignedInfoType](#) element that specifies the information necessary to compute the hash of the manifest.

ds:SignatureValue : A [SignatureValueType](#) element that specifies the encoded value of the signature.

ds:KeyInfo : A [KeyInfoType](#) element that specifies the public key to be used to verify the signature.

Attributes:

Id : An ID ([\[W3C-XSD\]](#) section 3.2.8) attribute. The value of the Id attribute MUST be "StrongNameSignature".

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="SignatureType" xmlns="http://www.w3.org/2001/XMLSchema">
  <sequence>
    <element ref="ds:SignedInfo"/>
    <element ref="ds:SignatureValue"/>
    <element ref="ds:KeyInfo"/>
  </sequence>
  <attribute name="Id" type="ID" use="optional"/>
</complexType>
```

2.3.1.3.2 SignatureValueType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignatureType](#), [SignatureValue](#)

The **SignatureValueType** complex type specifies the encoded value of the signature. The content of the SignatureValueType is defined in section 4.2 of [\[XMLDSig\]](#). All attributes of SignatureValueType are optional and are ignored.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="SignatureValueType" xmlns="http://www.w3.org/2001/XMLSchema">
  <simpleContent>
    <extension base="base64Binary"/>
  </simpleContent>
</complexType>
```

2.3.1.3.3 SignedInfoType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignatureType](#), [SignedInfo](#)

The **SignedInfoType** complex type specifies the information necessary to compute the hash of the manifest. The content of the SignedInfoType is defined in section 4.3 of [\[XMLDSig\]](#).

Child Elements:

ds:CanonicalizationMethod : A [CanonicalizationMethodType](#) element that specifies the canonicalization algorithm to be applied when the digital signature is verified.

ds:SignatureMethod : A [SignatureMethodType](#) element that specifies the digital signature algorithm to be used when the digital signature is verified.

ds:Reference : A [ReferenceType](#) element that specifies the XML node-set to be verified.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="SignedInfoType" xmlns="http://www.w3.org/2001/XMLSchema">
  <sequence>
    <element ref="ds:CanonicalizationMethod"/>
    <element ref="ds:SignatureMethod"/>
    <element ref="ds:Reference"/>
  </sequence>
</complexType>
```

2.3.1.3.4 CanonicalizationMethodType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignedInfoType](#), [CanonicalizationMethod](#)

The **CanonicalizationMethodType** complex type specifies the canonicalization algorithm that is applied to the SignedInfo element prior to computing the hash. The content of the CanonicalizationMethodType is defined in section 4.3.1 of [XMLDSig](#).

All child elements of CanonicalizationMethodType are optional and ignored.

Attributes:

Algorithm : An anyURI ([W3C-XSD](#) section 3.2.17) attribute that specifies the canonicalization algorithm. The canonicalization algorithm MUST be Exclusive XML CanonicalizationVersion 1.0 ([Excl-C14N](#)). The value of the Algorithm attribute MUST be "http://www.w3.org/2001/10/xml-exc-c14n#".

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="CanonicalizationMethodType" xmlns="http://www.w3.org/2001/XMLSchema">
  <attribute name="Algorithm" type="anyURI" use="required"/>
</complexType>
```

2.3.1.3.5 SignatureMethodType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignedInfoType](#), [SignatureMethod](#)

The **SignatureMethodType** complex type specifies the information necessary to compute the hash of the manifest. The content of the SignatureMethodType is defined in section 4.3.2 of [XMLDSig](#).

All child elements of SignatureMethodType are optional and are ignored.

Attributes:

Algorithm : An anyURI ([W3C-XSD] section 3.2.17) attribute that specifies the digital signature algorithm. The digital signature algorithm MUST be RSA with SHA-1 ([\[XMLDSig\]](#) section 6.4.2). The value of the Algorithm attribute MUST be "http://www.w3.org/2000/09/xmldsig#rsa-sha1".

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="SignatureMethodType" xmlns="http://www.w3.org/2001/XMLSchema">
  <attribute name="Algorithm" type="anyURI" use="required"/>
</complexType>
```

2.3.1.3.6 ReferenceType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignedInfoType](#), [Reference](#)

The **ReferenceType** complex type specifies the information necessary to compute the **digest** of the manifest. The content of the ReferenceType is defined in section 4.3.3 of [\[XMLDSig\]](#).

Child Elements:

ds:Transforms : A [TransformsType](#) element that specifies the transforms to be applied to the manifest when verifying the digital signature.

ds:DigestMethod : A [DigestMethodType](#) element that specifies the hashing algorithm to be applied to the manifest when the digital signature is verified.

ds:DigestValue : A [DigestValueType](#) element that specifies the encoded value of the digest.

Attributes:

URI : An anyURI ([W3C-XSD] section 3.2.17) attribute that specifies the node-set that contains the signature. The value of the URI attribute must be an empty string.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="ReferenceType" xmlns="http://www.w3.org/2001/XMLSchema">
  <sequence>
    <element ref="ds:Transforms"/>
    <element ref="ds:DigestMethod"/>
    <element ref="ds:DigestValue"/>
  </sequence>
  <attribute name="URI" type="anyURI" use="required"/>
</complexType>
```

2.3.1.3.7 TransformsType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [ReferenceType](#), [Transforms](#)

The **TransformsType** complex type specifies the information to describe how the signer obtained the data object that was digested. The content of the TransformsType is defined in section 4.3.3.4 of [\[XMLDSig\]](#).

Child Elements:

ds:Transform : A [TransformType](#) element that specifies the Enveloped Signature Transform ([\[XMLDSig\]](#) section 6.6.4). The value of the Algorithm attribute MUST be "http://www.w3.org/2000/09/xmldsig#enveloped-signature".

ds:Transform : A [TransformType](#) element that specifies the Exclusive XML CanonicalizationVersion 1.0 ([\[Excl-C14N\]](#)). The value of the Algorithm attribute MUST be "http://www.w3.org/2001/10/xml-exc-c14n#".

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="TransformsType" xmlns="http://www.w3.org/2001/XMLSchema">
  <sequence>
    <element ref="ds:Transform" maxOccurs="unbounded"/>
  </sequence>
</complexType>
```

2.3.1.3.8 TransformType

Target namespace: http://www.w3.org/2000/09/xmldsig#

Referenced by: [TransformsType](#), [Transform](#)

The **TransformType** complex type specifies the information to describe how the signer obtained the data object that was digested. The content of the TransformType is defined in section 4.3.3.4 of [\[XMLDSig\]](#).

Attributes:

Algorithm : An anyURI ([\[W3C-XSD\]](#) section 3.2.17) attribute that specifies a transform algorithm.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="TransformType" mixed="true" xmlns="http://www.w3.org/2001/XMLSchema">
  <attribute name="Algorithm" type="anyURI" use="required"/>
</complexType>
```

2.3.1.3.9 DigestMethodType

Target namespace: http://www.w3.org/2000/09/xmldsig#

Referenced by: [ReferenceType](#), [DigestMethod](#)

The **DigestMethodType** complex type specifies the digest algorithm to be applied to the manifest when the digital signature is verified. The content of the DigestMethodType is defined in section 4.3.3.5 of [\[XMLDSig\]](#).

Attributes:

Algorithm : An anyURI ([\[W3C-XSD\]](#) section 3.2.17) attribute that specifies the digest algorithm. The digest algorithm MUST be SHA-1 ([\[FIPS180-2\]](#)). The value of the Algorithm attribute MUST be "http://www.w3.org/2000/09/xmldsig#sha1" ([\[XMLDSig\]](#) section 6.2.1).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="DigestMethodType" mixed="true" xmlns="http://www.w3.org/2001/XMLSchema">
    <attribute name="Algorithm" type="anyURI" use="required"/>
</complexType>
```

2.3.1.3.10 KeyInfoType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignatureType](#), [KeyInfo](#)

The **KeyInfoType** complex type specifies the information about the public key to be used to verify the signature. The content of the KeyInfoType is defined in section 4.4 of [\[XMLDSig\]](#).

Child Elements:

ds:KeyValue : A [KeyValue](#) element that contains the public key to be used to verify the signature.

msrel:RelData : A [RelData](#) element that specifies information about the software publisher. This element MUST be present.

Attributes:

Id : An ID ([\[W3C-XSD\]](#) section 3.2.1) attribute that identifies a KeyInfo element to contain information about a **strong name** public key. The value of Id attribute MUST be "StrongNameKeyInfo".

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="KeyInfoType" xmlns="http://www.w3.org/2001/XMLSchema">
    <sequence>
        <element ref="ds:KeyValue"/>
        <element ref="msrel:RelData"/>
    </sequence>
    <attribute name="Id" type="ID" use="optional"/>
</complexType>
```

2.3.1.3.11 KeyValue

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [KeyInfo](#), [KeyValue](#)

The **KeyValue** complex type specifies the public key component of the key used to generate the strong name.

Child Elements:

ds:RSAKeyValue : A [RSAKeyType](#) element that specifies the modulus and exponent of an RSA public key ([\[RFC3447\]](#) section 3.1).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="KeyValueType" xmlns="http://www.w3.org/2001/XMLSchema">
  <sequence>
    <element ref="ds:RSAKeyValue"/>
  </sequence>
</complexType>
```

2.3.1.3.12 RSAKeyType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [KeyValuePair](#), [RSAKeyValue](#)

The **RSAKeyType** complex type specifies the modulus and exponent of an RSA public key ([\[RFC3447\]](#) section 3.1). The content of the RSAKeyType is defined in section 4.4.2.2 of [\[XMLDSig\]](#).

Child Elements:

Modulus : A [CryptoBinary](#) element that specifies the modulus of an RSA public key ([\[RFC3447\]](#) section 3.1).

Exponent : A CryptoBinary element that specifies the exponent of an RSA public key ([\[RFC3447\]](#) section 3.1).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="RSAKeyValue" xmlns="http://www.w3.org/2001/XMLSchema">
  <sequence>
    <element name="Modulus" type="ds: CryptoBinary" />
    <element name="Exponent" type="ds: CryptoBinary" />
  </sequence>
</complexType>
```

2.3.1.4 Simple Types

2.3.1.4.1 CryptoBinary

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [RSAKeyValue](#)

The **CryptoBinary** simple type as specified in section 4.0.1 of [\[XMLDSig\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<simpleType name="CryptoBinary" xmlns="http://www.w3.org/2001/XMLSchema">
  <restriction base="base64Binary" />
```

```
</simpleType>
```

2.3.1.4.2 DigestValueType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [ReferenceType](#), [DigestValue](#)

The **DigestValueType** simple type specifies the encoded value of the digest. The content of the DigestMethodType is defined in section 4.3.3.6 of [\[XMLDSig\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<simpleType name="DigestValueType" xmlns="http://www.w3.org/2001/XMLSchema">
  <restriction base="base64Binary"/>
</simpleType>
```

2.3.2 Target namespace:

<http://schemas.microsoft.com/windows/rel/2005/reldata>

2.3.2.1 Global Elements

2.3.2.1.1 RelData

Target namespace: <http://schemas.microsoft.com/windows/rel/2005/reldata>

A [RelDataType](#) element that specifies a global element that is referenced by [KeyInfoType](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsi:element name="RelData" type="RelDataType"/>
```

2.3.2.2 Global Attributes

None.

2.3.2.3 Complex Types

2.3.2.3.1 RelDataType

Target namespace: <http://schemas.microsoft.com/windows/rel/2005/reldata>

Referenced by: [RelData](#)

The **RelDataType** complex type specifies a container for a Rights Expression Language [\[ISO/IEC-21000-5\]](#) license that describes a software publisher.

Child Elements:

r:license : A [License](#) element that specifies publisher expressed using the Rights Expression Language [\[ISO/IEC-21000-5\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="RelDataType">
  <xs:sequence>
    <xs:element ref="r:license"/>
  </xs:sequence>
</xs:complexType>
```

2.3.2.4 Simple Types

None.

2.4 Software Publisher Signature

2.4.1 Target namespace: urn:mpeg:mpeg21:2003:01-REL-R-NS

2.4.1.1 Global Elements

2.4.1.1.1 license

Target namespace: urn:mpeg:mpeg21:2003:01-REL-R-NS

A [License](#) element that specifies a global element that is referenced by [RelDataType](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="license" type="r:License"/>
```

2.4.1.2 Global Attributes

None.

2.4.1.3 Complex Types

2.4.1.3.1 License

Target namespace: urn:mpeg:mpeg21:2003:01-REL-R-NS

Referenced by: [license](#)

The **License** complex type specifies a description of a software publisher expressed using the Rights Expression Language [\[ISO/IEC-21000-5\]](#).

All attributes of License are optional and are ignored.

Child Elements:

grant : A [Grant](#) element that specifies a manifest to have the right to be signed by a particular software publisher.

issuer : An [Issuer](#) element that specifies the XML digital signature ([XMLDSig](#)) of the software publisher.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="License">
  <xsd:sequence>
    <xsd:element name="grant" type="r:Grant"/>
    <xsd:element name="issuer" type="r:Issuer"/>
  </xsd:sequence>
</xsd:complexType>
```

2.4.1.3.2 Grant

Target namespace: urn:mpeg:mpeg21:2003:01-REL-R-NS

Referenced by: [License](#)

The **Grant** complex type specifies a container for description of a software publisher expressed using the Rights Expression Language [ISO/IEC-21000-5](#).

Child Elements:

as:ManifestInformation : A [ManifestInformationType](#) element that specifies a deployment manifest or an application manifest.

as:SignedBy : A [SignedByType](#) element that specifies the right for a manifest to be signed by a software publisher.

as:AuthenticodePublisher : An [AuthenticodePublisherType](#) element that specifies a software publisher.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="Grant">
  <xsd:sequence>
    <xsd:element ref="as:ManifestInformation"/>
    <xsd:element ref="as:SignedBy"/>
    <xsd:element ref="as:AuthenticodePublisher"/>
  </xsd:sequence>
</xsd:complexType>
```

2.4.1.3.3 Issuer

Target namespace: urn:mpeg:mpeg21:2003:01-REL-R-NS

Referenced by: [License](#)

The **Issuer** complex type specifies a container for a XML digital signature [XMLDSig](#).

All attributes of Issuer are optional and are ignored.

Child Elements:

dsig:Signature : A [SignatureType](#) element that specifies the necessary information to validate a signed deployment manifest or application manifest.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="Issuer">
  <xsd:sequence>
    <xsd:element ref="dsig:Signature"/>
  </xsd:sequence>
</xsd:complexType>
```

2.4.1.3.4 Right

Target namespace: urn:mpeg:mpeg21:2003:01-REL-R-NS

The **Right** complex type as specified in section 7.4.3 of [\[ISO/IEC-21000-5\]](#). Right is a conceptually abstract type and is used by this specification only as a base type for [SignedByType](#).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="Right"/>
```

2.4.1.4 Simple Types

None.

2.4.2 Target namespace:

<http://schemas.microsoft.com/windows/pki/2005/Authenticode>

2.4.2.1 Global Elements

2.4.2.1.1 ManifestInformation

Target namespace: <http://schemas.microsoft.com/windows/pki/2005/Authenticode>

A [ManifestInformationType](#) element that specifies a global element that is referenced by [Grant](#).

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment specifies the contents of this element.

```
<xss:element name="ManifestInformation" type="ManifestInformationType"/>
```

2.4.2.1.2 SignedBy

Target namespace: <http://schemas.microsoft.com/windows/pki/2005/Authenticode>

A [SignedByType](#) element that specifies a global element that is referenced by [Grant](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xs:element name="SignedBy" type="SignedByType"/>
```

2.4.2.1.3 AuthenticodePublisher

Target namespace: <http://schemas.microsoft.com/windows/pki/2005/Authenticode>

An [AuthenticodePublisherType](#) element specifies a global element that is referenced by [Grant](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xs:element name="AuthenticodePublisher" type="AuthenticodePublisherType"/>
```

2.4.2.1.4 Timestamp

Target namespace: <http://schemas.microsoft.com/windows/pki/2005/Authenticode>

A [CryptoBinary](#) element that specifies a global element that is referenced by [ObjectType](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xs:element name="Timestamp" type="ds: CryptoBinary"/>
```

2.4.2.2 Global Attributes

None.

2.4.2.3 Complex Types

2.4.2.3.1 ManifestInformationType

Target namespace: <http://schemas.microsoft.com/windows/pki/2005/Authenticode>

Referenced by: [ManifestInformation](#)

The **ManifestInformationType** complex type specifies a deployment manifest or application manifest.

Child Elements:

assemblyIdentity : An assemblyIdentityType (section [2.1.1.3.1](#) and section [2.2.1.3.1](#)) element that specifies either a deployment package or an application manifest.

Attributes:

Hash : A CryptoBinary ([\[XMLDSig\]](#) section 4.0.1) attribute that specifies the hash of the manifest that the software publisher signed.

Description : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that specifies a short description of the deployment package.

Url : An anyURI ([\[W3C-XSD\]](#) section 3.2.17) attribute that specifies a Url that a user can visit to obtain more information about the deployment package and or the software publisher.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="ManifestInformationType">
  <xs:sequence>
    <xs:element name="assemblyIdentity" type="asm.v1:assemblyIdentityType"/>
  </xs:sequence>
  <xs:attribute name="Hash" type="ds: CryptoBinary" use="required"/>
  <xs:attribute name="Description" type="xs:string" use="optional"/>
  <xs:attribute name="Url" type="xs:anyURI" use="optional"/>
</xs:complexType>
```

2.4.2.3.2 SignedByType

Target namespace: <http://schemas.microsoft.com/windows/pki/2005/Authenticode>

Referenced by: [SignedBy](#)

The **SignedByType** complex type specifies the right for a manifest to be signed by a software publisher.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="SignedByType">
  <xs:complexContent>
    <xs:restriction base="r:Right"/>
  </xs:complexContent>
</xs:complexType>
```

2.4.2.3.3 AuthenticodePublisherType

Target namespace: <http://schemas.microsoft.com/windows/pki/2005/Authenticode>

Referenced by: [AuthenticodePublisher](#)

The **AuthenticodePublisherType** complex type specifies information about a software publisher.

Child Elements:

X509SubjectName : A string ([\[W3C-XSD\]](#) section 3.2.1) element that specifies the identity of a software publisher. The string is generated by converting the Subject distinguished name of the software publisher certificate.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="AuthenticodePublisherType">
  <xs:sequence>
```

```
<xs:element name="X509SubjectName" type="xs:string"/>
</xs:sequence>
</xs:complexType>
```

2.4.2.4 Simple Types

None.

2.4.3 Target namespace: <http://www.w3.org/2000/09/xmldsig#>

2.4.3.1 Global Elements

2.4.3.1.1 Signature

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

A [SignatureType](#) element that is specified as a global element in [\[XMLDSig\]](#). This Signature element is referenced by [Issuer](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="Signature" type="ds:SignatureType" xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.4.3.1.2 SignatureValue

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignatureType](#)

A [SignatureValueType](#) that is specified as a global element in [\[XMLDSig\]](#). This SignatureValue element is referenced by SignatureType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="SignatureValue" type="ds:SignatureValueType"
xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.4.3.1.3 SignedInfo

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignatureType](#)

A [SignedInfoType](#) element that is specified as a global element in [\[XMLDSig\]](#). This SignedInfo element is referenced by SignatureType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="SignedInfo" type="ds:SignedInfoType"
xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.4.3.1.4 CanonicalizationMethod

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignedInfoType](#)

A [CanonicalizationMethodType](#) element that is specified as a global element in [\[XMLDSig\]](#). This CanonicalizationMethod element is referenced by SignedInfoType.

The following W3C XML Schema ([\[XMLSHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="CanonicalizationMethod" type="ds:CanonicalizationMethodType"
xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.4.3.1.5 SignatureMethod

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignedInfoType](#)

A [SignatureMethodType](#) element that is specified as a global element in [\[XMLDSig\]](#). This SignatureMethod element is referenced by SignedInfoType.

The following W3C XML Schema ([\[XMLSHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="SignatureMethod" type="ds:SignatureMethodType"
xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.4.3.1.6 Reference

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignedInfoType](#)

A [ReferenceType](#) element that is specified as a global element in [\[XMLDSig\]](#). This Reference element is referenced by SignedInfoType.

The following W3C XML Schema ([\[XMLSHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="Reference" type="ds:ReferenceType" xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.4.3.1.7 Transforms

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [ReferenceType](#)

A [TransformsType](#) element that is specified as a global element in [\[XMLDSig\]](#). This Transforms element is referenced by ReferenceType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="Transforms" type="ds:TransformsType"
xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.4.3.1.8 Transform

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [TransformsType](#)

A [TransformType](#) element that is specified as a global element in [\[XMLDSig\]](#). This Transform element is referenced by TransformsType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="Transform" type="ds:TransformType" xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.4.3.1.9 DigestMethod

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [ReferenceType](#)

A [DigestMethodType](#) element that is specified as a global element in [\[XMLDSig\]](#). This DigestMethod element is referenced by ReferenceType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="DigestMethod" type="ds:DigestMethodType"
xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.4.3.1.10 DigestValue

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [ReferenceType](#)

A [DigestValueType](#) element that is specified as a global element in [\[XMLDSig\]](#). This DigestValue element is referenced by ReferenceType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="DigestValue" type="ds:DigestValueType"
xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.4.3.1.11 Object

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignatureType](#)

A [ObjectType](#) element that is specified as a global element in [\[XMLDSig\]](#). This Object element is referenced by SignatureType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="Object" type="ds:ObjectType" xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.4.3.1.12 KeyInfo

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignatureType](#)

A [KeyInfoType](#) element that is specified as a global element in [\[XMLDSig\]](#). This KeyInfo element is referenced by SignatureType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="KeyInfo" type="ds:KeyInfoType" xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.4.3.1.13 KeyValue

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [KeyInfoType](#)

A [KeyValue](#) element that is specified as a global element in [\[XMLDSig\]](#). This KeyValue element is referenced by KeyInfoType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="KeyValue" type="ds:KeyValue" xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.4.3.1.14 X509Data

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [KeyInfoType](#)

A [X509Data](#) element that is specified as a global element in [\[XMLDSig\]](#). This X509Data element is referenced by KeyInfoType.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="X509Data" type="ds:X509DataType" xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.4.3.1.15 RSAKeyValue

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [KeyValue](#)

A [RSAKeyValue](#) element that is specified as a global element in [\[XMLDSig\]](#). This RSAKeyValue element is referenced by KeyValue.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<element name="RSAKeyValue" type="ds:RSAKeyValue" xmlns="http://www.w3.org/2001/XMLSchema"/>
```

2.4.3.2 Global Attributes

None.

2.4.3.3 Complex Types

2.4.3.3.1 SignatureType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [Signature](#)

The **SignatureType** complex type specifies the information that is necessary to verify the integrity of the digital signature. The content of the SignatureType is defined in section 4.1 of [\[XMLDSig\]](#).

Child Elements:

ds:SignedInfo : A [SignedInfo](#) element that specifies the information necessary to compute the digest of the manifest.

ds:SignatureValue : A [SignatureValue](#) element that specifies the encoded value of the signature.

ds:KeyInfo : A [KeyInfo](#) element that specifies the information about the public key to be used to verify the signature.

ds:Object : An [Object](#) element that specifies the **timestamp** information.

Other child elements of SignatureType are optional and are ignored.

Attributes:

Id : An ID ([W3C-XSD] section 3.2.8) attribute. The value of the Id attribute MUST be "AuthenticodeSignature".

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<complexType name="SignatureType" xmlns="http://www.w3.org/2001/XMLSchema">
  <sequence>
    <element ref="ds:SignedInfo"/>
    <element ref="ds:SignatureValue"/>
    <element ref="ds:KeyInfo"/>
    <element ref="ds:Object" minOccurs="0"/>
  </sequence>
  <attribute name="Id" type="ID" use="optional"/>
</complexType>

```

2.4.3.3.2 SignatureValueType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignatureType](#), [SignatureValue](#)

The **SignatureValueType** complex type specifies the encoded value of the signature. The content of the SignatureValueType is defined in section 4.2 of [\[XMLDSig\]](#).

The following W3C XML Schema ([\[XMLSHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<complexType name="SignatureValueType" xmlns="http://www.w3.org/2001/XMLSchema">
  <simpleContent>
    <extension base="base64Binary"/>
  </simpleContent>
</complexType>

```

2.4.3.3.3 SignedInfoType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignatureType](#), [SignedInfo](#)

The **SignedInfoType** complex type specifies the information necessary to compute the digest of the manifest. The content of the SignedInfoType is defined in section 4.3 of [\[XMLDSig\]](#).

Child Elements:

ds:CanonicalizationMethod : A [CanonicalizationMethodType](#) element that specifies the canonicalization algorithm to be applied to SignedInfo element when the digital signature is verified.

ds:SignatureMethod : A [SignatureMethodType](#) element that specifies the digital signature algorithm to be used when the digital signature is verified.

ds:Reference : A [ReferenceType](#) element that specifies the XML node-set to be verified.

The following W3C XML Schema ([\[XMLSHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<complexType name="SignedInfoType" xmlns="http://www.w3.org/2001/XMLSchema">
  <sequence>
    <element ref="ds:CanonicalizationMethod"/>
    <element ref="ds:SignatureMethod"/>
    <element ref="ds:Reference"/>
  </sequence>
</complexType>

```

```
</sequence>
</complexType>
```

2.4.3.3.4 CanonicalizationMethodType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignedInfoType](#), [CanonicalizationMethod](#)

The **CanonicalizationMethodType** complex type specifies the canonicalization algorithm that is applied to the [SignedInfo](#) element prior to computing the digest.

Attributes:

Algorithm : An anyURI ([\[W3C-XSD\]](#) section 3.2.17) attribute that specifies the canonicalization algorithm. The canonicalization algorithm MUST be Exclusive XML CanonicalizationVersion 1.0 ([\[Excl-C14N\]](#)). The value of the Algorithm attribute MUST be "http://www.w3.org/2001/10/xml-exc-c14n#"

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="CanonicalizationMethodType" xmlns="http://www.w3.org/2001/XMLSchema">
  <attribute name="Algorithm" type="anyURI" use="required"/>
</complexType>
```

2.4.3.3.5 SignatureMethodType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignedInfoType](#), [SignatureMethod](#)

The **SignatureMethodType** complex type specifies the information necessary to compute the digest of the manifest. The content of the SignatureMethodType is defined in section 4.3.2 of [\[XMLDSig\]](#).

Attributes:

Algorithm : An anyURI ([\[W3C-XSD\]](#) section 3.2.17) attribute that specifies the digital signature algorithm. The digital signature algorithm MUST be RSA with SHA-1 ([\[XMLDSig\]](#) section 6.4.2). The value of the Algorithm attribute MUST be "http://www.w3.org/2000/09/xmldsig#rsa-sha1".

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="SignatureMethodType" xmlns="http://www.w3.org/2001/XMLSchema">
  <attribute name="Algorithm" type="anyURI" use="required"/>
</complexType>
```

2.4.3.3.6 ReferenceType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignedInfoType](#), [Reference](#)

The **ReferenceType** complex type specifies the information necessary to compute the digest of the manifest. The content of the ReferenceType is defined in section 4.3.3 of [\[XMLDSig\]](#).

Child Elements:

ds:Transforms : A [TransformsType](#) element that specifies the transforms to be applied to the manifest when verifying the digital signature.

ds:DigestMethod : A [DigestMethodType](#) element that specifies the digest algorithm to be applied to the manifest when the digital signature is verified.

ds:DigestValue : A [DigestValueType](#) element that specifies the encoded value of the digest.

Attributes:

URI : An anyURI ([\[W3C-XSD\]](#) section 3.2.17) attribute that specifies the node-set that contains the signature. The value of the URI attribute MUST be an empty string.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="ReferenceType" xmlns="http://www.w3.org/2001/XMLSchema">
  <sequence>
    <element ref="ds:Transforms"/>
    <element ref="ds:DigestMethod"/>
    <element ref="ds:DigestValue"/>
  </sequence>
  <attribute name="URI" type="anyURI" use="required"/>
</complexType>
```

2.4.3.3.7 TransformsType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [ReferenceType](#), [Transforms](#)

The **TransformsType** complex type specifies the information to describe how the signer obtained the data that was digested. The content of the TransformsType is defined in section 4.3.3.4 of [\[XMLDSig\]](#).

Child Elements:

ds:Transform : A [TransformType](#) element that specifies the Enveloped Signature Transform ([\[XMLDSig\]](#) section 6.6.4). The value of the Algorithm attribute MUST be "http://www.w3.org/2000/09/xmldsig#enveloped-signature".

ds:Transform : A TransformType element that specifies the Exclusive XML CanonicalizationVersion 1.0 ([\[Excl-C14N\]](#)). The value of the Algorithm attribute MUST be "http://www.w3.org/2001/10/xml-exc-c14n#".

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="TransformsType" xmlns="http://www.w3.org/2001/XMLSchema">
  <sequence>
    <element ref="ds:Transform" maxOccurs="unbounded"/>
```

```
</sequence>
</complexType>
```

2.4.3.3.8 TransformType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [TransformsType](#), [Transform](#)

The **TransformType** complex type specifies the information to describe how the signer obtained the data object that was digested. The content of the TransformType is defined in section 4.3.3.4 of [\[XMLDSig\]](#).

Attributes:

Algorithm : An anyURI ([\[W3C-XSD\]](#) section 3.2.17) attribute that specifies a transform algorithm.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="TransformType" mixed="true" xmlns="http://www.w3.org/2001/XMLSchema">
  <attribute name="Algorithm" type="anyURI" use="required"/>
</complexType>
```

2.4.3.3.9 DigestMethodType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [ReferenceType](#), [DigestMethod](#)

The **DigestMethodType** complex type specifies the digest algorithm to be applied to the manifest when the digital signature is verified. The content of the DigestMethodType is defined in section 4.3.3.5 of [\[XMLDSig\]](#).

Attributes:

Algorithm : An anyURI ([\[W3C-XSD\]](#) section 3.2.17) attribute that specifies the digest algorithm. The digest algorithm MUST be SHA-1 [\[FIPS180-2\]](#). The value of the Algorithm attribute MUST be "http://www.w3.org/2000/09/xmldsig#sha1" ([\[XMLDSig\]](#) section 6.2.1).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="DigestMethodType" mixed="true" xmlns="http://www.w3.org/2001/XMLSchema">
  <attribute name="Algorithm" type="anyURI" use="required"/>
</complexType>
```

2.4.3.3.10 ObjectType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignatureType](#), [Object](#)

The **ObjectType** complex type as specified in section 4.5 of [\[XMLDSig\]](#).

Child Elements:

as:Timestamp : A [CryptoBinary](#) element that specifies a base 64 encoded [\[RFC2045\]](#) timestamp that SHOULD be signed by a **time stamp authority**. The timestamp is formatted as a PKCS#7 SignedData ([\[RFC2315\]](#) section 9.1) according to the following restrictions:

- The version field MUST be 1.
- The digestAlgorithms field MUST contain at least one object identifier (OID) ([\[ITUX680\]](#)) for either MD5 (1.2.840.113549.2.5) [\[RFC1321\]](#) or SHA-1 (1.3.14.3.2.26) [\[RFC3279\]](#).
- The contentInfo field MUST consists of the following:
 - The contentType field MUST be the OID 1.2.840.113549.1.7.1.
 - The content field MUST contain the signature value of the software publisher signature (e.g. the content of the [SignatureValueType](#) that is not encoded using base64 [\[RFC2045\]](#)).
- The certificates field contains the certificate chain of the time stamp authority.
- The crls field is not used and MUST be null.
- The signerInfos field MUST contain one signerInfo ([\[RFC2315\]](#) section 9.2).
 - The digestEncryptionAlgorithm field MUST contain one of the following OIDs:
 - RSA-MD5 (1.2.840.113549.1.1.4)
 - RSA-SHA-1 (1.2.840.113549.1.1.5)
 - DSA-SHA-1 (1.2.840.10040.4.3)?
 - The unauthenticatedAttributes field MUST contain the following attributes:
 - ContentType ([\[PKCS9\]](#) section 6.3): The attribute's value MUST be set to PKCS #7 Data ([\[RFC2315\]](#) section 8).
 - SigningTime ([\[PKCS9\]](#) section 6.5): The value MUST be set as specified by [\[PKCS9\]](#) section 6.5.
 - messageDigest ([\[PKCS9\]](#) section 6.4): The value MUST be set as specified by [\[PKCS9\]](#) section 6.6.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="ObjectType" xmlns="http://www.w3.org/2001/XMLSchema">
  <sequence>
    <element ref="as:Timestamp"/>
  </sequence>
</complexType>
```

2.4.3.3.11 KeyInfoType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [SignatureType](#), [KeyInfo](#)

The **KeyInfoType** complex type specifies the information about the public key to be used to verify the signature. The content of the KeyInfoType is defined in section 4.4 of [\[XMLDSig\]](#).

Child Elements:

ds:KeyValue : A [KeyValue](#) element that contains the public key to be used to verify the signature.

ds:X509Data : A [X509Data](#) element that specifies the digital certificate chain ([\[RFC3280\]](#)) of the software publisher.

Attributes:

Id : A string ([\[W3C-XSD\]](#) section 3.2.1) attribute that identifies a KeyInfo element. The Id attribute is optional and ignored.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="KeyInfoType" xmlns="http://www.w3.org/2001/XMLSchema">
  <sequence>
    <element ref="ds:KeyValue"/>
    <element ref="msrel:RelData"/>
  </sequence>
  <attribute name="Id" type="ID" use="optional"/>
</complexType>
```

2.4.3.3.12 KeyValueType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [KeyInfoType](#), [KeyValue](#)

The **KeyValueType** complex type specifies the information about the public key component of the key used to generate the strong name. The content of the KeyValueType is defined in section 4.4.2 of [\[XMLDSig\]](#).

Child Elements:

ds:RSAKeyValue : A [RSAKeyValue](#) element that specifies the modulus and exponent of an RSA public key ([\[RFC3447\]](#) section 3.1).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="KeyValueType" xmlns="http://www.w3.org/2001/XMLSchema">
  <sequence>
    <element ref="ds:RSAKeyValue"/>
  </sequence>
</complexType>
```

2.4.3.3.13 X509DataType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [KeyInfoType](#), [X509Data](#)

The **X509DataType** complex type specifies one or more digital certificates of the software publisher and the issuing certificate authority. Each digital certificate in the digital certificate chain is encoded in a separate X509Certificate child element. The content of the X509DataType is defined in section 4.4.4 of [\[XMLDSig\]](#).

Child Elements:

X509Certificate : A base64Binary ([\[W3C-XSD\]](#) section 3.2.16) element that specifies a base64 [\[RFC2045\]](#) encoded X.509 digital certificate [\[RFC3280\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="X509DataType" xmlns="http://www.w3.org/2001/XMLSchema">
  <sequence maxOccurs="unbounded">
    <element name="X509Certificate" type="base64Binary"/>
  </sequence>
</complexType>
```

2.4.3.3.14 RSAKeyValue

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [KeyValueType](#), [RSAKeyValue](#)

The **RSAKeyValue** complex type specifies the information about the modulus and exponent of an RSA public key ([\[RFC3447\]](#) section 3.1). The content of the RSAKeyValue is defined in section 4.4.2.2 of [\[XMLDSig\]](#).

Child Elements:

Modulus : A [CryptoBinary](#) element that specifies that specifies the modulus of an RSA public key ([\[RFC3447\]](#) section 3.1).

Exponent : A CryptoBinary element that specifies the exponent of an RSA public key ([\[RFC3447\]](#) section 3.1).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<complexType name="RSAKeyValue" xmlns="http://www.w3.org/2001/XMLSchema">
  <sequence>
    <element name="Modulus" type="ds: CryptoBinary"/>
    <element name="Exponent" type="ds: CryptoBinary"/>
  </sequence>
</complexType>
```

2.4.3.4 Simple Types

2.4.3.4.1 CryptoBinary

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [RSAKeyValue](#), [ObjectType](#)

The **CryptoBinary** simple type as specified in [\[XMLDSig\]](#) section 4.0.1.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<simpleType name="CryptoBinary" xmlns="http://www.w3.org/2001/XMLSchema">
  <restriction base="base64Binary"/>
</simpleType>
```

2.4.3.4.2 DigestValueType

Target namespace: <http://www.w3.org/2000/09/xmldsig#>

Referenced by: [ReferenceType](#), [DigestValue](#)

The **DigestValueType** simple type specifies the encoded value of the digest. The content of the DigestMethodType is defined in section 4.3.3.6 of [\[XMLDSig\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<simpleType name="DigestValueType" xmlns="http://www.w3.org/2001/XMLSchema">
  <restriction base="base64Binary"/>
</simpleType>
```

2.5 Algorithms

This section specifies algorithms used by section [2.1](#), section [2.2](#), section [2.3](#) and section [2.4](#).

2.5.1 HashTransforms.Identity

The HashTransforms.Identity algorithm is a transform algorithm as specified by [\[XMLDSig\]](#) section 6.6. The identifier for the algorithm is "urn:schemas-microsoft-com:HashTransforms.Identity". The algorithm has a single implicit parameter that is a byte stream. The output of this transform is a byte stream whose contents are exactly the same as the input byte stream.

2.5.2 Verification of Strong Name Signature

The strong name signature MUST be verified in accordance to the following criteria:

1. The manifest signature MUST be verified according to section 3.2 of [\[XMLDSig\]](#) and the profile of [\[XMLDSig\]](#) specified in section [2.3.1](#), using the RSA public key ([\[RFC3447\]](#) section 3.1) included in the [RSAKeyValue](#).
2. The value of the publicKeyToken attribute in the assemblyIdentity element (section [2.1.1.3.1](#) and section [2.2.1.3.1](#)) MUST be equal to the public key used in step 1, after the public key has been converted from the RSAKeyValue format into the hexBinary ([\[W3C-XSD\]](#) section 3.2.15) representation in accordance with section [2.5.2.1](#).
3. publisherIdentity element (section [2.1.2.3.6](#) and section [2.2.2.3.9](#)) MUST be present:
 - A software publisher signature (section [2.4](#)) MUST be present:

- The [RelData](#) element MUST be present.
- The RelData element MUST contain a [license](#) element.
- The string representation (section [2.5.3.4](#)) of the Subject name ([\[RFC3280\]](#) section 4.1.2.6) in the software publisher certificate MUST be identical with the value of the X509SubjectName element (section [2.4.2.3.3](#)), as well as the value of the name attribute of the publisherIdentity element (section [2.1.2.3.6](#) and section [2.2.2.3.9](#)).
- The SHA-1 hash ([\[FIPS180-2\]](#) section 6.1) of the public key of the certification authority that issued the software publisher certificate MUST be identical to the value of the issuerKeyHash attribute on the publisherIdentity element (section [2.1.2.3.6](#) and section [2.2.2.3.9](#)).

2.5.2.1 Conversion from RSA Public Key to publicKeyToken

1. Convert the RSA public key ([\[RFC3447\]](#) section 3.1) into the CryptoAPI PUBLICKEYBLOB format described in section [2.5.2.2](#).
2. Construct the PublicKeyBlob using the result from step 1 in accordance with section [2.5.2.3](#).
3. Compute the SHA-1 hash ([\[FIPS180-2\]](#) section 6.1) of the PublicKeyBlob.
4. Take the last 8 bytes from the result of step 3, then reverse the order of those bytes.
5. Encode the result of step 4 into the hexBinary ([\[W3C-XSD\]](#) section 3.2.15) representation.

2.5.2.2 CryptoAPI PUBLICKEYBLOB Format

0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	3	0	1													
0x06								0x02								0x00								0x00																					
0x00								0x24								0x00								0x00																					
0x52								0x53								0x41								0x31																					
0x00								0x08								0x00								0x00																					
Public Exponent																																													
Modulus																																													
...																																													
...																																													
...																																													
...																																													

...
...
(Variable)

Public Exponent (4 bytes): This MUST be a 32-bit unsigned number in little-endian format. It MUST be the public exponent of the key pair, referred to as **e** in [\[RFC3447\]](#) section 2.

Modulus (Variable): This MUST be the RSA modulus, referred to as **n** in [\[RFC3447\]](#) section 2. It MUST be encoded in little-endian format.

2.5.2.3 PublicKeyBlob Format

0	1	2	3	4	5	6	7	8	9	1	0	1	2	3	4	5	6	7	8	9	2	0	1	2	3	4	5	6	7	8	9	3	0	1												
0x00								0x24								0x00								0x00																						
0x04								0x80								0x00								0x00																						
Size of Public Key																																														
...																																														
Public Key																																														
...																																														
...																																														
...																																														
(Variable)																																														

Size of Public Key (8 bytes): This MUST be a 64-bit unsigned integer in little-endian format. It MUST contain the size of the Public Key in bytes.

Public Key (Variable): This MUST be an RSA public key ([\[RFC3447\]](#) section 3.1) encoded as described in section [2.5.2.1](#). The size of the Public Key MUST be equal to the value defined by Size of Public Key.

2.5.3 Software Publisher Identity Verification

The software publisher identity MUST be verified according to the following criteria:

- The Rights Expression Language [\[ISO/IEC-21000-5\]](#) license MUST be verified according to section [2.5.3.1](#).
- If a timestamp is present, verify the timestamp according to the timestamp processing rules described in section [2.5.3.3](#).
- Verify the software publisher certificate according to the software publisher certificate processing rules described in section [2.5.3.2](#).
- The value of the hash attribute in the [ManifestInformationType](#) MUST be the same as the computed hash value for the manifest, excluding the signature element (section [2.1.1.3.3](#) and section [2.2.1.3.2](#)).

2.5.3.1 REL License Verification

The Rights Expression Language [\[ISO/IEC-21000-5\]](#) license MUST be verified according to the following criteria:

- The Rights Expression Language [\[ISO/IEC-21000-5\]](#) license MUST be conformant to the profile defined in section [2.3.2](#).
- The [license](#) element subtree MUST be verified as a separate XML document where the license element is the root node of the XML document.
- The manifest signature MUST be verified according to section 3.2 of [\[XMLDSig\]](#) and the profile of [\[XMLDSig\]](#) specified in section [2.4.3](#), using the RSA public key ([\[RFC3447\]](#) section 3.1) included in the [RSAKeyValue](#) type.
- The signature of the REL license MUST be verified using the public key in the software publisher certificate. The RSAKeyValue type MUST be present and it MUST contain the same public key as the key in the software publisher certificate.
- The string representation (section [2.5.3.4](#)) of the Subject name ([\[RFC3280\]](#) section 4.1.2.6) in the software publisher certificate MUST be identical with the value of the X509SubjectName element (section [2.4.2.3.3](#)).

2.5.3.2 Software Publisher Certificate Processing

The software publisher's signing certificate and certificate chain MUST be verified against the following criteria:

- The certificate chain MUST be validated to a trusted root certificate by using X.509 path validation rules as specified by [\[RFC3280\]](#) section 6.
- Either the signing certificate MUST contain the extended key usage (EKU) ([\[RFC3280\]](#) section 4.2.1.13) value for code signing ("1.3.6.1.5.5.7.3.3.") or there MUST be no EKU fields present in the signing certificate.
- The certificate chain MUST be within its validity period. If the certificate chain is not within its validity period, the signature MUST have a timestamp and that timestamp MUST be validated according to the timestamp processing rules (section [2.5.3.3](#)). If the signature has a timestamp, the certificate chain MUST be within its validity period at the timestamp time.

If any of these conditions are not met, the signature MUST be treated as invalid.

2.5.3.3 Timestamp Processing

A timestamp MUST be verified according to the following criteria:

- The signature of the timestamp MUST be verified according to ([\[RFC2315\]](#) section 9).
- The certificate chain obtained from the timestamp MUST be built to a trusted root certificate using X.509 path validation rules as specified by [\[RFC3280\]](#) section 6.
- The time stamp authority certificate MUST contain the EKU value for timestamping ("1.3.6.1.5.5.7.3.8") ([\[RFC3280\]](#) section 4.2.1.13).
- The base 64 encoded value of the content field of the timestamp element (section [2.4.3.3.10](#)) MUST be equal to the value of [SignatureValueType](#).

2.5.3.4 Converting an X.500 Distinguish Name to a String

The Subject name field of an X.509 certificate ([\[RFC3280\]](#) section 4.1.2.6) is converted to a string according to [\[RFC1779\]](#) but with the following deviations:

1. <spaced-separator> is defined as a comma, followed by a space character:

<spaced-separator> ::= "," "

2. No optional space characters are added when converting attributes:

<attribute> ::= <string> | <key> "=" <string>

3. If the attribute type is listed in the following table, the corresponding keyword is used.

Object Identifier	Keyword
2.5.4.3	CN
2.5.4.7	L
2.5.4.10	O
2.5.4.11	OU
1.2.840.113549.1.9.1	E
2.5.4.6	C
2.5.4.8	S
2.5.4.9	STREET
2.5.4.12	T
2.5.4.42	G
2.5.4.43	I
2.5.4.4	SN
2.5.4.5	SERIALNUMBER
0.9.2342.19200300.100.1.25	DC

Object Identifier	Keyword
2.5.4.13	Description
2.5.4.17	PostalCode
2.5.4.18	POBox
2.5.4.20	Phone

1. If the attribute type is not listed, the attribute is represented by the prefix "OID.", followed by the dotted-decimal representation of the OBJECT IDENTIFIER. For example,

CN=John Doe, OID.1.3.6.1.4.1.311.1.1=Sample Text

2. Double quotation characters ("") are added around a converted attribute value if:

- a leading or trailing space character is present
- one or more of the following characters are present:
 - Comma (,)
 - Plus sign (+)
 - Equal sign (=)
 - ASCII line feed character (decimal 10)
 - Less than sign (<)
 - Greater than sign (>)
 - Number sign (#)
 - Semicolon (;)
 - Single quotation ('')

3. Single quotation characters ('') are added around a converted attribute value if the double quotation character ("") is present.
4. Strings that contain consecutive spaces are not enclosed within quotation marks.
5. Empty strings are enclosed within double quotation marks.

3 Structure Examples

In the following sections, the schema definition might differ from the processing rules imposed by the application. The XSD in this specification provides a base description of the file format. The text that introduces the XSD specifies additional restrictions that reflect actual Microsoft product behavior. For example, the schema definition might allow for an element to be empty, null, or not present but the behavior of the application as specified restricts the same elements to being non-empty, present, and not null.

The following example describes the contents of a typical deployment package that contains a single add-in with one additional file. The package also defines a post-deployment action.

The deployment package consists of the following files:

- deployment manifest: SolutionAddIn.vsto
- application manifest: application.manifest
- package files: file.txt.deploy and SolutionAddIn.dll.deploy

The package files have not been included in this example.

The hashes and signature information in this sample have to be updated to match the customization assemblies, dependent files, and certificate being used.

3.1 Deployment Manifest

The deployment manifest specifies a deployment package with "Solution" product name. The deployment manifest also specifies "DefaultPublisher" as the publisher. The version of the deployment package is 1.0.0.0. The deployment manifest specifies an application manifest with "application.manifest" file name.

File name: SolutionAddIn.vsto

```
<?xml version="1.0" encoding="utf-8"?>
<asmv1:assembly xsi:schemaLocation="urn:schemas-microsoft-com:asm.v1 assembly.adaptive.xsd"
manifestVersion="1.0" xmlns:dsig="http://www.w3.org/2000/09/xmldsig#" xmlns="urn:schemas-
microsoft-com:asm.v2" xmlns:asmv1="urn:schemas-microsoft-com:asm.v1"
xmlns:asmv2="urn:schemas-microsoft-com:asm.v2" xmlns:xrml="urn:mpeg:mpeg21:2003:01-REL-R-NS"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
    <assemblyIdentity name="SolutionAddIn.vsto" version="1.0.0.0"
publicKeyToken="b066060cc54477c1" language="neutral" processorArchitecture="msil"
xmlns="urn:schemas-microsoft-com:asm.v1" />
    <description asmv2:publisher="DefaultPublisher" asmv2:product="Solution"
xmlns="urn:schemas-microsoft-com:asm.v1" />
    <deployment install="false" mapFileExtensions="true" />
    <dependency>
        <dependentAssembly dependencyType="install" codebase="application.manifest" size="12267">
            <assemblyIdentity name="SolutionAddIn.dll" version="1.0.0.0"
publicKeyToken="b066060cc54477c1" language="neutral" processorArchitecture="msil"
type="win32" />
            <hash>
                <dsig:Transforms>
                    <dsig:Transform Algorithm="urn:schemas-microsoft-com:HashTransforms.Identity" />
                </dsig:Transforms>
                <dsig:DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
                <dsig:DigestValue>ZPE5LAa0vNtrMu975iuZUyCQdvU=</dsig:DigestValue>
            </hash>
        </dependentAssembly>
    </dependency>
</assembly>
```

```

        </dependentAssembly>
    </dependency>
    <publisherIdentity name="CN=domain\user_name"
issuerKeyHash="9c928594208093ebb2e5ef59a0741d206f531315" />
    <Signature Id="StrongNameSignature" xmlns="http://www.w3.org/2000/09/xmldsig#">
        <SignedInfo>
            <CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
            <SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1" />
            <Reference URI="">
                <Transforms>
                    <Transform Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-signature" />
                    <Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
                </Transforms>
                <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
                <DigestValue>HffV8wZDgFWlf2qTe5BLbjG2Fmo=</DigestValue>
            </Reference>
        </SignedInfo>

        <SignatureValue>dqbdbvXmZ8X+P01EfJopm78P4yUOHChvPbuzovIevdFEiFZy7cQyiA6v/1SO fzUGY0Mv/DmqQF/EIU
vnF9PuWesxilkyCuaQuQHPRsdDcmAkq+aNW09OnYrymL27uSSc+KxlaGN+3U/zxPieOTyJoh+8/f3+tRcpjZFIOQ1po3F
Q=</SignatureValue>
        <KeyInfo Id="StrongNameKeyInfo">
            <KeyValue>
                <RSAKeyValue>

```

<Modulus>3WAAL94VOOQBWMFmGR5520LjqvUtfZZ5x8mXBy1xIj5SNwwiLZCFCDEn3jWFC/QyII0jbsRh7t6/UjojcVkJ
9q0IOMZH7LiREiCQytbQZhtlRt8cgP3Vbob9ChKuKbA8QrvisaFmjniOLyT3T46Wd3ywF3prqGXQmcXuRcaRIjc=</Mod
ulus>

```

                <Exponent>AQAB</Exponent>
                </RSAKeyValue>
            </KeyValue>
            <msrel:RelData xmlns:msrel="http://schemas.microsoft.com/windows/rel/2005/reldata">
                <r:license xmlns:r="urn:mpeg:mpeg21:2003:01-REL-R-NS"
xmlns:as="http://schemas.microsoft.com/windows/pki/2005/Authenticode">
                    <r:grant>
                        <as:ManifestInformation Hash="6a16b6316e4b907b936a7fa555804306f3d5f71d"
Description="" Url="">
                            <as:assemblyIdentity name="SolutionAddIn.vsto" version="1.0.0.0"
publicKeyToken="b066060cc54477c1" language="neutral" processorArchitecture="msil"
xmlns="urn:schemas-microsoft-com:asm.v1" />
                        </as:ManifestInformation>
                        <as:SignedBy />
                        <as:AuthenticodePublisher>
                            <as:X509SubjectName>CN=domain\user_name</as:X509SubjectName>
                        </as:AuthenticodePublisher>
                    </r:grant>
                    <r:issuer>
                        <Signature Id="AuthenticodeSignature" xmlns="http://www.w3.org/2000/09/xmldsig#">
                            <SignedInfo>
                                <CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
                            </SignedInfo>
                            <SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1" />
                            <Reference URI="">
                                <Transforms>
                                    <Transform Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-
signature" />
                                    <Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
                                </Transforms>
                                <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
                                <DigestValue>K/VSW7AqnTijU4lOgquOt+t6rZI=</DigestValue>


```

```

        </Reference>
    </SignedInfo>

<SignatureValue>WV+k1Z2TSa7mBdGZZWHykPVYRXIvyFC3D+ZFPv5bdtegUNGx7+Wy+82cn1UGfQdQvzt90BRpESV5
Bt7R46TdV63V1X57/vpBqT+4NsQbvVarPKmslGp9lg5kWeO43PPjNe9B6GRNAaTqk35znR+CZJVeIpiV0jfnpn/Ka3vM3T
w=</SignatureValue>
    <KeyInfo>
        <KeyValue>
            <RSAKeyValue>

```

<Modulus>3WAAL94VOOQBWMFmGR552OLjqvUtfZZ5x8mXBy1xIj5SNwwiLZCFcDEN3jWFC/QyII0jbsRh7t6/UjojcVkJ
9q0IOMZH7LiREiCQytbQZht1Rt8cgP3Vbob9ChKuKbA8QrvisaFmjniOLyT3T46Wd3ywF3prqGXQmcXuRcaRIjc=</Mod
ulus>

```

                <Exponent>AQAB</Exponent>
            </RSAKeyValue>
        </KeyValue>
    <X509Data>
```

<X509Certificate>MIIB6jCCAVegAwIBAgIQ/K/TJGThnqRP5PtyhbwTljAJBgUrDgMCHQUAMCsxKTAnBgNVBAMeIABS
AEUARABNAE8ATgBEAFwAYBgBpAGEAcABwAGwAYQBiMB4XDTA5MDUyNjE3MTkyOFoXDTM5MDEwMjAwMDAwMFowKzEpMCCGA
1UEAx4gAFIARQBEAE0AtwBOAEQAXABiAGkAYQBwAHAAAbABhAGIwgZ8wDQYJKoZIhvcNAQEBBQADgY0AMIGJAoGBAN1gAC
/eFTjkAVjBZhkeedji46r1LX2WeclfJlwctcSI+UjcmIi2QhXAxAj941hQv0MiCNI27Exe7ev1I6I3FZCfatCDjGR+y4kRI
gkMrW0GybZUbfHID91W6G/QoSrimwPEK74rGhzo54j18k90+Oln8sBd6a6h10JnF7kXGkSI3AgMBAAGjFzAVMBMGA1Ud
JQQMMAoGCCsGAQUFBwMDMAkGBSSOAwiDbQADgYEAlAHOz8X1R8tq25Kzu1hX3VclbhetoPBPM0WT/eCTRqqUY6xUO+9T
7e/tHWC/cXKPgmBa34ft8BozX61vPsk8xhLtEqJ8uvgn/K6pBU3rYjNtk9mblyPPWNi0/ALzdQEFEYa5hjbNggIjDqLzK
YuNVpCzJK/TFdX4HH+FDTBKrA=</X509Certificate>

```

        </X509Data>
    </KeyInfo>
</Signature>
<r:issuer>
<r:license>
<msrel:RelData>
<KeyInfo>
</Signature>
</asmv1:assembly>
```

3.2 Application Manifest

The application manifest specifies a single customization of the type add-in implemented by the "SolutionAddIn.dll" assembly. The "SolutionAddIn.dll" assembly is a package file included in the deployment package. The application manifest specifies another file with the name "file.txt" that is included in the deployment package. The application manifest also specifies a post-deployment action with the "SolutionDeploymentPostAction" entry point.

File name: application.manifest

```

<?xml version="1.0" encoding="utf-8"?>
<asmv1:assembly xsi:schemaLocation="urn:schemas-microsoft-com:asm.v1 assembly.adaptive.xsd"
manifestVersion="1.0" xmlns:dsig="http://www.w3.org/2000/09/xmldsig#" xmlns="urn:schemas-
microsoft-com:asm.v2" xmlns:asmv1="urn:schemas-microsoft-com:asm.v1"
xmlns:asmv2="urn:schemas-microsoft-com:asm.v2" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance">
    <asmv1:assemblyIdentity name="SolutionAddIn.dll" version="1.0.0.0"
publicKeyToken="b066060cc54477c1" language="neutral" processorArchitecture="msil"
type="win32" />
    <application />
    <entryPoint>
        <co.v1:customHostSpecified xmlns:co.v1="urn:schemas-microsoft-com:clickonce.v1" />
    </entryPoint>

```

```

<trustInfo>
  <security xmlns="urn:schemas-microsoft-com:asm.v2">
    <applicationRequestMinimum>
      <PermissionSet Unrestricted="true" ID="Custom" SameSite="site" />
      <defaultAssemblyRequest permissionSetReference="Custom" />
    </applicationRequestMinimum>
  </security>
  <asmv3 xmlns="urn:schemas-microsoft-com:asm.v3">
    <requestedExecutionLevel level="asInvoker" xmlns="urn:schemas-microsoft-com:asm.v3" />
  </asmv3>
</trustInfo>
<dependency>
  <dependentOS>
    <osVersionInfo>
      <os majorVersion="4" minorVersion="10" buildNumber="0" servicePackMajor="0" />
    </osVersionInfo>
  </dependentOS>
</dependency>
<dependency>
  <dependentAssembly dependencyType="preRequisite" allowDelayedBinding="true">
    <assemblyIdentity name="Microsoft.Windows.CommonLanguageRuntime" version="2.0.50727.0" />
    <dependentAssembly>
    </dependentAssembly>
  </dependency>
<dependency>
  <dependentAssembly dependencyType="install" allowDelayedBinding="true" codebase="SolutionAddIn.dll" size="10752">
    <assemblyIdentity name="SolutionAddIn" version="1.0.0.0" publicKeyToken="B066060CC54477C1" language="neutral" processorArchitecture="msil" />
    <hash>
      <dsig:Transforms>
        <dsig:Transform Algorithm="urn:schemas-microsoft-com:HashTransforms.Identity" />
      </dsig:Transforms>
      <dsig:DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
      <dsig:DigestValue>UwfhkV3zY6EMHgP00BmYMA9cFJY=</dsig:DigestValue>
    </hash>
  </dependentAssembly>
</dependency>
<file name="file.txt" size="3">
  <hash>
    <dsig:Transforms>
      <dsig:Transform Algorithm="urn:schemas-microsoft-com:HashTransforms.Identity" />
    </dsig:Transforms>
    <dsig:DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
    <dsig:DigestValue>VyGMMWtpIeLNQJ6I4ftwxotlHE=</dsig:DigestValue>
  </hash>
</file>
<vstav3:addIn xmlns:vstav3="urn:schemas-microsoft-com:vsta.v3">
  <vstav3:entryPointsCollection xmlns:vstav3="urn:schemas-microsoft-com:vsta.v3">
    <vstav3:entryPoints>
      <vstav3:entryPoint class="SolutionAddIn.ThisAddIn">
        <assemblyIdentity name="SolutionAddIn" version="1.0.0.0" publicKeyToken="B066060CC54477C1" language="neutral" processorArchitecture="msil" />
        </vstav3:entryPoint>
      </vstav3:entryPoints>
    </vstav3:entryPointsCollection>
    <vstav3:update enabled="false" xmlns:vstav3="urn:schemas-microsoft-com:vsta.v3" />
    <vstav3:postActions xmlns:vstav3="urn:schemas-microsoft-com:vsta.v3">
      <vstav3:postAction>

```

```

<vstav3:entryPoint class="SolutionAddIn.SolutionDeploymentPostAction">
    <assemblyIdentity name="SolutionAddIn" version="1.0.0.0"
publicKeyToken="94de0004b6e3fcc5" language="neutral" processorArchitecture="msil" />
    </vstav3:entryPoint>
    <vstav3:postActionData>
    </vstav3:postActionData>
    </vstav3:postAction>
</vstav3:postActions>
<vstav3:application xmlns:vstav3="urn:schemas-microsoft-com:vsta.v3">
    <vstov4:customizations xmlns:vstov4="urn:schemas-microsoft-com:vsto.v4">
        <vstov4:customization>
            <vstov4:appAddIn application="Outlook" loadBehavior="2" keyName="OutlookAddIn1">
                <vstov4:friendlyName>OutlookAddIn1</vstov4:friendlyName>
                <vstov4:description>OutlookAddIn1</vstov4:description>
            </vstov4:appAddIn>
            </vstov4:customization>
        </vstov4:customizations>
    </vstav3:application>
</vstav3:addIn>
<publisherIdentity name="CN=domain\user_name"
issuerKeyHash="9c928594208093ebb2e5ef59a0741d206f531315" />
<Signature Id="StrongNameSignature" xmlns="http://www.w3.org/2000/09/xmldsig#">
    <SignedInfo>
        <CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
        <SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1" />
        <Reference URI="">
            <Transforms>
                <Transform Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-signature" />
                <Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
            </Transforms>
            <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
            <DigestValue>aexIJyfGPdjKGHXnb1IPnuDjY3s=</DigestValue>
        </Reference>
    </SignedInfo>

<SignatureValue>R5zs62eeKbJyHooS5YDvKBiBzixFFMvQ5VynRND2MguZe3phsuCwHvRwZVs+eDq0bU1SfsclsI69c0
+R/olM6wfmPvroQdnVA6xSI33Ud17GDJemKS7o/0nQaiOjXnD8tB9/hIoeZPSD5Zic6LbX8bzXtickKV2HmQiKmaZqXgY
8=</SignatureValue>
<KeyInfo Id="StrongNameKeyInfo">
    <KeyValue>
        <RSAKeyValue>
```

<Modulus>3WAAL94VOOQBWMFmGR5520LjqvUtfZZ5x8mXBy1xIj5SNwwiLZCFcDEn3jWFC/QyII0jbsRh7t6/UjojcVkJ
9q0IOMZH7LiREiCQytbQZht1Rt8cgP3Vbob9ChKuKbA8QrvisaFmjniOLyT3T46Wd3ywF3prqGXQmcXuRcaRIjc=</Mod
ulus>
 <Exponent>AQAB</Exponent>
 </RSAKeyValue>
</KeyValue>
<msrel:RelData xmlns:msrel="http://schemas.microsoft.com/windows/rel/2005/reldata">
 <r:license xmlns:r="urn:mpeg:mpeg21:2003:01-REL-R-NS"
xmlns:as="http://schemas.microsoft.com/windows/pki/2005/Authenticode">
 <r:grant>
 <as:ManifestInformation Hash="7b63c9e09e0f526fe77518cad83dc6272748ec69"
Description="" Url="">
 <as:assemblyIdentity name="SolutionAddIn.dll" version="1.0.0.0"
publicKeyToken="b066060cc54477c1" language="neutral" processorArchitecture="msil"
type="win32" />
 </as:ManifestInformation>
 <as:SignedBy />
 <as:AuthenticodePublisher>

```

<as:X509SubjectName>CN=domain\user_name</as:X509SubjectName>
</as:AuthenticodePublisher>
</r:grant>
<r:issuer>
  <Signature Id="AuthenticodeSignature" xmlns="http://www.w3.org/2000/09/xmldsig#">
    <SignedInfo>
      <CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
      <SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1" />
      <Reference URI="">
        <Transforms>
          <Transform Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-signature" />
          <Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
        </Transforms>
        <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
        <DigestValue>ZdHni7uhJluZnODxK0NqWPRYdDE=</DigestValue>
      </Reference>
    </SignedInfo>

    <SignatureValue>oGL8ICFBIXxTbjK1iRwzidKGUh14VbleFHRjGxEFrTp+R2x4V+AmJxgM8d7qE2bS2ifqHJbJA3lphQG2e0iT4PyZrQCJTpc3TNmz837wnqaf7tT2U8KNc8W+apaNs8z+QCHIuGyOZZCzz/RjX/o5lph8Fgv1qVVwQtPTABpt8U=</SignatureValue>
    <KeyInfo>
      <KeyValue>
        <RSAKeyValue>

<Modulus>3WAAL94VOOQBWMFmGR5520LjqvUtfZZ5x8mXBy1xIj5SNwwiLZCFcDEN3jWFC/QyII0jbsRh7t6/UjojcVkJ9q0IOMZH7LiREiCQytbQZh1Rt8cgP3Vbob9ChKuKbA8QrvisaFmjniOLyT3T46Wd3ywF3prqGXQmcXuRcaRIjc=</Modulus>
        <Exponent>AQAB</Exponent>
      </RSAKeyValue>
    </KeyValue>
  <X509Data>

<X509Certificate>MIIB6jCCAveAwIBAgIQ/K/TJGThnqRP5PtyhbwTljAJBgUrDgMCHQUAMCsxKTAnBgNVBAMeIABS
AEUARABNAE8ATgBEAFwAYgBpAGEAcABwAGwAYQBiMB4XDTA5MDUyNjE3MTkyOFoXDTM5MDEwMjAwMDAwMFowKzEpMCcGA
1UEAx4gAFIARQBEAE0ATwBOAEQAXABiAGkAYQBwAHAAbABhAGIwgZ8wDQYJKoZIhvvcNAQEBBQADgY0AMIGJAoGBAN1gAC
/eFTjkAVjBZhkeedji46rlLX2WeclfJlwctcSI+UjcmIi2QhXAxJ941hQv0MiCNI27EYe7ev1I6i3FZCfatCDjGR+y4kRI
gkMrW0GYbZUbfHID91W6G/QoSrimwPEK74rGhzo54j18k90+O1nd8sBd6a6h10JnF7kXGkSI3AgMBAAGjFzAVMBMGA1UD
JQOMMAoGCCsGAQUFBwMDMAkGBSSOAwIdBQADgYEAlAHoZ8X1R8tq25Kzu1hX3VclbhtoeoPBPM0WT/eCTRqqUY6xUO+9T
7e/tHWC/cXKPgmBa34ft8BozX61vPsk8xh1tEqJ8uvgn/K6pBU3rYjNtk9mblyPPWNi0/ALzdQEFEYa5hjbNggIjDqLzK
YuNVpCzJK/TFdX4HH+FDTBKrA=</X509Certificate>
  </X509Data>
  <KeyInfo>
  </Signature>
</r:issuer>
<r:license>
<msrel:RelData>
<KeyInfo>
</Signature>
</asmv1:assembly>
```

The hashes and signature information in this sample have to be updated to match the customization assemblies, dependent files, and certificate being used.

4 Security Considerations

This structure simply represents a set of XML files. Implementations that process XML files contained in this format should guard against the same kinds of threats that occur when processing other XML files.

This structure uses the SHA-1 hashing algorithm for the hash of files in the deployment package. The application manifest contains a hash for all the package files that are referenced (section [2.2.2.3.4](#)). The deployment manifest contains a hash of the application manifest (section [2.1.2.3.4](#)).

The deployment package requests the unrestricted code access security permission set, any executable code that is deployed with the package runs with this permission set (section [2.2.2.3.12](#)).

4.1 Digital Signatures

To provide the evidence for the deployment package, both manifests contain a publisherIdentityType (section [2.1.2.3.6](#) and section [2.2.2.3.9](#)) and are signed using XML signatures as specified by section [2.3](#), section [2.4](#) and section [2.5](#) – see signature element in assemblyType (section [2.1.1.3.3](#) and section [2.2.1.3.2](#)).

5 Appendix A: XML Schema Files

5.1 Deployment Manifest XML Schemas

File: asm.xsd

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" xmlns="urn:schemas-microsoft-
com:asm.v1" xmlns:asm.v2="urn:schemas-microsoft-com:asm.v2" xmlns:asm.v1="urn:schemas-
microsoft-com:asm.v1" xmlns:xrml="http://www.xrml.org/schema/2001/11/xrml2core"
xmlns:r="urn:mpeg:mpeg21:2003:01-REL-R-NS" xmlns:ds="http://www.w3.org/2000/09/xmldsig#"
xmlns:enc="http://www.w3.org/2001/04/xmlenc#" xmlns:ds="http://www.w3.org/2000/09/xmldsig#"
targetNamespace="urn:schemas-microsoft-com:asm.v1" elementFormDefault="qualified"
attributeFormDefault="unqualified" >
    <xs:include schemaLocation="asm.v1.types.xsd" />
    <xs:import namespace="urn:schemas-microsoft-com:asm.v2" schemaLocation="asm.v2.types.xsd"
/>
    <xs:import namespace="http://www.w3.org/2000/09/xmldsig#"
schemaLocation="external/xmldsig-core-schema.0.0.0.2.xsd" />
    <xs:element name="assembly" type="assemblyType" >
        </xs:element>
    <xs:complexType name="assemblyType" >
        <xs:sequence>
            <xs:element name="assemblyIdentity" type="asm.v1:assemblyIdentityType" />
            <xs:element name="description" type="descriptionType" />
            <xs:element ref="asm.v2:deployment" />
            <xs:element ref="asm.v2:dependency" />
            <xs:element ref="asm.v2:publisherIdentity" />
            <xs:element ref="ds:Signature" />
        </xs:sequence>
        <xs:attribute name="manifestVersion" type="asm.v1:twoPartVersionType" use="required"
fixed="1.0" />
    </xs:complexType>
</xs:schema>
```

File: asm.v1.types.xsd

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:asm.v1="urn:schemas-microsoft-com:asm.v1" xmlns:asm.v2="urn:schemas-
microsoft-com:asm.v2" targetNamespace="urn:schemas-microsoft-com:asm.v1"
attributeFormDefault="unqualified" elementFormDefault="qualified"
xmlns:xs="http://www.w3.org/2001/XMLSchema" >
    <xs:import namespace="urn:schemas-microsoft-com:asm.v2" schemaLocation="asm.v2.types.xsd"
/>
    <xs:simpleType name="twoPartVersionType" >
        <xs:restriction base="xs:string">
            <xs:pattern value="(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-
9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-
4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])" />
        </xs:restriction>
    </xs:simpleType>
    <xs:simpleType name="publicKeyTokenType" >
        <xs:restriction base="xs:string">
            <xs:pattern value="([0-9]|[a-f]|[A-F])\{16\}" />
        </xs:restriction>
    </xs:simpleType>
    <xs:simpleType name="fourPartVersionType" >
        <xs:restriction base="xs:string">
```

```

<xs:pattern value="(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-
9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-
4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-
9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-
4][0-9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])" />
</xs:restriction>
</xs:simpleType>
<xs:simpleType name="fileNameStringType" >
<xs:restriction base="xs:string">
<xs:pattern value="([\u0020|[\u0021|[\u0024|[\u0025|[\u0027-\u0029|[\u002B-
\u002E|[\u0030-\u0039|[\u003B|[\u003D|[\u0040-\u005B|[\u005D-\u007B|[\u007D-
\uFFFD|[\u10000-\u10FFFF])*" />
</xs:restriction>
</xs:simpleType>
<xs:complexType name="assemblyIdentityType" >
<xs:attribute name="name" type="asm.v1:fileNameStringType" use="required" />
<xs:attribute name="version" type="asm.v1:fourPartVersionType" use="required" />
<xs:attribute name="processorArchitecture" type="xs:string" use="required" fixed="msil" />
<xs:attribute name="publicKeyToken" type="asm.v1:publicTokenType" use="required" />
<xs:attribute name="language" type="xs:string" use="required" fixed="neutral" />
</xs:complexType>
<xs:complexType name="descriptionType" mixed="true" >
<xs:attribute ref="asm.v2:publisher" use="required" />
<xs:attribute ref="asm.v2:product" use="required" />
</xs:complexType>
</xs:complexType>
</xs:schema>

```

File: asm.v2.types.xsd

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema targetNamespace="urn:schemas-microsoft-com:asm.v2"
attributeFormDefault="unqualified" elementFormDefault="qualified"
xmlns:xs="http://www.w3.org/2001/XMLSchema" xmlns:ds="http://www.w3.org/2000/09/xmldsig#"
xmlns:asm.v2="urn:schemas-microsoft-com:asm.v2">
<xs:import namespace="http://www.w3.org/2000/09/xmldsig#" schemaLocation="external/xmldsig-
core-schema.0.0.0.2.xsd" />
<xs:attribute name="publisher" type="asm.v2:fileNameStringType" fixed="DefaultPublisher" />
<xs:attribute name="product" type="asm.v2:fileNameStringType" />
<xs:element name="deployment" type="asm.v2:deploymentType" />
<xs:element name="dependency" type="asm.v2:dependencyType"/>
<xs:element name="publisherIdentity" type="asm.v2:publisherIdentityType" />
<xs:simpleType name="fourPartVersionType" >
<xs:restriction base="xs:string">
<xs:pattern value="(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-
9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-
4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-
9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-
4][0-9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])" />
</xs:restriction>
</xs:simpleType>
<xs:simpleType name="fileNameStringType" >
<xs:restriction base="xs:string">
<xs:pattern value="([\u0020|[\u0021|[\u0024|[\u0025|[\u0027-\u0029|[\u002B-
\u002E|[\u0030-\u0039|[\u003B|[\u003D|[\u0040-\u005B|[\u005D-\u007B|[\u007D-
\uFFFD|[\u10000-\u10FFFF])*" />
</xs:restriction>
</xs:simpleType>

```

```

<xs:simpleType name="publicKeyTokenType" >
  <xs:restriction base="xs:string">
    <xs:pattern value="([0-9]|[a-f][A-F]) {16}" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="deploymentType" >
  <xs:attribute name="install" type="xs:boolean" use="required" fixed="false" />
  <xs:attribute name="mapFileExtensions" type="xs:boolean" use="optional" default="false" />
</xs:complexType>
<xs:complexType name="dependencyType" >
  <xs:sequence>
    <xs:choice>
      <xs:element name="dependentAssembly" type="asm.v2:dependentAssemblyType" />
    </xs:choice>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="dependentAssemblyType" >
  <xs:sequence>
    <xs:element name="assemblyIdentity" type="asm.v2:assemblyIdentityType" />
    <xs:element name="hash" type="asm.v2:hashType" minOccurs="0" maxOccurs="unbounded" />
  </xs:sequence>
  <xs:attribute name="dependencyType" type="xs:string" use="required" fixed="install" />
  <xs:attribute name="codebase" type="xs:anyURI" />
  <xs:attribute name="size" type="xs:integer" use="optional" />
</xs:complexType>
<xs:complexType name="hashType" >
  <xs:complexContent>
    <xs:extension base="ds:ReferenceType">
      <xs:sequence>
        <xs:any namespace="#other" processContents="lax" minOccurs="0" maxOccurs="unbounded" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="assemblyIdentityType" >
  <xs:attribute name="name" type="asm.v2:fileNameStringType" use="required" />
  <xs:attribute name="version" type="asm.v2:fourPartVersionType" use="required" />
  <xs:attribute name="type" type="xs:string" use="optional" fixed="win32" />
  <xs:attribute name="processorArchitecture" type="xs:string" use="required" fixed="msil" />
  <xs:attribute name="publicKeyToken" type="asm.v2:publicKeyTokenType" use="required" />
  <xs:attribute name="language" type="xs:string" use="required" fixed="neutral" />
</xs:complexType>
<xs:complexType name="publisherIdentityType" >
  <xs:attribute name="name" type="xs:string" />
  <xs:attribute name="issuerKeyHash" type="xs:string" />
</xs:complexType>
</xs:schema>

```

5.2 Application Manifest XML Schemas

File: asm.xsd

```

<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" xmlns:vsta.v3="urn:schemas-microsoft-
com:vsta.v3" xmlns="urn:schemas-microsoft-com:asm.v1" xmlns:asm.v3="urn:schemas-microsoft-

```

```

com:asm.v3" xmlns:asm.v2="urn:schemas-microsoft-com:asm.v2" xmlns:asm.v1="urn:schemas-
microsoft-com:asm.v1" xmlns:xrml="http://www.xrml.org/schema/2001/11/xrml2core"
xmlns:r="urn:mpeg:mpeg21:2003:01-REL-R-NS" xmlns:ds="http://www.w3.org/2000/09/xmldsig#"
xmlns:enc="http://www.w3.org/2001/04/xmlenc#" targetNamespace="urn:schemas-microsoft-
com:asm.v1" elementFormDefault="qualified" attributeFormDefault="unqualified" >
    <xs:import namespace="http://www.w3.org/2000/09/xmldsig#" schemaLocation="external/xmldsig-core-schema.0.0.2.xsd" />
    <xs:include schemaLocation="asm.v1.types.xsd" />
    <xs:import namespace="urn:schemas-microsoft-com:asm.v2" schemaLocation="asm.v2.types.xsd" />
</xs:sequence>
<xs:element name="assembly" type="assemblyType" >
</xs:element>
<xs:complexType name="assemblyType" >
    <xs:sequence>
        <xs:element name="assemblyIdentity" type="asm.v1:assemblyIdentityType" />
        <xs:element ref="asm.v2:application" />
        <xs:element ref="asm.v2:entryPoint" />
        <xs:element ref="asm.v2:trustInfo" />
        <xs:element ref="asm.v2:dependency" minOccurs="0" maxOccurs="24575" />
        <xs:element ref="asm.v2:file" minOccurs="0" maxOccurs="24575" />
        <xs:element ref="vsta.v3:addIn" />
        <xs:element ref="asm.v2:publisherIdentity" />
        <xs:element ref="ds:Signature" />
    </xs:sequence>
    <xs:attribute name="manifestVersion" type="asm.v1:twoPartVersionType" use="required" fixed="1.0" />
</xs:complexType>
</xs:schema>

```

File: asm.v1.types.xsd

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:asm.v1="urn:schemas-microsoft-com:asm.v1" xmlns:asm.v2="urn:schemas-
microsoft-com:asm.v2" targetNamespace="urn:schemas-microsoft-com:asm.v1"
attributeFormDefault="unqualified" elementFormDefault="qualified"
xmlns:xs="http://www.w3.org/2001/XMLSchema" >
    <xs:import namespace="urn:schemas-microsoft-com:asm.v2" schemaLocation="asm.v2.types.xsd" />
    <xs:simpleType name="twoPartVersionType" >
        <xs:restriction base="xs:string">
            <xs:pattern value="(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-
9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-
4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])" />
        </xs:restriction>
    </xs:simpleType>
    <xs:simpleType name="publicKeyTokenType" >
        <xs:restriction base="xs:string">
            <xs:pattern value="([0-9]|[a-f]|[A-F])\{16\}" />
        </xs:restriction>
    </xs:simpleType>
    <xs:simpleType name="fourPartVersionType" >
        <xs:restriction base="xs:string">
            <xs:pattern value="(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-
9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-
4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-
9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-
4][0-9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])" />
        </xs:restriction>
    </xs:simpleType>

```

```

<xs:simpleType name="fileNameStringType" >
    <xs:restriction base="xs:string">
        <xs:pattern value="([\u0020] | [\u0021] | [\u0024] | [\u0025] | [\u0027-\u0029] | [\u002B-\u002E] | [\u0030-\u0039] | [\u003B] | [\u003D] | [\u0040-\u005B] | [\u005D-\u007B] | [\u007D-\uFFFD] | [\u10000-\u10FFFF])*" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="assemblyIdentityType" >
    <xs:attribute name="name" type="asm.v1:fileNameStringType" use="required" />
    <xs:attribute name="version" type="asm.v1:fourPartVersionType" use="required" />
    <xs:attribute name="type" type="xs:string" use="optional" fixed="win32" />
    <xs:attribute name="processorArchitecture" type="xs:string" use="required" fixed="msil" />
    <xs:attribute name="publicKeyToken" type="asm.v1:publicKeyTokenType" use="required" />
    <xs:attribute name="language" type="xs:string" use="required" fixed="neutral" />
</xs:complexType>
</xs:schema>

```

File: asm.v2.types.xsd

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema targetNamespace="urn:schemas-microsoft-com:asm.v2"
attributeFormDefault="unqualified" elementFormDefault="qualified"
xmlns:xs="http://www.w3.org/2001/XMLSchema" xmlns:ds="http://www.w3.org/2000/09/xmldsig#"
xmlns:asm.v2="urn:schemas-microsoft-com:asm.v2" xmlns:asm.v3="urn:schemas-microsoft-
com:asm.v3" xmlns:co.v1="urn:schemas-microsoft-com:clickonce.v1" >
    <xs:import namespace="http://www.w3.org/2000/09/xmldsig#" schemaLocation="external/xmldsig-
core-schema.0.0.0.2.xsd" />
    <xs:import namespace="urn:schemas-microsoft-com:clickonce.v1" schemaLocation="co.v1.xsd" />
    <xs:import namespace="urn:schemas-microsoft-com:asm.v3" schemaLocation="asm.v3.types.xsd" />
</xs:schema>
<xs:element name="application" type="asm.v2:applicationType" />
<xs:element name="entryPoint" type="asm.v2:entryPointType" />
<xs:element name="trustInfo" type="asm.v2:trustInfoType" />
<xs:element name="dependency" type="asm.v2:dependencyType" />
<xs:element name="file" type="asm.v2:fileType" />
<xs:element name="assemblyIdentity" type="asm.v2:assemblyIdentityType" />
<xs:element name="publisherIdentity" type="asm.v2:publisherIdentityType" />
<xs:complexType name="applicationType" />
<xs:complexType name="dependencyType" >
    <xs:sequence>
        <xs:choice>
            <xs:element name="dependentAssembly" type="asm.v2:dependentAssemblyType" />
            <xs:element name="dependentOS" type="asm.v2:dependentOSType" />
        </xs:choice>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="dependentAssemblyType" >
    <xs:sequence>
        <xs:element name="assemblyIdentity" type="asm.v2:assemblyIdentityType" />
        <xs:element name="hash" type="asm.v2:hashType" minOccurs="0" maxOccurs="unbounded" />
    </xs:sequence>
    <xs:attribute name="dependencyType" type="asm.v2:dependencyTypeType" use="optional" default="preRequisite" />
    <xs:attribute name="codebase" type="xs:anyURI" />
    <xs:attribute name="size" type="xs:integer" use="optional" />
    <xs:attribute name="allowDelayedBinding" type="xs:boolean" use="required" fixed="true" />
</xs:complexType>

```

```

    </xs:complexType>
<xs:complexType name="hashType" >
    <xs:complexContent>
        <xs:extension base="ds:ReferenceType">
            <xs:sequence>
                <xs:any namespace="#other" processContents="lax" minOccurs="0"
maxOccurs="unbounded" />
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="dependentOSType" >
    <xs:sequence>
        <xs:element name="osVersionInfo" type="asm.v2:osVersionInfoType" />
    </xs:sequence>
</xs:complexType>
<xs:complexType name="osVersionInfoType" >
    <xs:sequence>
        <xs:element name="os" type="asm.v2:osType" />
    </xs:sequence>
</xs:complexType>
<xs:complexType name="osType" >
    <xs:attribute name="majorVersion" type="asm.v2:TwoByteVersion" use="required" fixed="4"
/>
    <xs:attribute name="minorVersion" type="asm.v2:TwoByteVersion" use="required" fixed="10"
/>
    <xs:attribute name="buildNumber" type="asm.v2:TwoByteVersion" use="required" fixed="0"
/>
    <xs:attribute name="servicePackMajor" type="asm.v2:OneByteVersion" use="required"
fixed="0" />
</xs:complexType>
<xs:simpleType name="TwoByteVersion" >
    <xs:restriction base="xs:integer">
        <xs:minInclusive value="0" />
        <xs:maxInclusive value="65535" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="OneByteVersion" >
    <xs:restriction base="xs:integer">
        <xs:minInclusive value="0" />
        <xs:maxInclusive value="255" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="dependencyTypeType" >
    <xs:restriction base="xs:string">
        <xs:enumeration value="preRequisite" />
        <xs:enumeration value="install"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="fileNameStringType" >
    <xs:restriction base="xs:string">
        <xs:pattern value="([\u0020]|[\u0021]|[\u0024]|[\u0025]|[\u0027-\u0029]|[\u002B-
\u002E]|[\u0030-\u0039]|[\u003B]|[\u003D]|[\u0040-\u005B]|[\u005D-\u007B]|[\u007D-
\uFFFD]|[\u10000-\u10FFFF])*" />
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="assemblyIdentityType" >
    <xs:attribute name="name" type="asm.v2:fileNameStringType" use="required" />
    <xs:attribute name="version" type="asm.v2:fourPartVersionType" use="required" />

```

```

<xs:attribute name="type" type="xs:string" use="optional" fixed="win32" />
<xs:attribute name="processorArchitecture" type="xs:string" use="optional" fixed="msil" />
<xs:attribute name="publicKeyToken" type="asm.v2:publicKeyTokenType" use="optional" />
<xs:attribute name="language" type="xs:string" use="optional" fixed="neutral" />
</xs:complexType>
<xs:simpleType name="fourPartVersionType" >
  <xs:restriction base="xs:string">
    <xs:pattern value="(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])\.(0*[0-9]{1,4}|0*[1-5][0-9]{4}|0*6[0-4][0-9]{3}|0*65[0-4][0-9]{2}|0*655[0-2][0-9]|0*6553[0-5])" />
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="publicKeyTokenType" >
  <xs:restriction base="xs:string">
    <xs:pattern value="([0-9]|[a-f]|[A-F])\{16\}" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="publisherIdentityType" >
  <xs:attribute name="name" type="xs:string" />
  <xs:attribute name="issuerKeyHash" type="xs:string" />
</xs:complexType>
<xs:complexType name="entryPointType" >
  <xs:sequence>
    <xs:element ref="co.v1:customHostSpecified" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="trustInfoType" >
  <xs:sequence>
    <xs:element name="security" type="asm.v2:securityType" />
    <xs:element ref="asm.v3:asmv3" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="securityType" >
  <xs:sequence>
    <xs:element name="applicationRequestMinimum" type="asm.v2:applicationRequestMinimumType" />
    <xs:element name="requestedPrivileges" type="asm.v3:requestedPrivilegesType" />
    <xs:element ref="asm.v3:asmv3" minOccurs="0" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="applicationRequestMinimumType" >
  <xs:sequence>
    <xs:element name="PermissionSet" type="asm.v2:PermissionSetType" />
    <xs:element name="defaultAssemblyRequest" type="asm.v2:defaultAssemblyRequestType" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="PermissionSetType" >
  <xs:attribute name="ID" type="xs:ID" use="required" />
  <xs:attribute name="Unrestricted" type="xs:boolean" use="required" fixed="true" />
  <xs:attribute name="SameSite" type="xs:string" use="required" fixed="site" />
</xs:complexType>
<xs:complexType name="defaultAssemblyRequestType" >
  <xs:attribute name="permissionSetReference" type="xs:IDREF" />
</xs:complexType>
<xs:complexType name="fileType" >
  <xs:choice minOccurs="0" maxOccurs="unbounded">

```

```

        <xs:element name="hash" type="asm.v2:hashType" />
    </xs:choice>
    <xs:attribute name="name" type="xs:string" use="required" />
    <xs:attribute name="size" type="xs:unsignedLong" use="required" />
</xs:complexType>
</xs:schema>

```

File: asm.v3.types.xsd

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:asm.v3="urn:schemas-microsoft-com:asm.v3" targetNamespace="urn:schemas-
microsoft-com:asm.v3" attributeFormDefault="unqualified" elementFormDefault="qualified"
xmlns:xs="http://www.w3.org/2001/XMLSchema" >
    <xs:element name="asmv3" type="asm.v3:asmv3Type" />
    <xs:complexType name="requestedPrivilegesType" >
        <xs:sequence>
            <xs:element name="requestedExecutionLevel" type="asm.v3:requestedExecutionLevelType" />
        </xs:sequence>
    </xs:complexType>
    <xs:complexType name="requestedExecutionLevelType" >
        <xs:attribute name="level" type="xs:string" use="required" fixed="asInvoker" />
    </xs:complexType>
    <xs:complexType name="asmv3Type" >
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="#any" processContents="skip" />
        </xs:sequence>
    </xs:complexType>
</xs:schema>

```

File: co.v1.xsd

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" xmlns:co.v1="urn:schemas-microsoft-
com:clickonce.v1" targetNamespace="urn:schemas-microsoft-com:clickonce.v1" >
    <xs:element name="customHostSpecified" type="co.v1:customHostSpecifiedType" />
    <xs:complexType name="customHostSpecifiedType" />
</xs:schema>

```

File: vsta.v3.xsd

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" xmlns:asm.v2="urn:schemas-microsoft-
com:asm.v2" xmlns:vsto.v4="urn:schemas-microsoft-com:vsto.v4" xmlns:vsta.v3="urn:schemas-
microsoft-com:vsta.v3" targetNamespace="urn:schemas-microsoft-com:vsta.v3"
attributeFormDefault="unqualified" elementFormDefault="qualified" >
    <xs:import namespace="urn:schemas-microsoft-com:asm.v2" schemaLocation="asm.v2.types.xsd"
/>
    <xs:import namespace="urn:schemas-microsoft-com:vsto.v4" schemaLocation="vsto.v4.xsd" />
    <xs:element name="addIn" type="vsta.v3:addInType" />
    <xs:complexType name="addInType" >
        <xs:sequence>
            <xs:element name="entryPointsCollection" type="vsta.v3:entryPointsCollectionType"
minOccurs="1" maxOccurs="1" />
            <xs:element name="update" type="vsta.v3:updateType" maxOccurs="1" minOccurs="1" />
            <xs:element name="postActions" type="vsta.v3:postActionsType" maxOccurs="1"
minOccurs="0" />

```

```

<xs:element name="application" type="vsta.v3:applicationType" maxOccurs="1"
minOccurs="0" />
<xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other" processContents="skip"
/>
</xs:sequence>
<xs:anyAttribute namespace="##other" processContents="skip" />
</xs:complexType>
<xs:complexType name="entryPointsCollectionType" >
<xs:sequence>
<xs:element name="entryPoints" type="vsta.v3:entryPointsType" minOccurs="1"
maxOccurs="unbounded" />
<xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other" processContents="skip"
/>
</xs:sequence>
<xs:anyAttribute namespace="##other" processContents="skip" />
</xs:complexType>
<xs:complexType name="entryPointsType" >
<xs:sequence>
<xs:element name="entryPoint" type="vsta.v3:entryPointType" maxOccurs="unbounded" />
<xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other" processContents="skip"
/>
</xs:sequence>
<xs:attribute name="id" type="xs:string" use="optional" />
<xs:anyAttribute namespace="##other" processContents="skip" />
</xs:complexType>
<xs:complexType name="entryPointType" mixed="true" >
<xs:sequence minOccurs="1" maxOccurs="1">
<xs:element ref="asm.v2:assemblyIdentity" />
<xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other" processContents="skip"
/>
</xs:sequence>
<xs:attribute name="class" type="xs:string" use="required" />
<xs:anyAttribute namespace="##other" processContents="skip" />
</xs:complexType>
<xs:complexType name="postActionEntryPointType" mixed="true" >
<xs:sequence minOccurs="1" maxOccurs="1">
<xs:element ref="asm.v2:assemblyIdentity" />
<xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other" processContents="skip"
/>
</xs:sequence>
<xs:attribute name="class" type="xs:string" use="required" />
<xs:anyAttribute namespace="##other" processContents="skip" />
</xs:complexType>
<xs:complexType name="updateType" >
<xs:sequence>
<xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other" processContents="skip"
/>
</xs:sequence>
<xs:attribute name="enabled" type="xs:boolean" use="required" fixed="false" />
<xs:anyAttribute namespace="##other" processContents="skip" />
</xs:complexType>
<xs:complexType name="postActionsType" >
<xs:sequence>
<xs:element name="postAction" type="vsta.v3:postActionType" maxOccurs="unbounded"
minOccurs="0" />
<xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other" processContents="skip"
/>
</xs:sequence>
<xs:anyAttribute namespace="##other" processContents="skip" />
</xs:complexType>
```

```

<xs:complexType name="postActionType" >
  <xs:sequence>
    <xs:element name="entryPoint" type="vsta.v3:postActionEntryPointType" maxOccurs="1"
minOccurs="1" />
    <xs:element name="postActionData" type="vsta.v3:postActionDataType" maxOccurs="1"
minOccurs="0" />
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="#other" processContents="skip"
/>
  </xs:sequence>
  <xs:anyAttribute namespace="#other" processContents="skip" />
</xs:complexType>
<xs:complexType name="postActionDataType" >
  <xs:sequence>
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="#other" processContents="skip"
/>
  </xs:sequence>
  <xs:anyAttribute namespace="#other" processContents="skip" />
</xs:complexType>
<xs:complexType name="applicationType" >
  <xs:sequence>
    <xs:element ref="vsto.v4:customizations" />
  </xs:sequence>
</xs:complexType>
</xs:schema>

```

File: vsto.v4.xsd

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:vsto.v4="urn:schemas-microsoft-com:vsto.v4"
attributeFormDefault="unqualified" elementFormDefault="qualified"
targetNamespace="urn:schemas-microsoft-com:vsto.v4"
xmlns:xs="http://www.w3.org/2001/XMLSchema" >
  <xs:element name="customizations" type="vsto.v4:customizationsType" />
  <xs:complexType name="customizationsType" >
    <xs:sequence>
      <xs:element name="customization" type="vsto.v4:customizationType" minOccurs="1"
maxOccurs="unbounded" />
      <xs:any minOccurs="0" maxOccurs="unbounded" namespace="#other" processContents="skip"
/>
    </xs:sequence>
    <xs:anyAttribute namespace="#other" processContents="skip" />
  </xs:complexType>
  <xs:complexType name="customizationType" >
    <xs:sequence>
      <xs:choice minOccurs="1" maxOccurs="1">
        <xs:element name="appAddIn" type="vsto.v4:appAddInType" />
      </xs:choice>
      <xs:any minOccurs="0" maxOccurs="unbounded" namespace="#other" processContents="skip"
/>
    </xs:sequence>
    <xs:attribute name="id" type="xs:string" use="optional" />
    <xs:anyAttribute namespace="#other" processContents="skip" />
  </xs:complexType>
  <xs:complexType name="appAddInType" >
    <xs:sequence>
      <xs:element name="friendlyName" type="xs:string" maxOccurs="1" minOccurs="1"
/>
      <xs:element name="description" type="xs:string" maxOccurs="1" minOccurs="0" />
    </xs:sequence>
  </xs:complexType>

```

```

        <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##other"
processContents="skip" />
    </xs:sequence>
    <xs:attribute name="application" type="xs:string" use="required" fixed="Outlook"
/>
    <xs:attribute name="loadBehavior" type="vsto.v4:loadBehaviorType" use="optional"
/>
    <xs:attribute name="keyName" type="vsto.v4:keyStringType" use="required" />
    <xs:anyAttribute namespace="##other" processContents="skip" />
</xs:complexType>
<xs:simpleType name="loadBehaviorType" >
    <xs:restriction base="xs:int">
        <xs:enumeration value="2" />
        <xs:enumeration value="3" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="keyStringType" >
    <xs:restriction base="xs:string">
        <xs:pattern value="(\u0020|\u0021|[\u0023-\u0029]|[\u002B-
\u0039]|\u003B|\u003D|[\u0040-\u005B]|[\u005D-\u007B]|[\u007D-\uD7FF] |[\uE000-
\uFFFD] |[\u10000-\u10FFFF])*" />
    </xs:restriction>
</xs:simpleType>
</xs:schema>

```

5.3 <http://schemas.microsoft.com/windows/pki/2005/Authenticode>

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema targetNamespace="http://schemas.microsoft.com/windows/pki/2005/Authenticode"
elementFormDefault="qualified"
xmlns="http://schemas.microsoft.com/windows/pki/2005/Authenticode"
xmlns:xs="http://www.w3.org/2001/XMLSchema" xmlns:ds="http://www.w3.org/2000/09/xmldsig#"
xmlns:r="urn:mpeg:mpeg21:2003:01-REL-R-NS" xmlns:asm="urn:schemas-microsoft-com:asm.v1" >
    <xs:import namespace="urn:mpeg:mpeg21:2003:01-REL-R-NS"/>
    <xs:import namespace="urn:schemas-microsoft-com:asm.v1"/>
    <xs:import namespace="http://www.w3.org/2000/09/xmldsig#"/>
<xs:complexType name="ManifestInformationType">
    <xs:sequence>
        <xs:element name="assemblyIdentity" type="asm.v1:assemblyIdentityType"/>
    </xs:sequence>
    <xs:attribute name="Hash" type="ds: CryptoBinary" use="required"/>
    <xs:attribute name="Description" type="xs:string" use="optional"/>
    <xs:attribute name="Url" type="xs:anyURI" use="optional"/>
</xs:complexType>
<xs:complexType name="SignedByType">
    <xs:complexContent>
        <xs:restriction base="r:Right"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="AuthenticodePublisherType">
    <xs:sequence>
        <xs:element name="X509SubjectName" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:element name="ManifestInformation" type="ManifestInformationType"/>
<xs:element name="SignedBy" type="SignedByType"/>
<xs:element name="AuthenticodePublisher" type="AuthenticodePublisherType"/>
<xs:element name="Timestamp" type="ds: CryptoBinary"/>

```

</xs:schema>

6 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Office 2010 suites
- Microsoft® OneNote® Web App
- Microsoft® PowerPoint® Web App
- Microsoft® SharePoint® Server 2010
- Microsoft® SharePoint® Workspace 2010

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

8 Index

A

[Algorithms](#) 77
 [conversion from RS public key to publicKeyToken](#)
 78
 [converting an X.500 distinguish name to a string](#)
 81
 [CryptoAPI UBLICKEYBLOB format](#) 78
 [HashTransforms.Identity](#) 77
 [PublicKeyBlob format](#) 79
 [REL license verification](#) 80
 [software publisher certificate processing](#) 80
 [software publisher identity verification](#) 79
 [timestamp processing](#) 81
 [verification of strong name signature](#) 77
[Applicability](#) 11
[Application manifest](#) 22
 Application manifest – schema asm.v1
 [global_attributes](#) 23
[Application Manifest example](#) 85
[Application manifest xml schemas](#) 92
Attributes – schema asm.v2
 [product](#) 18
 [publisher](#) 17

C

[Change tracking](#) 103
Common data types and fields ([section 2](#) 13, [section 2](#) 13)
Complex type – schema reldata
 [RelDataType](#) 59
Complex types
 xmldsig#
 [CanonicalizationMethodType](#) 71
 [DigestMethodType](#) 73
 [KeyInfoType](#) 74
 [KeyValue-Type](#) 75
 [ObjectType](#) 73
 [ReferenceType](#) 71
 [RSAKeyValue-Type](#) 76
 [SignatureMethodType](#) 71
 SignatureType ([section 2.4.3.3.1](#) 69, [section 2.4.3.3.2](#) 70)
 [SignedInfoType](#) 70
 [TransformsType](#) 72
 [TransformType](#) 73
 [X509Data-Type](#) 75
Complex types – Authenticode schema
 [AuthenticodePublisherType](#) 64
 [ManifestInformationType](#) 63
 [SignedByType](#) 64
Complex types – schema asm.v1
 [assemblyIdentityType](#) ([section 2.1.1.3.1](#) 13, [section 2.2.1.3.1](#) 23)
 [assemblyType](#) ([section 2.1.1.3.3](#) 14, [section 2.2.1.3.2](#) 23)
 [descriptionType](#) 14
Complex types – schema asm.v2

[applicationRequestMinimumType](#) 34
[applicationType](#) 28
 [assemblyIdentityType](#) ([section 2.1.2.3.5](#) 20, [section 2.2.2.3.8](#) 31)
 [defaultAssemblyRequestType](#) 35
[dependencyType](#) ([section 2.1.2.3.2](#) 18, [section 2.2.2.3.2](#) 28)
 [dependentAssemblyType](#) ([section 2.1.2.3.3](#) 19, [section 2.2.2.3.3](#) 28)
 [dependentOSType](#) 30
 [deploymentType](#) 18
 [entryPointType](#) 32
 [fileType](#) 35
 [hashType](#) ([section 2.1.2.3.4](#) 19, [section 2.2.2.3.4](#) 29)
 [osType](#) 31
 [osVersionInfoType](#) 30
 [PermissionSetType](#) 34
 [publisherIdentityType](#) ([section 2.1.2.3.6](#) 21, [section 2.2.2.3.9](#) 32)
 [securityType](#) 33
 [trustInfoType](#) 33
[Complex types - schema clickonce.v1](#) 40
Complex types – schema vsta.v3
 [addInType](#) 40
 [applicationType](#) 45
 [entryPointsCollectionType](#) 41
 [entryPointsType](#) 42
 [entryPointType](#) 42
 [postActionData-Type](#) 45
 [postActionEntryPointType](#) 43
 [postActionsType](#) 44
 [postActionType](#) 44
 [updateType](#) 43
Complex types – schema vsto.v4
 [appAddInType](#) 47
 [customizationsType](#) 46
 [customizationType](#) 46
Complex types – schema xmldsig#
 [CanonicalizationMethodType](#) 54
 [DigestMethodType](#) 56
 [KeyInfoType](#) 57
 [KeyValue-Type](#) 57
 [ReferenceType](#) 55
 [RSAKeyValue-Type](#) 58
 [SignatureMethodType](#) 54
 [SignatureType](#) 52
 [SignatureValue-Type](#) 53
 [SignedInfoType](#) 53
 [TransformsType](#) 55
 [TransformType](#) 56
Complex types – URN 01-REL-R-NS
 [Grant](#) 61
 [Issuer](#) 61
 [License](#) 60
 [Right](#) 62
[Conversion from RSA public key to publicKeyToken algorithm](#) 78

[Converting an X.500 distinguish name to a string algorithm](#) 81
[CryptoAPI PUBLICKEYBLOB format algorithm](#) 78

D

Data types and fields - common ([section 2](#) 13, [section 2](#) 13)
[Deployment manifest](#) 13
[Deployment Manifest example](#) 83
[Deployment manifest XML schemas](#) 90
Details
[algorithms](#) 77
[application manifest](#) 22
common data types and fields ([section 2](#) 13, [section 2](#) 13)
[conversion from RSA public key to publicKeyToken algorithm](#) 78
[converting an X.500 distinguish name to a string algorithm](#) 81
[CryptoAPI PUBLICKEYBLOB format algorithm](#) 78
[deployment manifest](#) 13
[HashTransforms.Identity algorithm](#) 77
[PublicKeyBlob format algorithm](#) 79
[REL license verification algorithm](#) 80
[software publisher certificate processing algorithm](#) 80
[software publisher identity verification algorithm](#) 79
[strong name signature](#) 48
[timestamp processing algorithm](#) 81
[verification of strong name signature algorithm](#) 77
Details – Authenticode schema
[AuthenticodePublisher element](#) 63
[AuthenticodePublisherType complex type](#) 64
[ManifestInformation element](#) 62
[ManifestInformationType complex type](#) 63
[SignedBy element](#) 62
[SignedByType complex type](#) 64
[Timestamp element](#) 63
Details – schema asm.v1
[assembly element](#) ([section 2.1.1.1](#) 13, [section 2.2.1.1](#) 22)
[assemblyIdentityType complex type](#) ([section 2.1.1.3](#) 13, [section 2.2.1.3](#) 23)
[assemblyType complex type](#) 14
[descriptorType complex type](#) 14
[fileNameStringType simple type](#) ([section 2.1.1.4](#) 16, [section 2.2.1.4](#) 25)
[fourPartVersionType simple type](#) ([section 2.1.1.4](#) 16, [section 2.2.1.4](#) 25)
[publicKeyTokenType simple type](#) ([section 2.1.1.4](#) 16, [section 2.2.1.4](#) 25)
[twoPartVersionType simple type](#) ([section 2.1.1.4](#) 15, [section 2.2.1.4](#) 24)
Details – schema asm.v2
[application element](#) 26
[applicationRequestMinimumType complex type](#) 34
[applicationType complex type](#) 28
[assemblyIdentity element](#) 27

[assemblyIdentityType complex type](#) ([section 2.1.2.3.5](#) 20, [section 2.2.2.3.8](#) 31)
[defaultAssemblyRequestType complex type](#) 35
[dependency element](#) ([section 2.1.2.1.2](#) 17, [section 2.2.2.1.4](#) 27)
[dependencyType complex type](#) ([section 2.1.2.3.2](#) 18, [section 2.2.2.3.2](#) 28)
[dependencyTypeType simple type](#) 36
[dependentAssemblyType complex type](#) ([section 2.1.2.3.3](#) 19, [section 2.2.2.3.3](#) 28)
[dependentOSType complex type](#) 30
[deployment element](#) 17
[deploymentType complex type](#) 18
[entryPoint element](#) 26
[entryPointType complex type](#) 32
[file element](#) 27
[fileNameStringType simple type](#) ([section 2.1.2.4.2](#) 22, [section 2.2.2.4.4](#) 37)
[fileType complex type](#) 35
[fourPartVersionType simple type](#) ([section 2.1.2.4.1](#) 21, [section 2.2.2.4.5](#) 37)
[hashType complex type](#) ([section 2.1.2.3.4](#) 19, [section 2.2.2.3.4](#) 29)
[OneByteVersion simple type](#) 36
[osType complex type](#) 31
[osVersionInfoType complex type](#) 30
[PermissionSetType complex type](#) 34
[product attribute](#) 18
[publicKeyTokenType simple type](#) 37
[publicKeyTokenType simple type](#) 22
[publisher attribute](#) 17
[publisherIdentity element](#) ([section 2.1.2.1.3](#) 17, [section 2.2.2.1.7](#) 27)
[publisherIdentityType complex type](#) ([section 2.1.2.3.6](#) 21, [section 2.2.2.3.9](#) 32)
[securityType complex type](#) 33
[trustInfo element](#) 26
[trustInfoType complex type](#) 33
[TwoByteVersion simple type](#) 36
Details – schema asm.v3
[asmv3 element](#) 38
[asmv3Type complex type](#) 39
[requestedExecutionLevelType complex type](#) 39
[requestedPrivilegesType complex type](#) 38
Details - schema clickonce.v1
[customHostSpecified Type complex type](#) 40
Details – schema clickonce.v1
[customHostSpecified element](#) 39
Details - schema reldata
[RelData element](#) 59
[RelDataType complex type](#) 59
Details - schema vsta.v3
[addIn element](#) 40
[addInType complex type](#) 40
[applicationType complex type](#) 45
[entryPointsCollectionType complex type](#) 41
[entryPointsType complex type](#) 42
[entryPointType complex type](#) 42
[postActionDataType complex type](#) 45
[postActionEntryPointtype complex type](#) 43
[postActionsType complex type](#) 44

[postActionType complex type](#) 44
[simple types](#) 45
[updateType complex type](#) 43
 Details - schema vsto.v4
[appAddInType complex type](#) 47
[customizations element](#) 45
[customizationsType complex type](#) 46
[customizationType complex type](#) 46
[keyStringType simple type](#) 48
[loadBehaviorType simple type](#) 48
 Details - schema xmlsig#
[CanonicalizationMethod element](#) 49
[CanonicalizationMethodType complex type](#) 54
[CryptoBinary simple type](#) 58
[DigestMethod element](#) 51
[DigestMethodType complex type](#) 56
[DigestValue element](#) 51
[DigestValueType simple type](#) 59
[KeyInfo element](#) 51
[KeyInfoType complex type](#) 57
[KeyValue element](#) 52
[KeyValue-Type complex type](#) 57
[Reference element](#) 50
[ReferenceType complex type](#) 55
[RSAKeyValue element](#) 52
[RSAKeyValue-Type complex type](#) 58
[Signature element](#) 49
[SignatureMethod element](#) 50
[SignatureMethodType complex type](#) 54
[SignatureType complex type](#) 52
[SignatureValue element](#) 49
[SignatureValueType complex type](#) 53
[SignedInfo element](#) 49
[SignedInfoType complex type](#) 53
[Transform element](#) 51
[Transforms element](#) 50
[TransformsType complex type](#) 55
[TransformType complex type](#) 56
 Details - URN 01-REL-R-NS
[Grant complex type](#) 61
[Issuer complex type](#) 61
[License complex type](#) 60
[license element](#) 60
[Right complex type](#) 62
 Details - xmlsig#
[CanonicalizationMethod element](#) 66
[CanonicalizationMethodType complex type](#) 71
[CryptoBinary simple type](#) 76
[DigestMethod element](#) 67
[DigestMethodType complex type](#) 73
[DigestValue element](#) 67
[DigestValueType simple type](#) 77
[KeyInfo element](#) 68
[KeyInfoType complex type](#) 74
[KeyValue element](#) 68
[KeyValue-Type complex type](#) 75
[Object element](#) 68
[ObjectType complex type](#) 73
[Reference element](#) 66
[ReferenceType complex type](#) 71
[RSAKeyValue element](#) 69

[RSAKeyValue-Type complex type](#) 76
[Signature element](#) 65
[SignatureMethod element](#) 66
[SignatureMethodType complex type](#) 71
[SignatureType complex type](#) ([section 2.4.3.3.1](#)
 69, [section 2.4.3.3.2](#) 70)
[SignatureValue element](#) 65
[SignedInfo element](#) 65
[SignedInfoType complex type](#) 70
[Transform element](#) 67
[Transforms element](#) 66
[TransformsType complex type](#) 72
[TransformType complex type](#) 73
[X509Data element](#) 68
[X509DataType complex type](#) 75
 Details schema asm.v1
[assemblyType complex type](#) 23

E

Elements - Authenticode schema
[AuthenticodePublisher](#) 63
[ManifestInformation](#) 62
[SignedBy](#) 62
[Timestamp](#) 63
 Elements - schema asm.v1
[assembly](#) 22
 Elements - schema asm.v2
[application](#) 26
[assemblyIdentity](#) 27
[dependency](#) ([section 2.1.2.1.2](#) 17, [section 2.2.2.1.4](#) 27)
[deployment](#) 17
[entryPoint](#) 26
[file](#) 27
[publisherIdentity](#) ([section 2.1.2.1.3](#) 17, [section 2.2.2.1.7](#) 27)
[trustInfo](#) 26
 Elements - schema asm.v3
[asmv3](#) 38
 Elements - schema clickonce.v1
[customHostSpecified](#) 39
 Elements - schema reldata
[RelData](#) 59
 Elements - schema vsta.v3
[addin](#) 40
 Elements - schema vsto.v4
[customizations](#) 45
 Elements - schema xmlsig#
[CanonicalizationMethod](#) 49
[DigestMethod](#) 51
[DigestValue](#) 51
[KeyInfo](#) 51
[KeyValue](#) 52
[Reference](#) 50
[RSAKeyValue](#) 52
[Signature](#) 49
[SignatureMethod](#) 50
[SignatureValue](#) 49
[SignedInfo](#) 49
[Transform](#) 51
[Transforms](#) 50

Elements – URN 01-REL-R-NS

[license](#) 60

Elements – xmldsig#

[CanonicalizationMethod](#) 66

[DigestMethod](#) 67

[DigestValue](#) 67

[KeyInfo](#) 68

[KeyValue](#) 68

[Object](#) 68

[Reference](#) 66

[RSAKeyValue](#) 69

[Signature](#) 65

[SignatureMethod](#) 66

[SignatureValue](#) 65

[SignedInfo](#) 65

[Transform](#) 67

[Transforms](#) 66

[X509Data](#) 68

[Examples](#) 83

[Application Manifest](#) 85

[Deployment Manifest](#) 83

[overview](#) 83

F

[Fields - vendor-extensible](#) 12

G

Global attributes

[Authenticode schema](#) 63

[schema asm.v1](#) 13

[schema asm.v2](#) 27

[schema asm.v3](#) 38

[schema clickonce.v1](#) 40

[schema reldata](#) 59

[schema vsta.v3](#) 40

[schema vsto.v4](#) 46

[schema xmldsig#](#) 52

[URN 01-REL-R-NS](#) 60

[xmldsig#](#) 69

Global attributes – schema asm.v1

[application manifest](#) 23

[Glossary](#) 9

H

[HashTransforms.Identity algorithm](#) 77

http

<http://schemas.microsoft.com/windows/pki/2005/Authenticode> 100

I

[Implementer - security considerations](#) 89

[Informative references](#) 11

[Introduction](#) 9

L

[Localization](#) 12

N

[Normative references](#) 10

O

[Overview \(synopsis\)](#) 11

P

[Product behavior](#) 102

[PublicKeyBlob format algorithm](#) 79

R

References

[informative](#) 11

[normative](#) 10

[REL license verification algorithm](#) 80

[Relationship to protocols and other structures](#) 11

S

Schema asm.v1

assembly element ([section 2.1.1.1.1](#) 13, [section 2.2.1.1.1](#) 22)

assemblyIdentityType complex type ([section 2.1.1.3.1](#) 13, [section 2.2.1.3.1](#) 23)

assemblyType complex type ([section 2.1.1.3.3](#) 14, [section 2.2.1.3.2](#) 23)

[descriptiontype complex type](#) 14

[fileNameString simple type](#) 16

[fileNameStringType simple type](#) 25

fourPartVersionType simple type ([section 2.1.1.4.3](#) 16, [section 2.2.1.4.3](#) 25)

[global attributes](#) 13

[publicKeyTokenType simple type](#) ([section 2.1.1.4.2](#) 16, [section 2.2.1.4.2](#) 25)

twoPartVersionType simple type ([section 2.1.1.4.1](#) 15, [section 2.2.1.4.1](#) 24)

Schema asm.v2

[application element](#) 26

[applicationRequestMinimumType complex type](#) 34

[applicationType complex type](#) 28

[assemblyIdentity element](#) 27

assemblyIdentityType complex type ([section 2.1.2.3.5](#) 20, [section 2.2.2.3.8](#) 31)

[defaultAssemblyRequestType complex type](#) 35

[dependency complex type](#) 18

dependency element ([section 2.1.2.1.2](#) 17, [section 2.2.2.1.4](#) 27)

[dependencyType complex type](#) 28

[dependencyTypeType simple type](#) 36

dependentAssemblyType complex type ([section 2.1.2.3.3](#) 19, [section 2.2.2.3.3](#) 28)

[dependentOSType complex type](#) 30

[deployment complex type](#) 18

[deployment element](#) 17

[entryPoint element](#) 26

[entryPointType complex type](#) 32

[file element](#) 27

fileNameStringType simple type ([section 2.1.2.4.2](#) 22, [section 2.2.2.4.4](#) 37)
fileType complex type 35
fourPartVersionType simple type ([section 2.1.2.4.1](#) 21, [section 2.2.2.4.5](#) 37)
global attributes 27
hashType complex type ([section 2.1.2.3.4](#) 19, [section 2.2.2.3.4](#) 29)
OneByteVersion simple type 36
osType complex type 31
osVersionInfoType complex type 30
PermissionSetType complex type 34
product attribute 18
publicKeyTokenType simple type ([section 2.1.2.4.3](#) 22, [section 2.2.2.4.6](#) 37)
publisher attribute 17
publisherIdentity element ([section 2.1.2.1.3](#) 17, [section 2.2.2.1.7](#) 27)
publisherIdentityType complex type ([section 2.1.2.3.6](#) 21, [section 2.2.2.3.9](#) 32)
securityType complex type 33
trustInfo element 26
trustInfoType complex type 33
TwoByteVersion simple type 36
Schema **asm.v3**
 asmv3 element 38
 asmv3Type complex type 39
 global attributes 38
 requestedExecutionLevelType complex type 39
 requestedPrivilegesType complex type 38
 simple types 39
Schema **clickonce.v1**
 customHostSpecified element 39
 customHostSpecifiedType complex type 40
 global attributes 40
 simple types 40
Schema **vsta.v3**
 addIn element 40
 addInType complex type 40
 applicationType complex type 45
 entryPointsCollectionType complex type 41
 entryPointsType complex type 42
 entryPointType complex type 42
 global attributes 40
 postActionDataType complex type 45
 postActionEntryPointType complex type 43
 postActionsType complex type 44
 postActionType complex type 44
 updateType complex type 43
Schema **vsto.v4**
 appAddInType complex type 47
 customizations element 45
 customizationsType complex type 46
 customizationType complex type 46
 global attributes 46
 keyStringType simple type 48
 loadBehaviorType simple type 48
Security
 digital signatures 89
Security - implementer considerations 89
Simple types

Authenticode schema 65
schema asm.v3 39
schema clickonce.v1 40
schema reldata 60
schema vsta.v3 45
URN 01-REL-R-NS 62
xmldsig#
 CryptoBinary 76
 DigestValueType 77
Simple types – schema **asm.v1**
 fileNameString 16
 fileNameStringType 25
 fourPartVersion 16
 fourPartVersionType 25
 publicKeyTokenType ([section 2.1.1.4.2](#) 16, [section 2.2.1.4.2](#) 25)
 twoPartVersion 15
 twoPartVersionType 24
Simple types – schema **asm.v2**
 dependencyTypeType 36
 fileNameStringType ([section 2.1.2.4.2](#) 22, [section 2.2.2.4.4](#) 37)
 fourPartVersionType ([section 2.1.2.4.1](#) 21, [section 2.2.2.4.5](#) 37)
 OneByteVersion 36
 publicKeyTokenType 22
 TwoByteVersion 36
 TwoByteVersionType 37
Simple types – schema **asm.v3**
 asmv3Type 39
 requestedExecutionLevelType 39
 requestedPrivilegesType 38
Simple types – schema **vsto.v4**
 keyStringType 48
 loadBehaviorType 48
Simple types – schema **xmldsig#**
 CryptoBinary 58
 DigestValueType 59
Software publisher certificate processing algorithm 80
Software publisher identity verification algorithm 79
Strong name signature 48
Structures
 algorithms 77
 application manifest 22
 deployment manifest 13
 overview ([section 2](#) 13, [section 2](#) 13)
 strong name signature 48
Structures – schema **asm.v1**
 assembly element 13
 global attributes 13

T

[Timestamp processing algorithm](#) 81
[Tracking changes](#) 103

V

[Vendor-extensible fields](#) 12
[Verification of strong name signature algorithm](#) 77
[Versioning](#) 12

X

XML schema files
[application manifest xml schemas](#) 92
[deployment manifest xml schemas](#) 90
http
 [/schemas.microsoft.com/windows/pki/2005/A](http://schemas.microsoft.com/windows/pki/2005/A)
 [uthtenticode](#) 100

Xmldsig#
 [CanonicalizationMethodType complex type](#) 71
 [CryptoBinary simple type](#) 76
 [DigestMethodType complex type](#) 73
 [DigestValueType simple type](#) 77
 [KeyInfoType complex type](#) 74
 [KeyValue-Type complex type](#) 75
 [ObjectType complex type](#) 73
 [ReferenceType complex type](#) 71
 [RSAKeyValue-Type complex type](#) 76
 [Signature element](#) 65
 [SignatureMethodType complex type](#) 71
 [SignatureType complex type](#) 70
 [SignedInfoType complex type](#) 70
 [TransformsType complex type](#) 72
 [TransformType complex type](#) 73
 [X509Data-Type complex type](#) 75