

[MS-OXORSS]: RSS Object Protocol Specification

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.aspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

| Date | Revision History | Revision Class | Comments |
|------------|------------------|----------------|--|
| 04/04/2008 | 0.1 | | Initial Availability. |
| 04/25/2008 | 0.2 | | Revised and updated property names and other technical content. |
| 06/27/2008 | 1.0 | | Initial Release. |
| 08/06/2008 | 1.01 | | Revised and edited technical content. |
| 09/03/2008 | 1.02 | | Revised and edited technical content. |
| 12/03/2008 | 1.03 | | Revised and edited technical content. |
| 04/10/2009 | 2.0 | | Updated applicable product releases. |
| 07/15/2009 | 3.0 | Major | Revised and edited for technical content. |
| 11/04/2009 | 4.0.0 | Major | Updated and revised the technical content. |
| 02/10/2010 | 4.1.0 | Minor | Updated the technical content. |
| 05/05/2010 | 5.0.0 | Major | Updated and revised the technical content. |
| 08/04/2010 | 5.0.0 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 11/03/2010 | 5.0.0 | No change | No changes to the meaning, language, or formatting of the technical content. |

Contents

| | |
|--|-----------|
| 1 Introduction | 5 |
| 1.1 Glossary | 5 |
| 1.2 References | 5 |
| 1.2.1 Normative References | 5 |
| 1.2.2 Informative References | 6 |
| 1.3 Overview | 6 |
| 1.4 Relationship to Other Protocols | 6 |
| 1.5 Prerequisites/Preconditions | 6 |
| 1.6 Applicability Statement | 7 |
| 1.7 Versioning and Capability Negotiation | 7 |
| 1.8 Vendor-Extensible Fields | 7 |
| 1.9 Standards Assignments | 7 |
| 2 Messages | 8 |
| 2.1 Transport | 8 |
| 2.2 Message Syntax | 8 |
| 2.2.1 RSS Item Properties | 8 |
| 2.2.1.1 PidLidPostRssChannelLink | 8 |
| 2.2.1.2 PidLidPostRssItemLink | 8 |
| 2.2.1.3 PidLidPostRssItemHash | 9 |
| 2.2.1.4 PidLidPostRssItemGuid | 9 |
| 2.2.1.5 PidLidPostRssChannel | 9 |
| 2.2.1.6 PidLidPostRssItemXml | 9 |
| 2.2.1.7 PidLidPostRssSubscription | 9 |
| 2.2.1.8 PidTagMessageDeliveryTime | 9 |
| 2.2.2 Additional Property Constraints | 10 |
| 2.2.2.1 Attachment Objects | 10 |
| 2.2.2.1.1 Full Article Attachment Objects | 10 |
| 2.2.2.1.2 Enclosure Attachment Objects | 10 |
| 2.2.2.1.3 Other Attachment Objects | 10 |
| 2.2.2.2 PidNameExchangeJunkEmailMoveStamp | 10 |
| 2.2.2.3 PidTagMessageClass | 11 |
| 2.2.2.4 PidTagSenderName | 11 |
| 2.2.2.5 PidTagSenderEmailAddress | 11 |
| 2.2.2.6 PidTagSentRepresentingName | 11 |
| 2.2.2.7 PidTagSentRepresentingEmailAddress | 12 |
| 2.2.2.8 Recipients | 12 |
| 3 Protocol Details | 13 |
| 3.1 Common Details | 13 |
| 3.1.1 Abstract Data Model | 13 |
| 3.1.1.1 RSS Objects | 13 |
| 3.1.1.2 Folder Objects | 13 |
| 3.1.2 Timers | 13 |
| 3.1.3 Initialization | 13 |
| 3.1.4 Higher-Layer Triggered Events | 13 |
| 3.1.4.1 Creation of an RSS Object | 13 |
| 3.1.4.2 Modification of an RSS Object | 13 |
| 3.1.4.3 Deletion of an RSS Object | 13 |
| 3.1.5 Message Processing Events and Sequencing Rules | 14 |

| | | |
|----------|--|-----------|
| 3.1.6 | Timer Events | 14 |
| 3.1.7 | Other Local Events | 14 |
| 4 | Protocol Examples | 15 |
| 5 | Security | 19 |
| 5.1 | Security Considerations for Implementers | 19 |
| 5.2 | Index of Security Parameters | 19 |
| 6 | Appendix A: Product Behavior | 20 |
| 7 | Change Tracking..... | 21 |
| 8 | Index | 22 |

1 Introduction

This document specifies the RSS Object protocol, which defines **properties** of an object that model an item transmitted in a news feed format.

1.1 Glossary

The following terms are defined in [\[MS-OXGLOS\]](#):

Attachment object
Coordinated Universal Time (UTC)
feed
flags
Folder object
handle
Mail User Agent (MUA)
message
Message object
named property
property (1)
property ID
recipient (1)
remote operation (ROP)
restrictions
search criteria
Uniform Resource Locator (URL)
XML

The following terms are specific to this document:

Atom: The Atom Syndication Format, an **XML** format for Web **feeds**, as described in [\[RFC4287\]](#).

enclosure: An **XML** element in a **feed** that contains information, including a **URL**, about a file (usually a media file) that is associated with an **RSS** item or **Atom** entry (for example, a podcast).

RSS: An **XML** format for Web **feeds**, as described in [\[RSS2.0\]](#).

RSS object: A **Message object** that represents an entry from an **RSS** item or **Atom feed** and that adheres to the property descriptions in this document.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)", April 2008.

[MS-OXCFOLD] Microsoft Corporation, "[Folder Object Protocol Specification](#)", April 2008.

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol Specification](#)", April 2008.

[MS-OXCPRPT] Microsoft Corporation, "[Property and Stream Object Protocol Specification](#)", April 2008.

[MS-OXCSPAM] Microsoft Corporation, "[Spam Confidence Level Protocol Specification](#)", April 2008.

[MS-OXOMSG] Microsoft Corporation, "[E-Mail Object Protocol Specification](#)", April 2008.

[MS-OXPROPS] Microsoft Corporation, "[Exchange Server Protocols Master Property List](#)", April 2008.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>

[RFC4287] Nottingham, M., and Sayre, R., Eds., "The Atom Syndication Format", RFC 4287, December 2005, <http://www.ietf.org/rfc/rfc4287.txt>

[RSS2.0] Winer, D., "RSS 2.0 Specification", July 2003, <http://cyber.law.harvard.edu/rss/rss.html>

1.2.2 Informative References

[MS-OXBBODY] Microsoft Corporation, "[Best Body Retrieval Protocol Specification](#)", April 2008.

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)", April 2008.

1.3 Overview

The RSS Object protocol allows the representation of entries from **RSS** and **Atomfeeds**. The RSS Object protocol extends the Message and Attachment Object protocol in that it defines new properties and adds **restrictions** to the properties that are defined in [\[MS-OXCMSG\]](#).

The properties that are specific to an **RSS object** allow conversion from the **XML** of an RSS item ([\[RSS2.0\]](#)) or Atom entry ([\[RFC4287\]](#)), including metadata about the feed from which the item or entry came, to properties on a **Message object**. In addition to mapping XML entities from the two formats to shared properties, the XML of the entire RSS item or Atom entry is saved on the Message object.

1.4 Relationship to Other Protocols

The RSS object protocol has the same dependencies as the Message and Attachment Object protocol, which it extends. For details about the Message and Attachment Object protocol, see [\[MS-OXCMSG\]](#).

The RSS object protocol is a peer of the E-Mail Object protocol, and uses a subset of the properties specified in [\[MS-OXOMSG\]](#).

1.5 Prerequisites/Preconditions

The RSS Object protocol has the same prerequisites and preconditions as the Message and Attachment Object protocol, as specified in [\[MS-OXCMSG\]](#).

1.6 Applicability Statement

None.

1.7 Versioning and Capability Negotiation

None.

1.8 Vendor-Extensible Fields

This protocol provides no extensibility beyond what is already specified in [\[MS-OXCMSG\]](#).

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

The RSS Object protocol uses the protocols specified in [\[MS-OXCPRPT\]](#) and [\[MS-OXCMSG\]](#) as its primary transport mechanism.

2.2 Message Syntax

An RSS object can be created and modified by clients and servers. Except where noted below, this section defines constraints under which both clients and servers operate.

Clients operate on RSS objects by using the Message and Attachment Object protocol, as specified in [\[MS-OXCMSG\]](#). How a server operates on RSS objects is implementation-dependent. The results of any such operation are exposed to clients in a manner that is consistent with the RSS Object protocol.

Unless otherwise specified, an RSS object adheres to all property constraints, as specified in [\[MS-OXPROPS\]](#), and all property constraints, as specified in [\[MS-OXCMSG\]](#). An RSS object can also contain other properties, which are specified in [\[MS-OXPROPS\]](#), but these properties have no impact on the RSS Object protocol.

RSS feeds can be represented by using either the RSS or Atom protocols. Protocol clients **MUST** be capable of parsing Atom version 0.3, Atom version 1.0, RSS version 1.0, and RSS version 2.0, and creating RSS protocol objects based on those protocols.

RSS object properties can be of several different data types. The following data types used by RSS object properties are specified in [\[MS-OXCDATA\]](#) section 2.11.1:

- **PtypBinary**
- **PtypInteger32**
- **PtypString**
- **PtypString8**
- **PtypTime**

2.2.1 RSS Item Properties

The following properties that are specific to RSS objects are defined in this specification.

2.2.1.1 PidLidPostRssChannelLink

Type: **PtypString**.

Contains the **URL** of the RSS or Atom feed that the XML file came from.

2.2.1.2 PidLidPostRssItemLink

Type: **PtypString**.

Contains the URL of the link from the item. For an RSS item, this is the contents of the <link> sub-element. For an Atom entry, the following applies:

- If the rel attribute is not present, or if it is present and set to "alternate", then [PidLidPostRssItemLink](#) contains the value of the href attribute.
- If the rel attribute is present and set to anything besides "alternate", then [PidLidPostRssItemLink](#) is not set.

2.2.1.3 PidLidPostRssItemHash

Type: **PtypInteger32**.

Contains a hash of the feed XML computed by using an implementation-dependent algorithm; used to quickly determine whether two items are different.

2.2.1.4 PidLidPostRssItemGuid

Type: **PtypString**.

Contains a unique identifier for the object, copied from one of the elements listed in the following table.

| RSS items | Atom entries |
|-----------|--------------|
| <GUID> | <id> |
| <link> | <link> |

Note The href attribute of the <link> element is used for Atom entries if the <id> element is not present.

2.2.1.5 PidLidPostRssChannel

Type: **PtypString**.

Contains the contents of the <title> field from the XML of the Atom <feed> or RSS <channel>.

2.2.1.6 PidLidPostRssItemXml

Type: **PtypString**.

Contains the <item> element and all its sub-elements from an RSS feed, or the <entry> element and all its sub-elements from an Atom feed.

2.2.1.7 PidLidPostRssSubscription

Type: **PtypString**.

Contains the user's preferred name for the subscription.

2.2.1.8 PidTagMessageDeliveryTime

Type: **PtypTime**, in **UTC**.

An optional element that specifies the posting date of the item or entry, copied from one of the elements listed in the following table.

| RSS items | Atom entries |
|-----------|--------------|
| <date> | <modified> |
| <pubDate> | <issued> |
| | <updated> |
| | <published> |

If neither <date> nor <pubDate> is defined in the RSS item, then use the <lastBuildDate> element.

The Atom elements are defined as children of the <entry> element. The <modified> and <updated> elements are also defined as children of the <feed> element. If the <modified>, <issued>, <updated> or <published> elements are not defined under the <entry> element, then use the <modified> or <updated> elements under the <feed> element.

If no such element exists, then set to the current time.

2.2.2 Additional Property Constraints

This protocol specifies additional constraints on the following properties beyond what is specified in [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), and [\[MS-OXCSPAM\]](#).

2.2.2.1 Attachment Objects

2.2.2.1.1 Full Article Attachment Objects

A full article **Attachment object** contains the contents of the linked document. Its [PidTagAttachMethod](#) MUST be 0x00000001: afByValue (see [\[MS-OXCMSG\]](#)). The [PidLidPostRssItemLink](#) **property** MUST be set to the URL from which the document was downloaded.

An RSS object MUST NOT have more than one full article Attachment object.

2.2.2.1.2 Enclosure Attachment Objects

An **enclosure** Attachment object contains the contents of an enclosure, which is a file referenced in the **href** attribute of a <link> tag where the **rel** attribute is "enclosure" for an Atom entry, or the <enclosure> element of an RSS item.

An enclosure Attachment object MUST have a [PidTagAttachMethod](#) of 0x00000001: afByValue (see [\[MS-OXCMSG\]](#)). [PidLidPostRssItemLink](#) MUST be set to the URL from which the enclosure was downloaded.

2.2.2.1.3 Other Attachment Objects

An RSS object MUST NOT have Attachment objects other than full article Attachment objects and enclosure Attachment objects.

2.2.2.2 PidNameExchangeJunkEmailMoveStamp

As specified in [\[MS-OXCSPAM\]](#), but MUST be set on all RSS objects.

2.2.2.3 PidTagMessageClass

Type: **PtypString**, case-insensitive.

Specifies the type of the **message** item. The value MUST be "IPM.Post.RSS" or begin with "IPM.Post.RSS", in addition to meeting the criteria specified in [\[MS-OXCMSG\]](#).

2.2.2.4 PidTagSenderName

Type: **PtypString**.

Contains origination information about the RSS object, copied from one of the elements in the following table. If no such element exists, set to an empty string.

| RSS items | Atom entries |
|--------------|--------------|
| <author> | <name> |
| <publisher>* | <title>* |
| <title>* | |

Note *The element is from the metadata rather than the individual item or feed.

This property is further specified in [\[MS-OXOMSG\]](#).

2.2.2.5 PidTagSenderEmailAddress

Type: **PtypString**.

Contains the contents of the <email> element of the <author> element in an Atom entry if it exists. Does not apply to an RSS item.

This property is further specified in [\[MS-OXOMSG\]](#).

2.2.2.6 PidTagSentRepresentingName

Type: **PtypString**.

Contains origination information about the RSS object, copied from one of the elements in the following table. If no such element exists, set to an empty string.

| RSS items | Atom entries |
|--------------|--------------------|
| <author> | <name> of <author> |
| <publisher>* | <title>* |
| <title>* | |

Note *The element is from the metadata, rather than the individual item or feed.

This property is further specified in [\[MS-OXOMSG\]](#).

2.2.2.7 PidTagSentRepresentingEmailAddress

Type: **PtypString**.

Contains the contents of the <email> element of the <author> element in an Atom entry, if it exists. Does not apply to an RSS item.

This property is further specified in [\[MS-OXOMSG\]](#).

2.2.2.8 Recipients

An RSS object MUST NOT have **recipients**.

3 Protocol Details

General protocol details, as specified in [\[MS-OXPROPS\]](#) and [\[MS-OXCMSG\]](#), apply to RSS objects.

3.1 Common Details

The client and server roles are to create and manipulate RSS objects, and otherwise operate in their respective roles, as specified in [\[MS-OXCMSG\]](#).

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

3.1.1.1 RSS Objects

An RSS object extends the Message object, as specified in [\[MS-OXCMSG\]](#).

3.1.1.2 Folder Objects

RSS objects are created in **Folder objects** that have a container class of "IPF.Note.OutlookHomepage" unless the **Mail User Agent (MUA)** explicitly specifies otherwise.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Higher-Layer Triggered Events

3.1.4.1 Creation of an RSS Object

To create an RSS object, the server or client creates a Message object, as specified in [\[MS-OXCMSG\]](#), sets properties in accordance with the requirements specified in [\[MS-OXCPRPT\]](#) section 2, and saves the resulting Message object as specified in [\[MS-OXCMSG\]](#). In particular, the [PidNameExchangeJunkEmailMoveStamp](#) property MUST be set before the RSS object is saved the first time.

3.1.4.2 Modification of an RSS Object

When modifying an RSS object, the server or client opens a Message object, as specified in [\[MS-OXCMSG\]](#), modifies any properties in accordance with the requirements specified in [\[MS-OXCPRPT\]](#) section 2, and saves the resulting Message object as specified in [\[MS-OXCMSG\]](#).

3.1.4.3 Deletion of an RSS Object

RSS objects have no special semantics in relation to deletion beyond what is specified in [\[MS-OXCFOLD\]](#).

3.1.5 Message Processing Events and Sequencing Rules

None.

3.1.6 Timer Events

None.

3.1.7 Other Local Events

None.

4 Protocol Examples

Joe subscribes to an RSS feed. The client polls the feed and finds a new item. The following is a description of what a client might do to accomplish Joe's intentions and describes the responses a server might return. For information about **remote operations (ROPs)**, see [\[MS-OXCPRPT\]](#) and [\[MS-OXCMSG\]](#).

Before manipulating RSS objects, the client needs to ask the server to perform a mapping from **named properties** to **property IDs**, by using [RopGetPropertyIDsFromNames](#).

| Property | Property set GUID | NameID |
|---|--|--------|
| PidLidPostRssChannel | {00020041-0000-0000-C000-000000000046} | 0x8904 |
| PidLidPostRssChannelLink | {00020041-0000-0000-C000-000000000046} | 0x8900 |
| PidLidPostRssItemGuid | {00020041-0000-0000-C000-000000000046} | 0x8903 |
| PidLidPostRssItemHash | {00020041-0000-0000-C000-000000000046} | 0x8902 |
| PidLidPostRssItemLink | {00020041-0000-0000-C000-000000000046} | 0x8901 |
| PidLidPostRssItemXml | {00020041-0000-0000-C000-000000000046} | 0x8905 |
| PidLidPostRssSubscription | {00020041-0000-0000-C000-000000000046} | 0x8906 |
| PidLidSideEffects | {00062008-0000-0000-C000-000000000046} | 0x81f8 |

| Property | Property set GUID | NameID |
|---|---|--|
| | 6} | |
| PidNameExchangeJunkEmailMoveStamp | {00020329-0000-0000-C000-0000000000046} | HTTP://schemas.microsoft.com/exchange/junkemail/ovestamp |

The server might respond with the following identifiers, which will be used in the example that follows. (The actual identifiers are at the discretion of the server.)

| Property | Property ID |
|---|-------------|
| PidLidPostRssChannel | 0x8318 |
| PidLidPostRssChannelLink | 0x8314 |
| PidLidPostRssItemGuid | 0x8317 |
| PidLidPostRssItemHash | 0x8316 |
| PidLidPostRssItemLink | 0x8315 |
| PidLidPostRssItemXml | 0x8319 |
| PidLidPostRssSubscription | 0x831a |
| PidLidSideEffects | 0x81f8 |
| PidNameExchangeJunkEmailMoveStamp | 0x8415 |

To create an RSS object, the client uses [RopCreateMessage](#). The server returns a success code and a **handle** to the object.

After processing the contents of the RSS item, the client uses [RopSetProperties](#) to transmit its data to the server.

| Property | Property ID | Data Type | Value |
|--|-------------|------------------------|-----------------------------|
| PidLidPostRssChannel | 0x8318 | 0x001f (PtypString) | Help and How-To for Contoso |
| PidLidPostRssChannelLink | 0x8314 | 0x001f (PtypString) | HTTP://www.contoso.com |
| PidLidPostRssItemGuid | 0x8317 | 0x001f (PtypString) | HTTP://www.contoso.com |
| PidLidPostRssItemHash | 0x8316 | 0x0003 (PtypInteger32) | 0xCD0E93CF |
| PidLidPostRssItemLink | 0x8315 | 0x001f (PtypString) | HTTP://www.contoso.com |

| Property | Property ID | Data Type | Value |
|---|-------------|------------------------|--|
| PidLidPostRssItemXml | 0x8319 | 0x001f (PtypString) | See Note 1. |
| PidLidPostRssSubscription | 0x831a | 0x001f (PtypString) | Help and How-To for Contoso |
| PidLidSideEffects | 0x81f8 | 0x0003 (PtypInteger32) | 0x00000100 |
| PidTagHtml | 0x1013 | 0x0102 (PtypBinary) | See Note 2. |
| PidTagClientSubmitTime | 0x0039 | 0x0040 (PtypTime) | High: 0x01C87A36 Low: 0xD74C8CC0 (2008/02/28 18:22:13.900) |
| PidTagConversationTopic | 0x0070 | 0x001f (PtypString) | Learn to narrow your search criteria for better searches in Contoso |
| PidTagInternetCodepage | 0x3fde | 0x0003 (PtypInteger32) | 0x0000FDE9 |
| PidTagMessageClass | 0x001a | 0x001f (PtypString) | "IPM.Post.RSS" |
| PidTagMessageFlags | 0x0e07 | 0x0003 (PtypInteger32) | Flags: 0x00000000 <none> |
| PidTagNormalizedSubject | 0x0e1d | 0x001f (PtypString) | Learn to narrow your search criteria for better searches in Contoso |
| PidTagSenderName | 0x0c1a | 0x001f (PtypString) | Help and How-To for Contoso |
| PidTagSentRepresentingName | 0x0042 | 0x001f (PtypString) | Help and How-To for Contoso |
| PidTagSubjectPrefix | 0x003d | 0x001f (PtypString) | (null) |
| PidNameExchangeJunkEmailMoveStamp | 0x8415 | 0x0003 (PtypInteger32) | 0x802454D1 |

When the client has made all its changes to the item, it uses [RopSaveChangesMessage](#) to commit the properties to the server, and then [RopRelease](#) to release the RSS object. The values of some properties will change during the execution of [RopSaveChangesMessage](#), but the properties specified in this document will not change.

Note 1: [PidLidPostRssItemXml](#) contains the following text:

```
<?xml version="1.0"?>
<item>
<title>Learn to narrow your search criteria for better searches in Contoso</title>
<description>Instant Search can help you find information in a flash.</description>
```

```
<link>http://www.contoso.com</link>
</item>
```

Note 2: [PidTagHtml](#) contains the following text, encoded into binary as specified in [\[MS-OXBBODY\]](#):

```
<html>
  <body>
    <table>
      <tr>
        <td>Instant Search can help you find information in a flash.</td>
      </tr>
    </table>
    <p><BR/><A HREF="http://www.contoso.com">View article...</A></p>
  </body>
</html>
```

5 Security

5.1 Security Considerations for Implementers

There are no special security considerations specific to this protocol. General security considerations that pertain to the underlying transport apply as specified in [\[MS-OXCMSG\]](#) and [\[MS-OXCPRPT\]](#).

5.2 Index of Security Parameters

None.

6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products:

- Microsoft® Office Outlook® 2003
- Microsoft® Exchange Server 2003
- Microsoft® Office Outlook® 2007
- Microsoft® Exchange Server 2007
- Microsoft® Outlook® 2010
- Microsoft® Exchange Server 2010

Exceptions, if any, are noted below. If a service pack number appears with the product version, behavior changed in that service pack. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that product does not follow the prescription.

7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

8 Index

A

[Applicability](#) 7

C

[Capability negotiation](#) 7

[Change tracking](#) 21

Client

[overview](#) 13

E

Examples

[overview](#) 15

F

[Fields – vendor-extensible](#) 7

G

[Glossary](#) 5

I

[Implementer – security considerations](#) 19

[Index of security parameters](#) 19

[Informative references](#) 6

[Introduction](#) 5

M

Messages

[overview](#) 8

Messaging

[transport](#) 8

N

[Normative references](#) 5

O

[Overview \(synopsis\)](#) 6

P

[Parameters – security index](#) 19

[Preconditions](#) 6

[Prerequisites](#) 6

[Product behavior](#) 20

R

References

[informative](#) 6

[normative](#) 5

[Relationship to other protocols](#) 6

S

Security

[implementer considerations](#) 19

[overview](#) 19

[parameter index](#) 19

[Standards Assignments](#) 7

T

[Tracking changes](#) 21

[Transport](#) 8

V

[Vendor-extensible fields](#) 7

[Versioning](#) 7