

[MS-SPAFWI]: SharePoint Activity Feed Web Interfaces Protocol Specification

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplq@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
11/06/2009	0.1	Major	Initial Availability
02/19/2010	1.0	Minor	Updated the technical content
03/31/2010	1.01	Editorial	Revised and edited the technical content
04/30/2010	1.02	Editorial	Revised and edited the technical content
06/07/2010	1.03	Editorial	Revised and edited the technical content
06/29/2010	1.04	Editorial	Changed language and formatting in the technical content.
07/23/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
09/27/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
11/15/2010	1.05	Editorial	Changed language and formatting in the technical content.
12/17/2010	1.05	No change	No changes to the meaning, language, or formatting of the technical content.

Table of Contents

1 Introduction	5
1.1 Glossary	5
1.2 References	5
1.2.1 Normative References	5
1.2.2 Informative References	6
1.3 Protocol Overview (Synopsis)	6
1.4 Relationship to Other Protocols	6
1.5 Prerequisites/Preconditions	6
1.6 Applicability Statement	6
1.7 Versioning and Capability Negotiation	6
1.8 Vendor-Extensible Fields	6
1.9 Standards Assignments	6
2 Messages	7
2.1 Transport	7
2.2 Common Message Syntax	7
2.2.1 Namespaces	7
2.2.2 Messages	7
2.2.3 Elements	7
2.2.3.1 TTL (in <feed>)	8
2.2.3.2 Id (in <author>)	8
2.2.3.3 AccountName (in <author>)	8
2.2.3.4 Picture (in <author>)	9
2.2.3.5 Type (in <author>)	9
2.2.3.6 Name (in <entry>)	9
2.2.3.7 Value (in <entry>)	9
2.2.3.8 Link (in <entry>)	9
2.2.3.9 Link2 (in <entry>)	9
2.2.3.10 List (in <entry>)	9
2.2.3.11 DateOnly (in <entry>)	10
2.2.3.12 ActivityType (in <entry>)	10
2.2.3.13 Template (in <entry>)	10
2.2.3.14 Size (in <entry>)	10
2.2.3.15 Separator (in <entry>)	11
2.2.4 Complex Types	11
2.2.4.1 AF:Link	11
2.2.4.2 AF:List	11
2.2.5 Simple Types	11
2.2.6 Attributes	11
2.2.7 Groups	11
2.2.8 Attribute Groups	12
3 Protocol Details	13
3.1 Server Details	13
3.1.1 Abstract Data Model	13
3.1.2 Timers	13
3.1.3 Initialization	13
3.1.4 Message Processing Events and Sequencing Rules	14
3.1.5 Timer Events	14
3.1.6 Other Local Events	14

4 Protocol Examples	15
4.1 ATOM 1.0 Formatted Feed	15
4.2 RSS 2.0 Formatted Feed	20
5 Security	26
5.1 Security Considerations for Implementers.....	26
5.2 Index of Security Parameters	26
6 Appendix A: Full WSDL	27
7 Appendix B: Product Behavior	28
8 Change Tracking	29
9 Index	30

1 Introduction

This document specifies the SharePoint Activity Feed Web Interfaces Protocol, which specifies extensions for serializing and distributing social networking activity data of the users.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

XML

The following terms are defined in [\[MS-OFCGLOS\]](#):

site
social networking
URI (Uniform Resource Identifier)
Web site
XML namespace
XML namespace prefix
XML Schema

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>

[RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.ietf.org/rfc/rfc2616.txt>

[RFC4287] Nottingham, M., and Sayre, E.R., "The Atom Syndication Format", RFC 4287, December 2005, <http://www.ietf.org/rfc/rfc4287.txt>

[RSS 2.0] Winer, D., "RSS 2.0 Specification", Fall 2002, version 2.0.1: July 2003, <http://cyber.law.harvard.edu/rss/rss.html>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XMLNS] World Wide Web Consortium, "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation 8 December 2009, <http://www.w3.org/TR/REC-xml-names/>

[XMLSCHEMA1] Thompson, H.S., Ed., Beech, D., Ed., Maloney, M., Ed., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., Ed. and Malhotra, A., Ed., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)", March 2007.

[MS-OFCGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)", June 2008.

1.3 Protocol Overview (Synopsis)

This protocol defines the extensions to the [\[RSS 2.0\]](#) and ATOM 1.0, as described in [\[RFC4287\]](#), XML structures to support serializing and distributing **social networking** activity data for **Web site (2)** users. This protocol exposes social networking activities for any authenticated user accessing the Web site (2), whether or not the user accessing the Web site (2) participates in social networking activities.

1.4 Relationship to Other Protocols

This protocol is an extension of [\[RSS 2.0\]](#) and ATOM **XML** structure, as described in [\[RFC4287\]](#). It has the same relationship to other protocols that the standard [\[RSS 2.0\]](#) and ATOM 1.0 protocols have.

1.5 Prerequisites/Preconditions

None.

1.6 Applicability Statement

This protocol is designed for serializing and distributing social networking activity data of less than 200 distinct activities at a time, and activities that are less than two weeks old. This protocol is also designed for low impact social networking activities that typically take place at a much lower frequency than other online activities; for example, sending and receiving e-mail, or performing Web search.

1.7 Versioning and Capability Negotiation

None.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

No new transports are required by this protocol, except those already specified by [\[RSS 2.0\]](#) and ATOM 1.0, specified in [\[RFC4287\]](#), standards.

2.2 Common Message Syntax

This section contains common definitions used by this protocol. The syntax of the definitions uses the **XML Schema** as defined in [\[RFC4287\]](#) and [\[RSS 2.0\]](#).

2.2.1 Namespaces

This specification defines and references various **XML namespaces** using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific **XML namespace prefix** for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability. The namespaces are described in the following table.

Prefix	Namespace URI	Reference
s	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1]
xs	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1]
A10	ATOM 1.0 (also the default if none is specified)	[RFC4287]
AF	http://schemas.microsoft.com/SharePoint/ActivityFeed	

2.2.2 Messages

None.

2.2.3 Elements

The elements in the following table are the additional elements in the namespace <http://schemas.microsoft.com/SharePoint/ActivityFeed> (denoted by prefix "AF" in section [2.2.1](#)) that are specific to this protocol. These elements will be recognized as part of this protocol only if they are present in this namespace.

Element	Description
TTL	Within the feed or rss element. The validity period of the entire social networking activity feed, expressed in seconds.
Id	Within the author element. A unique identifier of the Web site (2) user that is represented by the author of an entry or item .
AccountName	Within the author element. The login user name of the site (2) user that is represented by the author of an entry or item .
Picture	Within the author element. The URI of a representation of the site (2) users that is represented by the author of an entry or item .
Type	Within the author element. The type of the site (2) user that is represented by the author of an entry or item . For example, "User", "Group", "Organization", "Contact",

Element	Description
	and so on. This value could be any string; the preceding are just typical examples. The value of this element does not drive any protocol behavior: it is informational only.
Name	The name of the subject of the social networking activity represented by an entry or item .
Value	The value of the subject of the social networking activity represented by an entry or item .
Link	A URI of the subject of the social networking activity represented by an entry or item .
Link2	Another URI value of the subject of the social networking activity represented by an entry or item .
List	A list of links related to the social networking activity represented by an entry or item .
DateOnly	The date portion of the date-time at which the activity took place. For example, if an anniversary activity was logged with the ATOM1.0 updated tag being "20091023T15.10.45.000-7:00" (October 10, 2009 at 3:10:45 PM in PDT), the DateOnly tag would be "20091023T00.00.00" in UTC.
ActivityType	The locale and language neutral string that indicates the type of social networking activity represented by an entry or item ; for example, profile changes, colleague changes, social tags, and so on. These MAY be used by clients of this protocol to group related entry elements in the feed together for display.
Template	A formatting hint that specifies how a client can obtain the content in ATOM 1.0, specified in [RFC4287] of an entry or description in RSS 2.0, specified in [RSS 2.0] of an item . This is done by using the information in one of the preceding tags, or one of the other tags in the standard ATOM 1.0 or RSS 2.0 formats.
Separator	A formatting hint that specifies how elements of a List element need to be separated during display for the social networking activity represented by an entry or item .
Size	Number of elements in the List element of the social networking activity represented by an entry or item .

2.2.3.1 TTL (in <feed>)

```
<xs:element name="TTL" type="xs:int" />
```

Contains the time to live in seconds. Defaults to 2 weeks in seconds.

2.2.3.2 Id (in <author>)

```
<xs:element name="Id" type="xs:long" />
```

Contains a unique identifier for the author represented by the **author** tag of ATOM 1.0 or [\[RSS 2.0\]](#).

2.2.3.3 AccountName (in <author>)

```
<xs:element name="AccountName" type="xs:string" />
```

Contains the login name of the author represented by the **author** tag ATOM 1.0 or [\[RSS 2.0\]](#).

2.2.3.4 Picture (in <author>)

```
<xs:element name="Picture" type="xs:anyURI" />
```

Contains a URI of the picture of the author represented by the **author** tag of ATOM 1.0 or [\[RSS 2.0\]](#).

2.2.3.5 Type (in <author>)

```
<xs:element name="Type" type="xs:string" />
```

Contains the name of the type of user represented by the **author** tag of ATOM 1.0 or [\[RSS 2.0\]](#).

2.2.3.6 Name (in <entry>)

```
<xs:element name="Name" type="xs:string" />
```

Contains the subject of the activity represented by the **entry** tag of ATOM 1.0 or **item** tag of [\[RSS 2.0\]](#).

2.2.3.7 Value (in <entry>)

```
<xs:element name="Value" type="xs:string" />
```

Contains the value of the subject of the activity represented by the **entry** tag of ATOM 1.0 or **<item>** tag of [\[RSS 2.0\]](#).

2.2.3.8 Link (in <entry>)

```
<xs:element name="Link" type="AF:Link" />
```

A URI related to the activity represented by the **entry** tag of ATOM 1.0 or **item** tag of [\[RSS 2.0\]](#).

2.2.3.9 Link2 (in <entry>)

```
<xs:element name="Link2" type=" AF:Link" />
```

A second URI related to the activity represented by the **entry** tag of ATOM 1.0 or **item** tag of [\[RSS 2.0\]](#).

2.2.3.10 List (in <entry>)

```
<xs:element name="List" type="AF:List" />
```

A list of links related to the activity represented by the **entry** tag of ATOM1.0 or **item** tag of [\[RSS 2.0\]](#).

2.2.3.11 DateOnly (in <entry>)

```
<xs:element name="DateOnly" type="xs:date" />
```

The date portion of the date-time at which the activity represented by the **entry** tag of ATOM 1.0 or **item** tag of [\[RSS 2.0\]](#) occurred.

2.2.3.12 ActivityType (in <entry>)

```
<xs:element name="ActivityType" type="xs:string" />
```

Contains a local and language independent name of the type of activity represented by the **entry** tag of ATOM1.0 or **item** tag of [\[RSS 2.0\]](#).

2.2.3.13 Template (in <entry>)

```
<xs:element name="Template" type="xs:string" />
```

Contains a formatting hint that can be used to compute the **content** of ATOM 1.0, specified in [\[RFC4287\]](#) or **description** of RSS 2.0, specified in [\[RSS 2.0\]](#).

The template is a string in any language, with special markers that indicate areas of replaceable text that are demarcated to be within enclosing curly braces, ({ }). Anything that occurs between braces is taken to be one of the following:

- A standard ATOM 1.0 tag, specified in [\[RFC4287\]](#).
- One of the tags in the "AF" namespace as described in this section (2.2.3).
- The string "Publisher", which indicates (is an alias for) the **author** tag of ATOM1.0.

There is no support for tags within tags, that is, the following "{some_text{nested_text}more_text}" is not a valid Template.

A client that is rendering a feed returned by this protocol MAY use the template string to generate alternate textual descriptions of the activity represented by the **entry** tag of ATOM 1.0 by taking the template string and replacing the regions within curly braces (including the braces) with information from one of the preceding tags or a subset of those tags. However, there is no requirement in this protocol for clients to generate alternate textual representations, because this protocol already computes an ATOM 1.0 / RSS 2.0 compliant textual representation in the **content** and **description** tags respectively, which ATOM 1.0 or RSS 2.0 clients can render natively. Hence, the **template** has informational content only and its usage is optional.

2.2.3.14 Size (in <entry>)

```
<xs:element name="Size" type="xs:int" />
```

The number of elements contained in the List element related to the activity represented by the **entry** tag of ATOM1.0 or **item** tag of [\[RSS 2.0\]](#).

2.2.3.15 Separator (in <entry>)

```
<xs:element name="Separator" type="xs:string" />
```

The separator to be used between the List elements during display related to the activity represented by the **entry** tag of ATOM1.0 or **item** tag of [\[RSS 2.0\]](#).

2.2.4 Complex Types

The following table summarizes the set of common XML Schema complex type definitions defined by this specification. XML Schema complex type definitions that are specific to a particular operation are described with the operation.

Complex type	Description
AF:Link	Specifies the Link.
AF:List	Specified a list of AF:Link elements.

2.2.4.1 AF:Link

```
<s:complexType name="Link">  
  <s:sequence>  
    <s:element name="Uri" maxOccurs="1" minOccurs="1" type="xs:string" />  
    <s:element name="Title" maxOccurs="1" minOccurs="1" type="xs:string" />  
  </s:sequence>  
</s:complexType>
```

Uri: Specifies the URI pointed by this link.

Title: Specifies the title of this link.

2.2.4.2 AF:List

```
<s:complexType name="List">  
  <s:sequence>  
    <s:element name="Link" maxOccurs="0" minOccurs="unbounded" type="AF:Link" />  
  </s:sequence>  
</s:complexType>
```

Link: Specifies the Link element or elements contained in this list.

2.2.5 Simple Types

This specification does not define any common XML Schema simple type definitions.

2.2.6 Attributes

This specification does not define any common XML Schema attribute definitions.

2.2.7 Groups

This specification does not define any common XML Schema group definitions.

2.2.8 Attribute Groups

This specification does not define any common XML Schema attribute group definitions.

3 Protocol Details

The client side of this protocol is simply a pass-through. That is, no additional timers or other state is required on the client side of this protocol. Calls made by the higher-layer protocol or application are passed directly to the transport, and the results returned by the transport are passed directly back to the higher-layer protocol or application.

Except where specified, protocol clients SHOULD interpret HTTP status codes returned by the protocol server, as specified in [\[RFC2616\]](#) section 10.

This protocol allows clients to retrieve social networking activities of Web interface users serialized in ATOM 1.0, as specified in [\[RFC4287\]](#), or [\[RSS 2.0\]](#) formats.

3.1 Server Details

This protocol is completely stateless, which means that the server does not retain information about any previous client connections or details of any previous requests. This protocol does not allow any changes (social networking or otherwise) to be made by the protocol client and there are no events that a client can listen to. Upon client request, the protocol server returns a feed of social networking activities that currently exist on the protocol server to the protocol client after serializing them into the [\[RSS 2.0\]](#) or ATOM 1.0, specified in [\[RFC4287\]](#), formats.

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

This protocol is used to distribute social networking activity data to any client that understands [\[RSS 2.0\]](#) or ATOM 1.0, specified in [\[RFC4287\]](#), syndication and serialization formats. This protocol describes the behavior of the protocol client and the protocol server. The only requirement is that the protocol client is authenticated by using standard mechanisms supported by the Web site (2). The client can request social networking activity data for any SharePoint user, including itself, and also specifies the format of either RSS 2.0 or ATOM 1.0. The server simply retrieves the requested data and returns it to the client after formatting it appropriately.

The only state relevant for this protocol is the current server state of the social networking activities done by the users of the site (2). This state changes as Web site (2) users perform social networking activities, and this protocol allows clients to see those changes upon request. It is completely up to the protocol implementation to decide which social networking activities to make available through this protocol: the protocol itself imposes no restrictions or requirements on protocol implementations.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Message Processing Events and Sequencing Rules

None.

3.1.5 Timer Events

None.

3.1.6 Other Local Events

None.

4 Protocol Examples

4.1 ATOM 1.0 Formatted Feed

This example describes an ATOM 1.0, as described in [\[RFC4287\]](#), formatted feed.

```
<feed xmlns="http://www.w3.org/2005/Atom">
  <title type="text">Activity Feed</title>
  <id>uuid:a523a693-d80c-44b6-aa74-fe8af92c7c32;id=1</id>
  <rights type="text">Copyright (c) Microsoft Corporation. All rights reserved.</rights>
  <updated>2010-01-30T02:26:58Z</updated>
  <TTL xmlns="AF">1209600</TTL>
  <entry xml:base="http://mosslatest/my">
    <id>7</id>
    <title type="text">Birthday</title>
    <summary type="html">
      &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; is celebrating a birthday today.&lt;br/&gt;Wish &lt;a
href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; a happy birthday!
    </summary>
    <published>2010-01-30T02:26:32-08:00</published>
    <updated>2010-01-30T02:25:59-08:00</updated>
    <author>
      <name>Dag Rovik</name>
      <uri>http://example/my/person.aspx?accountname=CONTOSO%5Cdagro</uri>
      <email>dagro@contoso.com</email>
      <Id xmlns="AF">10</Id>
      <AccountName xmlns="AF">CONTOSO\dagro</AccountName>
      <Type xmlns="AF">user</Type>
    </author>
    <content type="html">
      &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; is celebrating a birthday today.&lt;br/&gt;Wish &lt;a
href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; a happy birthday!
    </content>
    <ActivityType xmlns="AF">Birthday_Today</ActivityType>
    <Template xmlns="AF">
      {Publisher} is celebrating a birthday today.&lt;br/&gt;Wish {Publisher} a happy
birthday!
    </Template>
    <Name xmlns="AF">Saturday, January 30, 2010</Name>
    <DateOnly xmlns="AF">2010-01-30T00:00:00</DateOnly>
  </entry>
  <entry xml:base="http://mosslatest/my">
    <id>5</id>
    <title type="text">Profile update</title>
    <summary type="html">
      &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; updated profile.&lt;br/&gt;&lt;ol&gt;&lt;li&gt;Birthday:
January 30&lt;/li&gt;&lt;li&gt;Hire date: 2/1/2007&lt;/li&gt;&lt;/ol&gt;
    </summary>
    <published>2010-01-30T02:26:32-08:00</published>
    <updated>2010-01-30T02:25:05-08:00</updated>
    <author>
      <name>Dag Rovik</name>
      <uri>http://example/my/person.aspx?accountname=CONTOSO%5Cdagro</uri>
      <email>dagro@contoso.com</email>
```

```

        <Id xmlns="AF">10</Id>
        <AccountName xmlns="AF">CONTOSO\dagro</AccountName>
        <Type xmlns="AF">user</Type>
    </author>
    <content type="html">
        &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; updated profile.&lt;br/&gt;&lt;ol&gt;&lt;li&gt;Birthday:
January 30&lt;/li&gt;&lt;li&gt;Hire date: 2/1/2007&lt;/li&gt;&lt;/ol&gt;
    </content>
    <ActivityType xmlns="AF">ProfilePropertyChange</ActivityType>
    <Template xmlns="AF">
        {Publisher} updated profile.&lt;br/&gt;{List}
    </Template>
    <Size xmlns="AF">2</Size>
    <List xmlns="AF">
        <Link>
            <Uri></Uri>
            <Title>Birthday: January 30</Title>
        </Link>
        <Link>
            <Uri></Uri>
            <Title>Hire date: 2/1/2007</Title>
        </Link>
    </List>
</entry>
<entry xml:base="http://mosslatest/my">
    <id>8</id>
    <title type="text">Note Board post</title>
    <summary type="html">
        &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; posted a note on &lt;a
href="http://example/my/Person.aspx?accountname=CONTOSO%5Cdagro"&gt;CONTOSO\dagro&lt;/a&gt;.&
lt;br/&gt;sample noteboard post
    </summary>
    <published>2010-01-30T02:26:32-08:00</published>
    <updated>2010-01-30T02:21:39-08:00</updated>
    <author>
        <name>Dag Rovik</name>
        <uri>http://example/my/person.aspx?accountname=CONTOSO%5Cdagro</uri>
        <email>dagro@contoso.com</email>
        <Id xmlns="AF">10</Id>
        <AccountName xmlns="AF">CONTOSO\dagro</AccountName>
        <Type xmlns="AF">user</Type>
    </author>
    <content type="html">
        &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; posted a note on &lt;a
href="http://example/my/Person.aspx?accountname=CONTOSO%5Cdagro"&gt;CONTOSO\dagro&lt;/a&gt;.&
lt;br/&gt;sample noteboard post
    </content>
    <ActivityType xmlns="AF">NoteboardPosts</ActivityType>
    <Template xmlns="AF">
        {Publisher} posted a note on {Link}.&lt;br/&gt;{Value}
    </Template>
    <Value xmlns="AF">sample noteboard post</Value>
    <Link xmlns="AF">
        <Uri>http://example/my/Person.aspx?accountname=CONTOSO%5Cdagro</Uri>
        <Title>CONTOSO\dagro</Title>
    </Link>
</entry>

```



```

<entry xml:base="http://mosslatest/my">
  <id>6</id>
  <title type="text">New colleague</title>
  <summary type="html">
    &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; added 3 new colleagues.&lt;br/&gt;&lt;a
href='http://example/my/Person.aspx?accountname=CONTOSO%5Cpkmuser1' &gt;pkmuser1&lt;/a&gt;;
&lt;a
href='http://example/my/Person.aspx?accountname=CONTOSO%5Cstartlst' &gt;CONTOSO\startlst&lt;/a
&gt;; &lt;a
href='http://example/my/Person.aspx?accountname=CONTOSO%5Cpauldale' &gt;CONTOSO\pauldale&lt;/a
&gt;
  </summary>
  <published>2010-01-30T02:26:32-08:00</published>
  <updated>2010-01-30T02:21:23-08:00</updated>
  <author>
    <name>Dag Rovik</name>
    <uri>http://example/my/person.aspx?accountname=CONTOSO%5Cdagro</uri>
    <email>dagro@contoso.com</email>
    <Id xmlns="AF">10</Id>
    <AccountName xmlns="AF">CONTOSO\dagro</AccountName>
    <Type xmlns="AF">user</Type>
  </author>
  <content type="html">
    &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; added 3 new colleagues.&lt;br/&gt;&lt;a
href='http://example/my/Person.aspx?accountname=CONTOSO%5Cpkmuser1' &gt;pkmuser1&lt;/a&gt;;
&lt;a
href='http://example/my/Person.aspx?accountname=CONTOSO%5Cstartlst' &gt;CONTOSO\startlst&lt;/a
&gt;; &lt;a
href='http://example/my/Person.aspx?accountname=CONTOSO%5Cpauldale' &gt;CONTOSO\pauldale&lt;/a
&gt;
  </content>
  <ActivityType xmlns="AF">ColleagueAddition</ActivityType>
  <Template xmlns="AF">
    {Publisher} added {Size} new colleagues.&lt;br/&gt;{List}
  </Template>
  <Link xmlns="AF">
    <Uri>http://example/my/Person.aspx?accountname=CONTOSO%5Cpkmuser1</Uri>
    <Title>pkmuser1</Title>
  </Link>
  <Size xmlns="AF">3</Size>
  <Separator xmlns="AF">, </Separator>
  <List xmlns="AF">
    <Link>
      <Uri>http://example/my/Person.aspx?accountname=CONTOSO%5Cpkmuser1</Uri>
      <Title>pkmuser1</Title>
    </Link>
    <Link>
      <Uri>http://example/my/Person.aspx?accountname=CONTOSO%5Cstartlst</Uri>
      <Title>CONTOSO\startlst</Title>
    </Link>
    <Link>
      <Uri>http://example/my/Person.aspx?accountname=CONTOSO%5Cpauldale</Uri>
      <Title>CONTOSO\pauldale</Title>
    </Link>
  </List>
</entry>
<entry xml:base="http://mosslatest/my">
  <id>4</id>

```

```

<title type="text">Profile update</title>
<summary type="html">
  &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; updated profile.&lt;br/&gt;Interests: interest1, interest2
</summary>
<published>2010-01-30T02:26:32-08:00</published>
<updated>2010-01-30T02:15:45-08:00</updated>
<author>
  <name>Dag Rovik</name>
  <uri>http://example/my/person.aspx?accountname=CONTOSO%5Cdagro</uri>
  <email>dagro@contoso.com</email>
  <Id xmlns="AF">10</Id>
  <AccountName xmlns="AF">CONTOSO\dagro</AccountName>
  <Type xmlns="AF">user</Type>
</author>
<content type="html">
  &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; updated profile.&lt;br/&gt;Interests: interest1, interest2
</content>
<ActivityType xmlns="AF">ProfilePropertyChange</ActivityType>
<Template xmlns="AF">
  {Publisher} updated profile.&lt;br/&gt;{List}
</Template>
<Size xmlns="AF">2</Size>
<Separator xmlns="AF">, </Separator>
<List xmlns="AF">
  <Link>
    <Uri></Uri>
    <Title>Interests: interest1</Title>
  </Link>
  <Link>
    <Uri></Uri>
    <Title>interest2</Title>
  </Link>
</List>
</entry>
<entry xml:base="http://mosslatest/my">
  <id>3</id>
  <title type="text">Profile update</title>
  <summary type="html">
    &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; updated profile.&lt;br/&gt;Skills: skill1, skill2
  </summary>
  <published>2010-01-30T02:26:32-08:00</published>
  <updated>2010-01-30T02:15:45-08:00</updated>
  <author>
    <name>Dag Rovik</name>
    <uri>http://example/my/person.aspx?accountname=CONTOSO%5Cdagro</uri>
    <email>dagro@contoso.com</email>
    <Id xmlns="AF">10</Id>
    <AccountName xmlns="AF">CONTOSO\dagro</AccountName>
    <Type xmlns="AF">user</Type>
  </author>
  <content type="html">
    &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; updated profile.&lt;br/&gt;Skills: skill1, skill2
  </content>
  <ActivityType xmlns="AF">ProfilePropertyChange</ActivityType>
  <Template xmlns="AF">

```

```

        {Publisher} updated profile.&lt;br/&gt;{List}
    </Template>
    <Size xmlns="AF">2</Size>
    <Separator xmlns="AF">, </Separator>
    <List xmlns="AF">
        <Link>
            <Uri></Uri>
            <Title>Skills: skill1</Title>
        </Link>
        <Link>
            <Uri></Uri>
            <Title>skill2</Title>
        </Link>
    </List>
</entry>
<entry xml:base="http://mosslatest/my">
    <id>2</id>
    <title type="text">Profile update</title>
    <summary type="html">
        &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; updated profile.&lt;br/&gt;Ask Me About: Activity Feed,
Sync, Profile Store
    </summary>
    <published>2010-01-30T02:26:32-08:00</published>
    <updated>2010-01-30T02:15:45-08:00</updated>
    <author>
        <name>Dag Rovik</name>
        <uri>http://example/my/person.aspx?accountname=CONTOSO%5Cdagro</uri>
        <email>dagro@contoso.com</email>
        <Id xmlns="AF">10</Id>
        <AccountName xmlns="AF">CONTOSO\dagro</AccountName>
        <Type xmlns="AF">user</Type>
    </author>
    <content type="html">
        &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; updated profile.&lt;br/&gt;Ask Me About: Activity Feed,
Sync, Profile Store
    </content>
    <ActivityType xmlns="AF">ProfilePropertyChange</ActivityType>
    <Template xmlns="AF">
        {Publisher} updated profile.&lt;br/&gt;{List}
    </Template>
    <Size xmlns="AF">3</Size>
    <Separator xmlns="AF">, </Separator>
    <List xmlns="AF">
        <Link>
            <Uri></Uri>
            <Title>Ask Me About: Activity Feed</Title>
        </Link>
        <Link>
            <Uri></Uri>
            <Title>Sync</Title>
        </Link>
        <Link>
            <Uri></Uri>
            <Title>Profile Store</Title>
        </Link>
    </List>
</entry>

```

```

<entry xml:base="http://mosslatest/my">
  <id>1</id>
  <title type="text">Status Message</title>
  <summary type="html">
    &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; says "Testing Feeds".
  </summary>
  <published>2010-01-30T02:26:32-08:00</published>
  <updated>2010-01-30T02:14:40-08:00</updated>
  <author>
    <name>Dag Rovik</name>
    <uri>http://example/my/person.aspx?accountname=CONTOSO%5Cdagro</uri>
    <email>dagro@contoso.com</email>
    <Id xmlns="AF">10</Id>
    <AccountName xmlns="AF">CONTOSO\dagro</AccountName>
    <Type xmlns="AF">user</Type>
  </author>
  <content type="html">
    &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; says "Testing Feeds".
  </content>
  <ActivityType xmlns="AF">StatusMessage</ActivityType>
  <Template xmlns="AF">
    {Publisher} says "{Value}".
  </Template>
  <Name xmlns="AF">Status Message</Name>
  <Value xmlns="AF">Testing Feeds</Value>
</entry>
</feed>

```

4.2 RSS 2.0 Formatted Feed

This example describes the same feed as the one in section [4.1](#), but in RSS 2.0, described in [\[RSS 2.0\]](#) format.

```

<rss xmlns:a10="http://www.w3.org/2005/Atom" version="2.0">
  <channel>
    <title>Activity Feed</title>
    <description />
    <copyright>Copyright (c) Microsoft Corporation. All rights reserved.</copyright>
    <lastBuildDate>Sat, 30 Jan 2010 02:43:33 Z</lastBuildDate>
    <TTL xmlns="AF">1209600</TTL>
    <item xml:base="http://mosslatest/my">
      <guid isPermaLink="false">7</guid>
      <author>Dag Rovik</author>
      <title>Birthday</title>
      <description>
        &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro"
title="Dag Rovik"&gt;CONTOSO\dagro&lt;/a&gt; is celebrating a birthday today.&lt;br/&gt;Wish
&lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik"&gt;CONTOSO\dagro&lt;/a&gt; a happy birthday!
      </description>
      <pubDate>Sat, 30 Jan 2010 02:26:32 -0800</pubDate>
      <a10:updated>2010-01-30T02:25:59-08:00</a10:updated>
      <a10:content type="html">
        &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro"
title="Dag Rovik"&gt;CONTOSO\dagro&lt;/a&gt; is celebrating a birthday today.&lt;br/&gt;Wish

```

```

<a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro" title="Dag
Rovik">CONTOSO\dagro</a> a happy birthday!
  </a10:content>
  <ActivityType xmlns="AF">Birthday_Today</ActivityType>
  <Template xmlns="AF">
    {Publisher} is celebrating a birthday today.<br/>Wish {Publisher} a
happy birthday!
  </Template>
  <Name xmlns="AF">Saturday, January 30, 2010</Name>
  <DateOnly xmlns="AF">2010-01-30T00:00:00</DateOnly>
</item>
<item xml:base="http://mosslatest/my">
  <guid isPermaLink="false">5</guid>
  <author>Dag Rovik</author>
  <title>Profile update</title>
  <description>
    <a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro"
title="Dag Rovik">CONTOSO\dagro</a> updated
profile.<br/><ol><li>Birthday: January 30</li><li>Hire date:
2/1/2007</li></ol>
  </description>
  <pubDate>Sat, 30 Jan 2010 02:26:32 -0800</pubDate>
  <a10:updated>2010-01-30T02:25:05-08:00</a10:updated>
  <a10:content type="html">
    <a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro"
title="Dag Rovik">CONTOSO\dagro</a> updated
profile.<br/><ol><li>Birthday: January 30</li><li>Hire date:
2/1/2007</li></ol>
  </a10:content>
  <ActivityType xmlns="AF">ProfilePropertyChange</ActivityType>
  <Template xmlns="AF">
    {Publisher} updated profile.<br/>{List}
  </Template>
  <Size xmlns="AF">2</Size>
  <List xmlns="AF">
    <Link>
      <Uri></Uri>
      <Title>Birthday: January 30</Title>
    </Link>
    <Link>
      <Uri></Uri>
      <Title>Hire date: 2/1/2007</Title>
    </Link>
  </List>
</item>
<item xml:base="http://mosslatest/my">
  <guid isPermaLink="false">8</guid>
  <author>Dag Rovik</author>
  <title>Note Board post</title>
  <description>
    <a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro"
title="Dag Rovik">CONTOSO\dagro</a> posted a note on <a
href="http://example/my/Person.aspx?accountname=CONTOSO%5Cdagro">CONTOSO\dagro</a>.<br/>sample noteboard post
  </description>
  <pubDate>Sat, 30 Jan 2010 02:26:32 -0800</pubDate>
  <a10:updated>2010-01-30T02:21:39-08:00</a10:updated>
  <a10:content type="html">
    <a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro"
title="Dag Rovik">CONTOSO\dagro</a> posted a note on <a

```

```

href='http://example/my/Person.aspx?accountname=CONTOSO%5Cdagro'&gt;CONTOSO\dagro&lt;/a&gt;.&
lt;br/&gt;sample noteboard post
</a10:content>
<ActivityType xmlns="AF">NoteboardPosts</ActivityType>
<Template xmlns="AF">
  {Publisher} posted a note on {Link}.&lt;br/&gt;{Value}
</Template>
<Value xmlns="AF">sample noteboard post</Value>
<Link xmlns="AF">
  <Uri>http://example/my/Person.aspx?accountname=CONTOSO%5Cdagro</Uri>
  <Title>CONTOSO\dagro</Title>
</Link>
</item>
<item xml:base="http://mosslatest/my">
  <guid isPermaLink="false">6</guid>
  <author>Dag Rovik</author>
  <title>New colleague</title>
  <description>
    &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro"
title="Dag Rovik"&gt;CONTOSO\dagro&lt;/a&gt; added 3 new colleagues.&lt;br/&gt;&lt;a
href='http://example/my/Person.aspx?accountname=CONTOSO%5Cpkmuser1'&gt;pkmuser1&lt;/a&gt;,
&lt;a
href='http://example/my/Person.aspx?accountname=CONTOSO%5Cstartlst'&gt;CONTOSO\startlst&lt;/a
&gt;, &lt;a
href='http://example/my/Person.aspx?accountname=CONTOSO%5Cpauldale'&gt;CONTOSO\pauldale&lt;/a
&gt;
  </description>
  <pubDate>Sat, 30 Jan 2010 02:26:32 -0800</pubDate>
  <a10:updated>2010-01-30T02:21:23-08:00</a10:updated>
  <a10:content type="html">
    &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro"
title="Dag Rovik"&gt;CONTOSO\dagro&lt;/a&gt; added 3 new colleagues.&lt;br/&gt;&lt;a
href='http://example/my/Person.aspx?accountname=CONTOSO%5Cpkmuser1'&gt;pkmuser1&lt;/a&gt;,
&lt;a
href='http://example/my/Person.aspx?accountname=CONTOSO%5Cstartlst'&gt;CONTOSO\startlst&lt;/a
&gt;, &lt;a
href='http://example/my/Person.aspx?accountname=CONTOSO%5Cpauldale'&gt;CONTOSO\pauldale&lt;/a
&gt;
  </a10:content>
  <ActivityType xmlns="AF">ColleagueAddition</ActivityType>
  <Template xmlns="AF">
    {Publisher} added {Size} new colleagues.&lt;br/&gt;{List}
  </Template>
  <Link xmlns="AF">
    <Uri>http://example/my/Person.aspx?accountname=CONTOSO%5Cpkmuser1</Uri>
    <Title>pkmuser1</Title>
  </Link>
  <Size xmlns="AF">3</Size>
  <Separator xmlns="AF">,</Separator>
  <List xmlns="AF">
    <Link>
      <Uri>http://example/my/Person.aspx?accountname=CONTOSO%5Cpkmuser1</Uri>
      <Title>pkmuser1</Title>
    </Link>
    <Link>
      <Uri>http://example/my/Person.aspx?accountname=CONTOSO%5Cstartlst</Uri>
      <Title>CONTOSO\startlst</Title>
    </Link>
    <Link>

```

```

<Uri>http://example/my/Person.aspx?accountname=CONTOSO%5Cpauldale</Uri>
  <Title>CONTOSO\pauldale</Title>
</Link>
</List>
</item>
<item xml:base="http://mosslatest/my">
  <guid isPermaLink="false">4</guid>
  <author>Dag Rovik</author>
  <title>Profile update</title>
  <description>
    &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro"
title="Dag Rovik"&gt;CONTOSO\dagro&lt;/a&gt; updated profile.&lt;br/&gt;Interests: interest1,
interest2
  </description>
  <pubDate>Sat, 30 Jan 2010 02:26:32 -0800</pubDate>
  <a10:updated>2010-01-30T02:15:45-08:00</a10:updated>
  <a10:content type="html">
    &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro"
title="Dag Rovik"&gt;CONTOSO\dagro&lt;/a&gt; updated profile.&lt;br/&gt;Interests: interest1,
interest2
  </a10:content>
  <ActivityType xmlns="AF">ProfilePropertyChange</ActivityType>
  <Template xmlns="AF">
    {Publisher} updated profile.&lt;br/&gt;{List}
  </Template>
  <Size xmlns="AF">2</Size>
  <Separator xmlns="AF">, </Separator>
  <List xmlns="AF">
    <Link>
      <Uri></Uri>
      <Title>Interests: interest1</Title>
    </Link>
    <Link>
      <Uri></Uri>
      <Title>interest2</Title>
    </Link>
  </List>
</item>
<item xml:base="http://mosslatest/my">
  <guid isPermaLink="false">3</guid>
  <author>Dag Rovik</author>
  <title>Profile update</title>
  <description>
    &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro"
title="Dag Rovik"&gt;CONTOSO\dagro&lt;/a&gt; updated profile.&lt;br/&gt;Skills: skill1,
skill2
  </description>
  <pubDate>Sat, 30 Jan 2010 02:26:32 -0800</pubDate>
  <a10:updated>2010-01-30T02:15:45-08:00</a10:updated>
  <a10:content type="html">
    &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro"
title="Dag Rovik"&gt;CONTOSO\dagro&lt;/a&gt; updated profile.&lt;br/&gt;Skills: skill1,
skill2
  </a10:content>
  <ActivityType xmlns="AF">ProfilePropertyChange</ActivityType>
  <Template xmlns="AF">
    {Publisher} updated profile.&lt;br/&gt;{List}
  </Template>
  <Size xmlns="AF">2</Size>

```

```

<Separator xmlns="AF">, </Separator>
<List xmlns="AF">
  <Link>
    <Uri></Uri>
    <Title>Skills: skill1</Title>
  </Link>
  <Link>
    <Uri></Uri>
    <Title>skill2</Title>
  </Link>
</List>
</item>
<item xml:base="http://mosslatest/my">
  <guid isPermaLink="false">2</guid>
  <author>Dag Rovik</author>
  <title>Profile update</title>
  <description>
    <a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro"
title="Dag Rovik">&#x26;CONTOSO\&#x26; updated profile.&#x0D;&#x26;Ask Me About:
Activity Feed, Sync, Profile Store
  </description>
  <pubDate>Sat, 30 Jan 2010 02:26:32 -0800</pubDate>
  <a10:updated>2010-01-30T02:15:45-08:00</a10:updated>
  <a10:content type="html">
    <a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro"
title="Dag Rovik">&#x26;CONTOSO\&#x26; updated profile.&#x0D;&#x26;Ask Me About:
Activity Feed, Sync, Profile Store
  </a10:content>
  <ActivityType xmlns="AF">ProfilePropertyChange</ActivityType>
  <Template xmlns="AF">
    {Publisher} updated profile.&#x0D;&#x26;{List}
  </Template>
  <Size xmlns="AF">3</Size>
  <Separator xmlns="AF">, </Separator>
  <List xmlns="AF">
    <Link>
      <Uri></Uri>
      <Title>Ask Me About: Activity Feed</Title>
    </Link>
    <Link>
      <Uri></Uri>
      <Title>Sync</Title>
    </Link>
    <Link>
      <Uri></Uri>
      <Title>Profile Store</Title>
    </Link>
  </List>
</item>
<item xml:base="http://mosslatest/my">
  <guid isPermaLink="false">1</guid>
  <author>Dag Rovik</author>
  <title>Status Message</title>
  <description>
    <a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro"
title="Dag Rovik">&#x26;CONTOSO\&#x26; says "Testing Feeds".
  </description>
  <pubDate>Sat, 30 Jan 2010 02:26:32 -0800</pubDate>
  <a10:updated>2010-01-30T02:14:40-08:00</a10:updated>

```



```
<a10:content type="html">
  &lt;a href="http://example/my/person.aspx?accountname=CONTOSO%5Cdagro"
title="Dag Rovik"&gt;&gt;CONTOSO\dagro&lt;/a&gt; says "Testing Feeds".
</a10:content>
<ActivityType xmlns="AF">StatusMessage</ActivityType>
<Template xmlns="AF">
  {Publisher} says "{Value}".
</Template>
<Name xmlns="AF">Status Message</Name>
<Value xmlns="AF">Testing Feeds</Value>
</item>
</channel>
</rss>
```

5 Security

5.1 Security Considerations for Implementers

None.

5.2 Index of Security Parameters

None.

6 Appendix A: Full WSDL

None.

7 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Outlook® 2010
- Microsoft® SharePoint® Server 2010

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

8 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

9 Index

A

Abstract data model
 [server](#) 13
[AccountName \(in <author>\) element](#) 8
[ActivityType \(in <entry>\) element](#) 10
[AF:Link complex type](#) 11
[AF:List complex type](#) 11
[Applicability](#) 6
[ATOM 1.0 formatted feed example](#) 15
[Attribute groups](#) 12
[Attributes](#) 11

C

[Capability negotiation](#) 6
[Change tracking](#) 29
[Complex types](#) 11
 [AF:Link](#) 11
 [AF:List](#) 11

D

Data model - abstract
 [server](#) 13
[DateOnly \(in <entry>\) element](#) 10

E

Elements
 [AccountName \(in <author>\) element](#) 8
 [ActivityType \(in <entry>\) element](#) 10
 [DateOnly \(in <entry>\) element](#) 10
 [Id \(in <author>\) element](#) 8
 [Link \(in <entry>\) element](#) 9
 [Link2 \(in <entry>\) element](#) 9
 [List \(in <entry>\) element](#) 9
 [Name \(in <entry>\) element](#) 9
 [Picture \(in <author>\) element](#) 9
 [Separator \(in <entry>\) element](#) 11
 [Size \(in <entry>\) element](#) 10
 [Template \(in <entry>\) element](#) 10
 [TTL \(in <feed>\) element](#) 8
 [Type \(in <author>\) element](#) 9
 [Value \(in <entry>\) element](#) 9

Events

[local - server](#) 14
 [timer - server](#) 14

Examples

[ATOM 1.0 formatted feed](#) 15
 [overview](#) 15
 [RSS 2.0 formatted feed](#) 20

F

[Fields - vendor-extensible](#) 6
[Full WSDL](#) 27

G

[Glossary](#) 5
[Groups](#) 11

I

[Id \(in <author>\) element](#) 8
[Implementer - security considerations](#) 26
[Index of security parameters](#) 26
[Informative references](#) 6
Initialization
 [server](#) 13
[Introduction](#) 5

L

[Link \(in <entry>\) element](#) 9
[Link2 \(in <entry>\) element](#) 9
[List \(in <entry>\) element](#) 9
Local events
 [server](#) 14

M

Message processing
 [server](#) 14
Messages
 [AccountName \(in <author>\) element](#) 8
 [ActivityType \(in <entry>\) element](#) 10
 [AF:Link complex type](#) 11
 [AF:List complex type](#) 11
 [attribute groups](#) 12
 [attributes](#) 11
 [complex types](#) 11
 [DateOnly \(in <entry>\) element](#) 10
 [elements](#) 7
 [enumerated](#) 7
 [groups](#) 11
 [Id \(in <author>\) element](#) 8
 [Link \(in <entry>\) element](#) 9
 [Link2 \(in <entry>\) element](#) 9
 [List \(in <entry>\) element](#) 9
 [Name \(in <entry>\) element](#) 9
 [namespaces](#) 7
 [Picture \(in <author>\) element](#) 9
 [Separator \(in <entry>\) element](#) 11
 [simple types](#) 11
 [Size \(in <entry>\) element](#) 10
 [syntax](#) 7
 [Template \(in <entry>\) element](#) 10
 [transport](#) 7
 [TTL \(in <feed>\) element](#) 8
 [Type \(in <author>\) element](#) 9
 [Value \(in <entry>\) element](#) 9

N

[Name \(in <entry>\) element](#) 9
[Namespaces](#) 7
[Normative references](#) 5

O

[Overview \(synopsis\)](#) 6

P

[Parameters - security index](#) 26
[Picture \(in <author>\) element](#) 9
[Preconditions](#) 6
[Prerequisites](#) 6
[Product behavior](#) 28

R

References
[informative](#) 6
[normative](#) 5
[Relationship to other protocols](#) 6
[RSS 2.0 formatted feed example](#) 20

S

Security
[implementer considerations](#) 26
[parameter index](#) 26
[Separator \(in <entry>\) element](#) 11
Sequencing rules
[server](#) 14
Server
[abstract data model](#) 13
[initialization](#) 13
[local events](#) 14
[message processing](#) 14
[sequencing rules](#) 14
[timer events](#) 14
[timers](#) 13
[Simple types](#) 11
[Size \(in <entry>\) element](#) 10
[Standards assignments](#) 6
Syntax
[messages - overview](#) 7

T

[Template \(in <entry>\) element](#) 10
Timer events
[server](#) 14
Timers
[server](#) 13
[Tracking changes](#) 29
[Transport](#) 7
[TTL \(in <feed>\) element](#) 8
[Type \(in <author>\) element](#) 9
Types
[complex](#) 11
[simple](#) 11

V

[Value \(in <entry>\) element](#) 9
[Vendor-extensible fields](#) 6
[Versioning](#) 6

W

[WSDL](#) 27