

# [MS-XWDDOC]: Web Distributed Authoring and Versioning (WebDAV) Extensions for Documents Support

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplq@microsoft.com](mailto:iplq@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
12/03/2008	1.0	Major	Initial Release.
03/04/2009	1.0.1	Editorial	Revised and edited technical content.
04/10/2009	2.0	Major	Deprecated for Exchange 2010.
07/15/2009	3.0	Major	Changes made for template compliance.
11/04/2009	3.1.0	Minor	Updated the technical content.
02/10/2010	4.0.0	Major	Updated and revised the technical content.
05/05/2010	4.0.1	Editorial	Revised and edited the technical content.
08/04/2010	4.0.1	No change	No changes to the meaning, language, or formatting of the technical content.
11/03/2010	4.0.1	No change	No changes to the meaning, language, or formatting of the technical content.

# Contents

<b>1 Introduction</b> .....	<b>5</b>
1.1 Glossary .....	5
1.2 References.....	5
1.2.1 Normative References.....	5
1.2.2 Informative References .....	7
1.3 Overview .....	7
1.4 Relationship to Other Protocols.....	7
1.5 Prerequisites/Preconditions .....	7
1.6 Applicability Statement.....	8
1.7 Versioning and Capability Negotiation.....	8
1.8 Vendor-Extensible Fields.....	8
1.9 Standards Assignments .....	8
<b>2 Messages</b> .....	<b>9</b>
2.1 Transport.....	9
2.2 Message Syntax .....	9
2.2.1 DAV: Namespace Properties .....	9
2.2.1.1 PidNameContentClass .....	9
2.2.1.2 PidNameDavId .....	9
2.2.1.3 PidNameDavIsCollection .....	9
2.2.1.4 PidNameDavIsStructuredDocument.....	9
2.2.1.5 PidNameDavParentName .....	10
2.2.1.6 PidNameDavUid.....	10
2.2.1.7 PidTagAttributeHidden.....	10
2.2.1.8 PidTagAttributeReadOnly .....	10
2.2.1.9 PidTagSubfolder .....	10
2.2.1.10 PidTagUrlName.....	10
2.2.2 <a href="http://schemas.microsoft.com/exchange/">http://schemas.microsoft.com/exchange/</a> Namespace Properties .....	11
2.2.2.1 PidTagExchangeNTSecurityDescriptor.....	11
2.2.2.2 PidTagFlatUrlName .....	11
2.2.2.3 PidTagMessageClass .....	11
2.2.2.4 PidTagMid.....	11
2.2.3 <a href="urn:schemas-microsoft-com:office:office">urn:schemas-microsoft-com:office:office</a> Namespace Properties.....	12
2.2.3.1 PidNameApplicationName .....	12
2.2.3.2 PidNameAuthor .....	12
2.2.3.3 PidNameByteCount .....	12
2.2.3.4 PidNameCategory .....	12
2.2.3.5 PidNameCharacterCount.....	12
2.2.3.6 PidNameComments.....	13
2.2.3.7 PidNameCompany.....	13
2.2.3.8 PidNameCreateDateTimeReadOnly.....	13
2.2.3.9 PidNameDocumentParts .....	13
2.2.3.10 PidNameEditTime.....	13
2.2.3.11 PidNameHeadingPairs.....	14
2.2.3.12 PidNameHiddenCount .....	14
2.2.3.13 PidNameKeywords .....	14
2.2.3.14 PidNameLastAuthor.....	14
2.2.3.15 PidNameLastPrinted .....	14
2.2.3.16 PidNameLastSaveDateTime.....	15
2.2.3.17 PidNameLineCount.....	15

2.2.3.18	PidNameLinksDirty .....	15
2.2.3.19	PidNameManager .....	15
2.2.3.20	PidNameMultimediaClipCount .....	15
2.2.3.21	PidNameNoteCount .....	16
2.2.3.22	PidNamePageCount .....	16
2.2.3.23	PidNameParagraphCount .....	16
2.2.3.24	PidNamePresentationFormat.....	16
2.2.3.25	PidNameRevisionNumber .....	16
2.2.3.26	PidNameScale .....	17
2.2.3.27	PidNameSecurity .....	17
2.2.3.28	PidNameSlideCount .....	17
2.2.3.29	PidNameSubject .....	17
2.2.3.30	PidNameTemplate .....	17
2.2.3.31	PidNameThumbnail .....	18
2.2.3.32	PidNameTitle .....	18
2.2.3.33	PidNameWordCount .....	18
<b>3</b>	<b>Protocol Details .....</b>	<b>19</b>
3.1	Client and Server Details .....	19
3.1.1	Abstract Data Model .....	19
3.1.2	Timers .....	19
3.1.3	Initialization .....	19
3.1.4	Higher-Layer Triggered Events.....	19
3.1.5	Message Processing Events and Sequencing Rules.....	19
3.1.6	Timer Events .....	19
3.1.7	Other Local Events .....	19
<b>4</b>	<b>Protocol Examples.....</b>	<b>20</b>
4.1	Using PROPFIND to retrieve all properties on a document .....	20
4.1.1	Request .....	20
4.1.2	Response .....	20
4.2	Using PROPFIND to retrieve specific properties on a document .....	21
4.2.1	Request .....	21
4.2.2	Response .....	22
4.3	Using PROPPATCH to set a document property .....	24
4.3.1	Request .....	24
4.3.2	Response .....	24
<b>5</b>	<b>Security.....</b>	<b>25</b>
5.1	Security Considerations for Implementers.....	25
5.2	Index of Security Parameters .....	25
<b>6</b>	<b>Appendix A: Product Behavior.....</b>	<b>26</b>
<b>7</b>	<b>Change Tracking.....</b>	<b>27</b>
<b>8</b>	<b>Index .....</b>	<b>28</b>

# 1 Introduction

This document specifies **property** extensions to [\[RFC2518\]](#), [\[MS-WDVME\]](#), [\[MS-WDVSE\]](#), and [\[MS-WDV\]](#) to allow for the creation and manipulation of **Document objects** by using **WebDAV**. Document objects are **Message objects** with additional properties. These properties are available for query and manipulation as specified in [\[MS-OXODOC\]](#) or by using WebDAV and the properties specified in this document.

## 1.1 Glossary

The following terms are defined in [\[MS-OXGLOS\]](#):

**access control list (ACL)**  
**collection**  
**folder**  
**Hypertext Transfer Protocol (HTTP)**  
**Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS)**  
**Inbox folder**  
**message**  
**message ID (MID)**  
**Message object**  
**optional attendee**  
**orphan instance**  
**property**  
**signal time**  
**store**  
**Uniform Resource Locator (URL)**  
**unsendable attendee**  
**WebDAV**  
**WebDAV client**  
**WebDAV server**

The following terms are specific to this document:

**Document object:** The **Document object** is used to represent a file, such as a document generated by a word-processing application. The file is embedded within the **Document object** and is referred to as an attachment. Specifically, the **Document object** is a **Message object** that contains one file, and includes additional properties to describe the file.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-DTYP] Microsoft Corporation, "Windows Data Types", March 2007, <http://msdn.microsoft.com/en-us/library/cc230273.aspx>

- [MS-OSHARED] Microsoft Corporation, "Office Common Data Types and Objects Structure Specification", June 2008, <http://msdn.microsoft.com/en-us/library/cc313156.aspx>
- [MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)", April 2008.
- [MS-OXCFXICS] Microsoft Corporation, "[Bulk Data Transfer Protocol Specification](#)", April 2008.
- [MS-OXCMAIL] Microsoft Corporation, "[RFC2822 and MIME to E-Mail Object Conversion Protocol Specification](#)", April 2008.
- [MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol Specification](#)", April 2008.
- [MS-OXODOC] Microsoft Corporation, "[Document Object Protocol Specification](#)", April 2008.
- [MS-OXOMSG] Microsoft Corporation, "[E-Mail Object Protocol Specification](#)", April 2008.
- [MS-OXPROPS] Microsoft Corporation, "[Exchange Server Protocols Master Property List](#)", April 2008.
- [MS-WDV] Microsoft Corporation, "Web Distributed Authoring and Versioning (WebDAV) Protocol: Client Extensions", July 2006, <http://msdn.microsoft.com/en-us/library/cc250046.aspx>
- [MS-WDVME] Microsoft Corporation, "Web Distributed Authoring and Versioning (WebDAV) Protocol: Microsoft Extensions", September 2007, <http://msdn.microsoft.com/en-us/library/cc250108.aspx>
- [MS-WDVSE] Microsoft Corporation, "Web Distributed Authoring and Versioning (WebDAV) Protocol: Server Extensions", September 2007, <http://msdn.microsoft.com/en-us/library/cc250200.aspx>
- [MS-XWDEXT] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Core Extensions](#)", April 2009.
- [MS-XWDSTRUCTDOC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Structured Documents](#)", December 2008.
- [RFC2068] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2068, January 1997, <http://www.ietf.org/rfc/rfc2068.txt>
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>
- [RFC2291] Slein, J., Vitali, F., Whitehead, E., and Durand, D., "Requirements for a Distributed Authoring and Versioning Protocol for the World Wide Web", RFC 2291, February 1998, <ftp://ftp.rfc-editor.org/in-notes/rfc2291.txt>
- [RFC2518] Goland Y., Whitehead, E., Faizi, A., et al., "HTTP Extensions for Distributed Authoring -- WEBDAV", RFC 2518, February 1999, <http://www.ietf.org/rfc/rfc2518.txt>
- [RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000, <http://www.ietf.org/rfc/rfc2818.txt>
- [RFC3744] Clemm, G., Reschke, J., Sedlar, E., and Whitehead, J., "Web Distributed Authoring and Versioning (WebDAV) Access Control Protocol", RFC 3744, May 2004, <ftp://ftp.rfc-editor.org/in-notes/rfc3744.txt>
- [RFC4648] Josefsson, S., "The Base16, Base32, and Base64 Data Encodings", RFC 4648, October 2006, <http://www.ietf.org/rfc/rfc4648.txt>

## 1.2.2 Informative References

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)", April 2008.

[MSDN-CESHU] Microsoft Corporation, "Constructing Exchange Store HTTP URLs", June 2006, [http://msdn.microsoft.com/en-us/library/aa493863\(EXCHG.80\).aspx](http://msdn.microsoft.com/en-us/library/aa493863(EXCHG.80).aspx)

## 1.3 Overview

This document specifies extensions to [\[RFC2518\]](#), [\[MS-WDVME\]](#), [\[MS-WDVSE\]](#), and [\[MS-WDV\]](#) to allow for manipulation of Document objectproperties by using WebDAV. Document objects are Message objects, as specified in [\[MS-OXOMSG\]](#) with additional properties. The additional properties available on Document objects are available for query and manipulation by using WebDAV as specified in this document, or by using the protocol specified in [\[MS-OXODOC\]](#).

Standard and Microsoft extensions to WebDAV constructs are used to manipulate and query Document objectproperties. No additional headers or methods are specified in this document. Standard WebDAV constructs are specified in [\[RFC2518\]](#), Microsoft extensions to WebDAV constructs are specified in [\[MS-WDVME\]](#), [\[MS-WDVSE\]](#), and [\[MS-WDV\]](#).

## 1.4 Relationship to Other Protocols

This specification is dependent on the WebDAV Protocol as specified in [\[RFC2518\]](#). WebDAV, in turn, relies on **Hypertext Transfer Protocol (HTTP)** 1.1, as specified in [\[RFC2068\]](#). These extensions also rely on **Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS)**, as specified in [\[RFC2818\]](#), for data protection services.

This protocol is also dependent on the client, server and Microsoft extensions to [\[RFC2518\]](#) as specified in [\[MS-WDVME\]](#), [\[MS-WDVSE\]](#), and [\[MS-WDV\]](#). This protocol is also dependent on the Microsoft extension to [\[RFC2518\]](#), [\[MS-XWDEXT\]](#), for verb, header, and element definitions.

The WebDAV document properties specified in section 2.2 of this document map to Document object properties, as specified in [\[MS-OXODOC\]](#) section 2.2.2, and [\[MS-OXCMAIL\]](#) section 2.1.

All properties in this specification are listed in [\[MS-OXPROPS\]](#). The data type and format of the properties is specified in [\[MS-OXCDATA\]](#).

## 1.5 Prerequisites/Preconditions

This specification requires the following:

- A **WebDAV server**, as defined in [\[RFC2291\]](#).
- The **WebDAV client** has a **URL** that points to the WebDAV server.
- The WebDAV client obtains the URL through a mechanism that is outside of WebDAV and that is determined by the implementer.
- The WebDAV client and server support WebDAV **access control lists (ACL)** as specified in [\[RFC3744\]](#).
- The WebDAV client and server support ETags, as specified in [\[RFC2068\]](#) section 14.19.

For more information about constructing WebDAV server URLs, see [\[MSDN-CESHU\]](#).

## 1.6 Applicability Statement

A client can use this protocol to communicate Document object data with a server by using WebDAV.

## 1.7 Versioning and Capability Negotiation

This document covers versioning issues in the following areas:

- **Supported Transports:** This specification uses HTTP as its only transport.
- **Versioning:** This document introduces no new versioning mechanisms except those that already exist in WebDAV and HTTP as specified in [\[RFC2518\]](#) and [\[RFC2068\]](#).
- **Capability Negotiation:** This specification introduces no new capability negotiations except those that already exist in [\[RFC2518\]](#) sections 10.1 and 18, and in [\[RFC2068\]](#) section 9.2, via the OPTIONS method.

## 1.8 Vendor-Extensible Fields

None.

## 1.9 Standards Assignments

None.



## 2 Messages

### 2.1 Transport

**Messages** are transported using HTTP, as specified in [\[RFC2518\]](#) and [\[RFC2068\]](#).

### 2.2 Message Syntax

This section contains the WebDAV property extensions for Document object support. Many of these properties map directly to the Document object properties specified in [\[MS-OXODOC\]](#).

#### 2.2.1 DAV: Namespace Properties

##### 2.2.1.1 PidNameContentClass

**DAV property names:** DAV:contentclass, urn:schemas:mailheader:content-class, Content-Class

**Data type:** PtypString

Gets or sets the content class for the document item.

For more details about [PidNameContentClass](#), see [\[MS-OXPROPS\]](#) section 2.432 and [\[MS-OXCMAIL\]](#) section 2.1.2.2.

##### 2.2.1.2 PidNameDavId

**DAV property name:** DAV:id

**Data type:** PtypString

Gets the calculated value that contains the unique ID for the document.

For more details about [PidNameDavId](#), see [\[MS-OXPROPS\]](#) section 2.443.

##### 2.2.1.3 PidNameDavIsCollection

**DAV property name:** DAV:iscollection

**Data type:** PtypBoolean

Gets the calculated value that specifies whether an item is a **collection**, as specified in [\[MS-WDVME\]](#) section 2.2.9.1. True if the item is a collection; otherwise, false.

For more details about [PidNameDavIsCollection](#), see [\[MS-OXPROPS\]](#) section 2.444.

##### 2.2.1.4 PidNameDavIsStructuredDocument

**DAV property name:** DAV:isstructureddocument

**Data type:** PtypBoolean

Gets the calculated value that specifies whether an item is a structured document, as specified in [\[MS-XWDSTRUCTDOC\]](#). True if the item is a structured document; otherwise, false.

For more details about [PidNameDavIsStructuredDocument](#), see [\[MS-OXPROPS\]](#) section 2.445.

### 2.2.1.5 PidNameDavParentName

**DAV property name:** DAV:parentname

**Data type:** PtypString

Gets the calculated value that specifies the absolute URL of the **folder** that contains the item.

For more details about [PidNameDavParentName](#), see [\[MS-OXPROPS\]](#) section 2.446.

### 2.2.1.6 PidNameDavUid

**DAV property name:** DAV:uid

**Data type:** PtypString

Gets the calculated unique identifier for the item.

For more details about [PidNameDavUid](#), see [\[MS-OXPROPS\]](#) section 2.450.

### 2.2.1.7 PidTagAttributeHidden

**DAV property name:** DAV:ishidden

**Data type:** PtypBoolean

Gets or sets the value that indicates whether the item is hidden, as specified in [\[MS-WDVME\]](#) section 2.2.9.3. True if the item is hidden; otherwise, false.

For more details about [PidTagAttributeHidden](#), see [\[MS-OXPROPS\]](#) section 2.677.

### 2.2.1.8 PidTagAttributeReadOnly

**DAV property name:** DAV:isreadonly

**Data type:** PtypBoolean

Gets or sets the value that indicates whether the item can be modified or deleted. True if the item is read-only; otherwise, false.

For more details about [PidTagAttributeReadOnly](#), see [\[MS-OXPROPS\]](#) section 2.678.

### 2.2.1.9 PidTagSubfolder

**DAV property name:** DAV:isfolder

**Data type:** PtypBoolean

Gets a value that indicates whether the item is a folder. True if the item is a folder and is viewable in the mail client; otherwise, false. This property is further specified in [\[MS-WDVME\]](#) section 2.2.9.

For more details about [PidTagSubfolder](#), see [\[MS-OXPROPS\]](#) section 2.1152.

### 2.2.1.10 PidTagUrlName

**DAV property name:** DAV:href

**Data type:** PtypString

Gets the absolute URL of the document.

For more details about [PidTagUrlName](#), see [\[MS-OXPROPS\]](#) section 2.1177.

## 2.2.2 [http://schemas.microsoft.com/exchange/](#) Namespace Properties

### 2.2.2.1 PidTagExchangeNTSecurityDescriptor

**DAV property name:** [http://schemas.microsoft.com/exchange/ntsecuritydescriptor](#)

**Data type:** PtypBinary

Gets or sets the calculated the security descriptor for the item. The security descriptor MUST contain the item's primary owner and group, and a discretionary access control list granting and denying various rights to particular users and groups. Clients MUST NOT manipulate the security descriptor directly. The **PidTagExchangeNTSecurityDescriptor** property is a base64 encoded ([\[RFC4648\]](#) section 4) **SECURITY\_DESCRIPTOR**, as specified in [\[MS-DTYP\]](#).

For more details about [PidTagExchangeNTSecurityDescriptor](#), see [\[MS-OXPROPS\]](#) section 2.765.

### 2.2.2.2 PidTagFlatUrlName

**DAV property name:** [http://schemas.microsoft.com/exchange/permanenturl](#)

**Data type:** PtypString

Gets the unique identifier for an item across the **store**. This value MUST NOT change as long as the item remains in the same folder. The [PidTagFlatUrlName](#) property contains the ID of the parent folder of the item, which changes when the item is moved to a different folder or deleted. Changing a property on an item does not change the [PidTagFlatUrlName](#) property, nor will adding more items to the folder with the same **display name** or message subject. This property corresponds to the **MS-Exchange-Permanent-URL** header value, as specified in [\[MS-XWDEXT\]](#) section 2.2.2.11.

For more details about [PidTagFlatUrlName](#), see [\[MS-OXPROPS\]](#) section 2.776.

### 2.2.2.3 PidTagMessageClass

**DAV property name:** [http://schemas.microsoft.com/exchange/outlookmessageclass](#)

**Data type:** PtypString

Gets or sets the type of document.

For more details about [PidTagMessageClass](#), see [\[MS-OXPROPS\]](#) section 2.886 and [\[MS-OXCMSG\]](#) section 2.2.1.3.

### 2.2.2.4 PidTagMid

**DAV property name:** [http://schemas.microsoft.com/exchange/mid](#)

**Data type:** PtypInteger64

Gets the **message ID (MID)**.

For more details about [PidTagMid](#), see [\[MS-OXPROPS\]](#) section 2.900 and [\[MS-OXCFXICS\]](#) section 2.2.1.2.1.

## 2.2.3 urn:schemas-microsoft-com:office:office Namespace Properties

### 2.2.3.1 PidNameApplicationName

**DAV property names:** AppName, urn:schemas-microsoft-com:office:office#NameOfApplication

**Data type:** PtypString

Gets or sets the name of the application used to create the document. This property corresponds to the GKPIDSI\_APPNAME property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNameApplicationName](#), see [\[MS-OXPROPS\]](#) section 2.366.

### 2.2.3.2 PidNameAuthor

**DAV property names:** Author, urn:schemas-microsoft-com:office:office#Author

**Data type:** PtypString

Gets or sets the author of the document. This property corresponds to the GKPIDSI\_AUTHOR property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNameAuthor](#), see [\[MS-OXPROPS\]](#) section 2.377.

### 2.2.3.3 PidNameByteCount

**DAV property names:** ByteCount, urn:schemas-microsoft-com:office:office#Bytes

**Data type:** PtypInteger32

Gets or sets the size of the document in bytes. This property corresponds to the GKPIDDI\_BYTECOUNT property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.2.1.

For more details about [PidNameByteCount](#), see [\[MS-OXPROPS\]](#) section 2.380

### 2.2.3.4 PidNameCategory

**DAV property name:** Category, urn:schemas-microsoft-com:office:office#Category

**Data type:** PtypString

Gets or sets the category associated with the document. This property corresponds to the GKPIDDI\_CATEGORY property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.2.1.

For more details about [PidNameCategory](#), see [\[MS-OXPROPS\]](#) section 2.409.

### 2.2.3.5 PidNameCharacterCount

**DAV property name:** CharCount, urn:schemas-microsoft-com:office:office#Characters

**Data type:** PtypInteger32

Gets or sets the number of characters in the document. This property corresponds to the GKPIDSI\_CHARCOUNT property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNameCharacterCount](#), see [\[MS-OXPROPS\]](#) section 2.411.

### 2.2.3.6 PidNameComments

**DAV property name:** Comments, urn:schemas-microsoft-com:office:office#Comments

**Data type:** PtypString

Gets or sets the comments associated with the document. This property corresponds to the GKPIDSI\_COMMENTS property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNameComments](#), see [\[MS-OXPROPS\]](#) section 2.412.

### 2.2.3.7 PidNameCompany

**DAV property name:** Company, urn:schemas-microsoft-com:office:office#Company

**Data type:** PtypString

Gets or sets the author's company. This property corresponds to the GKPIDDSI\_COMPANY property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.2.1.

For more details about [PidNameCompany](#), see [\[MS-OXPROPS\]](#) section 2.413.

### 2.2.3.8 PidNameCreateDateTimeReadOnly

**DAV property name:** CreateDtmRo, urn:schemas-microsoft-com:office:office#Created

**Data type:** PtypTime

Gets or sets the date and time that the document was created. This property corresponds to the GKPIDSI\_CREATE\_DTM property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNameCreateDateTimeReadOnly](#), see [\[MS-OXPROPS\]](#) section 2.440.

### 2.2.3.9 PidNameDocumentParts

**DAV property name:** DocParts, urn:schemas-microsoft-com:office:office#PartTitles

**Data type:** PtypMultipleString

Gets or sets the titles of the document parts. This property corresponds to the GKPIDDSI\_DOCPARTS property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.2.1.

For more details about [PidNameDocumentParts](#), see [\[MS-OXPROPS\]](#) section 2.454.

### 2.2.3.10 PidNameEditTime

**DAV property name:** EditTime, urn:schemas-microsoft-com:office:office#TotalTime

**Data type:** PtypString

Gets or sets the total editing time for the document. This property corresponds to the GKPIDSI\_EDITTIME property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNameEditTime](#), see [\[MS-OXPROPS\]](#) section 2.455.

### 2.2.3.11 PidNameHeadingPairs

**DAV property names:** HeadingPairs, urn:schemas-microsoft-com:office:office#HeadingPairs

**Data type:** PtypBinary

Gets or sets the group of headings that are indented in the document. This property corresponds to the GKPIDDSI\_HEADINGPAIR property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.2.1.

For more details about [PidNameHeadingPairs](#), see [\[MS-OXPROPS\]](#) section 2.473.

### 2.2.3.12 PidNameHiddenCount

**DAV property names:** HiddenCount, urn:schemas-microsoft-com:office:office#HiddenSlides

**Data type:** PtypInteger32

Gets or sets the number of hidden slides in the document. This property corresponds to the GKPIDDSI\_HIDDENCOUNT property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.2.1.

For more details about [PidNameHiddenCount](#), see [\[MS-OXPROPS\]](#) section 2.474.

### 2.2.3.13 PidNameKeywords

**DAV property names:** urn:schemas-microsoft-com:office:office#Keywords, http://schemas.microsoft.com/exchange/keywords-utf8, Keywords

**Data type:** PtypMultipleString

Gets or sets a list of keywords for the document. This property corresponds to the GKPIDSI\_KEYWORDS property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNameKeywords](#), see [\[MS-OXPROPS\]](#) section 2.495.

### 2.2.3.14 PidNameLastAuthor

**DAV property names:** LastAuthor, urn:schemas-microsoft-com:office:office#LastAuthor

**Data type:** PtypString

Gets or sets the most recent author of the document. This property corresponds to the GKPIDSI\_LASTAUTHOR property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNameLastAuthor](#), see [\[MS-OXPROPS\]](#) section 2.496.

### 2.2.3.15 PidNameLastPrinted

**DAV property names:** LastPrinted, urn:schemas-microsoft-com:office:office#LastPrinted

**Data type:** PtypTime

Gets or sets the date and time when the document was last printed. This property corresponds to the GKPIDSI\_LASTPRINTED property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNameLastPrinted](#), see [\[MS-OXPROPS\]](#) section 2.497.

### 2.2.3.16 PidNameLastSaveDateTime

**DAV property names:** LastSaveDtm, urn:schemas-microsoft-com:office:office#LastSaved

**Data type:** PtypTime

Gets or sets the date and time that the document was last saved. This property corresponds to the GKPIDSI\_LASTSAVE\_DTM property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNameLastSaveDateTime](#), see [\[MS-OXPROPS\]](#) section 2.498.

### 2.2.3.17 PidNameLineCount

**DAV property names:** LineCount, urn:schemas-microsoft-com:office:office#Lines

**Data type:** PtypInteger32

Gets or sets the number of lines in the document. This property corresponds to the GKPIDDSI\_LINECOUNT property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.2.1.

For more details about [PidNameLineCount](#), see [\[MS-OXPROPS\]](#) section 2.499.

### 2.2.3.18 PidNameLinksDirty

**DAV property names:** LinksDirty, urn:schemas-microsoft-com:office:office#LinksUpToDate

**Data type:** PtypBoolean

Gets or sets a value that indicates whether the links in the document are up to date. True if the links are up to date; otherwise, false. This property corresponds to the GKPIDDSI\_LINKSDIRTY property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.2.1.

For more details about [PidNameLinksDirty](#), see [\[MS-OXPROPS\]](#) section 2.501.

### 2.2.3.19 PidNameManager

**DAV property name:** Manager, urn:schemas-microsoft-com:office:office#Manager

**Data type:** PtypString

Gets or sets the manager of the author of the document. This property corresponds to the GKPIDDSI\_MANAGER property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.2.1.

For more details about [PidNameManager](#), see [\[MS-OXPROPS\]](#) section 2.504.

### 2.2.3.20 PidNameMultimediaClipCount

**DAV property names:** MMClipCount, urn:schemas-microsoft-com:office:office#MultimediaClips

**Data type:** PtypInteger32

Gets or sets the number of multimedia clips in the document. This property corresponds to the GKPIDDSI\_MMCLIPCOUNT property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.2.1.

For more details about [PidNameMultimediaClipCount](#), see [\[MS-OXPROPS\]](#) section 2.507.

### 2.2.3.21 PidNameNoteCount

**DAV property names:** NoteCount, urn:schemas-microsoft-com:office:office#Notes

**Data type:** PtypInteger32

Gets or sets the number of notes in the document. This property corresponds to the GKPIDDSI\_NOTECOUNT property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.2.1.

For more details about [PidNameNoteCount](#), see [\[MS-OXPROPS\]](#) section 2.510.

### 2.2.3.22 PidNamePageCount

**DAV property names:** PageCount, urn:schemas-microsoft-com:office:office#Pages

**Data type:** PtypInteger32

Gets or sets the number of pages in the document. This property corresponds to the GKPIDDSI\_PAGECOUNT property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNamePageCount](#), see [\[MS-OXPROPS\]](#) section 2.522.

### 2.2.3.23 PidNameParagraphCount

**DAV property names:** ParCount, urn:schemas-microsoft-com:office:office#Paragraphs

**Data type:** PtypInteger32

Gets or sets the number of paragraphs in the document. This property corresponds to the GKPIDDSI\_PARACOUNT property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.2.1.

For more details about [PidNameParagraphCount](#) see [\[MS-OXPROPS\]](#) section 2.523.

### 2.2.3.24 PidNamePresentationFormat

**DAV property names:** PresFormat, urn:schemas-microsoft-com:office:office#PresentationFormat

**Data type:** PtypString

Gets or sets the presentation format for the document. This property corresponds to the GKPIDDSI\_PRESFORMAT property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.2.1.

For more details about [PidNamePresentationFormat](#), see [\[MS-OXPROPS\]](#) section 2.527.

### 2.2.3.25 PidNameRevisionNumber

**DAV property names:** RevNumber, urn:schemas-microsoft-com:office:office#Revision

**Data type:** PtypString

Gets or sets the revision number of the document. This property corresponds to the GKPIDDSI\_REVNUMBER property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNameRevisionNumber](#), see [\[MS-OXPROPS\]](#) section 2.537.



### 2.2.3.26 PidNameScale

**DAV property names:** Scale, urn:schemas-microsoft-com:office:office#ScaleCrop

**Data type:** PtypBoolean

Gets or sets a value that indicates whether the image is to be scaled or cropped. Set to **TRUE** for thumbnail scaling, or **FALSE** for cropping. This property corresponds to the GKPIDDSI\_SCALE property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.2.1.

For more details about [PidNameScale](#), see [\[MS-OXPROPS\]](#) section 2.540.

### 2.2.3.27 PidNameSecurity

**DAV property names:** Security, urn:schemas-microsoft-com:office:office#Security

**Data type:** PtypInteger32

Gets or sets the security level of the document. This property corresponds to the GKPIDSI\_DOC\_SECURITY property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNameSecurity](#), see [\[MS-OXPROPS\]](#) section 2.541.

### 2.2.3.28 PidNameSlideCount

**DAV property names:** SlideCount, urn:schemas-microsoft-com:office:office#Slides

**Data type:** PtypInteger32

Gets or sets the number of slides in the document. This property corresponds to the GKPIDDSI\_SLIDECOUNT property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.2.1.

For more details about [PidNameSlideCount](#), see [\[MS-OXPROPS\]](#) section 2.544.

### 2.2.3.29 PidNameSubject

**DAV property names:** Subject, urn:schemas-microsoft-com:office:office#Subject

**Data type:** PtypString

Gets or sets the subject of the document. This property corresponds to the GKPIDSI\_SUBJECT property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1. This property is different from the mailheaders subject property, which is commonly the display name.

For more details about [PidNameSubject](#) see [\[MS-OXPROPS\]](#) section 2.545.

### 2.2.3.30 PidNameTemplate

**DAV property names:** Template, urn:schemas-microsoft-com:office:office#Template

**Data type:** PtypString

Gets or sets the template file that the document was created from. This property corresponds to the GKPIDSI\_TEMPLATE property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNameTemplate](#), see [\[MS-OXPROPS\]](#) section 2.547.

### 2.2.3.31 PidNameThumbnail

**DAV property names:** Thumbnail, urn:schemas-microsoft-com:office:office#ThumbNail

**Data type:** PtypBinary

Gets or sets the thumbnail image of the document or part of the document. This property corresponds to the GKPIDSI\_THUMBNAIL property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNameThumbnail](#), see [\[MS-OXPROPS\]](#) section 2.550.

### 2.2.3.32 PidNameTitle

**DAV property names:** Title, urn:schemas-microsoft-com:office:office#Title

**Data type:** PtypString

Gets or sets the title of the document. This property corresponds to the GKPIDSI\_TITLE property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNameTitle](#), see [\[MS-OXPROPS\]](#) section 2.551.

### 2.2.3.33 PidNameWordCount

**DAV property names:** WordCount, urn:schemas-microsoft-com:office:office#Words

**Data type:** PtypInteger32

Gets or sets the number of words in the document. This property corresponds to the GKPIDSI\_WORDCOUNT property, which is specified in [\[MS-OSHARED\]](#) section 2.3.3.2.1.1.

For more details about [PidNameWordCount](#), see [\[MS-OXPROPS\]](#) section 2.553.

## 3 Protocol Details

### 3.1 Client and Server Details

#### 3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

The WebDAV Extensions for Documents Support protocol supports querying and manipulation of properties and searching for documents, which can be individual documents or documents attached to messages in public and private folders. The document properties are exposed to query and manipulation through the WebDAV document properties specified in section [2.2](#).

#### 3.1.2 Timers

None.

#### 3.1.3 Initialization

None.

#### 3.1.4 Higher-Layer Triggered Events

None.

#### 3.1.5 Message Processing Events and Sequencing Rules

Use the **PROPFIND** method, as specified in [\[RFC2518\]](#) section 8.1, to retrieve WebDAV document properties.

Use the **PROPPATCH** method, as specified in [\[RFC2518\]](#) section 8.2, to set or remove WebDAV document properties.

Use the **SEARCH** method, as specified in [\[MS-WDVSE\]](#) section 2.2.4, to search documents with specified properties.

#### 3.1.6 Timer Events

None.

#### 3.1.7 Other Local Events

None.

## 4 Protocol Examples

### 4.1 Using PROPFIND to retrieve all properties on a document

#### 4.1.1 Request

In the following example, the user wants to retrieve all the properties set on the Product Planning document in their **Inbox folder**. To achieve this, the user connects the WebDAV client to the WebDAV server and uses the PROPFIND method to retrieve all properties set on the Product Planning document.

```
PROPFIND /exchange/Mailbox/Inbox/Product%20Planning.docx HTTP/1.1
Content-Type: text/xml
Depth: 0

<?xml version="1.0" encoding="utf-8"?>
<a:propfind xmlns:a="DAV:">
  <allprop />
</a:propfind>
```

#### 4.1.2 Response

The response message returns all the properties set on the document.

```
HTTP/1.1 207 Multi-Status
Cache-Control: no-cache
Transfer-Encoding: chunked
Content-Type: text/xml
Accept-Ranges: rows
Server: Microsoft-IIS/7.0
MS-WebStorage: 08.01.10240
X-Powered-By: ASP.NET
Date: Mon, 27 Oct 2008 16:49:27 GMT

<?xml version="1.0"?>
<a:multistatus xmlns:b="urn:uuid:c2f41010-65b3-11d1-a29f-00aa00c14882/"
xmlns:g="urn:schemas:htmppmail:" xmlns:c="xml:"
xmlns:e="http://schemas.microsoft.com/exchange/" xmlns:d="urn:schemas-microsoft-
com:office:office" xmlns:f="http://schemas.microsoft.com/repl/" xmlns:h="urn:schemas-
microsoft-com:exch-data:" xmlns:a="DAV:">
  <a:response>
    <a:href>https://Server01/exchange/Mailbox/Inbox/Product%20Planning.docx</a:href>
    <a:propstat>
      <a:status>HTTP/1.1 200 OK</a:status>
      <a:prop>
        <a:contentclass>urn:content-classes:document</a:contentclass>
        <a:supportedlock>
          <lockentry xmlns="DAV:">
            <locktype>
              <transaction>
                <groupoperation />
              </transaction>
            </locktype>
            <lockscope>
              <local />
            </lockscope>
          </lockentry>
        </a:supportedlock>
      </a:prop>
    </a:propstat>
  </a:response>
</a:multistatus>
```

```

        </lockentry>
        </a:supportedlock>
        <e:permanenturl>https://Server01/-FlatUrlSpace-
/1c5a707ee8157a47bfce2b746a3dba25-12c281f/1c5a707ee8157a47bfce2b746a3dba25-
403ac2e6fa</e:permanenturl>
        <a:getcontenttype>application/vnd.openxmlformats-
officedocument.wordprocessingml.document</a:getcontenttype>
        <a:id>AQEAAAABLcGfAQAAQDrC5voAAAA</a:id>
        <e:mid b:dt="i8">-367392764146483199</e:mid>
        <a:isfolder b:dt="boolean">0</a:isfolder>
        <a:resourcetype />
        <a:getetag>"1c5a707ee8157a47bfce2b746a3dba2500403ac30c72"</a:getetag>
        <lockdiscovery xmlns="DAV:">
        </lockdiscovery>
        <e:outlookmessageclass>IPM.Document.*docx</e:outlookmessageclass>
        <a:creationdate b:dt="dateTime.tz">2008-10-27T16:44:43.838Z</a:creationdate>
        <e:ntsecuritydescriptor
b:dt="bin.base64">CAAEAAAAAAAAABAC+MMAAAAEwAAAAAAAAFAAAAAIAHAABAAAAARAUAL8PhwABAQAAAAABQcAAAA
BBQAAAAAABRUAAAD0l0oajmNmy/EPPr4pXBAAAAQUAAAAAAUVAAAA9JdKGo5jZsvxD6+KAQIAAA==</e:ntsecurityde
scriptor>
        <a:ishidden b:dt="boolean">0</a:ishidden>
        <a:parentname>https://Server01/exchange/Mailbox/Inbox/</a:parentname>
        <a:getcontentlength b:dt="int">9984</a:getcontentlength>
        <a:isstructureddocument b:dt="boolean">0</a:isstructureddocument>
        <f:repl-uid>rid:1c5a707ee8157a47bfce2b746a3dba2500403ac2e6fa</f:repl-uid>
        <a:displayname>Product Planning.docx</a:displayname>
        <a:href>https://Server01/exchange/Mailbox/Inbox/Product%20Planning.docx</a:hr
ef>
        <a:isreadonly b:dt="boolean">0</a:isreadonly>
        <a:uid>AQEAAEA6wub6AAAAAAAAAAAAAAAA</a:uid>
        <a:getlastmodified b:dt="dateTime.tz">2008-10-
27T16:44:43.838Z</a:getlastmodified>
        <a:iscollection b:dt="boolean">0</a:iscollection>
        <g:read b:dt="boolean">1</g:read>
        <f:resourcetag>rt:1c5a707ee8157a47bfce2b746a3dba2500403ac2e6fa1c5a707ee8157a4
7bfce2b746a3dba2500403ac30c72</f:resourcetag>
        </a:prop>
    </a:propstat>
</a:response>
</a:multistatus>

```

## 4.2 Using PROPFIND to retrieve specific properties on a document

### 4.2.1 Request

In the following example, the user wants to retrieve specific properties set on the Product Planning document in their Inbox folder. To achieve this, the user connects the WebDAV client to the WebDAV server and uses the PROPFIND method to retrieve specific properties set on the Product Planning document.

```

PROPFIND /exchange/Mailbox/Inbox/Product%20Planning.doc HTTP/1.1
Content-Type: text/xml
Depth: 0

<?xml version="1.0" encoding="utf-8"?>
<a:propfind xmlns:a="DAV:">
  <a:prop xmlns:o="urn:schemas-microsoft-com:office:office">

```

```

    <o:Author />
    <o:Bytes />
    <o:Category />
    <o:Characters />
    <o:Comments />
    <o:Company />
    <o:Created />
    <o:HeadingPairs />
    <o:HiddenSlides />
    <o:Keywords />
    <o>LastAuthor />
    <o>LastPrinted />
    <o>LastSaved />
    <o:Lines />
    <o:LinksUpToDate />
    <o:Manager />
    <o:MultimediaClips />
    <o:NameOfApplication />
    <o:Notes />
    <o:Pages />
    <o:Paragraphs />
    <o:PartTitles />
    <o:PresentationFormat />
    <o:Revision />
    <o:ScaleCrop />
    <o:Security />
    <o:Slides />
    <o:Subject />
    <o:Template />
    <o:ThumbNail />
    <o:Title />
    <o:TotalTime />
    <o:Version />
    <o:Words />
  </a:prop>
</a:propfind>

```

## 4.2.2 Response

The response message returns the values of the properties specified in the request.

```

HTTP/1.1 207 Multi-Status
Cache-Control: no-cache
Transfer-Encoding: chunked
Content-Type: text/xml
Accept-Ranges: rows
Server: Microsoft-IIS/7.0
MS-WebStorage: 08.01.10240
X-Powered-By: ASP.NET
Date: Mon, 27 Oct 2008 17:14:49 GMT

<?xml version="1.0"?>
<a:multistatus xmlns:b="urn:uuid:c2f41010-65b3-11d1-a29f-00aa00c14882/" xmlns:c="xml:"
xmlns:d="urn:schemas-microsoft-com:office:office" xmlns:a="DAV:">
  <a:response>
    <a:href>https://Server01/exchange/Mailbox/Inbox/Product%20Planning.doc</a:href>
    <a:propstat>

```

```

<a:status>HTTP/1.1 200 OK</a:status>
<a:prop>
  <d:Author>Holly Holt</d:Author>
  <d:Category>Planning</d:Category>
  <d:Characters b:dt="int">58</d:Characters>
  <d:Comments>This is the product planning document.</d:Comments>
  <d:Company>Contoso</d:Company>
  <d:Created b:dt="dateTime.tz">2008-10-27T17:07:00.000Z</d:Created>
  <d:HeadingPairs
b:dt="bin.base64">AgAAAB4AAAAIAAAAVG10bGUAAAADAAAAQAAAA==</d:HeadingPairs>
  <d:Keywords b:dt="mv.string">
    <c:v>Product;</c:v>
    <c:v>Planning</c:v>
  </d:Keywords>
  <d>LastAuthor>Holly Holt</d>LastAuthor>
  <d>LastSaved b:dt="dateTime.tz">2008-10-27T17:07:00.000Z</d>LastSaved>
  <d:Lines b:dt="int">1</d:Lines>
  <d:LinksUpToDate b:dt="boolean">0</d:LinksUpToDate>
  <d:Manager>Don Hall</d:Manager>
  <d:NameOfApplication>Microsoft Office Word</d:NameOfApplication>
  <d:Pages b:dt="int">1</d:Pages>
  <d:Paragraphs b:dt="int">1</d:Paragraphs>
  <d:PartTitles b:dt="mv.string">
    <c:v>
    </c:v>
  </d:PartTitles>
  <d:Revision>2</d:Revision>
  <d:ScaleCrop b:dt="boolean">0</d:ScaleCrop>
  <d:Security b:dt="int">0</d:Security>
  <d:Subject>Contoso Product Planning</d:Subject>
  <d:Template>Normal</d:Template>
  <d>Title>Product Planning</d>Title>
  <d:Words b:dt="int">10</d:Words>
</a:prop>
</a:propstat>
<a:propstat>
  <a:status>HTTP/1.1 415 Unsupported Media Type</a:status>
  <a:prop>
    <d:TotalTime />
  </a:prop>
</a:propstat>
<a:propstat>
  <a:status>HTTP/1.1 404 Resource Not Found</a:status>
  <a:prop>
    <d:Bytes />
    <d:HiddenSlides />
    <d>LastPrinted />
    <d:MultimediaClips />
    <d:Notes />
    <d:PresentationFormat />
    <d:Slides />
    <d:ThumbNail />
    <d:Version />
  </a:prop>
</a:propstat>
</a:response>
</a:multistatus>

```

## 4.3 Using PROPPATCH to set a document property

### 4.3.1 Request

In the following example, the user wants to set the [PidNameCategory](#) property on the Product Planning document. To achieve this, the user connects the WebDAV client to the WebDAV server and uses the PROPPATCH method to set the category property.

```
PROPPATCH /Server01/exchange/Mailbox/Inbox/Product%20Planning.doc HTTP/1.1
Content-type: text/xml

<?xml version="1.0"?>
<a:propertyupdate xmlns:a="DAV:" xmlns:o="urn:schemas-microsoft-com:office:office">
  <a:set>
    <a:prop>
      <o:Category>Product Planning.</o:Category>
    </a:prop>
  </a:set>
</a:propertyupdate>
```

### 4.3.2 Response

The response message returns an HTTP status code indicating that the change was successful.

```
HTTP/1.1 207 Multi-Status
Cache-Control: no-cache
Content-Length: 306
Content-Type: text/xml
Server: Microsoft-IIS/7.0
MS-Exchange-Permanent-URL: https://Server01/-FlatUrlSpace-/1c5a707ee8157a47bfce2b746a3dba25-12c281f/1c5a707ee8157a47bfce2b746a3dba25-403ac2e6fb
Repl-UID: <rid:1c5a707ee8157a47bfce2b746a3dba2500403ac2e6fb>
ResourceTag:
<rt:1c5a707ee8157a47bfce2b746a3dba2500403ac2e6fb1c5a707ee8157a47bfce2b746a3dba2500403ac30c7c>
MS-WebStorage: 08.01.10240
X-Powered-By: ASP.NET
Date: Mon, 27 Oct 2008 17:19:47 GMT

<?xml version="1.0"?>
<a:multistatus xmlns:b="urn:schemas-microsoft-com:office:office" xmlns:a="DAV:">
  <a:response>
    <a:href>https://Server01/exchange/Mailbox/Inbox/Product%20Planning.doc</a:href>
    <a:propstat>
      <a:status>HTTP/1.1 200 OK</a:status>
      <a:prop>
        <b:Category />
      </a:prop>
    </a:propstat>
  </a:response>
</a:multistatus>
```



## **5 Security**

### **5.1 Security Considerations for Implementers**

None.

### **5.2 Index of Security Parameters**

None.

## 6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products:

- Microsoft® Exchange Server 2003
- Microsoft® Exchange Server 2007

Exceptions, if any, are noted below. If a service pack number appears with the product version, behavior changed in that service pack. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that product does not follow the prescription.

## 7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

## 8 Index

### A

Abstract data model  
[client](#) 19  
[server](#) 19  
[Applicability](#) 8

### C

[Capability negotiation](#) 8  
[Change tracking](#) 27  
Client  
[abstract data model](#) 19  
[message processing](#) 19  
[sequencing rules](#) 19

### D

Data model – abstract  
[client](#) 19  
[server](#) 19

### E

[Examples - overview](#) 20

### F

[Fields - vendor-extensible](#) 8

### G

[Glossary](#) 5

### I

[Informative references](#) 7  
[Introduction](#) 5

### M

Message processing  
[client](#) 19  
[server](#) 19  
Messages  
[overview](#) 9  
[transport](#) 9

### N

[Normative references](#) 5

### O

[Overview \(synopsis\)](#) 7

### P

[Preconditions](#) 7

[Prerequisites](#) 7  
[Product behavior](#) 26

### R

References  
[informative](#) 7  
[normative](#) 5  
[Relationship to other protocols](#) 7

### S

Security  
[overview](#) 25  
Sequencing rules  
[client](#) 19  
[server](#) 19  
Server  
[abstract data model](#) 19  
[message processing](#) 19  
[sequencing rules](#) 19

### T

[Tracking changes](#) 27  
[Transport](#) 9

### V

[Vendor-extensible fields](#) 8  
[Versioning](#) 8